Dalton Transactions

Accepted Manuscript

This is an *Accepted Manuscript*, which has been through the Royal Society of Chemistry peer review process and has been accepted for publication.

Accepted Manuscripts are published online shortly after acceptance, before technical editing, formatting and proof reading. Using this free service, authors can make their results available to the community, in citable form, before we publish the edited article. We will replace this *Accepted Manuscript* with the edited and formatted *Advance Article* as soon as it is available.

You can find more information about *Accepted Manuscripts* in the [Information for Authors](http://www.rsc.org/Publishing/Journals/guidelines/AuthorGuidelines/JournalPolicy/accepted_manuscripts.asp).

Please note that technical editing may introduce minor changes to the text and/or graphics, which may alter content. The journal's standard [Terms & Conditions](http://www.rsc.org/help/termsconditions.asp) and the Ethical quidelines still apply. In no event shall the Royal Society of Chemistry be held responsible for any errors or omissions in this *Accepted Manuscript* or any consequences arising from the use of any information it contains.

www.rsc.org/dalton

Journal Name RSCPublishing

Cite this: DOI: 10.1039/x0xx00000x

Received 00th January 2012, Accepted 00th January 2012 DOI: 10.1039/x0xx00000x

www.rsc.org/

ARTICLE

Thermoelectric properties of the Zintl phases $Yb_5M_2Sb_6 (M = Al, Ga, In)$

Umut Aydemir^{a,*}, Alex Zevalkink^b, Alim Ormeci^c, Heng Wang^a, Saneyuki Ohno^a, Sabah Bux^b and G. Jeffrey Snyder^a

Zintl compounds with chemical formula Yb₅*M*₂Sb₆ (*M* = Al, Ga, and In) form one of two known $A_5M_2Pn_6$ structure types characterized by double chains of corner-linked $MPn₄$ tetrahedra bridged by $Pn₂$ dumbbells. High temperature electronic and thermal transport measurements were used to characterize the thermoelectric properties of $Yb_5M_2Sb_6$ compounds. All samples were found to exhibit similar high *p*-type carrier concentrations, low resistivity and low Seebeck coefficients in agreement with the band structure calculations. These results, combined with previous studies, suggest that $Yb_5M_2Sb_6$ compounds are semimetals (i.e., they lack an energy gap between the valence and conduction bands), in contrast to the semiconducting alkaline earth (Ca, Sr, Ba) and Eu based $A_5M_2Sb_6$ compounds. Yb $_5M_2Sb_6$ compounds have very low lattice thermal conductivity, comparable to other closely related $A_5M_2Sb_6$ and A_3MSb_3 phases. However, due to the semimetallic behaviour, the figure of merit of investigated samples remains low (*zT* < 0.15).

Introduction

The thermoelectric efficiency of a material is governed by its figure of merit ($zT = \alpha^2 T/\rho \kappa$). High efficiency is typically obtained in heavily doped semiconductors that simultaneously possess a large Seebeck coefficient (α) , low electrical resistivity (*ρ*), and low thermal conductivity $(\kappa)^{1,2}$ Zintl compounds have emerged recently as a promising class of materials for thermoelectric applications.^{3, 4} These phases are composed of electropositive cations (alkali, alkaline-earth or rare-earth) that donate their valence electrons to anions, which in turn form covalent bonds to satisfy valence requirements.⁵ Their complex crystal structures lead to low lattice thermal conductivity and provide opportunities for targeted chemical substitutions to tune the electronic and thermal properties. $6-12$

Within $A_5M_2Pn_6$ Zintl phases ($A = Ca$, Sr, Ba, Eu, Yb, $M =$ Al, Ga, In, and $Pn = As$, Sb, Bi), promising zT values have been achieved in several antimonides.¹³⁻¹⁵ Two closely related structure types are formed by $A_5M_2Pn_6$ compounds, represented by the prototypical compounds, $Ca₅Ga₂As₆$ and $Ca₅Al₂Bi₆$ (Fig. 1).^{16, 17} In both structures, corner-sharing chains of MPn_4 tetrahedra are bridged by Pn_2 dumbbells to form infinite, parallel double chains ("ladders"). The primary distinguishing feature between the two $A_5M_2Pn_6$ structure types is in the packing geometry of the ladders. Zintl counting in these anionic double chains yields two Pn^{-1} bridging across the chains, two *Pn*^{−1} from the corner-sharing tetrahedra, and two *Pn*^{−2} that are only bonded to *M*. The two *M* atoms are each bound to four *Pn* atoms, yielding a formal valence of −1. The 5*A* +2 atoms are situated between the chains, providing overall Zintl charge balance of $[A^{2+}]_5[(4b)M]_2[(2b)Pn^-]_4[(1b)Pn^2^-]_2$.

Fig. 1 The crystal structures of **a**) $Ca₅Ga₂As₆$ and **b**) $Ca₅Al₂Bi₆$ with double chains of different packing geometry.

Representatives of the $Ca₅Ga₂As₆$ structure type include $Ca₅M₂Sb₆$ with *M* = Al, Ga, and In and $A₅In₂Sb₆$ with *A* = Sr, Ba, or Eu. All of the compounds with this structure type appear to be semiconducting with band gaps ranging from 0.3-0.6 eV.¹⁸⁻²⁰ In this structure type, the carrier concentrations can be controlled by doping, leading to promising thermoelectric properties.^{13-15, 21, 22} The second structure type $(Ca_5Al_2Bi_6)$ is formed by several bismuthides and by the title compounds, $Yb_5M_2Sb_6$, where $M = A1$, Ga or In.²³⁻²⁵ Previous reports of the resistivity in $Yb_5In_2Sb_6$ and $Yb_5Al_2Sb_6$ revealed metallic behaviour indicative of either very high defect concentrations or of a semimetallic electronic structure.^{23, 25} In contrast, a recent investigation of the Ga analogue shows some evidence for semiconducting behavior.²⁴

 In an attempt to resolve these conflicting reports and to present a comprehensive picture of the thermoelectric properties of this series, the current study investigates the high temperature electronic and thermal transport properties of the three $Yb_5M_2Sb_6$ compounds ($M = A1$, Ga, In) concurrently. The results of electronic structure calculations and chemical bonding analyses are also reported.

Experimental Procedures

Synthesis.Yb₅ M_2 Sb₆ ($M =$ Al, Ga, and In) samples were synthesized by ball milling followed directly by hot pressing. GaSb and InSb were synthesized as precursors by heating the elements in quartz ampoules up to 600 °C and 800 °C, respectively. After annealing for 12 h at these temperatures, the ampoules were cooled to room temperature in 6 h. Stoichiometric amounts of small-cut Yb ingot (99.9, Alfa Aesar), Sb shot (99.999% Alfa Aesar) and either Al shot (99.999%, Alfa Aesar), GaSb or InSb were loaded under argon into stainless-steel vials with ½ inch stainless-steel balls. The contents were ball-milled for 1 h using a SPEX Sample Prep 8000 Series Mixer/Mill. The resulting fine powder was hot-pressed in highdensity graphite dies (POCO) under argon using a maximum pressure and temperature of 45 MPa and 550 °C, respectively, for 1 h. The samples were cooled down to room temperature slowly under no load.

Characterization. X-ray diffraction (XRD) was performed on either polished polycrystalline samples or powdered materials using a Philips XPERT MPD diffractometer with reflection mode (Cu- $K\alpha$ radiation). The lattice parameter determination using α -Si as internal standard and Rietveld refinements were performed by WinCSD program package. 26 Scanning electron microscopy (SEM) and energy dispersive X-ray spectroscopy (EDXS) were performed using a Zeiss 1550 VP SEM. Microprobe analysis with wavelength dispersive X-ray spectroscopy (WDXS, JEOL JXA - 8200 system) was carried out to determine the chemical composition of $Yb_5Al_2Sb_6$ phase. High temperature electronic and thermal transport properties were characterized up to 873 K under dynamic vacuum. The Seebeck coefficients were measured by using Chromel-Nb thermocouples.²⁷ Hall coefficients and resistivity (Van der

Pauw, 4-point probe) were measured simultaneously using a 0.8 T magnet with tungsten pressure contacts.²⁸ A Netzch LFA 457 was used to measure the thermal diffusivity *D*, from which the thermal conductivity was calculated using $\kappa = D \times C_P \times d$, where C_P is the Dulong Petit heat capacity, and d is the geometrical density. One should consider that the Dulong-Petit heat capacity may lead to overestimation of the thermal conductivity, especially at high temperatures.

Electronic structure calculations. First-principles electronic structure calculations were performed by using the all-electron, full-potential local orbital (FPLO) method.²⁹ Because the 4*f* electrons of Yb give rise to states with narrow band widths, local spin density approximation to the density functional theory had to be augmented by employing the so-called LSDA+U formalism. $30, 31$ The value of the on-site Coulomb repulsion, *U*, was taken as 8 eV, a typical value for the 4*f* electrons in the FPLO package. 32 For the double counting correction, the fully-localized or atomic limit was applied. Brillouin zone integrations were handled by the linear tetrahedron method with a mesh of $12 \times 4 \times 20$.

 Besides the standard band structure analysis using density of states (DOS) and electron energy band dispersions, chemical bonding was investigated in real space by a combined electron density - electron localizability indicator (ED-ELI) approach. This approach is based on Bader's quantum theory of atoms in molecules $(QTAIM).^{33}$ The topological analysis of ELI provides information regarding the nature of bonds (two- or multi-centered, number of electrons participating in the bond), lone-pair-like features and core shells.^{34, 35} The basin intersection technique allows identification of individual atom contributions to the electron populations of the bond basins.³⁶ The ED and ELI were calculated using a module implemented in the FPLO package. 37 The topological analysis and the basin intersection calculations were carried out by the program DGRID.³⁸

Results and Discussion

Phase analysis. $Yb_5A1_2Sb_6$ was originally obtained by Todorov *et al.* as a by-product during the solid state synthesis of YbAlSbGe.²⁵ Their attempts to prepare $Yb_5Al_2Sb_6$ as a single phase from the stoichiometric mixture of the elements failed, and eventually they suggested that a small amount of Ge was required in the reaction. It was proposed that Ge might act as a catalyst or form a low-temperature eutectic, which prevents formation of binary phases of Yb and Sb. In our studies, we found that the $Yb_5Al_2Sb_6$ sample prepared from the stoichiometric amount of elements contained more than 5 wt-% Yb₅Sb₃ as a secondary phase. This might indicate that during the synthesis process, some Al might be lost or the phase is stabilized with higher Al content. Therefore, in the next iteration, the sample was prepared with excess Al (0.65 at-%, corresponding to $Yb_5Al_{2.1}Sb_6$). In this way, $Yb_5Al_2Sb_6$ was obtained in very high yield with less than $2 wt$ -% Yb_5Sb_3 as a secondary phase (Fig. 2). $Yb_5Ga_2Sb_6$ and $Yb_5In_2Sb_6$ were previously prepared by either metal flux technique or solid state reaction of the elements.^{23, 24} In this investigation, after ballmilling followed by hot-pressing, they were obtained in very high yield with less than 1-2 wt-% GaSb or InSb as by-products (Fig. 2).

 The SEM images in secondary electron imaging mode are shown in Fig. 3. Hot-pressed samples show almost homogenous microstructures with no noticeable grain boundaries. The secondary phase of GaSb is marked for the $Yb_5Ga_2Sb_6$ sample. This impurity phase appears to be distributed in the grains of the main phase, rather than precipitating at possible grain boundaries. The chemical compositions of the $Yb_5Ga_2Sb_6$ and $Yb_5In_2Sb_6$ samples were determined by EDXS as $Yb_{4.97}Ga_{2.03}Sb_{6.01}$ and $Yb_{5.02}In_{1.99}Sb_{5.99}$, respectively. The determination of the chemical composition of $Yb_5Al_{2.1}Sb_6$ phase was hindered by the overlapping Yb-*M* and Al-*K*^α energy levels (1.486 and 1.521 eV, respectively). Taking that into consideration, WDXS analysis revealed a composition of $Yb_{4.72(5)}Al_{2.40(9)}Sb_{5.88(6)}$, indicating an Al-excess composition. The composition was determined additionally by Rietveld refinement as $Yb_{4.82}Al_{2.38}Sb_{5.98}$, which is similar to the microprobe result. This seems to suggest that an Al-rich composition is stable, explaining why a higher concentration of Yb₅Sb₃ was observed in the sample with a synthetic composition of $Yb_5Al_2Sb_6$, compared with $Yb_5Al_{2.1}Sb_6$.

Fig. 2 The Rietveld fit of $Yb_5M_2Sb_6$ samples (R_i , R_p , R_{wp} : 0.07, 0.15, 0.14; 0.04, 0.14, 0.12; 0.06, 0.12, 0.12 for *M* = Al, Ga, and In, respectively. All reflections of the main phases could be indexed using the reported crystal structure data.²³⁻²⁵ For the middle panel, the upper and lower ticks mark the calculated reflection positions of $Yb_5Ga_2Sb_6$ and GaSb ³⁹, respectively, and for others the ticks show the calculated reflection position of the target phases. The difference profiles are shown beneath of each panel.

Fig. 3 SEM images of **a**) $Yb_5Al_2Sb_6$, **b**) $Yb_5Ga_2Sb_6$ and **c**) $Yb_5In_2Sb_6$ in secondary electron imaging mode show homogenous microstructure and high density. The secondary phase of GaSb is marked for $Yb_5Ga_2Sb_6$.

Crystal structure. As discussed above, $Yb_5M_2Sb_6$ compounds crystallize in the $Ca₅Al₂Bi₆$ structure type comprising ${}_{\infty}^{1}(M_{2}Sb_{6})^{10}$ double chains separated by Yb atoms (Fig. 4a). In this crystal structure, single chains are formed by cornersharing $MSB₄$ tetrahedra, which are further bridged by Sb3 atoms to form double chains (Fig. 4b). It was previously reported that depending on the cation size *e.g.*, Ba or Ca, dimeric anion $(M_2Sb_6)^{12}$ or polymeric chains of $\frac{1}{\infty}(MSb_6)^{3}$ may also form, as in Ba_3AlSb_3 or Ca_3AlSb_3 , respectively.^{17, 40-42} In this case, the $\frac{1}{\infty} (M_2 \text{Sb}_6)^{10}$ double chain can be considered to be obtained by removing one Ca from the crystal structure of $Ca₃AlSb₃ (Ca₆Al₂Sb₆)$ which leads to oxidative coupling of Sb-Sb bonds in $\left(\text{Al}_2\text{Sb}_6 \right)^{25}$

The $Yb_5M_2Sb_6$ compounds crystallize in the orthorhombic unit cell *Pbam* (no. 55), with lattice parameters given in Table

1. Currently refined lattice parameters for $M = Ga$ and In are very close to the previously reported ones. In case of $M = A$ l, our refinement gives values close to the ones reported by Fornasini *et al.*⁴³ but substantially different than the ones reported by Todorov *et al.*, ²⁵ which needs further clarification. In the crystal structure of $Yb_5M_2Sb_6$, there are $3 \times Yb$ (Yb1, Yb2: $4g(x, y, 0)$; Yb3: $2a(0, 0, 0)$, $1 \times M(4h(x, y, \frac{1}{2}))$ and 3 \times Sb (Sb1: 4*g* (*x*, *y*, 0); Sb2, Sb3: 4*h* (*x*, *y*, ¹/₂)) positions. During the Rietveld refinements (see Fig. 2), all the atomic positions were refined with full occupancy. In Yb₅ M_2Sb_6 , MSb_4 tetrahedral distances vary from $2.59 - 2.81$ Å for Al, from 2.70 -2.84 Å for Ga and $2.81 - 2.95$ Å for In, in accordance with the increase in the atomic radius down the group III elements. The bridging Sb3-Sb3 distances on the other hand remain almost constant $(2.93 - 2.95 \text{ Å})$. Similar behaviour is observed in the $Ae_5\text{In}_2\text{Sb}_6$ ($Ae = \text{Ca}$, Sr, Ba) series where the Sb-Sb distances do not change even if the cation size changes dramatically.^{15, 44, 45} This may indicate that the space requirement is fulfilled by changing the size of the *M*Sb⁴ tetrahedra and relaxing the corresponding angles among the *M* and Sb atoms. While Yb1 atoms have $7 \times$ Sb and $2 \times M$ atoms as nearest neighbours, Yb2 and Yb3 atoms form an almost regular octahedral arrangement with $6 \times$ Sb atoms (Fig. 4c; interatomic distances of Yb1: 3.21 – 3.49 Å, 3.20 – 3.50 Å, and $3.25 - 3.59$ Å; Yb2: $3.16 - 3.22$ Å, $3.17 - 3.21$ Å and $3.20 -$ 3.23 Å; Yb3: 3.11, 3.11, and 3.16 Å; for *M* = Al, Ga and In, respectively).

Fig. 4 a) The crystal structure of $Yb_5M_2Sb_6$ ($M = AI$, Ga, and In) compounds crystallizing in the orthorhombic unit cell. **b**) Infinite double chains ${}_{\infty}^{1}(M_{2}Sb_{6})^{10}$ formed by Sb3-Sb3 bridging of *M*Sb4 tetrahedra. **c**) Local environments of Yb atoms.

Table 1: The lattice parameters (Å) of currently investigated samples and previously reported ones.

The electronic band structure and chemical bonding. The electronic DOS calculated for the title compounds are presented in Fig. 5. The top panels show the total DOS with the 4*f* contributions subtracted. The sharply peaked 4*f* states (not shown for clarity purposes) are mainly located between -2.5 and -2.0 eV in all cases. The middle (bottom) panels show the *s* (*p*) partial DOS of the Sb1, Sb2, Sb3 and the *M* atoms. The overall behavior observed in these figures are very similar for all three compounds. The occupied states are grouped in three energy ranges with approximate boundaries (a) -11 to -8 eV, (b) -5.5 to -4.5 eV ($M =$ Al, In) or -6.5 to -5 eV ($M =$ Ga), (c) -4.5 to 0 (Fermi energy) eV. The energy range -8, -11 eV is dominated by Sb *s* contributions, while somewhat smaller *M* atom *p* and *s* states also show up. The states of group (b) are mainly dominated by M atom s and Sb p contributions. These hybridizations are expected to take part in the *M*-Sb bonds of the *MS*b₄ tetrahedra. The group (a) and group (b) states have band gaps of 2.8, 2.0 and 2.3 eV for $M = Al$, Ga and In, respectively. The band gaps between group (b) and (c) states are, on the other hand, 0.03 , 0.6 and 0.4 eV for $M = Al$, Ga and In, respectively. The group (c) states are composed of Sb and *M p* states; the Yb 5*d* states (not shown) are sizeable only in the interval (-2.5, -0.5) eV with maximum values around 1 states eV^{-1} per spin. Sb1, Sb2, M p partial DOS and all Yb 5*d* partial DOS display a pseudogap behavior between Fermi energy and 1 eV, but Sb3 5*p* state contributions do not go to zero, rather they stay constant around 0.6 states eV^{-1} per spin (with the exception of some peaks). The Sb3 atoms form the Sb-Sb dimers bridging the MSh_4 tetrahedra. The different behavior of the Sb3 5*p* states in this energy range may reflect the Sb3-Sb3 two-center bonds detected in the ELI analysis (see below) and

S owes the most to these states.

 According to the topological analysis of the electron density, ED, Al loses about 1.2 electrons and In about 0.2, whereas Ga is almost neutral. In all cases and for all symmetry types of Yb atoms, the 4*f* occupancy was found to be 14, suggesting $a + 2$ valence. However, the calculated electron populations of the Yb atoms show that each Yb atom contributes a total of 0.8-0.9 electrons to the ELI bond basins. The topological analysis of the ELI reveals that the expected bonding situation in the $Yb_5M_2Sb_6$, $M = A1$, Ga, In compounds is realized only for the $M = A1$ case. The ELI distribution obtained for $Yb_5Al_2Sb_6$ is displayed in Fig. 6 using an isosurface value of $Y = 1.25$. The Sb-Al two-center bonds and the lone-pair like features of the Sb atoms are all separate. The basin intersection analysis shows that Sb contributions are about 3-4 times that of Al. The basins corresponding to the lone pairs of the Sb atoms contain Yb contributions between 5 and 10 % of the total basin electron populations. In contrast, in $Yb_5Ga_2Sb_6$ the Sb-Ga bond and lone pair attractors merge into a single attractor for the Sb3 symmetry type, while they remain separated for Sb1 and Sb2. In Yb₅In₂Sb₆ the attractors merge for both Sb1 and S3. Although the bond and lone pair attractors are separate for Sb2, there are contributions from the In atoms to the basins of the lone pairs at the level of Yb contributions, namely about 5- 10 per cent. The Sb3-Sb3 bond, found in all cases, has an electron population of 0.4, and a lower attractor value, $Y =$ 1.08-1.09, than the Sb-*M* and lone pair attractors

Fig. 5 Total and partial density of states of $Yb_5M_2Sb_6$ ($M = A1$, Ga, In) compounds. The vertical dashed line stands for the Fermi level.

Fig.6 Distribution of the electron localizability indicator in Yb₅Al₂Sb₆ (Yb: blue; Al: Red; Sb: black). The positions of the ELI maxima reflecting the Ga–Sb and Sb-Sb bonds and the 'lone pairs' are visualized by the isosurfaces with $Y = 1.25$.

Electronic transport. The $Yb_5M_2Sb_6$ structure can be rationalized using the Zintl-Klemm concept as discussed above, suggesting that $Yb_5M_2Sb_6$ compounds might exhibit semiconducting electronic behaviour similar to $Ca₅M₂Sb₆$ compounds. However, as predicted by DFT calculations, the electronic transport measurements of Yb₅M₂Sb₆ compounds reveal metallic behaviour, rather than semiconducting. As illustrated by Fig. 7a, Yb₅M₂Sb₆ compounds have very high *p*type carrier concentrations on the order of 5×10^{21} h⁺/cm³. The resistivity and Seebeck coefficients, shown in Fig. 7b and d, are low at room temperature and increase linearly with increasing temperature. The Hall mobility (Fig. 7c) is similar in magnitude to that observed in other $A_5M_2Sb_6$ compounds, and it decreases with temperature as expected when acoustic phonons are the primary scattering source. These results in $Yb_5Al_2Sb_6$ and $Yb_5In_2Sb_6$ are consistent with previous reports of metallic electronic conductivity.^{23, 25} The Seebeck coefficients of $Yb_5Al_2Sb_6$ in the current study are identical to those reported by Todorov *et al.*. ²⁵ There are several potential explanations for the observed metallic behaviour: i) a valence imbalance due to positively charged site defects, ii) valence imbalance resulting from mixed valence of Yb, or iii) $Yb_5M_2Sb_6$ compounds are semimetals in which the conduction band minima and valence band maxima overlap, as supported by DFT results. Each of these possibilities is explored below.

 Charged point defects are responsible for high carrier concentrations in several well-known thermoelectric materials $(La_{3-x}Te_4, Ba_8Ge_{43}\Box_3^{46-48})$, including AZn_2Sb_2 ($A = Sr$, Ca, Eu, Yb) Zintl compounds with the CaAl₂Si₂ structure type.^{49, 50} To explain the large observed carrier concentrations in $Yb_5M_2Sb_6$ compounds however, an unrealistically large concentration of point defects would be necessary. For example, if each Yb vacancy yields two holes, then a 15% Yb deficiency would correspond to a carrier concentration of 4×10^{21} h⁺/cm³. Subbarao *et al.* have suggested that Yb is in a mixed $2+/3+$ valence state 24 , as observed in several other Zintl phases.⁵¹ However, the presence of Yb^{3+} would be expected to lead to *n*type behaviour, rather than the observed *p*-type behaviour.

Finally, as DFT calculations suggest, $Yb_5M_2Sb_6$ compounds may have overlapping valence and conduction bands, leading to semimetallic behaviour. The temperature dependent transport of a semimetal resembles a degenerate (heavily doped) semiconductor, which has a finite band gap. There are, however, a few noticeable differences: for example the Seebeck coefficient for a degenerate semiconductor is 0 at 0 K and increases linearly with temperature, whereas that of a semimetal is often nonlinear (although also passes through the origin). More specifically, for a small overlap $E_g = -0.1$ eV, a semimetal that has large free carrier concentration reveals an upward deviation, whereas a semimetal with low free carrier concentration reveals a downward deviation. The Seebeck coefficient value of a semimetal is also affected by parameters of both the majority carrier band and the minority carrier band (such influence is small when the free carrier concentration is high), whereas for degenerate semiconductors, the minority band usually has negligible influence. The observed temperature dependency of the Seebeck coefficient (Fig. 7d), clearly nonlinear and increasing faster at higher temperatures, can be well explained under the framework of a semimetal with high free carrier concentration, using reasonable material parameters (for example, quantitatively assuming $E_g = -0.1eV$, $n = 2 \times 10^{21}$ h⁺/cm³, single parabolic band with effective mass of 1 for electrons and 2 for holes, deformation potential coefficient of 15eV for both, elastic constant $C_1 = 150$ GPa). This also explains the large Hall carrier concentration $(1/eR_H)$ that is largely temperature independent (Fig. 7a). The Hall mobility is low partly due to the large carrier concentration, and decreases with increasing temperature as a result of phonon scattering (Fig. 7c).

Fig. 7 a) $Yb_5M_2Sb_6$ compounds exhibit high *p*-type carrier concentrations with **b**) resistivity behaviour characteristic of a semimetal. **c**) Hall mobility is comparable to $Ca₅M₂Sb₆$ compounds with a similar structure type. **d**) $Yb_5M_2Sb_6$ displays low Seebeck coefficients.

Thermal transport. The total (κ_{total}) and lattice $(\kappa_{Lattice})$ thermal conductivities of the $Yb_5M_2Sb_6$ samples are shown in Fig. 8. The electronic contribution, κ_e , was estimated using the Wiedemann-Franz relation ($\kappa_e = LT/\rho$). Calculating the Lorenz number, L, using a single parabolic band model yields κ_e >

indicating that *L* in these compounds are very poorly described by this model.⁵² Consequently, the non-degenerate value, $L =$ 1.5×10^{-8} WΩK⁻², was used to estimate $κ$ _L in Fig. 8. This leads to lattice thermal conductivities $($ \sim 0.6 W/mK) at high temperatures that are comparable to κ_L in $Ca_5M_2Sb_6$ compounds.

Fig. 8 The total thermal conductivity in $Yb_5M_2Sb_6$ compounds is high due to the large electronic contribution. Subtracting the electronic term (assumes $L = 1.5 \times 10^{-8} \text{ W}\Omega\text{K}^{-2}$) yields lattice thermal conductivities comparable to that of other $A_5M_2Sb_6$ phases.

 Table 2 shows the sound velocities and elastic moduli of Yb₅ M_2 Sb₆ compounds, obtained from ultrasonic measurements. The sound velocity in a solid is related to the material's density, *d*, and stiffness, *E*, by the general expression $v \propto \sqrt{E/d}$. In $Yb_5M_2Sb_6$, the transition towards heavier triel elements (Al, Ga, In) leads to increased theoretical density, decreased lattice stiffness, and a corresponding decrease in the speed of sound. Compared with the $Ca₅M₂Sb₆$ series, the speeds of sound in Yb₅M₂Sb₆ compounds are approximately 20% lower, which implies that κ_L in the Yb-based compounds should also be lower. However, the large electronic thermal conductivity in these compounds makes it difficult to accurately compare the lattice thermal conductivities.

Table 2: Physical properties of $Yb_5M_2Sb_6$ compounds: theoretical density, *d*; shear and bulk modulus, *G* and *K*; transverse and longitudinal sound velocities, v_T and v_L .

Compounds	d	G	K	ν_{Γ}	и.
	(g/cm^3)	GPa)	(GPa)	(m/s)	(m/s)
$Yb_5Al_2Sb_6$	7 47	28.4	39.4	1950	3215
$Yb_5Ga_2Sb_6$	7.68	26.5	34.9	1860	3025
Yb5In,Sb6	7.89	25.2	34.1	1785	2930

Figure of merit. The $Yb_5M_2Sb_6$ compounds have similar figure of merit, *zT*, values (Fig. 9). The low *zT* values (< 0.15) are attributable to the metallic electronic properties of the samples. A band gap between bonding and anti-bonding states is necessary for good thermoelectric performance because it

c

allows for a single carrier type to dominate transport.⁵³ In a semimetal, the two competing carrier types will always lead to low, compensated Seebeck coefficients. Efforts to increase the *zT* in these compounds should thus be directed at opening a band gap and increasing its magnitude, perhaps through substitutions on the cation or pnictogen site.

Fig. 9 The figures of merit of $Yb_5M_2Sb_6$ compounds are lower than 0.15 due to semimetallic transport behaviour.

Conclusions

 $Yb_5M_2Sb_6$ Zintl compounds of $(M = Al, Ga, and In)$ were obtained in very high yield by ball milling followed by hot pressing. The band structure calculations revealed finite density of states at the Fermi level implying semimetallic behaviour. High temperature thermoelectric properties measurements show that all three compounds have relatively low electrical resistivity, low Seebeck coefficients and high total thermal conductivities in agreement with the calculations. Consequently, the thermoelectric figures of merit of all compounds remain relatively low, less than 0.15, in the whole temperature range investigated.

Acknowledgements

U. A. greatly acknowledges the financial assistance of The Scientific and Technological Research Council of Turkey. This research was partially carried out at the Jet Propulsion Laboratory, California Institute of Technology, under a contract with the National Aeronautics and Space Administration and was supported by the NASA Science Missions Directorate's Radioisotope Power Systems Technology Advancement Program. A. O. thanks Ulrike Nitzsche from IFW Dresden, Germany for technical help in computational work.

Notes and references

- *a* Department of Applied Physics and Materials Science, California Institute of Technology, 1200 E California Blvd, Pasadena, USA
- *b* Thermal Energy Conversion Technologies Group, Jet Propulsion Laboratory, 4800 Oak Grove Drive, Pasadena, USA

 Max Planck Institute for Chemical Physics of Solids, Nöthnitzer Str. 40, Dresden, Germany

- 1. G. J. Snyder and E. S. Toberer, *Nature Mater.*, 2008, 7, 105-114.
- 2. F. J. DiSalvo, *Science*, 1999, 285, 703-706.
	- 3. S. M. Kauzlarich, S. R. Brown and G. J. Snyder, *Dalton Trans*, 2007, DOI: 10.1039/b702266b, 2099-2107.
- 4. E. S. Toberer, A. F. May and G. J. Snyder, *Chem. Mater.*, 2010, 22, 624-634.
- 5. S. M. Kauzlarich, *Chemistry, Structure, and Bonding of Zintl Phases and Ions*, Wiley-VCH, 1996.
- 6. E. S. Toberer, A. Zevalkink and G. J. Snyder, *J. Mater. Chem.*, 2011, 21, 15843-15852.
- 7. S. K. Bux, A. Zevalkink, O. Janka, D. Uhl, S. Kauzlarich, J. G. Snyder and J. P. Fleurial, *J Mater Chem A*, 2014, 2, 215-220.
- 8. S. R. Brown, S. M. Kauzlarich, F. Gascoin and G. J. Snyder, *Chem. Mater.*, 2006, 18, 1873-1877.
- 9. U. Aydemir, L. Akselrud, W. Carrillo-Cabrera, C. Candolfi, N. Oeschler, M. Baitinger, F. Steglich and Y. Grin, *J. Am. Chem. Soc.*, 2010, 132, 10984-10985.
- 10. C. Candolfi, U. Aydemir, A. Ormeci, W. Carrillo-Cabrera, U. Burkhardt, M. Baitinger, N. Oeschler, F. Steglich and Y. Grin, *J. Appl. Phys.*, 2011, 110, 043715.
- 11. C. Candolfi, U. Aydemir, M. Baitinger, N. Oeschler, F. Steglich and Y. Grin, *J. Appl. Phys.*, 2012, 111, 043706.
- 12. C. Candolfi, U. Aydemir, A. Ormeci, M. Baitinger, N. Oeschler, F. Steglich and Y. Grin, *Phys Rev B*, 2011, 83, 205102.
- 13. S. I. Johnson, A. Zevalkink and G. J. Snyder, *J Mater Chem A*, 2013, 1, 4244-4249.
- 14. E. S. Toberer, A. Zevalkink, N. Crisosto and G. J. Snyder, *Adv. Funct. Mater.*, 2010, 20, 4375-4380.
- 15. A. Zevalkink, J. Swallow and G. J. Snyder, *Dalton T*, 2013, 42, 9713-9719.
- 16. P. Verdier, P. Lharidon, M. Maunaye and Y. Laurent, *Acta Crystallogr B*, 1976, 32, 726-728.
- 17. G. Cordier, H. Schafer and M. Stelter, *Z Naturforsch B*, 1984, 39, 727-732.
- 18. Y. L. Yan and Y. X. Wang, *J. Mater. Chem.*, 2011, 21, 12497- 12502.
- 19. Y. L. Yan, Y. X. Wang and G. B. Zhang, *Comp Mater Sci*, 2014, 85, 88-93.
- 20. A. Zevalkink, G. S. Pomrehn, S. Johnson, J. Swallow, Z. M. Gibbs and G. J. Snyder, *Chem. Mater.*, 2012, 24, 2091-2098.
- 21. A. Zevalkink, J. Swallow and G. J. Snyder, *J. Electron. Mater.*, 2012, 41, 813-818.
- 22. A. Zevalkink, E. S. Toberer, T. Bleith, E. Flage-Larsen and G. J. Snyder, *J. Appl. Phys.*, 2011, 110, 013721.
- 23. S. J. Kim, J. R. Ireland, C. R. Kannewurf and M. G. Kanatzidis, *J. Solid State Chem.*, 2000, 155, 55-61.
- 24. U. Subbarao, S. Sarkar, V. K. Gudelli, V. Kanchana, G. Vaitheeswaran and S. C. Peter, *Inorg Chem*, 2013, 52, 13631- 13638.
- 25. I. Todorov, D. Y. Chung, L. Ye, A. J. Freeman and M. G. Kanatzidis, *Inorg Chem*, 2009, 48, 4768-4776.
- 26. L. Akselrud and Y. Grin, *J Appl Crystallogr*, 2014, 47, 803-805.
- 27. S. Iwanaga, E. S. Toberer, A. LaLonde and G. J. Snyder, *Rev. Sci. Instrum.*, 2011, 82, 063905.
- 28. K. A. Borup, E. S. Toberer, L. D. Zoltan, G. Nakatsukasa, M. Errico, J. P. Fleurial, B. B. Iversen and G. J. Snyder, *Rev. Sci. Instrum.*, 2012, 83, 123902.
- 29. H. E. K. Koepernik, *Phys Rev B*, 1999, 59, 1743-1757.
30. J. P. Perdew and Y. Wang, *Phys Rev B*, 1992, 45, 1324
	- 30. J. P. Perdew and Y. Wang, *Phys Rev B*, 1992, 45, 13244-13249.
- 31. V. I. Anisimov, J. Zaanen and O. K. Andersen, *Phys Rev B*, 1991, 44, 943-954.
- 32. H. Eschrig, K. Koepernik and I. Chaplygin, *J. Solid State Chem.*, 2003, 176, 482-495.
- 33. R. F. W. Bader, *Atoms in Molecules : A Quantum Theory*, Clarendon Press, Oxford, 1990.
-
- 34. M. Kohout, *Faraday Discuss.*, 2007, 135, 43-54.
- 35. F. R. Wagner, V. Bezugly, M. Kohout and Y. Grin, *Chem-Eur J*, 2007, 13, 5724-5741.
- 36. S. Raub and G. Jansen, *Theor. Chem. Acc.*, 2001, 106, 223-232.
- 37. A. Ormeci, H. Rosner, F. R. Wagner, M. Kohout and Y. Grin, *J. Phys. Chem. A*, 2006, 110, 1100-1105.
- 38. M. Kohout, Program DGRID, Version 4.6, Radebeul, Germany, 2011.
- 39. M. E. Straumanis, Aka, E.Z., *J. Appl. Phys.*, 1952, 23, 330-334.
- 40. G. Cordier, G. Savelsberg and H. Schafer, *Z Naturforsch B*, 1982, 37, 975-980.
- 41. W. G. Zeier, A. Zevalkink, E. Schechtel, W. Tremel and G. J. Snyder, *J. Mater. Chem.*, 2012, 22, 9826-9830.
- 42. A. Zevalkink, E. S. Toberer, W. G. Zeier, E. Flage-Larsen and G. J. Snyder, *Energ Environ Sci*, 2011, 4, 510-518.
- 43. M. L. Fornasini and P. Manfrinetti, *Z Krist-New Cryst St*, 2009, 224, 345-346.
- 44. G. Cordier, H. Schafer and M. Stelter, *Z Naturforsch B*, 1985, 40, 5-8.
- 45. G. Cordier and M. Stelter, *Z Naturforsch B*, 1988, 43, 463-466.
- 46. A. F. May, J.-P. Fleurial and G. J. Snyder, *Phys. Rev. B*, 2008, 78, 125205.
- 47. U. Aydemir, C. Candolfi, H. Borrmann, M. Baitinger, A. Ormeci, W. Carrillo-Cabrera, C. Chubilleau, B. Lenoir, A. Dauscher, N. Oeschler, F. Steglich and Y. Grin, *Dalton Transactions*, 2010, 39, 1078-1088.
- 48. C. Candolfi, U. Aydemir, M. Baitinger, N. Oeschler, F. Steglich and Y. Grin, *J. Electron. Mater.*, 2010, 39, 2039-2042.
- 49. G. S. Pomrehn, A. Zevalkink, W. G. Zeier, A. van de Walle and G. J. Snyder, *Angew. Chem.*, 2014, 126, 3490-3494.
- 50. A. Zevalkink, W. G. Zeier, E. Cheng, J. Snyder, J. P. Fleurial and S. Bux, *Chem. Mater.*, 2014, 26, 5710-5717.
- 51. J. R. Salvador, D. Bilc, S. D. Mahanti, T. Hogan, F. Guo and M. G. Kanatzidis, *J. Am. Chem. Soc.,* 2004, 126, 4474-4475.
- 52. E. Flage-Larsen and O. Prytz, *Appl. Phys. Lett.*, 2011, 99, 202108.
- 53. G. D. Mahan, *Solid State Phys.*, 1998, 51, 81-157.

Thermoelectric properties of the Zintl phases $Yb_5M_2Sb_6$ **(** $M = AI$ **, Ga, In)**

Umut Aydemir^{a,*}, Alex Zevalkink^b, Alim Ormeci^c, Heng Wang^a, Saneyuki Ohno^a, Sabah Bux^b and G. Jeffrey Snyder^a

Graphical abstract caption:

Zintl compounds of $Yb_5M_2Sb_6 (M = A1, Ga, and In)$ exhibit semimetallic properties with high *p*type carrier concentrations, low resistivities and low Seebeck coefficients in agreement with our band structure calculations.

Graphical abstract:

