# **RSC Advances**



## **REVIEW**

View Article Online
View Journal | View Issue



Cite this: RSC Adv., 2024, 14, 18978

# Synthesis and properties of anhydrous rare-earth phosphates, monazite and xenotime: a review

Saehwa Chong, (1) \*\* Brian J. Riley, (1) \*\* Xiaonan Lu, (1) \*\* Jincheng Du, (1) \*\* Thiruvillamalai Mahadevan \*\* and Vinay Hegde \*\*

The synthesis methods, crystal structures, and properties of anhydrous monazite and xenotime (REPO $_4$ ) crystalline materials are summarized within this review. For both monazite and xenotime, currently available Inorganic Crystal Structure Database data were used to study the effects of incorporating different RE cations on the unit cell parameters, cell volumes, densities, and bond lengths. Domains of monazite-type and xenotime-type structures and other AXO $_4$  compounds (A = RE; X = P, As, V) are discussed with respect to cation sizes. Reported chemical and radiation durabilities are summarized. Different synthesis conditions and chemicals used for single crystals and polycrystalline powders, as well as first-principles calculations of the structures and thermophysical properties of these minerals are also provided.

Received 14th February 2024 Accepted 26th May 2024

DOI: 10.1039/d4ra01142b

rsc.li/rsc-advances

## 1 Introduction

Monazite and xenotime compounds are anhydrous rare-earth (RE) phosphates with the chemical formula REPO<sub>4</sub> but with different crystal symmetries. The mineral name "monazite" is derived from "monazein" meaning "to be solitary" in Greek, and the mineral name "xenotime" is derived from the combined words of "xenos" and "time" meaning "foreign" and "honor" in Greek.1 Naturally occurring monazite and xenotime minerals are often found as accessory minerals along with allanite, sphene, fluorite, and apatite in granitic rocks, pegmatites, carbonatites, and gneisses. 1,2 The monazite and xenotime minerals found in nature often contain mixed RE elements as well as thorium and/or uranium along with other oxides, and the deposits are found in various countries including Australia, Brazil, Canada, China, India, Italy, Madagascar, Sri Lanka, and the United States. 1,3-5 For example, the compositions of natural monazites from seven different regions were 35-65 mass% of mixed REs, 24-30 mass% of P2O5, 0-16 mass% of UO2, 4-14 mass% of ThO2, and 2-7 mass% of other oxides, and among the mixed REs, La, Ce, and Nd were the major components. 2,3,6 The natural xenotime mineral generally contains mixed heavy REs (i.e., RE = Gd  $\rightarrow$  Lu + Y, Sc) and less actinides compared to monazite (i.e., RE = La  $\rightarrow$  Dy). The compositions of natural xenotime from two regions were 62-65 mass% of mixed RE oxides, 29-36 mass% of P<sub>2</sub>O<sub>5</sub>, 0.1-1.6 mass% of UO<sub>2</sub>, 0.2-0.3 mass% of ThO<sub>2</sub>, and 0.1-1.3 mass% of other oxides, and among the mixed REs, Y, Gd, Dy, and Er were the major components. 7.8 Rhabdophane minerals are hydrated RE-phosphates with the chemical formula of REPO<sub>4</sub>· xH<sub>2</sub>O and they are found as accessory minerals in granitic rocks. Rhabdophane minerals generally contains mixed REs with relatively high amounts of Ce and La elements, U and Th actinides, and one water molecule (7–8 mass%) per formula unit. 9 Studies have shown that the rhabdophane structure can transform to the monoclinic monazite structure through heat treatments. 10,11

Both monazite and xenotime compounds have attractive physical and chemical properties over a wide range of applications including nuclear waste forms, 12-20 light emitting materials (e.g., as scintillators for  $\gamma$ -ray or X-ray detection, as thermophosphors),1,21-25 and coating materials.26-28 For applications in nuclear waste forms, the REPO<sub>4</sub> compounds have been studied extensively due to high chemical durabilities, resistance to radiation damage, a wide variety of natural analogs, and their potential to incorporate RE, U, and Th elements in the structures. 12-15,17,29 The flexibility of the RE-O bond distances in REO<sub>x</sub> polyhedra, while maintaining the structure, enables the incorporation and substitution of different heavy radioactive cations. This possibility of monazite and xenotime to incorporate many different radionuclides into a single structure makes it an ideal waste form that eliminates the need to determine the radionuclide partition coefficients between phases and concerns for differences in mechanical properties and corrosion mechanisms.12 Both monazite and xenotime can be synthesized relatively easily (see Section 2 for details), and their chemical durabilities are much higher (up to a factor of 20 in leach rates for certain elements) than borosilicate glass waste forms.12 Natural monazite was shown to maintain high retention of fission products during erosion,

<sup>&</sup>lt;sup>a</sup>Pacific Northwest National Laboratory, Richland, WA 99354, USA. E-mail: saehwa. chong@pnnl.gov; brian.riley@pnnl.gov; Tel: +1-509-375-2469; +1-509-372-4651 <sup>b</sup>University of North Texas, Denton, TX 76203, USA

<sup>&</sup>lt;sup>c</sup>Citrine Informatics, Redwood City, CA 94063, USA

Review

which was attributed to its slow dissolution rate.  $^{13}$  In addition, both compounds have high thermal stabilities with melting temperatures above 2000  $^{\circ}$ C. $^{12}$ 

Monazite compounds can be used as light emitting materials with interesting optical properties. 21-23 Wang et al. 21 investigated the luminescence behavior of Eu-doped LaPO4 nanorods and showed the emission spectrum dependency on polarization for electric and magnetic dipole transitions. With high quantum efficiency and a high degree of polarization, the Eu-doped LaPO<sub>4</sub> nanorods can be used as high resolution probes in 3D flow-shear tomography.21 Hashimoto et al.22 observed that doping a small amount of Th and borate into monazite compounds containing mixed RE cations of La, Ce, and/or Tb improved the light emission intensity and stability of green light, and these phosphors used in fluorescent lamps can minimize the brightness loss at high temperatures. Jeon et al.23 doped La- and Ca-containing monazite compounds with Eu and/or Dy ions, and single-phase white-light emission was observed at near-ultraviolet excitation.

The LaPO<sub>4</sub> monazite has also been explored as a coating material to minimize high-temperature oxidation.26-28 Morgan et al.27 showed that LaPO4 and alumina interfaces without impurities were stable and retained the ability to debond after heat treatment at 1600 °C in air but observed the formation of La-containing β-alumina-magnetoplumbite in the presence of alkali metal or divalent elements near the interface. Kuo and Kriven<sup>26</sup> showed that three laminates composed of LaPO<sub>4</sub> as one component and  $Al_2O_3$ ,  $Y_3Al_5O_{12}$ , or  $LaAl_{11}O_{18}$  as the other component were thermally stable up to 1600 °C and could be used as high-temperature materials in an oxidizing environment. Boakye et al.28 showed that coating the SiC fibers with LaPO<sub>4</sub> did not degrade fiber strength, and a heat treatment at 1200 °C for 1-20 h in argon resulted in the formation of La<sub>2</sub>Si<sub>2</sub>O<sub>7</sub>, while the monazite was stable with SiC when the same heat treatment was done in air.

In this review, synthesis methods, crystal structures, and properties of anhydrous REPO<sub>4</sub> compounds are summarized. Studies on the chemical durability and radiation stability, as well as different models for phase stability of monazite and xenotime are also summarized.

## 2 Synthesis methods

Different methods, including flux-assisted, solid state, hydrothermal, aqueous, dehydration, and gel-based methods, have been used for the synthesis of monazite and xenotime compounds. Table 1 summarizes the synthesis conditions for  $REPO_4$  compounds.

Feigelson<sup>30</sup> synthesized single crystals of LaPO<sub>4</sub>, CePO<sub>4</sub>, PrPO<sub>4</sub>, NdPO<sub>4</sub>, SmPO<sub>4</sub>, EuPO<sub>4</sub>, and GdPO<sub>4</sub> monazite compounds as well as TbPO<sub>4</sub> and YbPO<sub>4</sub> xenotime compounds using Pb<sub>2</sub>P<sub>2</sub>O<sub>7</sub> flux. The mixture of RE oxides and lead hydrogen phosphate (PbHPO<sub>4</sub>) with the mass ratio of 1:24 was placed in the Pt crucible and heated to 1300 °C at 300 °C h<sup>-1</sup> and dwelled for 12 h at 1300 °C, and PbHPO<sub>4</sub> was converted to lead pyrophosphate (Pb<sub>2</sub>P<sub>2</sub>O<sub>7</sub>) on heating. The mixture was slowly cooled to 975 °C at <4 °C h<sup>-1</sup> and then naturally cooled to room

temperature as the authors believed that crystallization did not proceed below 975 °C. The single crystals of monazite compounds were separated from the flux using diluted HNO3 solution. The monazite crystals had platelike morphologies, and the crystal sizes of LaPO<sub>4</sub>, PrPO<sub>4</sub>, and NdPO<sub>4</sub> were  $\sim$ 6 mm  $\times \sim$ 3 mm  $\times \sim$ 0.5 mm (the crystal sizes of other monazites were not reported). Decreasing cooling rate increased the crystal sizes of xenotime compounds. For YbPO<sub>4</sub>, a plate crystal with dimensions of 45 mm imes 25 mm imes 0.25 mm was obtained when cooled at 0.5 °C h<sup>-1</sup>. The single crystal or polycrystalline compound of TbPO4 could be prepared using TbO2-x with PbHPO<sub>4</sub> or H<sub>3</sub>PO<sub>4</sub> respectively, and similar optical characteristics were observed from each compound. For the flux matrix, Pb<sub>2</sub>P<sub>2</sub>O<sub>7</sub> was the main phase, but other phosphates including Pb<sub>5</sub>P<sub>4</sub>O<sub>15</sub>, Pb<sub>4</sub>P<sub>2</sub>O<sub>9</sub>, and/or Pb<sub>3</sub>P<sub>2</sub>O<sub>8</sub> were found with loss of phosphorus after formation of REPO<sub>4</sub>.

Similar to Feigelson's flux method, Mullica *et al.*<sup>31,40,45</sup> synthesized the single crystals of LaPO<sub>4</sub>, PrPO<sub>4</sub>, NdPO<sub>4</sub>, SmPO<sub>4</sub>, EuPO<sub>4</sub>, and GdPO<sub>4</sub> using Pb<sub>2</sub>P<sub>2</sub>O<sub>7</sub> as a flux. The mixture of RE oxides and PbHPO<sub>4</sub> with the mass ratio of 1:17 was placed in a Pt crucible and heated to 1360 °C for 16 h. After heat treatment, the mixture was slowly cooled to 900 °C at 1 °C h<sup>-1</sup> and then naturally cooled to room temperature.

Hirsch *et al.*<sup>35</sup> used a solid-state method to prepare polycrystalline powders of LaPO<sub>4</sub>, PrPO<sub>4</sub>, and mixed La<sub>1-x</sub>Pr<sub>x</sub>PO<sub>4</sub> monazite compounds. The appropriate amounts of RE oxides and NH<sub>4</sub>H<sub>2</sub>PO<sub>4</sub> (ADP) were homogenized, pressed into pellets, placed in alumina crucibles, and heated at 1250 °C for 24 h at ambient atmosphere, and the final products were pure monazites.<sup>35</sup> Perrière *et al.*<sup>34</sup> used a similar method to synthesize LaPO<sub>4</sub>, CePO<sub>4</sub>, PrPO<sub>4</sub>, NdPO<sub>4</sub>, SmPO<sub>4</sub>, EuPO<sub>4</sub>, and GdPO<sub>4</sub>. The mixture of RE oxides and ADP was heated at 1350 °C for 2 h in air twice to make pure monazite powders.<sup>34</sup>

Khalili *et al.*<sup>36</sup> prepared LaPO<sub>4</sub> monazite, Lu<sub>2</sub>O<sub>3</sub> xenotime, and Yb<sub>2</sub>O<sub>3</sub> xenotime using RE<sub>2</sub>O<sub>3</sub> and H<sub>3</sub>PO<sub>4</sub>. Powder of RE<sub>2</sub>O<sub>3</sub> (0.002 mol) was added to round bottomed flask containing 13.7 mL of 14.6 M H<sub>3</sub>PO<sub>4</sub> and stirred with magnetic stir for 1–24 h. The solution was diluted by adding 100 mL of water and refluxed at 130 °C for 2 h. The precipitate was filtered and washed with DIW. The sample was dried overnight and then heated to 80 °C for 1 h, and half of sample was heated at 200 °C for up to 48 h for complete dehydration. Sample heated at 80 and 200 °C were compared. The synthesized LaPO<sub>4</sub> monazite was a polycrystalline powder containing some rhabdophane, and the xenotime powders were pure LuPO<sub>4</sub> and YbPO<sub>4</sub> compounds.

Cao et al.  $^{32}$  synthesized LaPO $_4$  and CePO $_4$  nanorods using LaNO $_3$ , CeNO $_3$ , and H $_3$ PO $_4$  precursors. Here, 1 M La(NO $_3$ ) $_3$  or 1 M Ce(NO $_3$ ) $_3$  and 0.7 M H $_3$ PO $_4$  were added to a solution of cetrimonium bromide in cyclohexane and n-pentanol. Solutions were mixed for 30 min and transferred to autoclaves. The autoclaves were heated at 140 °C for 12 h and cooled to room temperature. The crystals were washed with ethanol and DIW several times and dried in vacuum at room temperature. The obtained LaPO $_4$  and CePO $_4$  nanorods had about 5  $\mu$ m lengths and 20–60 nm diameters.

Table 1 Summary of monazite and xenotime synthesis. La  $\rightarrow$  Dy\* are monazite compounds, and Tb  $\rightarrow$  Lu + Y, Sc are xenotime compounds. For the synthesized compound, S and P denote single crystal and polycrystalline compound. The ratio represents the mass ratio of RE oxide to flux

RE	Form	Method	Precursors	Flux	Ratio	T (°C)	$t_{\rm d}$ (h)	<i>T</i> <sub>c</sub> (°C)	<i>r</i> <sub>c</sub> (°C h <sup>−1</sup> )	Ref.
La	S	Flux	La <sub>2</sub> O <sub>3</sub> , PbHPO <sub>4</sub>	$Pb_2P_2O_7$	1:24	1300	12	975	2	30
La	S	Flux	$La_2O_3$ , PbHPO <sub>4</sub>	$Pb_2P_2O_7$	1:17	1360	16	900	1	31
La	S	Hydrothermal	LaCl <sub>3</sub> ·7H <sub>2</sub> O, H <sub>3</sub> PO <sub>4</sub>	_	_	140	12	_	_	32
La	S	Hydrothermal	$La(NO_3)_3 \cdot 6H_2O$ , $NaH_2PO_4$	_	_	120-200	_	_	_	33
La	P	Solid state	$La_2O_3$ , $NH_4H_2PO_4$	_	_	1350	2	_	_	34
La	P	Solid state	$La_2O_3$ , $NH_4H_2PO_4$	_	_	1250	24	_	_	35
La	P	Aqueous	$La_2O_3$ , $H_3PO_4$	_	_	80-200	1-48	_	_	36
La	P	Dehydration	$LaPO_4 \cdot xH_2O$	_	_	500	1	_	_	10
Ce	S	Flux	CeO <sub>2</sub> , PbHPO <sub>4</sub>	$Pb_2P_2O_7$	1:24	1300	12	975	1	30
Ce	S	Hydrothermal	$Ce(NO_3)_3 \cdot 6H_2O$ , $H_3PO_4$	_	_	140	12	_	_	32
Ce	P	Solid state	$CeO_2$ , $NH_4H_2PO_4$	_	_	1350	2		_	34
Ce	P	Dehydration	$CePO_4 \cdot xH_2O$	_	_	800	1	_	_	37
Ce	P	Dehydration	$CePO_4 \cdot xH_2O$	_	_	600	1	_	_	10
Pr	S	Flux	Pr <sub>6</sub> O <sub>11</sub> , PbHPO <sub>4</sub>	$Pb_2P_2O_7$	1:24	1300	12	975	2	30
Pr	P	Solid state	$Pr_2O_3$ , $NH_4H_2PO_4$	_	_	1250	24	_	_	35
Pr	P	Solid state	$Pr_2O_3$ , $NH_4H_2PO_4$	_	_	1350	2	_	_	34
Pr	P	Dehydration	$PrPO_4 \cdot xH_2O$	_	_	700	1	_	_	10
Nd	S	Flux	$Nd_2O_3$ , $KH_2PO_4$	$K_6P_4O_{13}$	1:4	1000	24	840	<0.2	38
Nd	S	Flux	Nd <sub>2</sub> O <sub>3</sub> , Li <sub>2</sub> CO <sub>3</sub> , MoO <sub>3</sub>	$Li_2Mo_2O_7$	1:4	1020	720	_	<0.2	39
Nd	S	Flux	Nd <sub>2</sub> O <sub>3</sub> , PbHPO <sub>4</sub>	$Pb_2P_2O_7$	1:24	1300	12	975	2	30
Nd	S	Flux	Nd <sub>2</sub> O <sub>3</sub> , PbHPO <sub>4</sub>	$Pb_2P_2O_7$	1:17	1360	16	900	1	40
Nd	P	Solid state	$Nd_2O_3$ , $NH_4H_2PO_4$	_	_	1350	2	_	_	34
Nd	P	Dehydration	$NdPO_4 \cdot xH_2O$	_	_	700	1		_	10
Sm	S	Flux	$Sm_2O_3$ , $PbHPO_4$	$Pb_2P_2O_7$	1:24	1300	12	975	<4	30
Sm	P	Solid state	$Sm_2O_3$ , $NH_4H_2PO_4$	_	_	1350	2		_	34
Sm	P	Dehydration	$SmPO_4 \cdot xH_2O$	_	_	700	1		_	10
Eu	S	Flux	$Eu_2O_3$ , PbHPO <sub>4</sub>	$Pb_2P_2O_7$	1:24	1300	12	975	<4	30
Eu	P	Solid state	$Eu_2O_3$ , $NH_4H_2PO_4$	_	_	1350	2		_	34
Gd	S	Flux	$Gd_2O_3$ , $PbHPO_4$	$Pb_2P_2O_7$	1:24	1300	12	975	<4	30
Gd	P	Solid state	$Gd_2O_3$ , $NH_4H_2PO_4$	_	_	1350	2		_	34
Gd	P	Dehydration	$GdPO_4 \cdot xH_2O$	_	_	800	1		_	10
Tb*	P	Aqueous	$Tb(NO_3)_3 \cdot nH_2O, H_3PO_4$	_	_	950	8	_	_	41
Dy*	P	Aqueous	$Dy(NO_3)_3 \cdot nH_2O, H_3PO_4$	_	_	730	4	_	_	41
Tb	S	Flux	$Gd_2O_3$ , $PbHPO_4$	$Pb_2P_2O_7$	1:24	1300	12	975	<4	30
Tb	P, S	Aqueous-flux	$Tb(NO_3)_3 \cdot xH_2O$ , $NH_4H_2PO_4$	Na <sub>2</sub> CO <sub>3</sub> -MoO <sub>3</sub>	$1:50^{a}$	1350	15	870	3	42
Dy	P	Dehydration	$DyPO_4 \cdot xH_2O$	_	_	1050	1	_	_	10
Dy	P, S	Aqueous-flux	$Dy(NO_3)_3 \cdot xH_2O$ , $NH_4H_2PO_4$	NaHCO <sub>3</sub> -MoO <sub>3</sub>	$1:50^{a}$	1375	144-168	870	3	43
Но	P, S	Aqueous-flux	$Ho(NO_3)_3 \cdot xH_2O$ , $NH_4H_2PO_4$	Na <sub>2</sub> CO <sub>3</sub> -MoO <sub>3</sub>	$1:50^{a}$	1350	15	870	3	42
Er	P, S	Aqueous-flux	$Er(NO_3)_3 \cdot xH_2O$ , $NH_4H_2PO_4$	NaHCO <sub>3</sub> -MoO <sub>3</sub>	$1:50^{a}$	1375	144-168	870	3	43
Tm	P, S	Aqueous-flux	$Tm(NO_3)_3 \cdot xH_2O$ , $NH_4H_2PO_4$	Na <sub>2</sub> CO <sub>3</sub> -MoO <sub>3</sub>	$1:50^{a}$	1350	15	870	3	42
Yb	S	Flux	$Yb_2O_3$ , $PbHPO_4$	$Pb_2P_2O_7$	1:24	1300	12	975	0.5	30
Lu	P, S	Aqueous-flux	$Lu(NO_3)_3 \cdot xH_2O$ , $NH_4H_2PO_4$	Na <sub>2</sub> CO <sub>3</sub> -MoO <sub>3</sub>	$1:50^{a}$	1350	15	870	3	42
Y	P, S	Aqueous-flux	$Y(NO_3)_3 \cdot xH_2O$ , $NH_4H_2PO_4$	NaHCO <sub>3</sub> -MoO <sub>3</sub>	$1:50^{a}$	1375	144-168	870	3	43
Y	S	Flux	$Y_2O_3$ , PbHPO <sub>4</sub>	$Pb_2P_2O_7$	1:24	1357	Several days	897	1	44
Sc	S	Flux	$Sc_2O_3$ , PbHPO <sub>4</sub>	$Pb_2P_2O_7$	1:24	1357	Several days	897	1	44

<sup>&</sup>lt;sup>a</sup> The molar ratio of REPO<sub>4</sub> to flux. The  $t_d$  is the dwell time, " $T_c$ " represents the temperature that the mixture was slowly cooled to grow single crystals, and  $r_c$  is the cooling rate.

Li and Ma<sup>33</sup> synthesized LaPO<sub>4</sub>:Eu crystals using La(NO<sub>3</sub>)<sub>3</sub>·6H<sub>2</sub>O and Eu(NO<sub>3</sub>)<sub>3</sub>·5H<sub>2</sub>O with a molar ratio of 1:0.05 dissolved in DIW, and addition 5 mL of 1 M NaH<sub>2</sub>PO<sub>4</sub> aqueous solution was done while stirring. Here, HNO<sub>3</sub> or NaOH were added to adjust to a specific pH. The solution was put into an autoclave and heated at different temperature (120–180 °C). The resulting product was centrifuged and washed with DIW and dried at 60 °C for 12 h.

Wang et al.<sup>39</sup> synthesized a single crystal of NdPO<sub>4</sub> using  $\text{Li}_2\text{Mo}_2\text{O}_7$  as a flux. The  $\text{Li}_2\text{CO}_3$  and  $\text{MoO}_3$  powders were used to prepare the  $\text{Li}_2\text{Mo}_2\text{O}_7$  flux. The mixture of Nd<sub>2</sub>O<sub>3</sub> and  $\text{Li}_2\text{Mo}_2\text{O}_7$ 

with the mass ratio of 1:4 was placed in the Pt crucible and heated to 1020 °C for 24 h. A seed crystal was immersed in the solution and rotated at 30 rpm, and the single crystal was grown in the mixture cooling at 0.05–0.2 °C h<sup>-1</sup> for  $\sim$ 30 d. The resulting single crystal had the size of several millimeters.

Poitrasson *et al.*<sup>46</sup> synthesized polycrystalline NdPO<sub>4</sub> and GdPO<sub>4</sub> compounds using a combined method of gelation and flux-assisted growth. The NdPO<sub>4</sub> gel was prepared by dissolving Nd(NO<sub>3</sub>)<sub>3</sub> and adding (NH<sub>4</sub>)<sub>2</sub>HPO<sub>4</sub> solution. Precipitation of NdPO<sub>4</sub> occurred while drying for several days, and the final NdPO<sub>4</sub> product was obtained after briefly heating above 600  $^{\circ}$ C

to remove  $NH_3$  and nitrates. The recovered  $NdPO_4$  powder was mixed with  $Li_2MoO_4$  and  $MoO_3$  in the mass ratio of  $\sim 2:1:1$ , respectively, and placed in a Pt crucible. The crucible was heated at 800 °C for 24 h, and polycrystalline  $NdPO_4$  powder was recovered by dissolving the flux in boiling water. A similar method was used for  $GdPO_4$  synthesis.

Different studies showed that monazite compounds can be easily synthesized by heat-treating rhabdophane. Jonasson and Vance<sup>10</sup> showed that La-, Ce-, Pr-, Nd-, Sm-, and Gd-rhabdophane compounds converted to corresponding monazite compounds in 500–900 °C range after dehydration in 100–400 °C range. They observed that Dy rhabdophane compound converted to mixed phases of monazite and xenotime compounds at 950 °C and complete xenotime compound at 1050 °C.<sup>10</sup> Adelstein *et al.*<sup>37</sup> prepared CePO<sub>4</sub> monazite by heating Ce rhabdophane at 800 °C for 1 h. However, a different study by Mesbah *et al.*<sup>47</sup> showed that heating Nd, Eu, Gd, and Dy rhabdophane compounds at 200–500 °C converted them to NdPO<sub>4</sub>, EuPO<sub>4</sub>, GdPO<sub>4</sub>, and DyPO<sub>4</sub> with tetragonal *P*3<sub>1</sub>21 space group, which is different symmetry from monazite or xenotime.

Heuser *et al.*<sup>41</sup> synthesized TbPO<sub>4</sub> and DyPO<sub>4</sub> with monazite structures using rhabdophane of TbPO<sub>4</sub>·nH<sub>2</sub>O and DyPO<sub>4</sub>·nH<sub>2</sub>O. The rhabdophane compounds were made using a similar precipitation method by Boakye *et al.*<sup>48</sup> Solutions containing RE(NO<sub>3</sub>)<sub>3</sub>·nH<sub>2</sub>O and H<sub>3</sub>PO<sub>4</sub> were mixed while controlling the RE:P ratio and pH, and the precipitates were collected. The rhabdophane powders were heated at 200 °C for 2 h. Subsequently, Tb and Dy rhabdophane powders were heated at 950 °C for 8 h and 730 °C for 4 h, respectively, to convert to corresponding monazite compounds. The heating temperature and time were selected to avoid possible formation of xenotime structures.

## 3 Crystal structures

Monazite crystallizes in the monoclinic  $P2_1/n$  space group (REs are coordinated by nine oxygens), and xenotime crystallizes in the tetragonal I4<sub>1</sub>/amd space group (REs are coordinated by eight oxygens) and is isostructural to zircon (ZrSiO<sub>4</sub>). Monazite compounds of lanthanides contain the lanthanide elements with larger ionic radii  $(r_i)$  including La, Ce, Pr, Nd, Pm, Sm, Eu, Gd, Tb, and Dy whereas xenotime compounds contain the heavy lanthanide elements with smaller  $r_i$  including Gd, Tb, Dy, Ho, Er, Tm, and Lu along with Sc and Y. The structural parameters of monazite and xenotime compounds at ambient conditions (293-300 K and 1 atm) reported in the Inorganic Crystal Structure Database (ICSD) are provided in Tables 2 and 3, respectively. It should be noted that, for the REPO<sub>4</sub> compounds with RE elements, the mid-range of lanthanides (i.e., Gd, Tb, Dy) can crystallize in both monazite and xenotime structures. Formation of monazite or xenotime for Gd, Tb, and Dy elements can be controlled by synthesis conditions (see Section 2 for details). Fig. 1 shows the relationship of monazite and xenotime structures with respect to the crystal radii ( $r_c$ ) from Shannon.<sup>49</sup> The unit cell parameters of the PmPO<sub>4</sub> compound have been reported,50 but the overall structure data has not been reported in the ICSD. As for other RE elements, namely Y and Sc, YPO4 and

ScPO<sub>4</sub> (pretulite) have the xenotime structure. Both monazite and xenotime structures are commonly found in non-phosphate compounds including RE vanadates (REVO<sub>4</sub>) and RE arsenates (REAsO<sub>4</sub>).¹ Details of the monazite and xenotime structures are discussed in the following sections.

The nine oxygen atoms coordinating the REs in monazite include five oxygen atoms forming a nearly equatorial pentagon whereas the other four oxygen atoms form a tetrahedron interpenetrating the pentagon (Fig. 2), and this coordination of REO<sub>9</sub> was described as a pentagonal interpenetrating tetrahedral polyhedron (PITP).<sup>31,45</sup> The interpenetrating tetrahedron of REO<sub>9</sub> shares the edges with two adjacent PO<sub>4</sub> tetrahedra (Fig. 2a), resulting in a chain-like structure along the c axis (Fig. 2b). Fig. 2c shows the atomic arrangement of RE and P atoms projected down [001].

Distortion of REO<sub>9</sub> polyhedra and PO<sub>4</sub> tetrahedra in the monazite structure was reported in the literature.1,59 The monazite structure has four oxygen atom positions (i.e., O1, O2, O3, and O4), and the O2 atom is shared by three RE cations and a P cation whereas O1, O3, and O4 atoms are shared by only two RE cations and a P cation. This bonding results in REO<sub>9</sub> polyhedra with one longer RE-O2 distance compared to other eight RE-O distances. For example, the difference in RE-O bonding results in one longer ~2.8 Å RE-O2 bond length compared to  $\sim$ 2.5-2.6 Å of other eight RE-O bond lengths in CePO<sub>4</sub>.<sup>59</sup> This RE-O coordination also affected the distortion of PO<sub>4</sub> tetrahedra with different P-O bond lengths and O-P-O bond angles within a given PO<sub>4</sub> tetrahedron.<sup>59</sup> The distortion index<sup>84</sup> value (D) can be used to show the average deviation of RE-O bond distances from their means within the REO9 polyhedra of monazite, and this is shown in eqn (1) where  $l_i$  is the distance from the central atom (i.e., RE) to the ith coordinating atom, and  $l_{av}$  is the average bond length. The distortion indices of REO<sub>9</sub> in monazite are in the range of 0.03-0.11 and were relatively higher than the distortion indices (0.01-0.06) of REO<sub>8</sub> in the xenotime structures. The larger D value of  $REO_x$  in monazite compared to xenotime was largely due to the one long RE-O2 bond. The distorted REO<sub>9</sub> polyhedron in monazite has a set of nine different RE-O bond lengths, and this coordination is correlated to its capability to incorporate various cations and polyoxoanions in the structure.14 Generally, this type of irregular coordination of metal ions does not induce severe symmetry, charge, or size constraints on the incorporated cation. 15,59

$$D = \frac{1}{n} \sum_{i=1}^{n} \frac{|l_i - l_{av}|}{l_{av}} \tag{1}$$

As mentioned earlier, the monazite structures incorporate light RE cations, including La  $\rightarrow$  Dy. With larger RE cations (*i.e.*, larger  $r_c$  values)<sup>49</sup> in the crystal structure, the unit cell parameters (*i.e.*, a, b, c) and volumes (V) increase linearly whereas the densities ( $\rho$ ) decrease nonlinearly (Fig. 3). Fig. 3 was drawn using the average values of a, b, c, V, and  $\rho$  of monazite compounds at atmospheric conditions reported in ICSD for each given RE. The crystal structure data of PmPO<sub>4</sub> was not

Table 2 Structural parameters of REPO<sub>4</sub> monazite compounds at ambient conditions (293–300 K and 1 atm) including unit cell parameters (a, b, c), β angle, cell volume (V), cell density (ρ), bond distances (i.e., RE–O, P–O), and the entry number for the Inorganic Crystal Structure Database (ICSD). The space group of listed compounds is  $P2_1/n$  (SG# 14). Volume and density are calculated values, and RE–O and P–O are the average distances

La         6.8313         7.0705         6.5034         103.27         305.73         5.08         2.5787         1.5384         79747         51           La         6.8413         7.078         6.5153         103.322         307         5.06         2.5855         1.6602         92155         32           La         6.825         7.057         6.482         103.21         303.94         5.11         2.5739         1.5350         201479         31           La         6.84133         7.07590         6.51233         103.28918         306.8         5.06         2.5729         1.5591         431743         33           Ce         6.77         7.01         6.45         103.63         297.48         5.23         2.6188         1.5421         22265         53           Ce         6.77         7.01         6.45         103.63         296.63         5.26         2.5467         1.5662         27860         54           Ce         6.77         6.99         6.45         103.63         296.63         5.26         2.5413         1.6024         43077         57           Ce         6.77         7.04         6.46         104         298.74         5.23<	RE	a (Å)	b (Å)	c (Å)	β (°)	$V\left(\mathring{\mathbf{A}}^3\right)$	ho (g cm <sup>-3</sup> )	RE-O (Å)	P-O (Å)	ICSD	Ref.
La         6.8413         7.078         6.5153         103.322         307         5.06         2.5855         1.6602         92155         52           La         6.825         7.057         6.482         103.21         303.94         5.11         2.5739         1.5350         201479         31           La         6.84133         7.07590         6.51233         103.28918         306.8         5.06         2.5729         1.5591         431743         33           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6188         1.5421         222.65         53           Ce         6.79         7         6.46         104         297.92         5.24         2.5971         1.5154         33598         55           Ce         6.79         7         6.46         104         297.92         5.24         2.5971         1.5154         33598         55           Ce         6.77         6.99         6.45         103.63         296.63         5.26         2.5413         1.6024         43077         57           Ce         6.77         7.04         6.46         104         298.74         5.21         2.5	La	6.7825	6.9896	6.6218	102.9602	305.92	5.08	2.5845	1.5493	46788	36
La         6.825         7.057         6.482         103.21         303.94         5.11         2.5739         1.5350         201479         31           La         6.84133         7.07590         6.51233         103.28918         306.8         5.06         2.5729         1.5591         431743         35           Ce         6.77         7.01         6.45         103.63         297.48         5.25         2.5467         1.5662         27860         54           Ce         6.77         7.01         6.45         103.63         297.48         5.25         2.5467         1.5662         27860         54           Ce         6.77         6.99         6.45         103.63         296.67         5.26         2.5310         1.6024         43077         57           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6084         1.6128         64850         53           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6084         1.6128         64850         53           Ce         6.78         7.0693         6.4671         103.38         299.99         5.21	La	6.8313	7.0705	6.5034	103.27	305.73	5.08	2.5787	1.5384	79747	51
La         6.84133         7.07590         6.51233         103.28918         306.8         5.06         2.5729         1.5591         431743         35           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6188         1.5421         22265         53           Ce         6.77         7.01         6.45         103.63         297.48         5.25         2.5467         1.5662         27860         35           Ce         6.79         7         6.46         104         297.92         5.24         2.5971         1.5154         33598         55           Ce         6.77         6.99         6.45         103.63         296.63         5.26         2.5360         1.6405         39135         56           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6084         1.6128         64850         53           Ce         6.780         7.003         6.4674         103.38         299.93         5.21         2.5586         1.5333         79746         51           Ce         6.7802         7.00689         6.47476         103.781         299.94         5.21	La	6.8413	7.078	6.5153	103.322	307	5.06	2.5855	1.6602	92155	52
Ce         6.77         7.04         6.46         104         298.74         5.23         2.6188         1.5421         22265         53           Ce         6.77         7.01         6.45         103.63         297.48         5.25         2.5467         1.5662         27860         54           Ce         6.77         6.99         6.45         103.6         296.67         5.26         2.5360         1.6405         39135         56           Ce         6.77         6.99         6.45         103.63         296.63         5.26         2.5360         1.6405         39135         56           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6084         1.6128         64850         53           Ce         6.7902         7.0203         6.4674         103.38         299.93         5.21         2.5586         1.5333         79746         51           Ce         6.788         7.0163         6.4650         103.43         299.93         5.21         2.5586         1.5337         79748         51           Ce         6.781         6.9804         6.459         103.781         299.93         5.21	La	6.825	7.057	6.482	103.21	303.94	5.11	2.5739	1.5350	201479	31
Ce         6.77         7.01         6.45         103.63         297.48         5.25         2.5467         1.5662         27860         54           Ce         6.79         7         6.46         104         297.92         5.24         2.5971         1.5154         33598         55           Ce         6.77         6.99         6.45         103.63         296.63         5.26         2.5413         1.6024         43077         57           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6084         1.6128         64850         53           Ce         6.7902         7.0203         6.4674         103.38         299.93         5.21         2.5586         1.5333         79746         51           Ce         6.788         7.0163         6.4650         103.43         299.94         5.21         2.5554         1.5375         79748         51           Ce         6.8072         7.00689         6.47476         103.781         299.94         5.21         2.5554         1.5375         79748         51           Ce         6.8004         7.0231         6.4717         103.46         300.6         519	La	6.84133	7.07590	6.51233	103.28918	306.8	5.06	2.5729	1.5591	431743	35
Ce         6.79         7         6.46         104         297.92         5.24         2.5971         1.5154         33598         55           Ce         6.77         6.99         6.45         103.6         296.67         5.26         2.5360         1.6405         39135         56           Ce         6.77         6.99         6.45         103.63         296.63         5.26         2.51413         1.6024         43077         57           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6084         1.6128         64850         53           Ce         6.7902         7.00639         6.4674         103.38         299.93         5.21         2.5586         1.5333         79748         51           Ce         6.8072         7.00689         6.47476         103.781         299.94         5.21         2.5552         1.5316         133670         38           Ce         6.7551         6.9804         6.4687         103.707         296.33         5.27         2.5450         1.5371         2918282         37           Ce         6.777         6.993         6.4471         103.54         296.95         5.26 </td <td>Ce</td> <td>6.77</td> <td>7.04</td> <td>6.46</td> <td>104</td> <td>298.74</td> <td>5.23</td> <td>2.6188</td> <td>1.5421</td> <td>22265</td> <td>53</td>	Ce	6.77	7.04	6.46	104	298.74	5.23	2.6188	1.5421	22265	53
Ce         6.77         6.99         6.45         103.6         296.67         5.26         2.5360         1.6405         39135         56           Ce         6.77         6.99         6.45         103.63         296.63         5.26         2.5413         1.6024         43077         57           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6084         1.6128         64850         53           Ce         6.7902         7.0203         6.4674         103.38         299.93         5.21         2.5586         1.5333         79746         51           Ce         6.788         7.0163         6.4650         103.781         299.94         5.21         2.5554         1.5375         79748         51           Ce         6.8072         7.00689         6.47476         103.781         299.94         5.21         2.5652         1.5316         133670         88           Ce         6.7551         6.9804         6.4687         103.707         296.33         5.27         2.5615         1.5371         201029         59           Ce         6.7777         6.993         6.445         103.794         29.72         <	Ce	6.77	7.01	6.45	103.63	297.48	5.25	2.5467	1.5662	27860	54
Ce         6.77         6.99         6.45         103.63         296.63         5.26         2.5413         1.6024         43077         5.7           Ce         6.77         7.04         6.46         104         298.74         5.23         2.6084         1.6128         64850         53           Ce         6.7902         7.0203         6.4674         103.38         299.93         5.21         2.5586         1.5333         79746         51           Ce         6.788         7.0163         6.4650         103.43         299.94         5.21         2.5554         1.5375         79748         51           Ce         6.8072         7.00689         6.47476         103.781         299.94         5.21         2.5652         1.5316         133669         58           Ce         6.7551         6.9804         6.4687         103.707         296.33         5.27         2.5450         1.5316         133670         58           Ce         6.777         6.993         6.445         103.54         296.95         5.26         2.5506         1.5271         201029         99           Ce         6.78985         7.01813         6.46662         103.5214         299.72 <td>Ce</td> <td>6.79</td> <td>7</td> <td>6.46</td> <td>104</td> <td>297.92</td> <td>5.24</td> <td>2.5971</td> <td>1.5154</td> <td>33598</td> <td>55</td>	Ce	6.79	7	6.46	104	297.92	5.24	2.5971	1.5154	33598	55
Ce         6.77         7.04         6.46         104         298.74         5.23         2.6084         1.6128         64850         53           Ce         6.7902         7.0203         6.4674         103.88         299.93         5.21         2.5586         1.5333         79746         51           Ce         6.788         7.0163         6.4650         103.43         299.94         5.21         2.5554         1.5375         79748         51           Ce         6.8072         7.00689         6.47476         103.781         299.94         5.21         2.5652         1.5318         133669         58           Ce         6.7551         6.9804         6.4687         103.707         296.33         5.27         2.5450         1.5316         133670         58           Ce         6.7551         6.9804         6.4687         103.707         296.33         5.27         2.5450         1.5316         133670         58           Ce         6.7577         6.993         6.4451         103.707         296.33         5.27         2.5615         1.5371         201029         37           Ce         6.7777         6.993         6.44266         103.42415         2	Ce	6.77	6.99	6.45	103.6	296.67	5.26	2.5360	1.6405	39135	56
Ce         6.7902         7.0203         6.4674         103.38         299.93         5.21         2.5586         1.5333         79746         51           Ce         6.788         7.0163         6.4650         103.43         299.49         5.21         2.5554         1.5375         79748         51           Ce         6.8072         7.00689         6.47476         103.781         299.94         5.21         2.5652         1.5318         133669         58           Ce         6.7551         6.9804         6.4687         103.707         296.33         5.27         2.5450         1.5316         133670         58           Ce         6.8004         7.0231         6.4717         103.46         300.6         5.19         2.5615         1.5316         133670         58           Ce         6.7777         6.993         6.445         103.54         296.95         5.26         2.5506         1.5271         201029         59           Ce         6.78985         7.01813         6.46662         103.42415         299.72         5.21         2.5580         1.5330         243620         60           Pr         6.7596         6.9812         6.4344         103.63	Ce	6.77	6.99	6.45	103.63	296.63	5.26	2.5413	1.6024	43077	57
Cc         6.788         7.0163         6.4650         103.43         299.49         5.21         2.5554         1.5375         79748         51           Cc         6.8072         7.00689         6.47476         103.781         299.94         5.21         2.5652         1.5318         133669         58           Ce         6.7551         6.9804         6.4687         103.707         296.33         5.27         2.5450         1.5316         133670         58           Ce         6.8004         7.0231         6.4717         103.46         300.6         5.19         2.5615         1.5397         182582         37           Ce         6.777         6.993         6.445         103.54         296.95         5.26         2.5506         1.5271         201029         59           Ce         6.78985         7.01813         6.46662         103.42415         299.72         5.21         2.5580         1.5330         243620         60           Pr         6.741         6.961         6.416         103.63         292.59         5.35         2.5323         1.5368         79749         51           Pr         6.77078         6.9912         6.44265         103.522914	Ce	6.77	7.04	6.46	104	298.74	5.23	2.6084	1.6128	64850	53
Ce         6.8072         7.00689         6.47476         103.781         299.94         5.21         2.5652         1.5318         133669         58           Ce         6.7551         6.9804         6.4687         103.707         296.33         5.27         2.5450         1.5316         133670         58           Ce         6.8004         7.0231         6.4717         103.46         300.6         5.19         2.5615         1.5397         182582         37           Ce         6.777         6.993         6.445         103.54         296.95         5.26         2.5506         1.5271         201029         59           Ce         6.78985         7.01813         6.46662         103.42415         299.72         5.21         2.5580         1.5330         243620         60           Pr         6.741         6.961         6.416         103.63         292.59         5.35         2.5323         1.5320         62161         40           Pr         6.7596         6.9812         6.4344         103.53         295.21         5.31         2.5395         1.5368         79749         51           Pr         6.777078         6.99017         6.42265         103.752	Ce	6.7902	7.0203	6.4674	103.38	299.93	5.21	2.5586	1.5333	79746	51
Ce         6.7551         6.9804         6.4687         103.707         296.33         5.27         2.5450         1.5316         133670         58           Ce         6.8004         7.0231         6.4717         103.46         300.6         5.19         2.5615         1.5397         182582         37           Ce         6.777         6.993         6.445         103.54         296.95         5.26         2.5506         1.5271         201029         59           Ce         6.78985         7.01813         6.46662         103.42415         299.72         5.21         2.5580         1.5330         243620         60           Pr         6.741         6.961         6.416         103.63         292.59         5.35         2.5323         1.5320         62161         40           Pr         6.7596         6.9812         6.4344         103.53         295.21         5.31         2.5325         1.5368         79749         51           Pr         6.77078         6.99017         6.44265         103.52914         296.46         5.28         2.5325         1.5361         431753         35           Nd         6.7322         6.933         6.390         103.72	Ce	6.788	7.0163	6.4650	103.43	299.49	5.21	2.5554	1.5375	79748	51
Ce         6.8004         7.0231         6.4717         103.46         300.6         5.19         2.5615         1.5397         182582         37           Ce         6.777         6.993         6.445         103.54         296.95         5.26         2.5506         1.5271         201029         59           Ce         6.78985         7.01813         6.46662         103.42415         299.72         5.21         2.5580         1.5330         243620         60           Pr         6.741         6.961         6.416         103.63         292.59         5.35         2.5323         1.5320         62161         40           Pr         6.7596         6.9812         6.4344         103.53         295.21         5.31         2.5395         1.5368         79749         51           Pr         6.77078         6.99017         6.44265         103.52914         296.46         5.28         2.5325         1.5631         431753         35           Nd         6.722         6.933         6.390         103.72         289.3         5.49         2.5192         1.5321         62162         40           Nd         6.7325         6.950         6.4049         103.68 <th< td=""><td>Ce</td><td>6.8072</td><td>7.00689</td><td>6.47476</td><td>103.781</td><td>299.94</td><td>5.21</td><td>2.5652</td><td>1.5318</td><td>133669</td><td>58</td></th<>	Ce	6.8072	7.00689	6.47476	103.781	299.94	5.21	2.5652	1.5318	133669	58
Ce         6.777         6.993         6.445         103.54         296.95         5.26         2.5506         1.5271         201029         59           Ce         6.78985         7.01813         6.46662         103.42415         299.72         5.21         2.5580         1.5330         243620         60           Pr         6.741         6.961         6.416         103.63         292.59         5.35         2.5323         1.5320         62161         40           Pr         6.7596         6.9812         6.4344         103.53         295.21         5.31         2.5395         1.5368         79749         51           Pr         6.77078         6.99017         6.44265         103.52914         296.46         5.28         2.5325         1.5631         431753         35           Nd         6.722         6.933         6.390         103.72         289.3         5.49         2.5192         1.5321         62162         40           Nd         6.732         6.930         6.383         103.61         289.42         5.49         2.5183         1.5369         62311         61           Nd         6.7352         6.9500         6.4049         103.68         2	Ce	6.7551	6.9804	6.4687	103.707	296.33	5.27	2.5450	1.5316	133670	58
Ce         6.78985         7.01813         6.46662         103.42415         299.72         5.21         2.5580         1.5330         243620         60           Pr         6.741         6.961         6.416         103.63         292.59         5.35         2.5323         1.5320         62161         40           Pr         6.7596         6.9812         6.4344         103.53         295.21         5.31         2.5395         1.5368         79749         51           Pr         6.77078         6.99017         6.44265         103.52914         296.46         5.28         2.5325         1.5631         431753         35           Nd         6.722         6.930         6.383         103.72         289.3         5.49         2.5192         1.5321         62162         40           Nd         6.732         6.930         6.383         103.61         289.42         5.49         2.5183         1.5369         62311         61           Nd         6.7352         6.9500         6.4049         103.68         291.31         5.45         2.5242         1.5371         79750         51           Sm         6.6818         6.8877         6.3653         103.86 <td< td=""><td>Ce</td><td>6.8004</td><td>7.0231</td><td>6.4717</td><td>103.46</td><td>300.6</td><td>5.19</td><td>2.5615</td><td>1.5397</td><td>182582</td><td>37</td></td<>	Ce	6.8004	7.0231	6.4717	103.46	300.6	5.19	2.5615	1.5397	182582	37
Pr         6.741         6.961         6.416         103.63         292.59         5.35         2.5323         1.5320         62161         40           Pr         6.7596         6.9812         6.4344         103.53         295.21         5.31         2.5395         1.5368         79749         51           Pr         6.77078         6.99017         6.44265         103.52914         296.46         5.28         2.5325         1.5631         431753         35           Nd         6.722         6.933         6.390         103.72         289.3         5.49         2.5192         1.5321         62162         40           Nd         6.732         6.930         6.383         103.61         289.42         5.49         2.5183         1.5369         62311         61           Nd         6.7352         6.9500         6.4049         103.68         291.31         5.45         2.5242         1.5371         79750         51           Sm         6.6818         6.8877         6.3653         103.89         292.7         5.57         2.5358         1.5305         133668         58           Sm         6.669         6.868         6.351         103.92         282.35 <td>Ce</td> <td>6.777</td> <td>6.993</td> <td>6.445</td> <td>103.54</td> <td>296.95</td> <td>5.26</td> <td>2.5506</td> <td>1.5271</td> <td>201029</td> <td>59</td>	Ce	6.777	6.993	6.445	103.54	296.95	5.26	2.5506	1.5271	201029	59
Pr         6.7596         6.9812         6.4344         103.53         295.21         5.31         2.5395         1.5368         79749         51           Pr         6.77078         6.99017         6.44265         103.52914         296.46         5.28         2.5325         1.5631         431753         35           Nd         6.722         6.933         6.390         103.72         289.3         5.49         2.5192         1.5321         62162         40           Nd         6.732         6.930         6.383         103.61         289.42         5.49         2.5183         1.5369         62311         61           Nd         6.7352         6.9500         6.4049         103.68         291.31         5.45         2.5242         1.5371         79750         51           Sm         6.6818         6.8877         6.3653         103.86         284.42         5.73         2.4988         1.5370         79751         51           Sm         6.6691         6.868         6.351         103.899         292.7         5.57         2.5358         1.5310         201839         45           Eu         6.6813         6.8618         6.3491         103.96         282.	Ce	6.78985	7.01813	6.46662	103.42415	299.72	5.21	2.5580	1.5330	243620	60
Pr         6.77078         6.99017         6.44265         103.52914         296.46         5.28         2.5325         1.5631         431753         35           Nd         6.722         6.933         6.390         103.72         289.3         5.49         2.5192         1.5321         62162         40           Nd         6.732         6.930         6.383         103.61         289.42         5.49         2.5183         1.5369         62311         61           Nd         6.7352         6.9500         6.4049         103.68         291.31         5.45         2.5242         1.5371         79750         51           Sm         6.6818         6.8877         6.3653         103.86         284.42         5.73         2.4988         1.5370         79751         51           Sm         6.73167         6.94489         6.44964         103.899         292.7         5.57         2.5358         1.5305         133668         58           Sm         6.669         6.868         6.351         103.92         282.35         5.77         2.4932         1.5310         201839         45           Eu         6.6813         6.8618         6.3491         103.96         2	Pr	6.741	6.961	6.416	103.63	292.59	5.35	2.5323	1.5320	62161	40
Nd         6.722         6.933         6.390         103.72         289.3         5.49         2.5192         1.5321         62162         40           Nd         6.732         6.930         6.383         103.61         289.42         5.49         2.5183         1.5369         62311         61           Nd         6.7352         6.9500         6.4049         103.68         291.31         5.45         2.5242         1.5371         79750         51           Sm         6.6818         6.8877         6.3653         103.86         284.42         5.73         2.4988         1.5370         79751         51           Sm         6.73167         6.94489         6.44964         103.899         292.7         5.57         2.5358         1.5305         133668         58           Sm         6.669         6.868         6.351         103.92         282.35         5.77         2.4932         1.5310         201839         45           Eu         6.6813         6.8618         6.3491         103.96         282.48         5.81         2.4902         1.5393         79752         51           Eu         6.639         6.823         6.318         104.00         277.69	Pr	6.7596	6.9812	6.4344	103.53	295.21	5.31	2.5395	1.5368	79749	51
Nd         6.732         6.930         6.383         103.61         289.42         5.49         2.5183         1.5369         62311         61           Nd         6.7352         6.9500         6.4049         103.68         291.31         5.45         2.5242         1.5371         79750         51           Sm         6.6818         6.8877         6.3653         103.86         284.42         5.73         2.4988         1.5370         79751         51           Sm         6.73167         6.94489         6.44964         103.899         292.7         5.57         2.5358         1.5305         133668         58           Sm         6.669         6.868         6.351         103.92         282.35         5.77         2.4932         1.5310         201839         45           Eu         6.6813         6.8618         6.3491         103.96         282.48         5.81         2.4902         1.5393         79752         51           Eu         6.639         6.823         6.318         104.00         277.69         5.91         2.4749         1.5299         201840         45           Gd         6.621         6.823         6.310         104.16         276.39 <td>Pr</td> <td>6.77078</td> <td>6.99017</td> <td>6.44265</td> <td>103.52914</td> <td>296.46</td> <td>5.28</td> <td>2.5325</td> <td>1.5631</td> <td>431753</td> <td>35</td>	Pr	6.77078	6.99017	6.44265	103.52914	296.46	5.28	2.5325	1.5631	431753	35
Nd         6.7352         6.9500         6.4049         103.68         291.31         5.45         2.5242         1.5371         79750         51           Sm         6.6818         6.8877         6.3653         103.86         284.42         5.73         2.4988         1.5370         79751         51           Sm         6.73167         6.94489         6.44964         103.899         292.7         5.57         2.5358         1.5305         133668         58           Sm         6.669         6.868         6.351         103.92         282.35         5.77         2.4932         1.5310         201839         45           Eu         6.6813         6.8618         6.3491         103.96         282.48         5.81         2.4902         1.5393         79752         51           Eu         6.639         6.823         6.318         104.00         277.69         5.91         2.4749         1.5299         201840         45           Gd         6.6435         6.8414         6.3281         103.976         279.1         6         2.4760         1.5383         79753         51           Gd         6.652         6.847         6.336         103.99         280.02 <td>Nd</td> <td>6.722</td> <td>6.933</td> <td>6.390</td> <td>103.72</td> <td>289.3</td> <td>5.49</td> <td>2.5192</td> <td>1.5321</td> <td>62162</td> <td>40</td>	Nd	6.722	6.933	6.390	103.72	289.3	5.49	2.5192	1.5321	62162	40
Sm         6.6818         6.8877         6.3653         103.86         284.42         5.73         2.4988         1.5370         79751         51           Sm         6.73167         6.94489         6.44964         103.899         292.7         5.57         2.5358         1.5305         133668         58           Sm         6.669         6.868         6.351         103.92         282.35         5.77         2.4932         1.5310         201839         45           Eu         6.6813         6.8618         6.3491         103.96         282.48         5.81         2.4902         1.5393         79752         51           Eu         6.639         6.823         6.318         104.00         277.69         5.91         2.4749         1.5299         201840         45           Gd         6.6435         6.8414         6.3281         103.976         279.1         6         2.4760         1.5383         79753         51           Gd         6.621         6.823         6.310         104.16         276.39         6.06         2.4693         1.5298         201841         45           Gd         6.652         6.847         6.336         103.99         280.02	Nd	6.732	6.930	6.383	103.61	289.42	5.49	2.5183	1.5369	62311	61
Sm         6.73167         6.94489         6.44964         103.899         292.7         5.57         2.5358         1.5305         133668         58           Sm         6.669         6.868         6.351         103.92         282.35         5.77         2.4932         1.5310         201839         45           Eu         6.6813         6.8618         6.3491         103.96         282.48         5.81         2.4902         1.5393         79752         51           Eu         6.639         6.823         6.318         104.00         277.69         5.91         2.4749         1.5299         201840         45           Gd         6.6435         6.8414         6.3281         103.976         279.1         6         2.4760         1.5383         79753         51           Gd         6.621         6.823         6.310         104.16         276.39         6.06         2.4693         1.5298         201841         45           Gd         6.652         6.847         6.336         103.99         280.02         5.98         2.4833         1.5373         230368         62           Gd         6.33571         6.84840         6.6516         104.023         280 <td>Nd</td> <td>6.7352</td> <td>6.9500</td> <td>6.4049</td> <td>103.68</td> <td>291.31</td> <td>5.45</td> <td>2.5242</td> <td>1.5371</td> <td>79750</td> <td>51</td>	Nd	6.7352	6.9500	6.4049	103.68	291.31	5.45	2.5242	1.5371	79750	51
Sm         6.669         6.868         6.351         103.92         282.35         5.77         2.4932         1.5310         201839         45           Eu         6.6813         6.8618         6.3491         103.96         282.48         5.81         2.4902         1.5393         79752         51           Eu         6.639         6.823         6.318         104.00         277.69         5.91         2.4749         1.5299         201840         45           Gd         6.6435         6.8414         6.3281         103.976         279.1         6         2.4760         1.5383         79753         51           Gd         6.621         6.823         6.310         104.16         276.39         6.06         2.4693         1.5298         201841         45           Gd         6.652         6.847         6.336         103.99         280.02         5.98         2.4833         1.5373         230368         62           Gd         6.33571         6.84840         6.6516         104.023         280         5.98         2.4827         1.5325         252925         63           Tb         6.61993         6.81106         6.31653         104.1091         276.21 </td <td>Sm</td> <td>6.6818</td> <td>6.8877</td> <td>6.3653</td> <td>103.86</td> <td>284.42</td> <td>5.73</td> <td>2.4988</td> <td>1.5370</td> <td>79751</td> <td>51</td>	Sm	6.6818	6.8877	6.3653	103.86	284.42	5.73	2.4988	1.5370	79751	51
Eu       6.6813       6.8618       6.3491       103.96       282.48       5.81       2.4902       1.5393       79752       51         Eu       6.639       6.823       6.318       104.00       277.69       5.91       2.4749       1.5299       201840       45         Gd       6.6435       6.8414       6.3281       103.976       279.1       6       2.4760       1.5383       79753       51         Gd       6.621       6.823       6.310       104.16       276.39       6.06       2.4693       1.5298       201841       45         Gd       6.652       6.847       6.336       103.99       280.02       5.98       2.4833       1.5373       230368       62         Gd       6.33571       6.84840       6.6516       104.023       280       5.98       2.4827       1.5325       252925       63         Tb       6.61993       6.81106       6.31653       104.1091       276.21       6.11       2.4571       1.5579       18864       41	Sm	6.73167	6.94489	6.44964	103.899	292.7	5.57	2.5358	1.5305	133668	58
Eu     6.639     6.823     6.318     104.00     277.69     5.91     2.4749     1.5299     201840     45       Gd     6.6435     6.8414     6.3281     103.976     279.1     6     2.4760     1.5383     79753     51       Gd     6.621     6.823     6.310     104.16     276.39     6.06     2.4693     1.5298     201841     45       Gd     6.652     6.847     6.336     103.99     280.02     5.98     2.4833     1.5373     230368     62       Gd     6.33571     6.84840     6.6516     104.023     280     5.98     2.4827     1.5325     252925     63       Tb     6.61993     6.81106     6.31653     104.1091     276.21     6.11     2.4571     1.5579     18864     41	Sm	6.669	6.868	6.351	103.92	282.35	5.77	2.4932	1.5310	201839	45
Gd         6.6435         6.8414         6.3281         103.976         279.1         6         2.4760         1.5383         79753         51           Gd         6.621         6.823         6.310         104.16         276.39         6.06         2.4693         1.5298         201841         45           Gd         6.652         6.847         6.336         103.99         280.02         5.98         2.4833         1.5373         230368         62           Gd         6.33571         6.84840         6.6516         104.023         280         5.98         2.4827         1.5325         252925         63           Tb         6.61993         6.81106         6.31653         104.1091         276.21         6.11         2.4571         1.5579         18864         41	Eu	6.6813	6.8618	6.3491	103.96	282.48	5.81	2.4902	1.5393	79752	51
Gd         6.621         6.823         6.310         104.16         276.39         6.06         2.4693         1.5298         201841         45           Gd         6.652         6.847         6.336         103.99         280.02         5.98         2.4833         1.5373         230368         62           Gd         6.33571         6.84840         6.6516         104.023         280         5.98         2.4827         1.5325         252925         63           Tb         6.61993         6.81106         6.31653         104.1091         276.21         6.11         2.4571         1.5579         18864         41	Eu	6.639	6.823	6.318	104.00	277.69	5.91	2.4749	1.5299	201840	45
Gd     6.652     6.847     6.336     103.99     280.02     5.98     2.4833     1.5373     230368     62       Gd     6.33571     6.84840     6.6516     104.023     280     5.98     2.4827     1.5325     252925     63       Tb     6.61993     6.81106     6.31653     104.1091     276.21     6.11     2.4571     1.5579     18864     41	Gd	6.6435	6.8414	6.3281	103.976	279.1	6	2.4760	1.5383	79753	51
Gd     6.33571     6.84840     6.6516     104.023     280     5.98     2.4827     1.5325     252925     63       Tb     6.61993     6.81106     6.31653     104.1091     276.21     6.11     2.4571     1.5579     18864     41	Gd	6.621	6.823	6.310	104.16	276.39	6.06	2.4693	1.5298	201841	45
Tb 6.61993 6.81106 6.31653 104.1091 276.21 6.11 2.4571 1.5579 18864 41	Gd	6.652	6.847	6.336	103.99	280.02	5.98	2.4833	1.5373	230368	62
	Gd	6.33571	6.84840	6.6516	104.023	280	5.98	2.4827	1.5325	252925	63
Dv 6 59737 6 78650 6 30380 104 1887 273 63 6 25 2 4487 1 5536 18863 41	Tb	6.61993	6.81106	6.31653	104.1091	276.21	6.11	2.4571	1.5579	18864	41
<i>Dy</i> 0.05707 0.7000 0.0000 10.1107 270.00 0.25 2.1107 1.0000 11	Dy	6.59737	6.78650	6.30380	104.1887	273.63	6.25	2.4487	1.5536	18863	41

reported in the ICSD, and the unit cell parameter values from a study by Weigel  $et\ al.^{50}$  were used to fit the trendline.

The RE-O bond distances of monazite compounds were compared, and larger cations in REO9 polyhedra resulted in longer average RE-O bond distances (Fig. 4a). As discussed above, the RE cation in the monazite structure is coordinated by nine oxygen atoms, but presenting a single-digit coordination number might not be accurate in relatively distorted coordination polyhedra. The effective coordination numbers (CN<sub>eff</sub>)85-87 can be used to express more reasonable coordination numbers by accounting for all the surrounding atoms with a weighting scheme. The CN<sub>eff</sub> values of REO<sub>9</sub> were calculated using eqn (2) and (3) where  $w_i$  is the bond weight of the  $i_{th}$  bond,  $l_{\rm av}$  is defined in eqn (4),  $l_i$  was defined above, and  $l_{\rm min}$  is the shortest bond distance in the coordination polyhedron. These equations were formulated by combining the concepts of Pauling with effective coordination numbers and mean fictive  $r_i$ values.  $^{87}$  The average  $\mathrm{CN}_{\mathrm{eff}}$  value calculated for each RE element in monazites is plotted in Fig. 4b, and REO $_9$  polyhedra with larger cations generally show higher CN $_{\rm eff}$  values.

$$CN_{\text{eff}} = \sum_{i} w_{i} \tag{2}$$

$$w_i = \exp\left[1 - \left(\frac{l_i}{l_{\rm av}}\right)^6\right] \tag{3}$$

$$l_{\text{av}} = \frac{\sum_{i} l_{i} \exp\left[1 - \left(\frac{l_{i}}{l_{\text{min}}}\right)^{6}\right]}{\sum_{i} \exp\left[1 - \left(\frac{l_{i}}{l_{\text{min}}}\right)^{6}\right]}$$
(4)

For the REO<sub>8</sub> coordination in xenotime, each oxygen atom is shared by two RE atoms and one P atom. Similar to monazite, the REO<sub>8</sub> polyhedra share the edges with two adjacent PO<sub>4</sub> tetrahedra (Fig. 2d), forming a chain-like structure along the *c* 

Table 3 Structural parameters of REPO<sub>4</sub> xenotime compounds at ambient conditions (293–300 K and 1 atm) including unit cell parameters (a, b, c), cell volume (V), cell density ( $\rho$ ), bond distances (i.e., RE-O, P-O), and the entry number for the Inorganic Crystal Structure Database (ICSD). The space group of listed compounds is  $I4_1/amd$  (SG# 141). Volume and density are calculated values, and RE-O and P-O are the average distances

RE	a (Å)	b (Å)	c (Å)	$V(\mathring{\mathbf{A}}^3)$	ho (g cm <sup>-3</sup> )	RE-O (Å)	P-O (Å)	ICSD	Ref.
	u (11)	<i>D</i> (11)	U (11)	, (11)	(g cm )	TEL 0 (11)	1 0 (11)	1000	
Gd	6.9670	6.9670	6.1112	296.63	5.64	2.3758	1.5541	118105	64
Tb	6.9414	6.9414	6.0704	292.49	5.77	2.3726	1.5302	29316	65
Tb	6.940	6.940	6.068	292.26	5.77	2.3822	1.5228	35704	66
Tb	6.9309	6.9309	6.0606	291.14	5.79	2.365	1.5359	79755	51
Tb	6.9391	6.9391	6.0694	292.25	5.77	2.3575	1.546	168751	67
Dy	6.91	6.91	6.04	288.4	5.93	2.3469	1.548	26440	68
Dy	6.907	6.907	6.046	288.43	5.93	2.3496	1.5491	35705	66
Dy	6.9052	6.9052	6.0384	287.92	5.94	2.3513	1.5372	79756	51
Dy	6.909	6.909	6.038	288.22	5.93	2.5927	1.3327	192553	69
Но	6.882	6.882	6.025	285.36	6.05	2.3465	1.5326	35706	66
Но	6.8773	6.8773	6.0176	284.62	6.07	2.3428	1.5319	79757	51
Но	6.8842	6.8842	6.0255	285.56	6.05	2.34	1.5408	246677	70
Но	6.8919	6.8919	6.0336	286.59	6.02	2.335	1.5525	257644	71
Но	6.886	6.886	6.027	285.78	6.04	2.3499	1.5251	257646	71
Er	6.863	6.863	6.007	282.93	6.16	2.3289	1.542	15670	72
Er	6.860	6.860	6.003	282.5	6.17	2.3361	1.5313	36052	73
Er	6.8507	6.8507	5.9968	281.44	6.19	2.3303	1.5356	79758	51
Tm	6.839	6.839	5.986	279.98	6.26	2.3252	1.5326	36053	73
Tm	6.8293	6.8293	5.9798	278.89	6.29	2.3098	1.5544	79759	51
Tm	6.8219	6.8219	5.97988	278.29	6.3	2.3238	1.5195	257645	71
Yb	6.816	6.816	5.966	277.17	6.42	2.3095	1.5439	36054	73
Yb	6.8093	6.8093	5.9639	276.53	6.44	2.313	1.5319	79760	51
Lu	6.792	6.792	5.955	274.71	6.53	2.3045	1.5327	2505	74
Lu	6.7443	6.7443	6.0105	273.39	6.56	2.2974	1.5481	46792	36
Lu	6.7827	6.7827	5.9467	273.58	6.55	2.3002	1.5337	79761	51
Lu	6.7895	6.7895	5.9560	274.56	6.53	2.3093	1.5327	162336	75
Lu	6.792	6.792	5.954	274.67	6.53	2.2998	1.5386	201133	76
Lu	6.7967	6.7967	5.9593	275.29	6.51	2.3096	1.533	246684	70
Y	6.876	6.876	6.186	292.47	4.18	2.243	1.7179	24514	77
Y	6.878	6.878	6.036	285.54	4.28	2.387	1.5365	28554	78
Y	6.9	6.9	6.026	286.9	4.26	2.2494	1.6709	56113	79
Y	6.8947	6.8947	6.0276	286.53	4.26	2.345	1.54	79754	51
Y	6.885	6.885	6.022	285.46	4.28	2.3324	1.5503	117962	80
Y	6.90706	6.90706	6.0348	287.91	4.24	2.403	1.5302	133671	58
Y	6.8817	6.8817	6.0177	284.99	4.29	2.3365	1.5435	201131	76
Sc	6.578	6.578	5.796	250.79	3.71	2.2295	1.5606	16648	81
Sc	6.5787	6.5787	5.7963	250.86	3.7	2.2116	1.5336	74483	82
Sc	6.574	6.574	5.791	250.27	3.71	2.2067	1.5341	201132	76
Sc	6.578	6.578	5.796	250.79	3.7	2.2078	1.5367	257305	83

axis (Fig. 2e). Fig. 2f shows the atomic arrangement of RE and P atoms projected down [001]. With smaller RE cations in the xenotime structures compared to monazite, the D values of REO<sub>8</sub> polyhedra in xenotime structures are lower than those reported for monazite structures. The xenotime compounds have shorter RE–O distances (2.2–2.4 Å) compared to monazites (2.4–2.6 Å) (Fig. 4a). The P–O bond distances of tetrahedra in xenotime compounds are generally shorter than those in monazite, but the differences are not significant. Xenotime has only one atomic position for the oxygen atom whereas monazite has four oxygen atomic positions. For both monazite and xenotime compounds, RE–P distances are dependent on the RE size, and xenotime has one RE–P distance along the chain whereas the monazite has two different RE–P distances. The RE–P distances of xenotime crystals are generally longer than

those of monazite, and RE–P distances between  $\mathrm{RE^{3^+}}$  and  $\mathrm{P^{5^+}}$  cations in xenotime are generally <3 Å. The  $\mathrm{CN_{eff}}$  values of xenotime compounds are smaller, in the range of 7.8–8.0, and smaller than monazite as expected (Fig. 4b). The unit cell parameters and volumes increase linearly with larger RE cations in the structures whereas the densities decrease nonlinearly (Fig. 5).

The RE<sup>3+</sup> cations at RE sites in the monazite and xenotime structures can be substituted by mixed +3 cations, a combination of +2 and +4 cations, or a combination of +2, +3, and +4 cations. Table 4 shows the list of synthetic monazite and xenotime compounds with mixed RE and summarizes the compositional effects. For monazites with mixed RE cations, increasing the average size of mixed cations in the structures increases the unit cell parameters and volumes as expected.<sup>88-90</sup>




Fig. 1 Illustration showing the relationship of (a) xenotime and (b) monazite structures of REPO<sub>4</sub> to the RE crystal radii ( $r_c$ ) from Shannon.<sup>49</sup> LuPO<sub>4</sub> (ICSD 46792) and LaPO<sub>4</sub> (ICSD 46788) were used to create the (a) xenotime and (b) monazite unit cell structures, respectively.

De Biasi et al.88 synthesized  $La_{1-x}Ce_xPO_4$  (x = 0-1) monazite compounds and showed that increasing La contents increased the unit cell parameters and cell volumes. Similarly, Terra et al.89 observed that increasing La contents in  $La_{1-x}Gd_xPO_4$  (x = 0-1) monazites increased the unit cell parameters and cell volumes. Thust et al.91 observed that increasing Eu content in  $La_{1-x}Eu_xPO_4$  (x = 0-1) monazite compounds increased the elastic stiffness coefficients, densities, heat capacities, and coefficients of thermal expansion (CTE). Arinicheva et al.92 observed that microhardness, fracture toughness, unit cell parameters, and cell volumes decreased linearly with increasing Eu content in  $La_{1-x}Eu_xPO_4$  (x = 0-1) monazite compounds. Van Emden et al. 90 synthesized  $Nd_{1-x}Y_xPO_4$  (x = 0.05-0.3) monazite compounds using a solid state method at 1000 °C and showed that increasing Nd content increased the unit cell parameters and cell volumes. The same group also observed cocrystallization of both monazite and xenotime in Nd<sub>1-x</sub>Y<sub>x</sub>PO<sub>4</sub> compounds when synthesized at 1200 °C.90 Hay et al.93 synthesized the  $Gd_{1-x}Dy_xPO_4$  (x = 0-1) xenotime compounds and observed that pressure and/or shear stress can cause phase transformation of xenotime to monazite. Strzelecki et al.94 investigated the thermodynamic properties of  $Er_{1-x}Yb_xPO_4$  (x =0-1) xenotime compounds and observed that increasing Er content increased the enthalpies of formation and decreased the Gibbs free energies. The unit cell parameters and cell volumes of  $Er_{1-x}Yb_xPO_4$  (x = 0-1) increased with higher Er content as predicted by Vegard's law.94 Xiao et al.95 synthesized Eu<sup>3+</sup>-doped xenotime single crystals including TbPO<sub>4</sub>, HoPO<sub>4</sub>, ErPO<sub>4</sub>, YbPO<sub>4</sub>, LuPO<sub>4</sub>, and YPO<sub>4</sub> with the Eu concentration of 200 ppm relative to the host RE cations. They observed that incorporation of Eu cations distorted the local structure around

RE sites and affected the rotations of PO<sub>4</sub> tetrahedra in the xenotime structures, and distortion levels were worse for xenotimes with large RE cations. Safiuddin *et al.* So synthesized solid solutions of  $La_{1-x}Yb_xPO_4$ ,  $La_{1-x}Y_xPO_4$ , and  $Sm_{1-x}Ho_xPO_4$  (x=0–1) and observed that these compounds with large differences in RE sizes resulted in the presence of both monazite and xenotime phases in the final product, and the phase fractions were dependent on the corresponding RE contents.

For the monazites with a mixed combination of +2 and +4 cations at RE sites, Pb, Cd, or alkaline earth metals (e.g., Mg, Ca, Sr, Ba) can be incorporated with actinide cations (e.g., Th, U, Np), respectively. The chemical formula is  $(M_x^{2+})(M_{(1-x)}^{4+})PO_4$ and many examples have been documented, including Ca<sub>0.5</sub>- $Th_{0.5}PO_{4},^{97} \quad Mg_{0.5}Th_{0.5}PO_{4},^{98} \quad Sr_{0.5}Th_{0.5}PO_{4},^{99} \quad Pb_{0.5}Th_{0.5}PO_{4},^{99}$  $Ca_{0.5}U_{0.5}PO_4$ ,  $^{100}Mg_{0.5}U_{0.5}PO_4$ ,  $^{98}Sr_{0.5}U_{0.5}PO_4$ ,  $^{98}Ca_{0.5}Np_{0.5}PO_4$ ,  $^{101}$  $Ca_{0.5}Np_{0.35}Pu_{0.15}PO_4$ , and  $Ca_{0.5}Th_{0.4}U_{0.1}PO_4$ . For the monazites with mixed combinations of +2 cations (e.g., Ba, Ca, Cd, Mg, Pb, Sr), +3 cations (REs), and +4 cations (actinides) can occupy RE sites, and the site occupancies of cations with different oxidation states can vary at the RE sites (e.g., Ca<sub>1/3</sub>Nd<sub>1/</sub>  $La_{0.808}Ba_{0.096}Th_{0.096}PO_4$ Ca<sub>0.146</sub>Nd<sub>0.716</sub>Th<sub>0.151</sub>-PO<sub>4</sub>). 98,99,104 The monovalent cations (e.g., Li, Na, K, Rb, Cs) with +3 RE cations or Ce<sup>4+</sup> can occupy the RE site of compounds that have similar structures to monazites [e.g., Na<sub>3</sub>La(PO<sub>4</sub>)<sub>2</sub>, LiCe<sub>2</sub>(- $PO_4$ <sub>3</sub>,  $K_2Ce(PO_4)_2$ ]. <sup>105,106</sup>

AXO<sub>4</sub> monazite-type structure stabilities can be dependent on various factors such as composition, temperature, pressure, and the irradiation conditions. Clavier *et al.*<sup>14</sup> reviewed crystal chemistry of the AXO<sub>4</sub> monazite-type compounds in terms of field of stability *versus* composition, with all the substitution

Review

Fig. 2 Structures of (a-c) monazite and (d-f) xenotime compounds. (a) Nine-fold coordination of the RE cation, (b) the chain of REO<sub>9</sub> and PO<sub>4</sub> along the *c* axis, and (c) atomic arrangements of RE and P viewed from the [001] direction in the monazite structure. (d) Eight-fold coordination of the RE cation, (e) the chain of REO<sub>8</sub> and PO<sub>4</sub> along the *c* axis, and (f) atomic arrangements of RE and P viewed from the [001] direction in the xenotime structure. The figure was made using CIFs of ICSD 431743 and ICSD 46792 for LaPO<sub>4</sub> monazite and LuPO<sub>4</sub> xenotime, respectively.

possibilities on the cationic and anionic sites leading to the monazite structure.

Several models, which include structure-field maps (Fig. 6a)107,108 and classification diagrams (see Fig. 6b for a modified Bastide diagram), 109-112 have been developed to correlate the stability of the monazite-type structure with geometric criteria. These representations provide opportunities to predict the structure of a compound. The challenge persists regarding the boundaries of the stability domain within this field. Numerous studies have investigated the stability domain of the monazite-type structure, aiming to develop predictive models that could anticipate whether a compound might take on the monazite structure. Carron et al.113 calculated that a value of 1.86 (ratio between the X-O bond length in the AXO<sub>4</sub> compounds and the  $r_i$ , denoted as  $X/r_i$ ) seems to specify the size limit of both the cation and the anion at the xenotime-monazite structural frontier. This ratio led to them113 proposing the potential for anionic isomorphous substitution among REphosphates, RE-silicates, RE-arsenates, and RE-vanadates. Macey114 further determined that monazite and zircon structures have  $X/r_i < 1/1.56$  and  $X/r_i > 1/1.56$ , respectively.

Podor and Cuney<sup>97</sup> subsequently explored the stability range of the monazite structure, primarily concentrating on  $(M_{1-2x}^{3+})(M_x^{2+})(M_x^{4+})PO_4$  compounds, where stability depends on three parameters  $(x, \text{ average } r_i, \text{ and the ratio of M elements})$ . Nonetheless, discrepancies with experimental observations could still occur, particularly concerning miscibility gaps. Kolitsch and Holtstam<sup>116</sup> devised a visual representation outlining the stability regions of both monazite and zircon-type structures, relying on existing data for REXO<sub>4</sub> (X = P, As, V) compounds. While this diagram offers a broad view of the monazite structure stability field, it is insufficient to correctly describe the partial solid solutions between two REXO<sub>4</sub> compounds, especially those involving a light RE element and a heavy RE element, and the presence of a miscibility gap.<sup>14</sup>

# 4 Properties

#### 4.1 Mechanical and thermal properties

Monazite and xenotime compounds exhibit interesting mechanical and thermal properties across different compositions and structures. Table 5 summarizes the mechanical




Fig. 3 Relationships of (a–c) unit cell parameters, (d) unit cell volumes, and (e) densities with respect to RE  $r_c$  of monazite compounds. Where multiple values were given, averages and standard deviations are reported.

properties of monazite and xenotime including Young's modulus (E), bulk modulus (B), shear modulus (G), hardness (H), and flexural strength (FS). Fig. 7 shows the relationships between Young's, bulk, and shear moduli and RE  $r_{\rm c}$  of monazite and xenotime. As the RE  $r_{\rm c}$  values decrease, this results in

increases for the Young's modulus, bulk modulus, and shear modulus, and this can be due to stronger interatomic bonding as the average RE-O distances are smaller for RE cations.<sup>117</sup> Different modulus values from various studies are also affected




Fig. 4 (a) Average RE-O bond distances and (b) effective coordination numbers of REO $_x$  polyhedral with respect to RE  $r_c$  in monazite and xenotime structures.

Review RSC Advances




Fig. 5 Relationships of (a and b) unit cell parameters, (c) unit cell volumes, and (d) densities with respect to RE  $r_c$  of xenotime compounds. Where multiple values were given, averages and standard deviations are reported.

by sample preparation and sintering conditions for the pellets.  $^{117,118}$ 

Table 6 summarizes the thermal properties of monazite and xenotime including heat capacity  $(C_p)$ , the CTE, thermal conductivity (k), thermal diffusivity ( $\alpha$ ), and melting temperatures  $(T_{\rm m})$ . In general, the CTE values of monazite compounds seem to increase with smaller RE cations and RE-O distances in the structures. In general, the CTE values of monazite compounds seem to increase with the larger RE cations and RE-O distances in the structures. The CTE value is related to the inter-atomic potential and depends on the dissymmetry of the potential well.34 Examples of calculated CTE values for both monazites and xenotimes are shown in Fig. 8.<sup>121</sup> The  $C_p$  values of monazite compounds are similar. The total heat capacity is the sum of the lattice component and an excess electronic term. The excess electronic heat capacity term increases for CePO<sub>4</sub>, PrPO<sub>4</sub>, NdPO<sub>4</sub>, SmPO<sub>4</sub>, and EuPO<sub>4</sub> monazites but not for LaPO<sub>4</sub> and GdPO4 due to empty and half-filled electron shell configurations, respectively, and this results in similar heat capacities among CePO<sub>4</sub> → EuPO<sub>4</sub>, and slightly lower values for LaPO<sub>4</sub> and GdPO4.34,117

Du et al.  $^{117}$  synthesized polycrystalline monazite compounds of LaPO<sub>4</sub>, CePO<sub>4</sub>, NdPO<sub>4</sub>, SmPO<sub>4</sub>, EuPO<sub>4</sub>, and GdPO<sub>4</sub> and

pressed into pellets using a spark plasma sintering apparatus at 1350 °C and 40 MPa for 3 min. Young's modulus increased linearly from LaPO<sub>4</sub> to GdPO<sub>4</sub> as the RE  $r_{\rm c}$  values decreased. The specific heat values of all the monazites were similar at a given temperatures from 25 °C to 1000 °C and increased as the temperature increased except Gd monazite, which showed lower values at higher temperatures (>600 °C) compared to other monazites. The thermal conductivities of monazite compounds decreased as the temperature increased from 25 to 1000 °C, except EuPO<sub>4</sub> and GdPO<sub>4</sub> that showed increased thermal conductivities from 800 to 1000 °C. This is possibly due to the contribution of radiation transport effect, which becomes more important at higher temperatures. The thermal diffusivity values showed similar behavior as thermal conductivity with respect to temperature.

Perrière *et al.*<sup>34</sup> investigated the structural dependence of the mechanical and thermal properties of monazite compounds including LaPO<sub>4</sub>, CePO<sub>4</sub>, PrPO<sub>4</sub>, NdPO<sub>4</sub>, SmPO<sub>4</sub>, EuPO<sub>4</sub>, and GdPO<sub>4</sub>. The synthesized monazite powders were pressed into pellets at 1500 °C and 65 MPa for 0.1–20 h. Both Young's modulus and shear modulus values increased with larger RE cations in the structure. The bending strengths of 94–122 MPa and fracture toughness around 1 MPa m<sup>1/2</sup> showed the brittle

Table 4 Monazite and xenotime compounds with mixed cations and their compositional effects. M and X denote monazite and xenotime structures, respectively

Composition	Struct.	Compositional effect	Ref.
$La_{1-x}Ce_{x}PO_{4}\left( x=0-1\right)$	M	Increasing La content increased the	88
		unit cell lengths and volumes	
$La_{1-x}Gd_xPO_4 (x = 0-1)$	M	Increasing La content increased the	89
		unit cell lengths and volumes	
$La_{1-x}Eu_xPO_4 (x = 0-1)$	M	Increasing Eu content increased the	91
		elastic stiffness coefficients,	
		density, heat capacity, and CTE	
$La_{1-x}Eu_xPO_4 (x = 0-1)$	M	Increasing Eu content decreased the	92
		hardness, toughness, unit cell	
		lengths, and cell volume	
$Nd_{1-x}Y_xPO_4$ ( $x = 0.05-0.3$ )	M	Increasing Nd content increased the	90
		unit cell parameters and cell	
		volumes	
$Gd_{1-x}Dy_xPO_4 (x = 0-1)$	X	Increasing Gd content increased the	93
		maximum indentation loadings	
$\operatorname{Er}_{1-x} \operatorname{Yb}_{x} \operatorname{PO}_{4} (x = 0 - 1)$	X	Increasing Er content increased the	94
		enthalpies of formation and unit	
		cell parameters and decreased the	
		Gibbs free energy values	
$REPO_4$ (RE = Tb, Ho, Er, Yb, Lu, Y)	X	Incorporation of Eu cations	95
doped with Eu <sup>3+</sup>		distorted the local structure around	
•		RE sites and affected the rotations	
		of PO <sub>4</sub> tetrahedra, and the	
		distortion level was worse for	
		xenotimes with larger RE cations	
$La_{1-x}Yb_xPO_4$ , $La_{1-x}Y_xPO_4$ ,	M, X	Both monazite and xenotime	96
$Sm_{1-x}Ho_xPO_4$ (x = 0-1)	,	phases were present in the final	
1-1 1 1 1 1 1		product depending on the	
		concentration of corresponding RE	
		elements	

behavior of monazite compounds, and this brittleness could cause inaccuracies when using micro-indentation analysis. The CTE values of monazites increased with smaller RE cations and RE–O distances in the structures and were in the 10– $11.5 \times 10^{-6}$  K<sup>-1</sup> range. The heat capacities of all the synthesized monazites

were  $\sim \! 105 \text{--} 112 \text{ J mol}^{-1} \text{ K}^{-1}$  (with La and Gd having the lowest values). Controlling porosity during fabrication was important for achieving accurate measurements of both thermal and mechanical properties.




Fig. 6 (a) Structure-field map of monazite and xenotime compounds based on the ionic radius (r<sub>i</sub>) of A (e.g., RE) and X (e.g., P) in AXO<sub>4</sub> compounds. <sup>107</sup> Reprinted with permission from Aldred. <sup>107</sup> Copyright 1984 American Chemical Society. (b) Modified Bastide diagram for ABX<sub>4</sub> compounds. Reprinted with permission from Hay et al. <sup>115</sup> Copyright 2013 Elsevier.

Table 5 Mechanical properties of monazite and xenotime compounds including Young's modulus (E), bulk modulus (B), shear modulus (G), hardness (H), and flexural strength (FS). M and X denote monazite and xenotime, and \* denotes calculated values

$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	RE	Struct.	E (GPa)	B (GPa)	G (GPa)	H (GPa)	FS (Mpa)
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	La	M	144*, <sup>119</sup> 151 (ref. 34)	134* <sup>121</sup>	(ref. 34)		
Nd M $\begin{array}{cccccccccccccccccccccccccccccccccccc$	Ce	M	146.5*, <sup>120</sup> 150, <sup>117</sup> 162* <sup>119</sup>	137.2* <sup>121</sup>			183 (ref. 123)
Nd M $154.1^{*,120} 157,^{117} 164,^{34} 168^{*119}$ $114.1^{*,120} 127,^{117} 135^{*,119}$ $60.4^{*,120} 61,^{117} 63,^{34} 65^{*119}$ — $122,^{34} 97$ (ref. $123$ )  Pm M $157.4^{*120}$ $171.1^{*120}$ $117.1^{*120}$ $61.7^{*120}$ $62,^{117} 63.1^{*,120} 66^{*119}$ — $135$ (ref. $123$ )  Sm M $160,^{117} 160.3^{*,120} 172^{*119}$ $116.2^{*,120} 127,^{117} 140^{*,119}$ $62,^{117} 63.1^{*,120} 66^{*119}$ — $99$ (ref. $146^{*12}$ )  Eu M $162,^{117} 163.1^{*,120} 174^{*,119} 202$ $118.1^{*,120} 127,^{117} 143^{*,119}$ $62,^{117} 64.2^{*,120} 67^{*,119} 79$ (ref. $99$ )  Gd M $165.2^{*,120} 172,^{117} 180^{*,119} 199$ $121^{*,120} 137,^{117} 150^{*,119} 149^{*,121}$ $64.9^{*,120} 67,^{117} 69^{*,119}$ $7.8,^{93} 7.9$ (ref. — $99$ )  Th M $164.5^{*,120}$ $123.3^{*,120}$ $123.3^{*,120}$ $123.3^{*,120}$ $124$ )  Tb X $48$ (ref. $93$ ) $138.8^{*,121}$ — $123.3^{*,120}$ $124$ ,	Pr	M	150.1*, <sup>120</sup> 164 (ref. 34)	113.5*, <sup>120</sup> 139.7* <sup>121</sup>	58.6*, 120 64 (ref. 34)	_	94 (ref. 34)
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Nd	M		142.3*121		_	122, <sup>34</sup> 97 (ref.
Eu M $162,^{117} 163.1^*,^{120} 174^*,^{119} 202$ $118.1^*,^{120} 127,^{117} 143^*,^{119}$ $62,^{117} 64.2^*,^{120} 67^*,^{119} 79$ (ref. $-$ 99 (ref. $34$ ) $-$ 147.1 $^{*121}$ $34$ ) $-$ 165.2 $^*,^{120} 172,^{117} 180^*,^{119} 199$ $121^*,^{120} 137,^{117} 150^*,^{119} 149^{*121}$ $64.9^*,^{120} 67,^{117} 69^{*119}$ $7.8,^{93} 7.9$ (ref. $-$ 124) $-$ 125 $-$ 127 (ref. $93$ ) $-$ 123.3 $^{*120}$ $-$ 123.3 $^{*120}$ $-$ 124 $-$ 125 $-$ 124 $-$ 127 (ref. $93$ ) $-$ 127.6 $^{*120}$ $-$ 128.8 $^{*121}$ $-$ 129 $-$ 1	Pm	M	157.4* <sup>120</sup>	117.1* <sup>120</sup>	61.7* <sup>120</sup>	_	
Eu M $\begin{array}{cccccccccccccccccccccccccccccccccccc$	Sm	M		116.2*, <sup>120</sup> 127, <sup>117</sup> 140*, <sup>119</sup> 146* <sup>121</sup>		_	135 (ref. 123)
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Eu	M	$162,^{117}$ $163.1*,^{120}$ $174*,^{119}$ $202$	$118.1^*,^{120}127,^{117}143^*,^{119}$	62, <sup>117</sup> 64.2*, <sup>120</sup> 67*, <sup>119</sup> 79 (ref.	_	99 (ref. 34)
$\begin{array}{cccccccccccccccccccccccccccccccccccc$					34)		
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Gd	M	165.2*, <sup>120</sup> 172, <sup>117</sup> 180*, <sup>119</sup> 199	121*, <sup>120</sup> 137, <sup>117</sup> 150*, <sup>119</sup> 149* <sup>121</sup>	64.9*, <sup>120</sup> 67, <sup>117</sup> 69* <sup>119</sup>	7.8, <sup>93</sup> 7.9 (ref.	_
$\begin{array}{cccccccccccccccccccccccccccccccccccc$			(ref. 93)			124)	
Tb X 48 (ref. 93) 138.8*121 — 1.3, $^{93}$ 5.7 (ref. — 124) — 124) — 124) — 125 (ref. 32) 141.5*121 — 4.6, $^{118}$ 6.6 (ref. — 124) — 125 (ref. 126) — 126)			164.5* <sup>120</sup>	$123.3^{*120}$	$64.4^{*120}$	_	_
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Dy	M		127.6* <sup>120</sup>	$64.4^{*120}$	_	_
Ho X $166.2^{*71}$ $138.9^{*,71}$ $143.4^{*121}$ $63.9^{*71}$ $  100$ (ref. 126) Er X $178^{*125}$ $144^{*,125}$ $146.1^{*,121}$ $168$ (ref. 125) $69^{*125}$ $ 100$ (ref. 126) Tm X $178.1^{*71}$ $144.1^{*,71}$ $147.2^{*121}$ $68.8^{*71}$ $  178.1^{*71}$ $147.2^{*121}$ $129^{*,125}$ $129^{*,125}$ $150^{*121}$ $129^{*,125}$ $129^{*,12$	Tb	X	48 (ref. 93)		_		_
Ho X $166.2^{*71}$ $138.9^{*,71}$ $143.4^{*121}$ $63.9^{*71}$ $  100$ (ref. 126) Er X $178^{*125}$ $144^{*,125}$ $146.1^{*,121}$ $168$ (ref. 125) $69^{*125}$ $ 100$ (ref. 126) Tm X $178.1^{*71}$ $144.1^{*,71}$ $147.2^{*121}$ $68.8^{*71}$ $  178.1^{*71}$ $147.2^{*121}$ $129^{*,125}$ $129^{*,125}$ $150^{*121}$ $129^{*,125}$ $129^{*,12$	Dy	X	127 (ref. 32)	$141.5^{*121}$	_	4.6, 118 6.6 (ref.	_
Er X $178^{*125}$ $144^{*,125}$ $146.1^{*,121}$ $168$ (ref. 125) $69^{*125}$ — 100 (ref. 126) Tm X $178.1^{*71}$ $144.1^{*,71}$ $147.2^{*121}$ $68.8^{*71}$ — — 135 (ref. 126) Y X $160^{*125}$ $129^{*,125}$ $150^{*121}$ $152.8^{*,121}$ $169.3^{*71}$ $170^{*125}$ $73.3^{*71}$ $81^{*125}$ $7.42$ (ref. 71) $155$ (ref. 126) Y X $145.5^{*71}$ $224^{*,125}$ $186$ (ref. 127) $132.4^{*71}$ $144.4^{*,121}$ $173^{*125}$ $132.4^{*71}$ $144.4^{*,121}$ $173^{*125}$ $144.4^{*,121}$ $173^{*125}$ $144.4^{*,121}$ $173^{*125}$ $144.4^{*,121}$ $173^{*125}$ $144.4^{*,121}$ $173^{*125}$ $144.4^{*,121}$ $173^{*125}$ $144.4^{*,121}$ $173^{*125}$ $144.4^{*,121}$ $173^{*125}$ $144.4^{*,121}$ $173^{*125}$ $154.5^{*1}$ $155^{*1}$ $1$							
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Но	X	166.2* <sup>71</sup>	138.9*, <sup>71</sup> 143.4* <sup>121</sup>	63.9* <sup>71</sup>	_	_
Yb X 160* <sup>125</sup> 129*, <sup>125</sup> 150* <sup>121</sup> 62* <sup>125</sup> — 135 (ref. 126) Lu X 192.1, <sup>71</sup> 210* <sup>125</sup> 152.8*, <sup>121</sup> 169.3, <sup>71</sup> 170* <sup>125</sup> 73.3, <sup>71</sup> 81* <sup>125</sup> 7.42 (ref. 71) 155 (ref. 126) Y X 145.5, <sup>71</sup> 224*, <sup>125</sup> 186 (ref. 127) 132.4, <sup>71</sup> 144.4*, <sup>121</sup> 173* <sup>125</sup> 55.2, <sup>71</sup> 87* <sup>125</sup> 5.83 (ref. 71) 95 (ref. 126)	Er	X	178* <sup>125</sup>	144*, 125 146.1*, 121 168 (ref. 125)	69* <sup>125</sup>	_	100 (ref. 126)
Lu X 192.1, <sup>71</sup> 210* <sup>125</sup> 152.8*, <sup>121</sup> 169.3, <sup>71</sup> 170* <sup>125</sup> 73.3, <sup>71</sup> 81* <sup>125</sup> 7.42 (ref. 71) 155 (ref. 126) Y X 145.5, <sup>71</sup> 224*, <sup>125</sup> 186 (ref. 127) 132.4, <sup>71</sup> 144.4*, <sup>121</sup> 173* <sup>125</sup> 55.2, <sup>71</sup> 87* <sup>125</sup> 5.83 (ref. 71) 95 (ref. 126)	Tm	X	178.1* <sup>71</sup>	$144.1^{*,71}$ $147.2^{*121}$	68.8* <sup>71</sup>	_	_
Lu X 192.1, <sup>71</sup> 210* <sup>125</sup> 152.8*, <sup>121</sup> 169.3, <sup>71</sup> 170* <sup>125</sup> 73.3, <sup>71</sup> 81* <sup>125</sup> 7.42 (ref. 71) 155 (ref. 126) Y X 145.5, <sup>71</sup> 224*, <sup>125</sup> 186 (ref. 127) 132.4, <sup>71</sup> 144.4*, <sup>121</sup> 173* <sup>125</sup> 55.2, <sup>71</sup> 87* <sup>125</sup> 5.83 (ref. 71) 95 (ref. 126)	Yb	X	$160^{*125}$		62*125	_	135 (ref. 126)
Y X 145.5, <sup>71</sup> 224*, <sup>125</sup> 186 (ref. 127) 132.4, <sup>71</sup> 144.4*, <sup>121</sup> 173* <sup>125</sup> 55.2, <sup>71</sup> 87* <sup>125</sup> 5.83 (ref. 71) 95 (ref. 126)	Lu	X	$192.1,^{71} 210^{*125}$				155 (ref. 126)
Co. V. 202 127 211 *125 175 1 * 121 140 *125 04 *125	Y	X	145.5, <sup>71</sup> 224*, <sup>125</sup> 186 (ref. 127)	$132.4,^{71}$ $144.4*,^{121}$ $173*^{125}$	55.2, <sup>71</sup> 87* <sup>125</sup>	5.83 (ref. 71)	95 (ref. 126)
Sc A 203, 211 1/3.17, 140 64 — —	Sc	X	203, 127 211*125	175.1*, <sup>121</sup> 140* <sup>125</sup>	84*125	_	_

Li *et al.*<sup>121</sup> calculated theoretical mechanical and thermal properties of monazite (La  $\rightarrow$  Gd) and xenotime (Tb  $\rightarrow$  Lu, Y, and Sc) compounds using the chemical bond theory of dielectric description. The CTE values increased with larger RE cations in the structures whereas the bulk moduli and lattice energies decreased. The CTE values were in the range of 7.78–7.47  $\times$  10 $^{-6}$  K $^{-1}$  for the La  $\rightarrow$  Gd monazite compounds and 5.88–5.72  $\times$  10 $^{-6}$  K $^{-1}$  range for Tb  $\rightarrow$  Lu xenotime compounds. The CTE and bulk modulus values were dependent on the RE–O bonds. The RE–O distances were ionically dominated and changed with different RE cations due to lanthanide contraction, and PO $_4$  tetrahedra showed relatively high lattice energies and behaved nearly rigidly during deformation.

Kenges *et al.*<sup>118</sup> synthesized pellet samples of LaPO<sub>4</sub> monazite compounds with different sintering temperatures from 900 °C to 1500 °C and measured mechanical and thermal properties. The LaPO<sub>4</sub> compounds contained a small amount of impurity phase La(PO<sub>3</sub>)<sub>3</sub> (lanthanum metaphosophate). The LaPO<sub>4</sub> monazite pellet sintered at 1100 °C showed the highest Young's modulus, toughness, and thermal conductivity. Increasing the sintering temperature increased the crystallite size and decreased the porosities of pellets. The LaPO<sub>4</sub> monazite pellet sintered at 1100 °C had a Young's modulus of 132 GPa, a hardness of 4.6 GPa, a toughness of 1.6 MPa m<sup>1/2</sup>, a CTE of  $8.2 \times 10^{-6} \ \text{K}^{-1}$ , and a thermal conductivity of 3.2 W m<sup>-1</sup> K<sup>-1</sup> at 25 °C.

Deepthi and Balamurugan<sup>131</sup> compared the flexural strength and Young's modulus of LaPO<sub>4</sub> and LaPO<sub>4</sub> mixed with 20 mass%  $Y_2O_3$ . The LaPO<sub>4</sub>/ $Y_2O_3$  pellets were sintered at 1000–1600 °C, and a pellet sintered at 1400 °C resulted in more uniform grain structure with less porosity. The LaPO<sub>4</sub>/ $Y_2O_3$  pellet showed a reduction in flexural strength by 22% but increase of 1.05% in Young's modulus compared to the LaPO<sub>4</sub> pellet.

Popa and Konings¹²²² synthesized EuPO $_4$  and SmPO $_4$  monazite compounds and calculated their heat capacities. They used the enthalpy data of Sm and Eu monazites along with data from other La, Ce, Nd, and Gd monazites and calculated the heat capacity as a sum of lattice contributions and an excess electronic term. The calculated heat capacities of La  $\rightarrow$  Gd monazites were in the range of 101.28–111.49 J mol $^{-1}$  K $^{-1}$  range, and these values were in good agreement with the experimental values.

Hay et al.<sup>93</sup> investigated the phase transformations and deformation mechanisms of GdPO<sub>4</sub>, TbPO<sub>4</sub>, and DyPO<sub>4</sub> compounds using scanning electron microscopy (SEM) and transmission electron microscopy (TEM) after indentation. The synthesized powders of TbPO<sub>4</sub> and DyPO<sub>4</sub> had xenotime structures whereas GdPO<sub>4</sub> had a monazite structure. These materials were cold pressed at ~300 MPa and sintered at 1600 °C for 20 h and 1700 °C for 1 h. The GdPO<sub>4</sub>, TbPO<sub>4</sub>, and DyPO<sub>4</sub> compounds showed Young's moduli of 199, 48, and 127 GPa and hardness values of 7.8, 1.3, and 4.6 GPa, respectively. The authors observed stress-induced transformations from xenotime to monazite and suggested ferroelastic behavior under certain conditions.




Fig. 7 (a and c) Young's modulus and (b and d) bulk modulus values of (a and b) monazite and (c and d) xenotime compounds as functions of crystal radius of the RE cation  $(r_c)$ .

Hikichi *et al.*<sup>126</sup> measured the specific heats, thermal diffusivities, thermal conductivities, and bending strengths of xenotime pellets including ErPO<sub>4</sub>, YbPO<sub>4</sub>, LuPO<sub>4</sub>, and YPO<sub>4</sub>. The xenotime pellets were sintered at 700 °C to 1700 °C. The YbPO<sub>4</sub> and LuPO<sub>4</sub> pellets sintered above 1300 °C as well as YPO<sub>4</sub> and ErPO<sub>4</sub> pellets sintered above 1500 °C showed relative densities of  $\geq$ 98%. The bending strengths increased with larger RE cations in the structures. The heat capacities of Er, Yb, Lu, and Y xenotime compounds were 0.40, 0.38, 0.38, and 0.48 J mol $^{-1}$  K $^{-1}$  at 20 °C, respectively. The CTE values were 6.0 × 10 $^{-6}$  K $^{-1}$  for Er and Yb compounds and 6.2 × 10 $^{-6}$  K $^{-1}$  for Lu and Y compounds.

Wilkinson *et al.*<sup>124</sup> studied bulk modulus and hardness properties of EuPO<sub>4</sub>, GdPO<sub>4</sub>, TbPO<sub>4</sub>, and DyPO<sub>4</sub> compounds using *in situ* nanoindentation for a range of loading rates and indentation depths. EuPO<sub>4</sub> and GdPO<sub>4</sub> formed monazite structures, and TbPO<sub>4</sub> and DyPO<sub>4</sub> formed xenotime structures. The bulk modulus values were decreasing in order of Gd, Eu, Dy, and Tb compounds. Both Eu and Gd compounds showed hardnesses of 8–9 GPa whereas Tb and Dy compounds showed hardnesses of 6–7 GPa. Hardnesses for all four compounds were not impacted by indentation depth or strain rate.

In addition to experimental methods, first principles calculations were also used to calculate the structural and physical

properties of monazite and xenotime crystals. Kowalski and Li<sup>120</sup> calculated elastic moduli of La, Ce, Pr, Nd, Pm, Sm, Eu, Gd, Tb, and Dy monazites using ab initio density functional theory (DFT). The Margules interaction parameters, which is related to excess enthalpy of mixing in a RE1<sub>r</sub>RE2<sub>(1-r)</sub>PO<sub>4</sub> solid solution, and moduli were related to the mismatch in the endmember volumes of different RE cations within the structures. The computed Young's moduli, bulk moduli, and shear moduli increased with decreases in RE cation radii. The range of Young's moduli, bulk moduli, and shear moduli were 139-165 GPa, 110-129 GPa, and 54-65 GPa, respectively. Feng et al.119 calculated theoretical mechanical and thermal properties of monazite compounds using the results of local spin density approximation and compared to the experimental values. The Young's moduli, bulk moduli, and shear moduli of LaPO<sub>4</sub>, CePO<sub>4</sub>, NdPO<sub>4</sub>, SmPO<sub>4</sub>, EuPO<sub>4</sub>, and GdPO<sub>4</sub> increased with smaller RE cations and shorter RE-O distances in the structures. The Young's modulus of monazite compounds showed high anisotropy. The calculated coefficients of linear thermal expansion were similar to experimental values, but the calculated thermal conductivities were higher than experimental values measured at >800 K.

Blanca-Romero *et al.*  $^{132}$  used the DFT + U method to calculate the structures and thermodynamic properties of monazite type

Table 6 Thermal properties of monazite and xenotime compounds including heat capacity ( $C_p$ ), coefficient of thermal expansion (CTE), thermal conductivity (k), thermal diffusivity ( $\alpha$ ), and melting temperature ( $T_m$ ). The measured and calculated temperatures are shown in the parentheses and \* denotes values that were calculated

RE	Struct.	$C_{\mathrm{p}}\left(\mathrm{J~mol^{-1}~K^{-1}}\right)$	CTE ( $\times 10^{-6} \text{ K}^{-1}$ )	$k (W m^{-1} K^{-1})$	$\alpha \ (mm^2 \ s^{-1})$	$T_{\mathrm{m}}$ (°C)
La	M	101.28 (25 °C), 128 101.28* (25 ° C), 128 106 (50 °C) <sup>34</sup>	7.78*, <sup>121</sup> 8.2 (25–1050 °C), <sup>118</sup> 8.894*, <sup>119</sup> 10 (20–1000 °C), <sup>123</sup> 10.3 (200–1000 °C) <sup>34</sup>	3.2 (25 °C), <sup>118</sup> 3.61 (25 °C), <sup>117</sup> 5.3 (50 °C) <sup>34</sup>	1.629 (25 ° C) <sup>117</sup>	2072 (ref. 129)
Се	M	106.4 (25 °C), $^{128}$ 106.63* (25 °C), $^{128}$ 110 (50 °C) $^{34}$	7.71*, <sup>121</sup> 9.029*, <sup>119</sup> 9.9 (20–1000 ° C) <sup>123</sup>	3.14 (25 °C) <sup>117</sup>	1.334 (25 ° C) <sup>117</sup>	2045 (ref. 129)
Pr	M	106.04* (25 °C), <sup>128</sup> 108 (50 °C) <sup>34</sup>	7.66*, <sup>121</sup> 10.9 (200–1000 °C) <sup>34</sup>	3.4 (50 °C) <sup>34</sup>	<del>_</del>	1938 (ref. 129)
Nd	M	104.8 (25 °C), <sup>128</sup> 104.92* (25 °C), <sup>128</sup> 108 (50 °C) <sup>34</sup>	$7.61^{*}$ , $^{121}$ $8.093^{*}$ , $^{119}$ $9.4^{*}$ , $^{119}$ $9.8$ $(20-1000$ °C), $^{123}$ $10.7$ $(200-1000$ °C) $^{34}$	3.05 (25 °C), <sup>117</sup> 4.4 (50 °C) <sup>34</sup>	1.274 (25 ° C) <sup>117</sup>	1975 (ref. 129)
Sm	M	105.59* (25 °C), 128 112 (50 °C) <sup>34</sup>	7.54*, <sup>121</sup> 9.7 (20–1000 °C), <sup>123</sup> 9.738*, <sup>119</sup> 11 (200–1000 °C) <sup>34</sup>	2.87 (25 °C), <sup>117</sup> 3.9 (50 °C) <sup>34</sup>	1.160 (25 ° C) <sup>117</sup>	1916 (ref. 129)
Eu	M	110 (50 °C), <sup>34</sup> 111.49 (25 °C) <sup>128</sup>	$7.51*,^{121},^{121},^{121},^{119},^{119},^{11.1},^{1$	2.99 (25 °C), <sup>117</sup> 5.8 (50 °C) <sup>34</sup>	1.135 (25 ° C) <sup>117</sup>	2200 (ref. 119)
Gd	M	102.21 (25 °C), $^{128}$ 102.21* (25 °C), $^{128}$ 105 (50 °C) $^{34}$	$7.47*,^{121},^{121},^{121},^{119},^{119},^{11.4}$	3.22 (25 °C), <sup>117</sup> 4.8 (50 °C) <sup>34</sup>	1.322 (25 ° C) <sup>117</sup>	2200 (ref. 119)
Tb	X	101.4* (25 °C) <sup>130</sup>	5.88*121	_	_	2150 (ref. 1)
Dy	X	102.5* (25 °C) <sup>130</sup>	5.85* <sup>121</sup>	_	_	2150 (ref. 1)
Но		102.4* (25 °C) <sup>130</sup>	5.82*121	_	_	_ ` `
Er	X	102.3* (25 °C) <sup>130</sup>	5.79*, <sup>121</sup> 6 (1000 °C) <sup>126</sup>	12.01 (20 °C) <sup>126</sup>	0.5 (20 °C) <sup>126</sup>	1896 (ref. 129)
Tm	X	102.7* (25 °C) <sup>130</sup>	5.78* <sup>121</sup>	_	_	_ ′
Yb	X	102.8* (25 °C) <sup>130</sup>	5.75*, <sup>121</sup> 6 (1000 °C) <sup>126</sup>	11.71 (20 °C) <sup>126</sup>	0.5 (20 °C) <sup>126</sup>	_
Lu	X	100.2* (25 °C) <sup>130</sup>	5.72*, 121 6.2 (1000 °C) 126	11.97 (20 °C) <sup>126</sup>	0.5 (20 °C) <sup>126</sup>	
Y	X	100.3* (25 °C) <sup>130</sup>	6.2 (1000 °C), 126 6.7*121	12.02 (20 °C) <sup>126</sup>	0.6 (20 °C) <sup>126</sup>	
Sc	X	_	6.95*121	_	_	




Fig. 8 Summary of calculated CTE values for both monazite and xenotime REPO $_4$  crystals from Li et  $al.^{121}$  as a function of RE  $r_c$ .

crystals, with a goal to test the accuracy of the method for modeling f electron-containing systems such as RE-monazites. They found significant improvement both in terms of structures (lattice parameters, unit cell volumes, and RE-O distances for both RE oxides and phosphates) and properties (formation energies for RE phosphates and band gaps for RE oxides) of the DFT  $\,^+$   $\,^U$  method as compared to the standard DFT in

comparison to experimental values. Overall, the DFT + U method with the PBEsol (Perdew-Burke-Ernzerhof functional revised for solids) exchange correlation functional and Hubbard U parameters derived from linear response-based ab initio calculations was found to be a good choice for studying RE oxides and monazites.

Beridze *et al.*<sup>133</sup> further investigated the DFT + U method for *ab initio* calculations of xenotime- and actinide-bearing complexes. The accuracy of the description of RE–O bond distances in xenotime was compared for two standard DFT xc functionals (PBEsol with f electrons in the core and f electrons in the valence shells) and the DFT + U (PBEsol +  $U_{LR}$ , with the U values calculated from *ab initio* linear response). It was found that the DFT + U method has the best description of RE–O distances in xenotime crystals while both DFT + U and DFT (PBEsol with f electrons in the core) describe formation energies with good agreement with experiment, when accounting for the overestimation of  $P_2O_5$  volume, similar to the case of monazites.<sup>132</sup>

#### 4.2 Chemical durability

In general, the chemical durabilities of RE-phosphate and actinide-phosphate compounds documented in the literature are very high. Solubility product constants ( $K_{\rm sp}$ ) for hydrated actinide-phosphate (AnPO<sub>4</sub>·xH<sub>2</sub>O) and RE-phosphate (REPO<sub>4</sub>-xH<sub>2</sub>O) compounds, which cover rhabdophane, monazite, and xenotime compounds, have been found within the range of

RSC Advances Review

 $\log(K_{S,0}^{\circ}) = -27.4$  to -24.5 for  $\text{LaPO}_4 \cdot 0.5 \text{H}_2 \text{O}^{134-136}$  to  $\log(K_{S,0}^{\circ}) = -66.6$  for  $\text{Th}_2(\text{PO}_4)_2(\text{HPO}_4) \cdot \text{H}_2 \text{O}^{135,136}$  at 25 °C. Values for  $\log(K_{S,0}^{\circ})$  at 100 °C were reported at -26.0 for  $\text{NdPO}_4 \cdot 0.5 \text{H}_2 \text{O}$  (rhabdophane), -25.7 for  $\text{PrPO}_4 \cdot 0.5 \text{H}_2 \text{O}$  (rhabdophane), and -25.5 for  $\text{ErPO}_4 \cdot n \text{H}_2 \text{O}$  (xenotime).  $^{46,134,136}$  Documented apparent activation energy ( $E_a$ ) values fall within the 39–45 kJ  $\text{mol}^{-1}$  range.  $^{89,137}$  Oftentimes, the REPO $_4$  compounds are used as surrogates for the actinide-equivalent analogs because they are easier and less costly to study than the actinide-containing phases.  $^{138,139}$  A summary of normalized release rate ( $\text{NR}_i$ ) data from the literature on these types of phosphate compounds is provided in Table 7.

In a study by Teng *et al.*,<sup>140</sup> a mixed  $Ce_{0.5}Pr_{0.5}PO_4$  monazite sample set was produced from  $Pr_6O_{11}$ ,  $Ce_2(C_2O_4)_3 \cdot 10H_2O$ , and ADP. Particles were ball milled in ethanol (4 h), dried at 60 °C (18 h), and calcined at 1000 °C (2 h). Calcined products were mixed with 5–10% polyvinyl alcohol (PVA). The calcined material was cold uniaxially pressed at 60 MPa, cold isostatically pressed at 200 MPa, and then calcined at 500 °C (6 h). Finally, samples were hot-pressed in evacuated graphite molds (<10 Pa of atmosphere, 30 MPa applied load) at temperatures of 1050–1250 °C for 0.5–4 h. A select set of samples (1150 °C for 2 h) were subjected to MCC-1 (ASTM C1220) chemical durability tests at

a 1:10 cm<sup>-1</sup> surface-area-to-volume (sample: leachant) ratio at 90 °C in PTFE containers for different testing durations ranging from 3 d to 42 d where leachates were quantitatively measured using inductively coupled plasma mass spectrometry (ICP-MS). After 42 d of leaching, the NR<sub>i</sub> values were found to be 5.7  $\times$  10<sup>-6</sup> g m<sup>-2</sup> d<sup>-1</sup> for Ce and 5.3  $\times$  10<sup>-5</sup> g m<sup>-2</sup> d<sup>-1</sup> for Pr.

In a study by Oelkers and Poitrasson, <sup>137</sup> dissolution tests were run on natural monazite from Manangotry (Madagascar) in open mixed flow reactors under different conditions of 50–229 °C (pH = 2) and 70 °C (pH = 1.6, 2.6, or 10) and closed reactors at 70 °C (pH = 2, 6, or 10). The starting material was ground to a 50–100  $\mu$ m particle size fraction. The results showed a range of leach rates with the highest releases revealed for the highest test temperatures ( $\geq$  200 °C).

In a study by Terra et~al., so several monazites were made in the solid solution system of  $La_{(1-x)}Gd_xPO_4$  (x=0,0.2,0.3,0.35,0.4,0.5,0.6,0.65,0.7,0.8, and 1.0). Starting materials included  $La(NO_3)_3 \cdot 6H_2O$ ,  $LaCl_3 \cdot 7H_2O$ ,  $Gd(NO_3)_3 \cdot 6H_2O$ ,  $GdCl_3 \cdot 6H_2O$ , and  $H_3PO_4$ . An excess of  $H_3PO_4$  was included to prevent  $RE_2O_3$  formation during synthesis. Aqueous solutions of the RE reagents (i.e., 0.6–1.4 M) were prepared and these were added to 5 M  $H_3PO_4$ . Three different methods were used to synthesize the compounds. In the first approach, heat was applied in different

Table 7 Summary of chemical durability data for REPO<sub>4</sub> compounds<sup>a</sup> including the composition (if given), test conditions, normalized release rate (NR<sub>i</sub>) for element "i" (if given), and the reference

Composition	Test conditions	$NR_i$ (g m <sup>-2</sup> d <sup>-1</sup> )	Ref.
Ce <sub>0.5</sub> Pr <sub>0.5</sub> PO <sub>4</sub>	MCC-1 (ASTM C1220); <i>T</i> = 90 °C, pH	$5.7 \times 10^{-6}  [\text{Ce}]$	140
	= 7, $t$ = 42 days, PTFE, DIW	$5.3  imes 10^{-5} [Pr]$	
Natural <sup>b</sup>	50 °C < T < 229 °C; 1.62 < pH < 10.04;	$8.13 \times 10^{-7}  [\text{Ce}]  (70  ^{\circ}\text{C},  \text{pH} = 6)$	137
	50–100 μm particles	$4.13 \times 10^{-5}$ [Ce] (70 °C, pH = 1.6)	
		$9.29 \times 10^{-7} [Ce] (50 \text{ °C, pH} = 2)$	
		$2.69 \times 10^{-3}$ [Ce] (229 °C, pH = 2)	
$GdPO_4$	200 mg in 5 mL acidic solution;	$2.2 \pm 0.7  imes 10^{-5}  [ ext{Gd}]  ( ext{RT})$	89
	removed 100 $\mu$ L for time resolved	$5.9 \pm 2.1  imes 10^{-4}   ext{[Gd]}  (90  {}^{\circ} ext{C})$	
	data points and replaced with fresh		
	solution; 90 °C; 0.1 M HNO <sub>3</sub>		
(La,Nd,Pr)PO <sub>4</sub>	Under saturation in either static	$10^{-3}$ to $10^{-7}$	136
	tests (in HDPE with low leachate		
	renewal) or dynamic tests (in PTFE		
	with high leachate removal)		
$REPO_4$	25 °C < T < 90 °C	$1.17 \times 10^{-3} [La] (90  ^{\circ}C)$	141
		$4.3 \times 10^{-4} [Ce] (90 °C)$	
		$1.01 \times 10^{-3} [Nd] (90 ^{\circ}\text{C})$	
		$4.02 \times 10^{-3}  [\text{Gd}]  (90  ^{\circ}\text{C})$	
$REPO_4$	$T = 90  ^{\circ}\text{C};  0.1  \text{M HNO}_3$	$1.4 \times 10^{-3} [La]$	142
		$1.8 \times 10^{-3}  [\text{Ce}]$	
		$1.0\times10^{-3}[\mathrm{Nd}]$	
		$1.6 \times 10^{-3}$ [Eu]	
		$1.0\times10^{-3}[\mathrm{Gd}]$	
$REPO_4$	50% H <sub>2</sub> O vapor balanced with O <sub>2</sub> at	$5.6 \times 10^{-2} [Sc]$	125
	$0.3~{\rm cm~s}^{-1}$ , 1500 °C, and 1 atm for	$6.0 imes10^{-2}  ilde{ ext{[Y]}}$	
	80 h.	$9.8 \times 10^{-2} [\mathrm{Er}]$	
		$1.0 \times 10^{-1} [\text{Yb}]$	
		$4.5 \times 10^{-2}  [\mathrm{Lu}]$	

<sup>&</sup>lt;sup>a</sup> ASTM denotes American Society for Testing and Materials International; DIW denotes deionized water; MCC denotes Materials Characterization Center;  $NR_i$  denotes the *i*-th element normalized release rate; PTFE denotes polytetrafluoroethylene; RT denotes room temperature (*i.e.*, ~20–25 °C). <sup>b</sup> Natural monazite from Manangotry (Madagascar) listed with composition of ( $Ca_{0.04}La_{0.21}Ce_{0.43}Pr_{0.05}Nd_{0.15}Sm_{0.02}Gd_{0.01}Th_{0.13})P_{0.90}Si_{0.09}O_4$  with a calculated (normalized) molecular weight of 248.85 g mol<sup>-1</sup>.

steps: (1) samples were dried through direct evaporation using a sand bath, (2) dried material was ground to finer particle size and heated at 400 °C (14 h), and (3) heated at 1300 °C (10–14 h). In the second approach, the mixture was placed in a PTFE container at 150 °C in a sand bath for 1–2 weeks. The third approach utilized a hydrothermal synthesis process with additives in PTFE Parr autoclaves at 150–200 °C for 1–2 months. The GdPO<sub>4</sub> compound was subjected to chemical durability testing as shown in Table 7.

In a study by Du Fou de Kerdaniel,  $^{136}$  AnPO $_4 \cdot x$ H $_2$ O compounds (An = Th, U) were produced using low-temperature methods based on procedures by Terra  $et~al.^{143}$  and Clavier  $et~al.^{144}$  or using dry chemistry routes by grinding mixtures and heating these mixtures to 1100-1400 °C where the target cations were Th, U, and REs. Leaching studies were performed under saturation in either static tests (in HDPE with low leachate renewal) or dynamic tests (in PTFE with high leachate removal) where solutions were analyzed with ICP-MS, time-resolved laser fluorescence spectroscopy, or  $\alpha$ -scintillation counting. Dissolved solids were determined as mass loss and reported as  $R_{L(i)}$  (i = element of interest) where  $R_{L(i)}$  values ranged from  $10^{-7}$  to  $10^{-3}$  g m $^{-2}$  d $^{-1}$ .

In a study by Hikichi et~al., <sup>126</sup> the stabilities of RE elements of ErPO<sub>4</sub>, YbPO<sub>4</sub>, LuPO<sub>4</sub>, and YPO<sub>4</sub> xenotime compounds in acidic or basic aqueous environments were investigated. The mass% losses of RE elements from xenotime compounds were measured using HCl, H<sub>2</sub>SO<sub>4</sub>, HNO<sub>3</sub>, NaOH, NH<sub>4</sub>OH solutions with concentrations of 6–36 N, and the test was conducted at 20 °C for 30 d. The results showed that the tested xenotime compounds were stable in these solutions, and the mass losses of RE elements were < 0.7 mass%.

In a study by Han *et al.*, <sup>125</sup> xenotime powders including ErPO<sub>4</sub>, YbPO<sub>4</sub>, LuPO<sub>4</sub>, ScPO<sub>4</sub>, and YPO<sub>4</sub> were cold pressed into pellets at 50 MPa and sintered at 1500 °C for 20 h in air. Chemical durability tests were performed using a vapor flow of 50% H<sub>2</sub>O balanced with O<sub>2</sub> at 0.3 cm s<sup>-1</sup> at 1500 °C and 1 atm for 80 h. The results showed dissolution rates of 5–10  $\times$  10<sup>-2</sup> g m<sup>-2</sup> d<sup>-1</sup> for xenotime compounds. However, the tests were performed in an alumina tube furnace, and formation of Al<sub>5</sub>RE<sub>3</sub>O<sub>12</sub> compounds were observed.

Rafiuddin and Grosvenor<sup>145</sup> investigated the room-temperature chemical durabilities of monazite-type, xenotime-type, and rhabdophane-type compounds on fine particles with specific surface areas ranging 1.3–15.1 m<sup>2</sup> g<sup>-1</sup>. Two types of tests were run including dynamic tests over 84 d and static tests over 3 months. The tests revealed that the rhabdophane (GdPO<sub>4</sub>·H<sub>2</sub>O) structure released higher quantities of Gd and P ions in deionized water within the initial week of exposure. Analysis of the long-range and local structures of these materials indicates that the structures of these materials remained unchanged after seven months of leaching.

Wronkiewicz *et al.*<sup>146</sup> studied the chemical durabilities of glass-crystal composites (GCCs) containing different crystalline phases, including apatite, monazite [(Ce,U)PO<sub>4</sub>], and spinel. The tests run included the product consistency test (PCT, t=7 d, 28 d, and 91 d),<sup>147</sup> the vapor hydration test (VHT),<sup>148</sup> and the Toxicity Characteristic Leach Procedure (TCLP).<sup>149</sup> The

monazite was noted as having fewer elements (*i.e.*, Ce, U, Th) compared to the apatite sample. The leachate from the PCTs (t=7–91 d) was noted as being slightly acidic (pH  $\approx 5.6$ –6.2). The apatite and monazite samples were noted as being 100– $300\times$  more durable than a glass waste form (*i.e.*, SRL-202U) for U release.

Poitrasson *et al.*<sup>150</sup> studied naturally formed magmatic monazites from European-based Paleozoic granites. Their studies showed that the hydrothermal alteration of these monazites was notably complex including a variety of mechanisms such as monoclinic  $\rightarrow$  hexagonal crystal structure transitions, chemical exchanges, cation substitutions, selective Th removal, dissolution followed by precipitation, and dissolution with replacement by different minerals. They also noted that temperatures up to 300 °C likely occurred within the vicinity of the minerals.

Mikhailova et al.  $^{151}$  studied Pu-containing Eu-monazite and have documented Pu release being attributed to the formation of hydrated (rhabdophane) PuPO<sub>4</sub> by storage in air. This calls into question the long-term disposal potential for actinides stored in REPO<sub>4</sub> compounds if moisture is present in the atmosphere, which could be reduced if storage was performed in inert and dry conditions.

#### 4.3 Radiation stability

The majority of naturally occurring monazites have been affected by radiation due to  $\alpha$  decay of actinides within these minerals. This radiation has the potential to cause metamict alterations in the crystal structures of minerals, consequently elevating their solubility. In contrast to many radioactive minerals, monazite retains its crystalline structure under substantial cumulative radiation doses. Monazites are known to remain within the crystalline states by an  $\alpha$ -healing mechanism through radiation-induced defects. Self-recovery of damaged structure was not observed in zircon minerals (isostructural to xenotime) with SiO<sub>4</sub>, but partial structural recovery was observed in xenotimes with PO<sub>4</sub>. Table 8 summarizes the critical amorphization dose of monazite and xenotime compounds.

Meldrum et al. 155 studied the effect of irradiation on monazite (LaPO<sub>4</sub>), xenotime (ScPO<sub>4</sub>), ZrSiO<sub>4</sub>, and ThSiO<sub>4</sub> using 800 keV Kr<sup>+</sup> ions. Recrystallization energies for the compounds were calculated to be 3.1-3.3 eV for the silicates and 1-1.5 eV for the phosphates. Radiation damage was monitored as a function of temperature, and above 700 °C, the amorphization of ZrSiO<sub>4</sub> could not be induced as the recrystallization process was faster than damage accumulation. The critical temperature was calculated to be only 35 °C for LaPO<sub>4</sub>, and the monazite would not undergo phase decomposition at the tested conditions. In another study by the same group, 159 monazite could not be amorphized when exposed to 800 keV Kr<sup>+</sup> ions at temperatures surpassing 175 °C. On the contrary, zircon underwent amorphization at temperatures reaching up to 740 °C. It was found that materials with the zircon structure (i.e., ZrSiO<sub>4</sub> and ScPO<sub>4</sub>) could be amorphized at slightly elevated temperatures

**RSC Advances** Review

Table 8 Critical amorphization dose for monazite and xenotime

Materials	Critical amorphization dose	Ref.
LaPO <sub>4</sub>	0.15 dpa (0 K)	159
Natural monazite	$7 \times 10^{16}  \alpha  \mathrm{mg}^{-1}$	160
Natural monazite	0.13 dpa (0 K)	159
Synthetic monazite (La,Pu)PO <sub>4</sub>	$\sim (0.2 - 0.3) \times 10^{16} \text{ a mg}^{-1}$	161
Natural xenotime with Th and U	$(1.4-14) \times 10^{16} \text{ a mg}^{-1}$	160
CePO <sub>4</sub>	~0.35–0.47 dpa (~298 K)	162
ErPO <sub>4</sub> xenotime	$(0.3-7.3) \times 10^{16} \alpha \mathrm{mg}^{-1}$	163
Nanocrystal phosphate Rb <sub>3</sub> Nd(PO <sub>4</sub> ) <sub>2</sub>	~0.52 dpa	164

compared to compounds with the monazite structure under equivalent irradiation conditions.

Seydoux-Guillaume et al. 165 studied the healing of radiation damage in natural monazite with annealing at 500-1200 °C. The natural monazite contained two domains with distorted lattice areas with  $\alpha$ -dose of 2.5  $\times$  10<sup>16</sup>  $\alpha$  mg<sup>-1</sup> accumulated since 474 Ma ago. From 500-900 °C, partial healing of the lattice occurred. At 900 °C after 10 days, only one domain remained, and a well-crystallized lattice was observed. The same group performed structural analysis using X-ray diffraction (XRD), TEM, SEM, and electron probe microanalysis and showed that monazites are not metamict despite the old ages of samples ranging from 24 to 1928 Ma.166

Bregiroux et al. 167 synthesized monazite powders containing plutonium(III), plutonium(IV) and americium(III). They examined the response of the monazite structure to  $\alpha$  self-irradiation using XRD. The results revealed a total amorphization of the crystalline structure after 300 days, reaching a cumulative dose of  $1.65 \times 10^{25} \alpha \text{ m}^{-3}$ .

Picot et al. 168 explored the impact of Au2+ and He+ ion irradiation on monazite to simulate α-decay effects. The Au<sup>2+</sup> ionirradiation induced significant alterations in the material properties. At a damage level of 6.7 dpa, monazite displayed an approximately 8.1% increase in volume, a 59% decrease in hardness, and complete structural amorphization. Conversely, no changes in the properties of these compounds were noted following He<sup>+</sup> ion implantation.

Deschanels et al. 169 investigated α-induced swelling in monazite and zirconolite ceramics. It was found that the macroscopic swelling and amorphization of monazite relied on the type of irradiation. Monazite samples irradiated externally with Au became amorphous and exhibited a maximum swelling of 8%. In contrast, the swelling in samples doped with  $^{238}$ Pu was significantly smaller, at approximately 1%.

Radiuddin and Grosvenor<sup>157</sup> studied the structural stabilities of La<sub>1-x</sub>Yb<sub>x</sub>PO<sub>4</sub> materials implanted with Au ions. The longand short-range order of  $La_{1-x}Yb_xPO_4$  (x = 0, 0.3, 0.7, 1.0) are influenced by ion-implantation, indicating the materials are prone to structural damage. Interestingly, in certain members of the  $La_{1-x}Yb_xPO_4$  series (x = 0.7 and 1.0), partial recovery of the structure was observed following high-dose Au ion implantation.

Sadhasivam and Rajesh<sup>38</sup> studied the effect of γ-irradiation on the NdPO<sub>4</sub> monazite compound using <sup>60</sup>Co γ-cell source at a dose rate of 4.5 kGy h<sup>-1</sup>. Defect center, ionization, and charge trapping did not occur during irradiation, and no significant structural change was observed up to 150 kGy  $\gamma$  dose. The high level of  $\gamma$  dose did not affect the crystallinity and optical

Rafiuddin et al. 163 evaluated irradiation effects on the ErPO<sub>4</sub> xenotime compound structure using high-energy dual ion-beam irradiation of 1.5 MeV Au2+ and 160 keV He+. The xenotime structure was found to undergo amorphization at a lower Au2+ ion-fluence than the monazite structure. Moreover, subsequential He<sup>+</sup> ion-irradiation on the amorphized ErPO<sub>4</sub> samples did not lead to the structural restoration of xenotime. Simultaneous ion-irradiation of Au<sup>2+</sup> and He<sup>+</sup> prevented the amorphization of ErPO<sub>4</sub> as higher amounts of electronic energy was applied, similar to the α-healing mechanism in the monazite structures where high energies cause recrystallization faster than damage accumulation. However, the α-healing mechanism for xenotime required ~4 times more energy compared to monazite.

Overstreet et al. 170 investigated the structural stability of SmPO<sub>4</sub> and TbPO<sub>4</sub> under swift heavy ion irradiation using 1.1 GeV <sup>197</sup>Au ions. Both SmPO<sub>4</sub> monazite and TbPO<sub>4</sub> xenotime structures experienced amorphization at comparable rates with increasing fluence, and complete amorphization occurred  $\sim$ 5  $\times$ 10<sup>12</sup> ions cm<sup>-2</sup> for both compounds. No irradiation-induced recrystallization was observed at higher fluences for both compounds. Findings from this study differed from other radiation damage using relatively low-energy ions, where the monazite compounds were more resistant to amorphization compared to xenotime compounds. The results from this study suggested that the crystal chemistries and structures of monazite and xenotime will not greatly affect the radiation tolerance to highly energetic ions.

Tisdale et al.164 synthesized single crystals of Rb3RE(PO4)2 (RE = Y, La, Pr, Nd, and Sm $\rightarrow$ Lu) by high-temperature flux growth methods. The 1.2 MeV Xe3+ ions were used on the Rb<sub>3</sub>Nd(PO<sub>4</sub>)<sub>2</sub> sample to investigate the radiation effect, and complete amorphization was observed by 0.22 dpa for a single crystal sample and  $\sim$ 0.52 dpa for a polycrystalline sample. DFT calculations were performed for trivalent actinide analogs of  $Rb_3M(PO_4)_2$  (M = Am, Cm), and the results indicated high tolerance to radiation damage.

Burakov et al.161 studied radiation resistance effects, including amorphization, of different crystalline host phases on Review **RSC Advances** 

Pu storage to simulate the effects of long-term disposal. The study included Pu-doped cubic zirconia (Zr<sub>0.79</sub>Gd<sub>0.14</sub>Pu<sub>0.07</sub>-O<sub>1.99</sub>), monazites [(La,Pu)PO<sub>4</sub>, PuPO<sub>4</sub>, and (Eu,Pu)PO<sub>4</sub>], zircon [(Zr,Pu)SiO<sub>4</sub>], and pyrochlore [(Ca,Gd,Hf,Pu,U)<sub>2</sub>Ti<sub>2</sub>O<sub>7</sub>]. The (La,Pu)PO<sub>4</sub> and PuPO<sub>4</sub> monazites remained crystalline until receiving cumulative doses of 1.19  $\times$  10<sup>25</sup>  $\alpha$  m<sup>-3</sup> and 4.2  $\times$  10<sup>24</sup>  $\alpha \text{ m}^{-3}$ .

#### Optical properties and applications

Several studies have documented the study of optical properties of REPO<sub>4</sub> compounds, including optical spectroscopy<sup>171,172</sup> and Raman spectroscopy. 173-175 Hernández and Martín 172 studied the ultraviolet-visible-near-infrared (UV-Vis-NIR, i.e., 200-3000 nm) absorption spectra of EuPO<sub>4</sub>. Absorption spectra show low to medium absorption within the  $\lambda = 400$ –1700 nm region of the spectrum (Vis-NIR) but high absorptions in the UV ( $\lambda$  < 400 nm) and NIR ( $\lambda > 1700$  nm). They noted that the absorption spectra remained unchanged, even after 18 kGy irradiation with <sup>60</sup>Co. Studies have shown the utility of doped REPO<sub>4</sub> compounds to function as scintillators when exposed to X-rays or γ-rays.<sup>1</sup> Examples of these types of materials include LuPO<sub>4</sub>:Ce,<sup>176</sup> LuPO<sub>4</sub>:Nd, 177 YPO<sub>4</sub>:Nd, 177 as well as Sm-doped or Eu-doped YPO<sub>4</sub>, ScPO<sub>4</sub>, and LuPO<sub>4</sub>.<sup>178</sup> REPO<sub>4</sub> compounds can also be used as thermophosphors to provide a remote-sensing probe for temperature determination, which was demonstrated using LuPO<sub>4</sub>: (Dy,Eu).<sup>24,25</sup> An example of where this would have utility is where it is not practical to use metal thermocouples, e.g., remote sensors within a microwave environment.

## Future work and perspectives

After considering the wealth of data collected on the wide range of anhydrous REPO4 compounds discussed within this paper, more work is needed to fill in research gaps summarized within this section. Additional thoughts and perspectives are provided throughout where future work could be done.

Regarding mechanical properties, extensive datasets are available for E, B, and G while several experimental gaps exist in datasets for H and FS (see Table 5). Many of the datasets from single studies do not correlate well with data from other studies or measured data fall far from calculated data (see Fig. 7), leading to difficulty in making accurate predictions in some cases. Gaps exist in the thermal properties for the different series (Table 6) and the data spread across literature values for single properties of a given REPO<sub>4</sub> compound tends to be rather high in some cases. For one dataset of calculated CTE values, the spread was very low (see Fig. 8), but that was anomalous against the entire set of summarized data. Two of the most populated datasets include  $C_p$  and CTE. More work needs to be done to better elucidate the variabilities in these properties across the full RE dataset.

Since APO<sub>4</sub> compounds are promising as stable options for long-term disposal of radionuclides, including rare earths and actinides, more detailed studies on their chemical durabilities are needed. The normalized release rates (NR<sub>i</sub>) for tested REPO<sub>4</sub> compounds show very low values (Table 7) as compared to other

nuclear waste forms, such as borosilicate glass. Understanding potential incongruent elemental release from these compounds is important, including comparisons between NR<sub>P</sub> and NR<sub>RE</sub> over long time scales under dilute conditions.

While some radiation stability tests have been documented in the literature for REPO<sub>4</sub> compounds (see Table 8 for examples), additional studies are needed. This includes wider compositional ranges as well as more high-energy exposure studies (e.g., γ-rays). Several studies have demonstrated amorphization doses for a variety of REPO4 compounds and types of irradiations. A study by Nasdala et al. 179 provided evidence that α-assisted annealing can prevent irradiationinduced amorphization in CePO<sub>4</sub> monazite, but only above a specific damage level. Understanding how REPO<sub>4</sub> compounds behave in potential geological repository environments and the transition of REPO<sub>4</sub> compounds to the hydrated (i.e., rhabdophane or REPO<sub>4</sub>·xH<sub>2</sub>O) forms is very important from a waste form perspective for long-term disposal.

An overview of DFT-based first principles calculations on mechanical, structural, and thermodynamic properties was briefly covered due to the effectiveness of the method to predict the structures and properties of this class of materials. It was found that the usage of the DFT + U method 180,181 to treat f electrons in RE elements was essential to improve the description of both structures and properties. More work can be done to study defect formation energies and mixing of RE elements in REPO<sub>4</sub> compounds using first principles methods. First principles calculations can also be used to study high-entropy monazite-based or xenotime-based ceramics formation and properties through mixing of various RE elements. In addition, classical molecular dynamics (MD) simulations can be used to study radiation effects and thermomechanical behaviors. 182 Recent advances using machine learning potentials<sup>183</sup> based on first principles calculations can help to alleviate the bottleneck of interatomic potential availability. However, extensive testing and validation of these new potentials will be needed. Combining these techniques, one can expect computational methods to provide valuable information regarding the distribution of RE elements within the crystal lattice, the role of dopants in controlling properties, radiation induced structural change and amorphization, and the mechanisms governing phase transformations under extreme conditions.

With the rapid development of applying machine learning techniques in material science,184 the integration of predictive models and machine learning holds transformative potential across various applications of REPO<sub>4</sub> compounds. 185-187 These models can be utilized to predict properties such as phase stability, mechanical behavior, and chemical reactivity under various/extreme conditions. Future efforts, including constructing a more consistent dataset including trace elements, developing high-throughput parallel simulation routines, and standardizing characterization methods, would greatly benefit the implementation of machine learning in studying monazite and xenotime composition-structure-property relationships. By training models on experimental and/or simulation data, researchers can extrapolate insights beyond the limits of

**RSC Advances** Review

traditional analysis, guiding experimental design and hypothesis generation.

#### 6 Summary and conclusions

The synthesis methods, crystal structures, and properties of anhydrous monazite and xenotime crystalline materials are summarized within this review. Monazite and xenotime compounds can be synthesized with a variety of different methods including flux-assisted, solid state, hydrothermal, aqueous, dehydration, and gel-based methods. For both monazite and xenotime structures, with larger and lighter RE cations in the crystal structure, the unit cell parameters (i.e., a, (v) and volumes (v) increase linearly whereas the densities  $(\rho)$ decrease nonlinearly. Similar trends were observed for solid solution compounds containing mixed RE cations. Some solid solutions containing RE cations with large difference in sizes (e.g., La and Yb) showed the presence of both monazite and xenotime phases. For RE cations, the distortions of REO<sub>x</sub> polyhedra were greater in monazites when compared to xenotimes. Decreasing RE radii increased the Young's modulus, bulk modulus, and shear modulus, and this can be due to stronger interatomic bonding as the average RE-O distances decreased with smaller RE cations. Different modulus values from different studies are also affected by different sample preparation and sintering conditions for the pellets. In general, the CTE values of monazite compounds seem to increase with the larger RE cations and RE-O distances in the structures. The calculated CTE values usually followed the trends, but the experimental CTE values from different studies often varied greatly, and it was difficult to create a general trendline. First-principles DFT calculations have been shown to be a reliable predictive method for both the structures and properties of monazite and xenotime crystals, although care was needed in the description of the f-electrons and the DFT + *U* method was found to be reliable and computationally feasible approach for this purpose. The chemical and radiation resistance of monazite and xenotime are similar to that of zircon, and thus the natural minerals are often used in geochronology. Monazite compounds are generally more resistant to irradiation damage compared to the xenotime compounds.

### Conflicts of interest

There are no conflicts to declare.

## Acknowledgements

The information, data, or work presented herein was funded in part by the Advanced Research Projects Agency-Energy (ARPA-E), U.S. Department of Energy, under Award Number DE-AR0001613. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof. Pacific Northwest National Laboratory (PNNL) is operated by Battelle Memorial Institute for the DOE under contract DE-AC05-76RL01830. Authors thank John Vienna (PNNL) for helpful comments.

## References

- 1 L. A. Boatner, Rev. Mineral. Geochem., 2002, 48, 87-121.
- 2 R. P. Rapp and E. B. Watson, Contrib. Mineral. Petrol., 1986, 94. 304-316.
- 3 A. Kumari, R. Panda, M. K. Jha, J. R. Kumar and J. Y. Lee, Miner. Eng., 2015, 79, 102-115.
- 4 L. Richter, L. W. Diamond, P. Atanasova, D. A. Banks and J. Gutzmer, Geology, 2018, 46, 263-266.
- 5 M. Rabiei, G. Chi, C. Normand, W. J. Davis, M. Fayek and N. J. Blamey, Econ. Geol., 2017, 112, 1483-1507.
- 6 H.-J. Förster, Am. Mineral., 1998, 83, 259-272.
- 7 C. J. Hetherington, D. E. Harlov and B. Budzyń, Mineral. Petrol., 2010, 99, 165-184.
- 8 C. J. Hetherington, M. J. Jercinovic, M. L. Williams and K. Mahan, Chem. Geol., 2008, 254, 133-147.
- 9 A. Berger, E. Gnos, E. Janots, A. Fernandez and J. Giese, Chem. Geol., 2008, 254, 238-248.
- 10 R. G. Jonasson and E. R. Vance, Thermochim. Acta, 1986, **108**, 65-72.
- 11 B. Glorieux, M. Matecki, F. Fayon, J. P. Coutures, S. Palau, A. Douy and G. Peraudeau, J. Nucl. Mater., 2004, 326, 156-162.
- 12 R. C. Ewing and W. Lutze, Ceram. Int., 1991, 17, 287-293.
- 13 E. H. Oelkers and J.-M. Montel, Elements, 2008, 4, 113-116.
- 14 N. Clavier, R. Podor and N. Dacheux, J. Eur. Ceram. Soc., 2011, 31, 941-976.
- 15 L. A. Boatner, G. W. Beall, M. M. Abraham, C. B. Finch, P. G. Huray and M. Rappaz, in Scientific Basis for Nuclear Waste Management, ed. C. J. M. Northrup, Springer US, Boston, MA, 1980, DOI: 10.1007/978-1-4684-3839-0\_35, pp. 289-296.
- 16 A. I. Orlova, J. Nucl. Mater., 2022, 559, 153407.
- 17 M. R. Rafiuddin, G. Donato, S. McCaugherty, A. Mesbah and A. P. Grosvenor, ACS Omega, 2022, 7, 39482-39490.
- 18 S. Chong, B. J. Riley and Z. J. Nelson, J. Rare Earths, 2021, 40, 365-380.
- 19 B. J. Riley, Ind. Eng. Chem. Res., 2020, 59, 9760-9774.
- 20 B. J. Riley, J. McFarlane, G. D. DelCul, J. D. Vienna, C. I. Contescu and C. W. Forsberg, Nucl. Eng. Des., 2019, 345, 94-109.
- 21 Z. Wang, J. Kim, L. Magermans, F. Corbella, I. Florea, E. Larquet, J. Kim and T. Gacoin, Nanoscale, 2021, 13, 16968-16976.
- 22 N. Hashimoto, Y. Takada, K. Sato and S. Ibuki, J. Lumin., 1991, 48-49, 893-897.
- 23 Y. I. Jeon, L. K. Bharat and J. S. Yu, J. Alloys Compd., 2015, 649, 531-536.
- 24 S. W. Allison, L. A. Boatner and G. T. Gillies, Appl. Opt., 1995, 34, 5624-5627.
- 25 S. W. Allison, M. R. Cates, L. A. Boatner and G. T. Gillies, High Temperature Thermometric Phosphors for Use in a Temperature Sensor, US Pat., 5730528A, 1998.
- 26 D.-H. Kuo and W. M. Kriven, Mater. Sci. Eng., A, 1996, 210, 123-134.

Review

27 P. E. D. Morgan, D. B. Marshall and R. M. Housley, *Mater. Sci. Eng.*, A, 1995, 195, 215–222.

- 28 E. E. Boakye, P. Mogilevsky, T. A. Parthasarathy, R. S. Hay, J. Welter and R. J. Kerans, J. Am. Ceram. Soc., 2006, 89, 3475–3480
- 29 L. Boatner and B. Sales, in *Radioactive Waste Forms for the Future*, ed. R. C. Ewing and W. Lutze, North-Holland, New York, 1988, ch. 8, pp. 495–564.
- 30 R. Feigelson, J. Am. Ceram. Soc., 1964, 47, 257-258.
- 31 D. F. Mullica, W. O. Milligan, D. A. Grossie, G. W. Beall and L. A. Boatner, *Inorg. Chim. Acta*, 1984, **95**, 231–236.
- 32 M. Cao, C. Hu, Q. Wu, C. Guo, Y. Qi and E. Wang, *Nanotechnology*, 2005, **16**, 282.
- 33 X. Li and J. Ma, J. Lumin., 2011, 131, 1355-1360.
- 34 L. Perrière, D. Bregiroux, B. Naitali, F. Audubert, E. Champion, D. S. Smith and D. Bernache-Assollant, *J. Eur. Ceram. Soc.*, 2007, 27, 3207–3213.
- 35 A. Hirsch, P. Kegler, I. Alencar, J. Ruiz-Fuertes, A. Shelyug, L. Peters, C. Schreinemachers, A. Neumann, S. Neumeier, H. P. Liermann, A. Navrotsky and G. Roth, *J. Solid State Chem.*, 2017, 245, 82–88.
- 36 R. Khalili, A.-C. Larsson, V.-V. Telkki, P. Lantto and A. M. Kantola, *J. Solid State Chem.*, 2022, 311, 123097.
- 37 N. Adelstein, B. S. Mun, H. L. Ray, P. N. Ross, J. B. Neaton and L. C. De Jonghe, *Phys. Rev. B: Condens. Matter Mater. Phys.*, 2011, **83**, 205104.
- 38 S. Sadhasivam and N. P. Rajesh, *Mater. Res. Bull.*, 2016, 74, 117–123.
- 39 Y. Wang, J. Li, J. Wang, S. Han and Y. Guo, *J. Cryst. Growth*, 2010, 312, 2779–2782.
- 40 D. F. Mullica, D. A. Grossie and L. A. Boatner, *J. Solid State Chem.*, 1985, **58**, 71–77.
- 41 J. M. Heuser, S. Neumeier, L. Peters, H. Schlenz, D. Bosbach and G. Deissmann, *J. Solid State Chem.*, 2019, 273, 45–52.
- 42 A. P. Gysi and D. Harlov, Chem. Geol., 2021, 567, 120072.
- 43 A. P. Gysi, D. Harlov, D. C. Filho and A. E. Williams-Jones, *Thermochim. Acta*, 2016, **627–629**, 61–67.
- 44 L. A. Boatner, K. B. Helean, A. Navrotsky and S. V. Ushakov, J. Mater. Res., 2001, 16, 2623–2633.
- 45 D. F. Mullica, D. A. Grossie and L. A. Boatner, *Inorg. Chim. Acta*, 1985, **109**, 105–110.
- 46 F. Poitrasson, E. Oelkers, J. Schott and J.-M. Montel, *Geochim. Cosmochim. Acta*, 2004, **68**, 2207–2221.
- 47 A. Mesbah, N. Clavier, E. Elkaim, S. Szenknect and N. Dacheux, *J. Solid State Chem.*, 2017, 249, 221–227.
- 48 E. E. Boakye, P. Mogilevsky, R. S. Hay and G. E. Fair, *J. Am. Ceram. Soc.*, 2008, **91**, 3841–3849.
- 49 R. D. Shannon, Acta Crystallogr., Sect. A, 1976, 32, 751–767.
- 50 F. Weigel, V. Scherer and H. Henschel, J. Am. Ceram. Soc., 1965, 48, 383–384.
- 51 Y. Ni, J. M. Hughes and A. N. Mariano, *Am. Mineral.*, 1995, 80, 21–26.
- 52 G. B. Callejas, M. Cabrera, S. Prieto, O. Luna, I. Choque and V. Crespo, *Rev. Boliv. Quim.*, 2000, 17, 22–27.
- 53 K. Ghouse, Indian J. Pure Appl. Phys., 1968, 6, 265-268.
- 54 R. C. L. Mooney, J. Chem. Phys., 1948, 16, 1003.
- 55 M. P. Kokkoros, Prakt. Akad. Athenon, 1942, 17, 163-174.

- 56 T. Ueda, in *Memoirs of the College of Science, University of Kyoto, Series B*, 1953, vol. 20, pp. 227–246.
- 57 T. Ueda, *J. Jpn. Assoc. Mineral.*, *Petrol. Econ. Geol.*, 1967, **58**, 170–179.
- 58 M. M. Zaman and S. M. Antao, Minerals, 2021, 11, 16.
- 59 G. W. Beall, L. A. Boatner, D. F. Mullica and W. O. Milligan, J. Inorg. Nucl. Chem., 1981, 43, 101–105.
- 60 S. Bevara, K. K. Mishra, S. J. Patwe, T. R. Ravindran, M. K. Gupta, R. Mittal, P. S. R. Krishna, A. K. Sinha, S. N. Achary and A. K. Tyagi, *Inorg. Chem.*, 2017, 56, 3335– 3348.
- 61 K. M. Kurbanov, V. A. Efremov and V. P. Orlovskij, *Kristallografiya*, 1986, **31**, 800–802.
- 62 P. Halappa, A. Mathur, M.-H. Delville and C. Shivakumara, J. Alloys Compd., 2018, 740, 1086–1098.
- 63 K. M. Heffernan, N. L. Ross, E. C. Spencer and L. A. Boatner, J. Solid State Chem., 2016, 241, 180–186.
- 64 S. Rodriguez-Liviano, A. I. Becerro, D. Alcántara, V. Grazú, J. M. de la Fuente and M. Ocaña, *Inorg. Chem.*, 2013, 52, 647–654.
- 65 J. Coing-Boyat, F. Sayetat and A. Apostolov, *J. Phys.*, 1975, 36, 1165–1174.
- 66 W. O. Milligan, D. F. Mullica, G. W. Beall and L. A. Boatner, *Inorg. Chim. Acta*, 1983, 70, 133–136.
- 67 J. López-Solano, P. Rodríguez-Hernández, A. Muñoz,
  O. Gomis, D. Santamaría-Perez, D. Errandonea,
  F. J. Manjón, R. S. Kumar, E. Stavrou and C. Raptis, *Phys. Rev. B: Condens. Matter Mater. Phys.*, 2010, 81, 144126.
- 68 W. Schäfer, Eine Apparatur für polarisierte Neutronen und Neutronenbeugungsuntersuchugen im System DyXO<sub>4</sub> (X = P, V, As), Publikationen vor 2000, Kernforschungsanlage Jülich, Verlag Jülich, 1972.
- 69 Z. Khadraoui, C. Bouzidi, K. Horchani-Naifer and M. Ferid, J. Alloys Compd., 2014, 617, 281–286.
- 70 S. Skanthakumar, C. K. Loong, L. Soderholm, J. W. Richardson, M. M. Abraham and L. A. Boatner, *Phys. Rev. B: Condens. Matter Mater. Phys.*, 1995, 51, 5644–5648.
- 71 O. Gomis, B. Lavina, P. Rodríguez-Hernández, A. Muñoz, R. Errandonea, D. Errandonea and M. Bettinelli, *J. Phys.: Condens. Matter*, 2017, **29**, 095401.
- 72 E. Patscheke, H. Fuess and G. Will, *Chem. Phys. Lett.*, 1968, 2, 47–50.
- 73 W. Milligan, D. Mullica, G. Beall and L. Boatner, *Acta Crystallogr.*, Sect. C: Cryst. Struct. Commun., 1983, 39, 23–24.
- 74 V. G. Lohmüller, G. Schmidt, B. Deppisch, V. Gramlich and C. Scheringer, *Acta Crystallogr., Sect. B: Struct. Crystallogr. Cryst. Chem.*, 1973, **29**, 141–142.
- 75 S. J. Patwe, S. N. Achary and A. K. Tyagi, *Am. Mineral.*, 2009, 94, 98–104.
- 76 W. O. Milligan, D. F. Mullica, G. W. Beall and L. A. Boatner, *Inorg. Chim. Acta*, 1982, **60**, 39–43.
- 77 M. Strada and G. Schwendimann, *Gazz. Chim. Ital.*, 1934, **64**, 662–674.
- 78 I. Krstanovic, Z. Kristallogr., 1965, 121, 315-316.
- 79 L. Vegard, *London, Edinburgh Dublin Philos. Mag. J. Sci.*, 1927, **4**, 511–525.

**RSC Advances** 

- 80 F. Angiuli, F. Mezzadri and E. Cavalli, J. Solid State Chem., 2011, 184, 1843-1849.
- 81 R. Mooney, Acta Crystallogr., 1956, 9, 677-678.
- 82 J.-E. Jørgensen, B. Lundtoft and S. E. Rasmussen, Powder Diffr., 1993, 8, 164-167.
- 83 R. Mi, J. Chen, Y.-g. Liu, M. Fang, L. Mei, Z. Huang, B. Wang and C. Zhaob, RSC Adv., 2016, 6, 28887-28894.
- 84 W. Baur, Acta Crystallogr., Sect. B: Struct. Crystallogr. Cryst. Chem., 1974, 30, 1195-1215.
- 85 C. Giacovazzo, Fundamentals of Crystallography, Oxford university press, USA, 2002.
- 86 R. Hoppe, Z. Kristallogr. Cryst. Mater., 1979, 150, 23-52.
- 87 R. Hoppe, S. Voigt, H. Glaum, J. Kissel, H. P. Müller and K. Bernet, J. Less-Common Met., 1989, 156, 105-122.
- 88 R. De Biasi, A. Fernandes and J. Oliveira, *J. Appl. Crystallogr.*, 1987, 20, 319-320.
- 89 O. Terra, N. Clavier, N. Dacheux and R. Podor, New J. Chem., 2003, 27, 957-967.
- 90 B. Van Emden, M. Thornber, J. Graham and F. Lincoln, Advances in X-Ray Analysis-The Proceedings of the Denver Xray Conferences, 1996, pp. 2-15.
- 91 A. Thust, Y. Arinicheva, E. Haussühl, J. Ruiz-Fuertes, L. Bayarjargal, S. C. Vogel, S. Neumeier and B. Winkler, J. Am. Ceram. Soc., 2015, 98, 4016-4021.
- 92 Y. Arinicheva, A. Bukaemskiy, S. Neumeier, G. Modolo and D. Bosbach, *Prog. Nucl. Energy*, 2014, 72, 144-148.
- 93 R. S. Hay, E. E. Boakye and P. Mogilevsky, J. Eur. Ceram. Soc., 2014, 34, 773-781.
- 94 A. C. Strzelecki, M. Reece, X. Zhao, W. Yu, C. Benmore, Y. Ren, C. Alcorn, A. Migdisov, H. Xu and X. Guo, ACS Earth Space Chem., 2022, 6, 1375-1389.
- 95 B. Xiao, H. Lösch, N. Huittinen and M. Schmidt, Chem.-Eur. J., 2018, 24, 13368-13377.
- 96 M. R. Rafiuddin, E. Mueller and A. P. Grosvenor, J. Phys. Chem. C, 2014, 118, 18000-18009.
- 97 R. Podor and M. Cuney, Am. Mineral., 1997, 82, 765-771.
- 98 D. B. Kitaev, Y. F. Volkov and A. I. Orlova, Radiochem, 2004, 46, 211-217.
- 99 J.-M. Montel, J.-L. Devidal and D. Avignant, Chem. Geol., 2002, 191, 89-104.
- 100 R. Podor, M. Cuney and T. C. Nguyen, Am. Mineral., 1995, 80, 1261-1268.
- 101 P. E. Raison, R. Jardin, D. Bouëxière, R. J. M. Konings, T. Geisler, C. C. Pavel, J. Rebizant and K. Popa, Phys. Chem. Miner., 2008, 35, 603-609.
- 102 A. Tabuteau, M. Pagès, J. Livet and C. Musikas, J. Mater. Sci. Lett., 1988, 7, 1315-1317.
- 103 O. Terra, N. Dacheux, N. Clavier, R. Podor and F. Audubert, J. Am. Ceram. Soc., 2008, 91, 3673-3682.
- 104 E. Gardés, O. Jaoul, J.-M. Montel, A.-M. Seydoux-Guillaume and R. Wirth, Geochim. Cosmochim. Acta, 2006, 70, 2325-2336.
- 105 L. Schwarz, B. Finke, M. Kloss, A. Rohmann, U. Sasum and D. Haberland, J. Lumin., 1997, 72-74, 257-259.
- 106 A. I. Orlova, D. B. Kitaev, N. G. Kazantsev, S. G. Samoilov, V. S. Kurazhkovskaya and E. N. Vopilina, Radiochem, 2002, 44, 326-331.

- 107 A. T. Aldred, in Geochemical Behavior of Disposed Radioactive Waste, American Chemical Society, 1984, vol. 246, ch. 18, pp. 305-314.
- 108 O. Muller and R. Roy, in The Major Ternary Structural Families, Springer, 1974, vol. 4, p. 143.
- 109 O. Fukunaga and S. Yamaoka, Phys. Chem. Miner., 1979, 5, 167-177.
- 110 J. P. Bastide, J. Solid State Chem., 1987, 71, 115-120.
- 111 R. J. Finch and J. M. Hanchar, Rev. Mineral. Geochem., 2003, 53, 1-25.
- 112 D. Errandonea and F. J. Manjón, Prog. Mater. Sci., 2008, 53, 711-773.
- 113 M. K. Carron, M. E. Mrose and K. J. Murata, Am. Mineral., 1958, 43, 985-989.
- 114 B. J. Macey, Masters thesis, Virginia Tech, 1995.
- 115 R. S. Hay, P. Mogilevsky and E. Boakye, Acta Mater., 2013, 61, 6933-6947.
- 116 U. Kolitsch and D. Holtstam, Eur. J. Mineral., 2004, 16, 117-126.
- 117 A. Du, C. Wan, Z. Qu and W. Pan, J. Am. Ceram. Soc., 2009, 92, 2687-2692.
- 118 K. Kenges, O. Proskurina, D. Danilovich, M. Aldabergenov and V. Gusarov, Russ. J. Appl. Chem., 2018, 91, 1538-1548.
- 119 J. Feng, B. Xiao, R. Zhou and W. Pan, Acta Mater., 2013, 61, 7364-7383.
- 120 P. M. Kowalski and Y. Li, J. Eur. Ceram. Soc., 2016, 36, 2093-2096.
- 121 H. Li, S. Zhang, S. Zhou and X. Cao, Inorg. Chem., 2009, 48, 4542-4548.
- 122 P. E. Morgan and D. B. Marshall, J. Am. Ceram. Soc., 1995, **78**, 1553–1563.
- 123 Y. Hikichi, T. Ota and T. Hattori, Mineral. J., 1997, 19, 123-130.
- 124 T. M. Wilkinson, D. Wu, M. A. Musselman, N. Li, N. Mara and C. E. Packard, Mater. Sci. Eng., A, 2017, 691, 203-210.
- 125 J. Han, Y. Wang, R. Liu and F. Wan, Sci. Rep., 2020, 10, 13681.
- 126 Y. Hikichi, T. Ota, K. Daimon, T. Hattori and M. Mizuno, J. Am. Ceram. Soc., 1998, 81, 2216-2218.
- 127 F. Zhang, J. Wang, M. Lang, J. Zhang, R. C. Ewing and L. A. Boatner, Phys. Rev. B: Condens. Matter Mater. Phys., 2009, 80, 184114.
- 128 K. Popa and R. J. M. Konings, Thermochim. Acta, 2006, 445, 49-52.
- 129 Y. Hikichi and T. Nomura, J. Am. Ceram. Soc., 1987, 70, C-252-C-253.
- 130 Y. Ji, G. Beridze, D. Bosbach and P. M. Kowalski, J. Nucl. Mater., 2017, 494, 172-181.
- 131 T. Deepthi and K. Balamurugan, Ceram. Int., 2019, 45, 18229-18235.
- 132 A. Blanca Romero, P. M. Kowalski, G. Beridze, H. Schlenz and D. Bosbach, J. Comput. Chem., 2014, 35, 1339-1346.
- 133 G. Beridze, A. Birnie, S. Koniski, Y. Ji and P. M. Kowalski, Prog. Nucl. Energy, 2016, 92, 142-146.
- 134 R. G. Jonasson, G. M. Bancroft and H. W. Nesbitt, Geochim. Cosmochim. Acta, 1985, 49, 2133-2139.
- 135 N. Clavier, DSc thesis, Université Paris Sud-Paris XI, 2004.

Review

136 E. Du Fou de Kerdaniel, N. Clavier, N. Dacheux, O. Terra and R. Podor, I. Nucl. Mater., 2007, 362, 451-458.

- 137 E. H. Oelkers and F. Poitrasson, Chem. Geol., 2002, 191, 73-87.
- 138 G. J. McCarthy, W. B. White and D. E. Pfoertsch, Mater. Res. Bull., 1978, 13, 1239-1245.
- 139 B. C. Sales, C. W. White and L. A. Boatner, Nucl. Chem. Waste Manage., 1983, 4, 281-289.
- 140 Y. Teng, P. Zeng, Y. Huang, L. Wu and X. Wang, J. Nucl. Mater., 2015, 465, 482-487.
- 141 C. Gausse, S. Szenknect, A. Mesbah, N. Clavier, S. Neumeier and N. Dacheux, Appl. Geochem., 2018, 93, 81-93.
- 142 E. Du Fou de Kerdaniel, DSc thesis, Université Paris Sud-Paris XI, 2007.
- 143 O. Terra, N. Dacheux, F. Audubert and R. Podor, J. Nucl. Mater., 2006, 352, 224-232.
- 144 N. Clavier, N. Dacheux, G. Wallez and M. Ouarton, J. Nucl. Mater., 2006, 352, 209-216.
- 145 M. R. Rafiuddin and A. P. Grosvenor, J. Nucl. Mater., 2018, **509**, 631-643.
- 146 D. J. Wronkiewicz, S. F. Wolf and T. S. DiSanto, Mater. Res. Soc., 1995, 412, 345-352.
- 147 ASTM C1285-21, Standard Test Methods for Determining Chemical Durability of Nuclear, Hazardous, and Mixed Waste Glasses and Multiphase Glass Ceramics: The Product Consistency Test (PCT), 2021.
- 148 ASTM C1663-18, Standard Test Method for Measuring Waste Glass or Glass Ceramic Durability by Vapor Hydration Test (VHT), 2018.
- 149 EPA, SW-846 Test Method 1311: Toxicity Characteristic Leaching Procedure, 1992.
- 150 F. Poitrasson, S. Chenery and T. J. Shepherd, Geochim. Cosmochim. Acta, 2000, 64, 3283-3297.
- 151 P. Mikhailova, B. Burakov, N. Eremin, A. Averin and A. Shiryaev, Sustainab, 2021, 13, 1203.
- 152 B. I. Omel'yanenko, T. S. Livshits, S. V. Yudintsev and B. S. Nikonov, Geol. Ore Deposits, 2007, 49, 173-193.
- 153 L. Nasdala, S. Akhmadaliev, A. Artac, C. Chanmuang N, G. Habler and C. Lenz, Phys. Chem. Miner., 2018, 45, 855-
- 154 A.-M. Seydoux-Guillaume, X. Deschanels, C. Baumier, S. Neumeier, W. J. Weber and S. Peuget, Am. Mineral., 2018, 103, 824-827.
- 155 A. Meldrum, R. C. Ewing and L. A. Boatner, Mineral. Mag., 2000, 64, 185-194.
- 156 L. Nasdala, M. Wenzel, G. Vavra, G. Irmer, T. Wenzel and B. Kober, Contrib. Mineral. Petrol., 2001, 141, 125-144.
- 157 M. R. Rafiuddin and A. P. Grosvenor, J. Alloys Compd., 2015, 653, 279-289.
- 158 V. S. Urusov, A. E. Grechanovsky and N. N. Eremin, Glass Phys. Chem., 2012, 38, 55-62.
- 159 A. Meldrum, L. A. Boatner, W. J. Weber and R. C. Ewing, Geochim. Cosmochim. Acta, 1998, 62, 2509-2520.
- 160 G. R. Lumpkin and T. Geisler-Wierwille, in Comprehensive Nuclear Materials, ed. R. J. M. Konings, Elsevier, Oxford, 2012, pp. 563-600, DOI: DOI: 10.1016/B978-0-08-056033-5.00111-7.

- 161 B. E. Burakov, V. M. Garbuzov, A. A. Kitsay, M. A. Yagovkina and V. A. Zirlin, Mater. Res. Soc. Symp. Proc., 2004, 824, CC4.
- 162 F. Lu, Y. Shen, X. Sun, Z. Dong, R. C. Ewing and J. Lian, Acta Mater., 2013, 61, 2984-2992.
- 163 M. R. Rafiuddin, A.-M. Seydoux-Guillaume, X. Deschanels, A. Mesbah, C. Baumier, S. Szenknect and N. Dacheux, J. Nucl. Mater., 2020, 539, 152265.
- 164 H. B. Tisdale, M. S. Christian, G. Morrison, T. M. Besmann, K. Sun, G. S. Was and H.-C. zur Loye, Chem. Mater., 2022, 34, 3819-3830.
- 165 A. M. Seydoux-Guillaume, R. Wirth, L. Nasdala, M. Gottschalk, J. M. Montel and W. Heinrich, Phys. Chem. Miner., 2002, 29, 240-253.
- 166 A.-M. Seydoux-Guillaume, R. Wirth, A. Deutsch and U. Schärer, Geochim. Cosmochim. Acta, 2004, 68, 2517-2527.
- 167 D. Bregiroux, R. Belin, P. Valenza, F. Audubert and D. Bernache-Assollant, J. Nucl. Mater., 2007, 366, 52-57.
- 168 V. Picot, X. Deschanels, S. Peuget, B. Glorieux, A. M. Seydoux-Guillaume and R. Wirth, J. Nucl. Mater., 2008, 381, 290-296.
- 169 X. Deschanels, A. M. Seydoux-Guillaume, V. Magnin, A. Mesbah, M. Tribet, M. P. Moloney, Y. Serruys and S. Peuget, J. Nucl. Mater., 2014, 448, 184-194.
- 170 C. Overstreet, J. Cooper, E. O'Quinn, W. Cureton, R. Palomares, J. Leys, G. Deissmann, S. Neumeier, C.-H. Chen and M. Lang, Nucl. Instrum. Methods Phys. Res., Sect. B, 2022, 527, 34-39.
- 171 A. N. Trukhin and L. A. Boatner, 13<sup>th</sup> Int. Conf. Defects Insul. Cryst. Mater. Sci. Forum, vol. 239-241, 1997.
- 172 T. Hernández and P. Martín, J. Eur. Ceram. Soc., 2007, 27, 109-114.
- 173 G. M. Begun, G. W. Beall, L. A. Boatner and W. J. Gregor, J. Raman Spectrosc., 1981, 11, 273-278.
- 174 P. C. Becker, N. Edelstein, G. M. Williams, J. J. Bucher, R. E. Russo, J. A. Koningstein, L. A. Boatner and M. M. Abraham, Phys. Rev. B: Condens. Matter Mater. Phys., 1985, 31, 8102-8110.
- 175 P. C. Becker, G. M. Williams, N. M. Edelstein, J. A. Koningstein, L. A. Boatner and M. M. Abraham, Phys. Rev. B: Condens. Matter Mater. Phys., 1992, 45, 5027-5030.
- 176 A. Lempicki, E. Berman, A. J. Wojtowicz, M. Balcerzyk and L. A. Boatner, IEEE Trans. Nucl. Sci., 1993, 40, 384-387.
- Wisniewski, S. Tavernier, A. J. Wojtowicz, M. Wisniewska, P. Bruyndonckx, P. Dorenbos, E. van Loef, C. W. E. van Eijk and L. A. Boatner, Nucl. Instrum. Methods Phys. Res., Sect. A, 2002, 486, 239-243.
- 178 W. W. Moses, M. J. Weber, S. E. Derenzo, D. Perry, P. Berdahl and L. A. Boatner, IEEE Trans. Nucl. Sci., 1988, 45, 462-466.
- 179 L. Nasdala, S. Akhmadaliev, B. E. Burakov, C. Chanmuang N and R. Skoda, Sci. Rep., 2020, 10, 14676.
- 180 W. Sun and J. Du, Comput. Mater. Sci., 2017, 126, 326-335.
- 181 J. Du, R. Devanathan, L. René Corrales and W. J. Weber, Comput. Theor. Chem., 2012, 987, 62-70.
- 182 J. Du, M. Motorsi, S. Barbi and X. Lu, in Atomistic Simulations of Glasses Fundamentals and Applications, John

**RSC Advances** 

- Wiley & Sons Inc., 2022, pp. 367-438, DOI: 10.1002/9781118939079.ch12.
- 183 A. M. Miksch, T. Morawietz, J. Kästner, A. Urban and N. Artrith, *Mach. Learn.: Sci. Technol.*, 2021, **2**, 031001.
- 184 R. Ramprasad, R. Batra, G. Pilania, A. Mannodi-Kanakkithodi and C. Kim, *npj Comput. Mater.*, 2017, 3, 54.
- 185 E. Di Napoli, X. Wu, T. Bornhake and P. M. Kowalski, *Front. Appl. Math. Stat.*, 2024, **10**, 1355726.
- 186 G. H. Alférez, O. A. Esteban, B. L. Clausen and A. M. M. Ardila, *Earth Sci. Inform.*, 2022, **15**, 1683–1698.
- 187 K. Itano, K. Ueki, T. Iizuka and T. Kuwatani, *Geosci.*, 2020, **10**, 63.