


 CrossMark  
 click for updates

 Cite this: *RSC Adv.*, 2015, 5, 70500

## Correction: Enhanced actuated strain of titanium dioxide/nitrile-butadiene rubber composite by the biomimetic method

 Dan Yang,<sup>ab</sup> Shuo Huang,<sup>bc</sup> Yibo Wu,<sup>ab</sup> Mengnan Ruan,<sup>bc</sup> Shuxin Li,<sup>ab</sup> Yuwei Shang,<sup>ab</sup> Xiuguo Cui,<sup>a</sup> Yang Wang<sup>a</sup> and Wenli Guo<sup>\*ab</sup>

DOI: 10.1039/c5ra90077h

[www.rsc.org/advances](http://www.rsc.org/advances)

 Correction for 'Enhanced actuated strain of titanium dioxide/nitrile-butadiene rubber composite by the biomimetic method' by Dan Yang *et al.*, *RSC Adv.*, 2015, 5, 65385–65394.

The authors regret that the value of 0.69% provided in the original manuscript as the actuated strain value of pure NBR at 20 kV mm<sup>-1</sup> is incorrect. This value is quoted in the **Abstract**, the subsection of the **Results and discussion** entitled *Actuated strain of dielectric composites*, and the **Conclusion**, and it should instead be 2.15%.

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

<sup>a</sup>Department of Material Science and Engineering, Beijing Institute of Petrochemical Technology, Beijing, 102617, China. E-mail: gwenli@bipt.edu.cn

<sup>b</sup>Beijing Key Lab of Special Elastomeric Composite Materials, Beijing, 102617, China

<sup>c</sup>Materials Science and Engineering, Beijing University of Chemical Technology, Beijing 100029, China

