Cite this: *J. Mater. Chem. C*, 2015, **3**, 9749

DOI: 10.1039/c5tc90164b

www.rsc.org/MaterialsC

Correction: Individual single-crystal nanowires as electrodes for organic single-crystal nanodevices

Guorui Wang,^a Qingxin Tang,^{*a} Yanhong Tong,^{*a} Wenping Hu^{*b} and Yichun Liu^{*a}

Correction for 'Individual single-crystal nanowires as electrodes for organic single-crystal nanodevices' by Guorui Wang *et al.*, *J. Mater. Chem. C*, 2015, DOI: 10.1039/c5tc01920f.

The equation for calculating mobility in the saturated regime (I_{SD}) in the last sentence of the experimental section on the second page of this article contained some errors. The correct version is as follows:

$$I_{SD} = \frac{W}{2L} \cdot \mu C_i (V_G - V_T)^2$$

where W is the channel width, L is the channel length, C_i is the dielectric unit area capacitance, μ is field-effect mobility, V_G is gate voltage, and V_T is the threshold voltage.

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

^a Key Laboratory of UV Light Emitting Materials and Technology under Ministry of Education, Northeast Normal University, Changchun 130024, P. R. China.
E-mail: tangqx@nenu.edu.cn, tongyh@nenu.edu.cn, ycliu@nenu.edu.cn; Fax: +86-431-85099873; Tel: +86-431-85099873

^b Beijing National Laboratory for Molecular Sciences, Key Laboratory of Organic Solids, Institute of Chemistry, Chinese Academy of Sciences, Beijing 100190, P. R. China.
E-mail: huwp@iccas.ac.cn