RSC Advances

PAPER

Cite this: RSC Adv., 2017, 7, 31475

Received 16th April 2017 Accepted 5th June 2017

DOI: 10.1039/c7ra04287f

rsc.li/rsc-advances

Introduction

Water pollution, a major challenge encountering the global society today, is due to the discharge of effluents from textile dye, paint, paper, mining and electroplating industries containing harmful chemicals such as dyes and heavy metal ions.¹⁻³ These effluents are toxic and non-biodegradable to fauna and flora, and some of them are mutagenic and carcinogenic to organisms.^{4,5} Manganese dioxide $(MnO₂)$ nanoparticles, as a typical type of transition-metal oxide, have been a subject of intense interest in various fields, including ion and molecular sieves, redox catalysts, wastewater treatment, biosensors and electrode materials due to their prominent structural multiformity as well as novel physical and chemical performances.^{6,7} In terms of high capacity and selectivity, $MnO₂$ nanoparticles exhibit excellent adsorption performance, which can contribute to deep removal of pollutants from aquatic systems to meet increasingly strict standards.⁸⁻¹⁰ However, the high surface energy of nanosized $MnO₂$ granules inevitably leads to poor stability. As a result, granules tend to agglomerate because of

In situ synthesis of hierarchical structured cotton fibers/ $MnO₂$ composites: a versatile and recyclable device for wastewater treatment†

Che[n](http://orcid.org/0000-0003-2114-3636)lu Jiao,^a Jin Tao,^a Sijun Xu,^b Desuo Zhang,^a Yuyue Chen \mathbb{D}^a and Hong Lin \mathbb{D}^{*a}

To improve the feasibility of MnO₂ nanoparticles for applications in wastewater treatment, cotton fibers-MnO₂ hierarchical composites (C-MHCs) were fabricated via a new and efficient two-step strategy. The as-prepared C-MHCs were characterized by FTIR, XPS, XRD, SEM and TEM analyses, and the results show that the C-MHCs possess hierarchical structure with a monolayer coverage of MnO₂ nanoparticles on the cotton fiber surfaces. The batch adsorption experiments were executed as a function of pH value, contact time and initial concentration. Adsorption behavior followed the pseudo-second-order model $(R^2 > 0.99)$ and Langmuir isotherm, with Langmuir maximum adsorption capacity of 68.3, 174.2, 109.4 and 247.0 mg q^{-1} for Cu^{2+} , Pb²⁺, CR and MB, respectively. The regeneration experiments show that more than 85% of the initial adsorption amount was retained at the 5th sequential adsorption–desorption cycle. Considering the simple and facile fabrication process, all-round adsorption feasibility and highefficiency regeneration performance, the C-MHCs are believed to be a versatile and renewable candidate for wastewater treatment. PAPER
 EXECUTE:
 CREAR SOUTHERN STRIP INSTRIMENT SOFT DETAIL ASSOCIATE CONTINUES IS OF NET ACTION STRIP INSTRIMENT SOFT AND A COMPOSITES: a versatile and recyclation of the set of the set of the set of the set of the s

van der Waals forces and other interactions, resulting in the reduction of reactivity.¹¹ Moreover, it is difficult to separate the nanoparticles from aqueous systems, which leads to the leaching of nanoparticles along with the treated effluents.

Recently, nano-biocomposites with enhanced properties have been deemed to be a promising alternative for industrial applications due to the integrated features of biopolymer matrices and nanomaterials. Moreover, the addition of biosupports can avoid the agglomeration of nanomaterials. The commonly used templates for nano-biocomposite preparation are biodegradable polymers such as starch, cellulose, pectin, poly(lactic acid), and chitosan.¹²

As an abundantly available, economical, renewable, and environment friendly material, natural cotton fiber is gaining interest as a support because of its nanoporous surface feature.13,14 Cotton fiber is composed of a large number of β - $(1 \rightarrow 4)$ -glycosidic bonds of D-glucose,^{15,16} and abundant hydroxyl groups facilitate the crosslinked cotton fibers to construct a flexible 3D netlike matrix with strong hydrophilic surfaces, which is suggested to be a suitable nanoreactor for the growth of $MnO₂$ nanoparticles. In addition, hierarchical nanostructured metal oxide has been widely used in gas sensors, water treatment, energy storage, etc.²⁰⁻²³ Although previous studies have reported manganese oxide (MnO_x) hybrids based on matrix materials,¹⁷⁻¹⁹ those reports were generally about MnO_x nanosheets with limited adsorption capacities, and some MnO_x were anchored onto nanosized supports and the loading content could not be tuned, leading to a poor separation performance and unclear analysis about adsorption efficiency. Hence, the hierarchical structured cotton fibers–MnO₂ nano-

YAL SOCIETY
CHEMISTRY

a National Engineering Laboratory for Modern Silk, College of Textile and Clothing Engineering, Soochow University, Suzhou 215123, P. R. China. E-mail: linhong523@ suda.edu.cn

b School of Textile and Clothing, Nantong University, Jiangsu 226019, P. R. China † Electronic supplementary information (ESI) available: Nitrogen sorption isotherms and pore size distribution curves of raw cotton and C-MHCs, effect of various MnO₂ loads on adsorption capacity, TG analysis, and pore structure characteristics of raw cotton and C-MHCs. See DOI: 10.1039/c7ra04287f

biocomposites with uniform coverage of $MnO₂$ nanospheres are valuable to be developed.

In this study, a new two-step strategy "ion exchange–redox reaction" was proposed to prepare cotton fibers– $MnO₂$ hierarchical composites (C-MHCs). The resultant C-MHCs exhibit inherent merits of cotton fibers such as macroscale, flexibility and high surface area for loading $MnO₂$ nanoparticles. The chemical composition, crystal performance and microstructure of C-MHCs were characterized by FTIR, XPS, XRD, SEM and TEM analyses, respectively. Various adsorption parameters such as pH value, initial concentration, contact time, kinetic models and adsorption isotherms were studied. BSC Advances Article composites with uniform coverage of MnO₂ nanospheres are a fusion in remembers on the composition of the common access are the common access the published on 2018. The common access Creative Common

Experimental

Materials

The cotton fibers were obtained from Yintong Cotton Co., Ltd, (Suzhou, China). Manganese π) sulfate monohydrate (MnSO₄·H₂-O), potassium permanganate (KMnO₄), copper(II) nitrate hydrate $[Cu(NO₃)₂·3H₂O]$, lead nitrate $[Pb(NO₃)₂]$, sodium hydroxide (NaOH), hydrochloric acid (HCl), and two typical dyes including cationic methylene blue (MB) and anionic Congo red (CR) were obtained from Sinopharm Chemical Reagent Co., Ltd. (Shanghai, China). All reagents were used without any treatment.

Activation of cotton fibers

First, the cotton fibers were pretreated by NaOH aqueous solution. In detail, 5 g cotton fibers were boiled in 250 mL NaOH aqueous solution $(2 wt\%)$ for 90 min, followed by filtering and transferring into 150 mL NaOH aqueous solution (18 wt%) and kept stirring for 2 h. Then, the resultant was filtered again and washed several times with abundant deionized water; alkali-activated cotton fibers were acquired after drying at 50 \degree C for 3 h.

Preparation of C-MHCs

In a typical synthesis, alkali-activated cotton fibers were added into a three-necked flask containing 45 mL 0.020 mol L^{-1} MnSO4 aqueous solution and kept stirring for 15 min. Then, the infiltrated cotton fibers were filtered and dropped into deionized water. Subsequently, 30 mL 0.020 mol L^{-1} KMnO₄ solution was added dropwise into the reaction system under continuous stirring for 6 h at room temperature. The resultant was washed several times with deionized water to remove residual reactants and dried at 50 \degree C for 4 h to obtain the product C-MHCs.

Characterization of C-MHCs

Fourier transform infrared spectroscopy (FTIR, Nicolet 5700, Thermo Nicolet, USA) was recorded to test the chemical characteristics. The valence of manganese was confirmed on an Xray photoelectron spectroscopy system (XPS, Axis Ultra HAS, Shimadzu, Japan). X-ray diffraction (XRD) studies were performed on an X-ray diffractometer (Bruker AXS, D8 Advance, Germany). The microstructures of C-MHCs were studied by field emission scanning electron microscopy (FE-SEM, S-4800, Hitachi, Japan). An energy-dispersive spectrometer (EDS, TM3030, Hitachi, Japan) was used to measure the element content and

distribution. The morphology of C-MHCs was observed by field emission transmission electron microscopy (TEM, G2 F20 S-Twin, USA). Thermal analyzer (TG, DIAMOND 5700, PerkinElmer, USA) was used to survey the $MnO₂$ content in C-MHCs from ambient condition to 800 \degree C with a heating rate of 10 \degree C min^{-1} in flowing N₂. Zeta potential was measured using a zetasizer (ZEN 3600, Malvern, UK).

Adsorption and desorption studies

Herein, 0.1 g C-MHCs was soaked into 100 mL wastewater containing metal ions or dyes. The initial pH values of the solutions were calibrated by dilute HCl or NaOH solutions. All the adsorption experiments were executed at 30 $^{\circ}$ C with stirring. The equalized adsorption capacity $Q_{\rm e}$ $(\rm mg~g^{-1})$ was calculated according to the following equation:

$$
Q_{\rm e} = \frac{(C_{\rm o} - C_{\rm e})V}{m} \tag{1}
$$

where $C_{\rm o}$ and $C_{\rm e}$ $(\rm mg\;L^{-1})$ are the adsorbate concentrations at initial and equalized time, respectively. $V(L)$ represents the volume of wastewater, and $m(g)$ denotes the mass of adsorbent used for the adsorption experiment.

The concentrations of metal ions were measured via inductively coupled plasma atomic emission spectroscopy (ICP-AES, iCAP 6000 DUO, Thermo Scientific, USA). The concentrations of CR and MB were calculated by UV-visible spectroscopy (UVvis, TU-1810, Purkinje General, China) at 497 and 664 nm, respectively.

For regeneration, the C-MHCs after adsorption were filtered out and soaked into different eluents with agitation at 30 $^{\circ}$ C for 4 h. Specifically, for C-MHCs loaded Cu^{2+} , Pb²⁺ and MB, the eluent was 0.05 mol L^{-1} HCl. Moreover, 0.05 mol L^{-1} NaOH was used for CR-loaded C-MHCs. After the elution course, the C-MHCs were washed and dried to obtain the regenerated C-MHCs. In order to investigate the reusability of C-MHCs, 5 cycles of sequential adsorption–desorption were tested.

Results and discussion

Principle and strategy for the preparation of C-MHCs

Alkali treatment of cellulose has been an important pretreatment step in the production of various cellulose derivatives since it was activated by the alkali solution for the main reactions.²⁴ As shown in Scheme 1, the alkali pretreatment of cotton fibers with NaOH solution results in the transformation of nonactive cotton cellulose to alkali-activated cotton cellulose. Then, with the addition of Mn^{2+} , the sodium salt of Cell \cdot O⁻Na⁺ was exchanged with the manganese salt of $(Cell \cdot O^{-})_{2}Mn^{2+}$ due to higher electronegativity of manganese (1.55) than sodium (0.93) .²⁵ Thereafter, redox reaction occurred as shown in eqn (2) when $\mathrm{MnO_4}^-$ was added, achieving the *in situ* formation of $MnO₂$ nanoparticles on the cotton fiber surface.

$$
3Mn^{2+} + 2MnO_4^- + 2H_2O \rightarrow 5MnO_2 + 4H^+ \tag{2}
$$

Scheme 1 (a) Schematic for the fabrication process of C-MHCs, and (b) cyclic adsorption diagram for pollutants by as-prepared C-MHCs

Chemical analyses of C-MHCs

FTIR spectroscopy of C-MHCs was performed to characterize the chemical and crystal change of cotton fibers before and after loading MnO₂. As shown in Fig. 1, a new peak at 532 cm⁻¹ appeared in C-MHCs, indicating the successful loading of the

Fig. 1 (A) FTIR spectra and (B) local magnified FTIR spectra of raw cotton, MnO₂ and C-MHCs.

Fig. 2 (a) XPS survey spectra of raw cotton and C-MHCs. (b) XPS highresolution spectrum of the Mn 2p region in C-MHCs. Fig. 3 Crystal structures of raw cotton, MnO₂ and C-MHCs.

manganese compound on the cotton matrix.²⁶ Furthermore, the region of 1500–800 cm^{-1} has been used to characterize the polymorphs of cellulose. The adsorption band at 1430 cm^{-1} shifted to 1422 cm^{-1} , demonstrating the crystalline change of cotton fibers from cellulose I to cellulose $II^{27,28}$

In order to investigate the valence of manganese, the cotton bers and C-MHCs were subjected to XPS analysis, and the result is shown in Fig. 2. The Mn 2p peak can be clearly seen in C-MHCs spectrum (Fig. 2a), confirming the deposition of manganese compound on cotton fibers. Fig. 2b shows the Mn $2p_{3/2}$ feature at 642.1 eV with a separation of 11.9 eV from Mn $2p_{1/2}$, which indicates that Mn is present in its IV state.²⁹ This result demonstrates that the resultant manganese compound is $MnO₂$.

Crystal structure of C-MHCs

To further analyze the crystalline properties, the XRD patterns of C-MHCs and related components are shown in Fig. 3. There is a strong peak at 2θ of 22.76° in natural cotton fibers, which

RSC Advances **Paper** Paper **Paper Paper Paper**

can be attributed to 002 lattice plane. The other three peaks at 2θ of 14.80°, 16.64° and 34.4° originate from 101, 101 and 040 lattice planes and are characteristic of cellulose I crystal structure.³⁰ As for $MnO₂$ nanoparticles, the intense diffraction peaks at 2 θ of 12.20°, 24.65°, 36.33° and 65.74° can be assigned to the characteristic peaks of birnessite $MnO₂$, demonstrating the poorly crystalline MnO₂ nanoparticles composed of layered structures containing K^+ and H_2O in the interlayer space.³¹ However, no significant diffraction peaks related to $MnO₂$ were observed in C-MHCs, which may be due to the strong diffraction

peaks of cotton fibers and the weak diffraction peaks of $MnO₂$. In addition, the crystal texture of cotton changes into cellulose II type as displayed in C-MHCs spectrum, which is consistent with the FTIR result and can be attributed to the alkaliactivation pretreatment of cotton fibers.³²

Microstructure of C-MHCs

The effect of precursor concentration on the $MnO₂$ loading was studied by SEM. As shown in Fig. 4, native cotton fibers act as the control group to indicate surface changes, and they show

SEM and digital images of C-MHCs prepared with different concentrations of precursors such as 0, 0.005, 0.010, 0.020 and 0.050 mol L^{-1} .

the typical natural twists and netting lines on the fiber surface. The C-MHCs exhibit an increasing load of $MnO₂$ nanoparticles along the fiber direction with increasing precursor concentration. With low concentration of 0.005 mol $\boldsymbol{\mathrm{L}}^{-1}$, nearly no $\boldsymbol{\mathrm{MnO_2}}$ nanoparticles are generated on the fiber surface. On increasing the concentration to 0.010 mol $\boldsymbol{\mathrm{L}}^{-1},$ a number of MnO $_2$ granules are deposited on the fiber surface, which are not enough to cover the entire fiber. Moreover, it is clear that these resultant MnO2 unit cells assemble along the grooves formed by adjacent netting lines of cotton, which provide abundant directional anchor points for the deposition of $MnO₂$ nanoparticles and facilitate the formation of C-MHCs with uniform coverage of MnO₂ nanoparticles.

When the precursor concentration is increased to 0.020 mol L^{-1} , these MnO₂ granules dispersing homogenously on fiber surface can be clearly observed, and magnified SEM image display the lamella-stacked plicated-typed nanospheres with a size of 200–350 nm. As shown in Fig. S1 and Table S1 (ESI†), the growth of $MnO₂$ nanoparticles onto cotton fibers increases the number of active sites and specific surface area (5.77 m² g⁻¹ for raw cotton and 21.72 m^2 g^{-1} for C-MHCs prepared by 0.020 mol L^{-1} precursor), which play an important role in the adsorption process. However, as the precursor concentration is further increased to 0.050 mol L^{-1} , considerable amount of $MnO₂$ aggregation appears with multilayer coverage as shown in the yellow circles, leading to an unfavorable adsorption. Moreover, the photograph colors change from white to dark brown, and their loading amounts calculated from the TG curves (Fig. S2†) are 0 wt%, 2.74 wt%, 5.64 wt%, 8.78 wt% and 14.25 wt%, indicating that the $MnO₂$ load can be tuned by varying the precursor concentration. This result is highly in line with the SEM result.

Furthermore, as shown in Fig. 5, the EDS mapping analyses also confirm the uniform dispersion of $MnO₂$ nanoparticles. In

Fig. 5 (a)–(d) EDS mapping results of C-MHCs prepared by 0.020 mol L^{-1} precursor, the scale bar is 10 μ m. (e) EDS spectrum of C-MHCs in selected area of (a). (f) Typical TEM image of C-MHCs.

RSC Advances **Paper** Paper **Paper Paper Paper**

terms of the structure of C-MHCs, TEM image shown in Fig. 5f demonstrates the hierarchical structured C-MHCs with monolayer coverage of MnO₂ nanoparticles. In addition, TEM further confirms that $MnO₂$ exhibits a structure with lots of small wormhole-like pores composed of lamella-stacked spherical granules, which enhances the adsorption of pollutants owing to their large surface area and substantial active sites.

Adsorption studies

Effect of various loads. As shown in Fig. S3†, the effect of $MnO₂$ loads on the adsorption capacity was performed at initial pH surrounding without adjustment, which is equal to 5.5 for Cu^{2+} , 5.4 for Pb²⁺, 9.2 for CR, and 5.8 for MB, respectively. Initially, the adsorption capacities of C-MHCs for all pollutants enhanced with increasing $MnO₂$ load, reached the maximum value with 8.78 wt% load, and then decreased slightly with further increasing $MnO₂$. The reason can be ascribed to the fact that C-MHCs can provide more active points and larger specific surface area when more MnO_2 are loaded, while too many MnO_2 granules can aggregate on cotton surface, leading to the decrease in reactivity. Therefore the C-MHCs prepared by 0.020 mol L^{-1} precursor can be considered as the optimum adsorbent.

Effect of pH values. The pH value of the solution plays a considerable role in the sorption study, which can be attributed to the variations of surface charge of the adsorbate and adsorbent with different pH values.³³ As depicted in Fig. 6b, the adjustable pH range is limited because the conjugated structures of dye molecules can be easily influenced by acidic and alkaline environments, because of which UV-vis spectrophotometer cannot precisely measure the concentration of dyes.

The CR adsorption capacity increased as the pH value increased from 4.0 to 5.0, and then decreased gradually with a further increase in the pH value to 12.0. This can be attributed to the protonation and deprotonation of functional groups of the adsorbent and adsorbate.³⁴ CR has a pK_a value of 4.5–5.5; it would be positively charged because the nitrogen atoms and sulfonate groups of the CR molecules become protonated when

the $pH < 5.0.^{35}$ Herein, the isoelectric point (pI) of C-MHCs is 4.4, as displayed in Fig. 6a. It follows that the removal is expected to increase at pH range of 4.4–5.0 and reached a maximum capacity (96.6 mg g^{-1}) at about pH = 5.0, for the C-MHCs was negatively charged and CR was either neutral or positively charged. When pH > 5.0, the surface charges of CR and C-MHCs become negative, and the adsorption is impeded, leading to a gradual decrease in the adsorption capacity.

The adsorption capacity for MB displays an "S-shape" increasing trend under the pH range of 3.0–10.0. In consideration of the pI of C-MHCs, the C-MHCs are positively charged in the pH range of 3.0–4.4 and are not conducive to adsorbing cationic MB due to electrostatic repulsion, generating a slow increase for adsorption capacity. When pH > 4.4, the adsorption rose rapidly owing to the electrostatic attraction between cationic MB molecules and negatively charged adsorbent. For metal ions, the effect of pH on the solubility and speciation of metal ions should be considered, and hence the corresponding initial pH value-3.0 was set. The adsorption capacity trends for Cu^{2+} and Pb²⁺ are close to that of MB because of the similar mechanism. The above results indicate that the adsorption ability of C-MHCs depends largely on the pH environment, and it possesses all-round adsorption feasibility for anionic and cationic pollutants. **Exchanges**
 OPEN Access Article Control Systems Article. The published on 19 September 10 Memorians Article is the common the three Commons are the formal in the common the set of the set of the set of the set of the se

Adsorption kinetics. Kinetics study is a crucial character that provides the adsorption mechanism and governs the solute uptake rate of adsorbent and therefore, determines its potential applications. As displayed in Fig. 7a, adsorption capacities for all pollutants increase dramatically in the first 2 h. Apparent equilibriums were reached gradually within 3 h for Cu^{2+} , Pb^{2+} and MB, and 4 h for CR. To further analyze the adsorption rate of C-MHCs for different adsorbates, the linear regression of pseudo-first-order (Fig. 7b) and pseudo-second-order models (Fig. 7c) was evaluated based on the experimental data:

Pseudo-first-order model

$$
\ln(Q_{1e} - Q_t) = \ln Q_{1e} - k_1 t \tag{3}
$$

Pseudo-second-order model

Fig. 6 (a) Zeta potential of C-MHCs, and (b) effect of pH values on the adsorption capacity of C-MHCs for Cu²⁺, Pb²⁺, CR and MB (adsorption condition: 500 mg L^{-1} , 4 h).

Fig. 7 (a) Adsorption behaviors of C-MHCs for Cu²⁺, Pb²⁺, CR and MB. (b) Pseudo-first-order and (c) pseudo-second-order kinetic plots of C-MHCs (adsorption condition: 500 mg L^{-1} , pH = 5.5, 5.4, 5.0 and 10.0 for Cu²⁺, Pb²⁺, CR and MB).

$$
\frac{t}{Q_t} = \frac{t}{Q_{2e}} + \frac{1}{k_2 Q_{2e}^2} \tag{4}
$$

where $Q_{1\text{e}}\,(\text{mg}\ \text{g}^{-1})$ and $Q_{2\text{e}}\,(\text{mg}\ \text{g}^{-1})$ represent the adsorption capacity calculated from the kinetic models, Q_t is the adsorption amount at given time t (min), and k_1 (min $^{-1}$) and k_2 (g (mg $\mathrm{min})^{-1}$) are the rate constants of pseudo-first-order and pseudosecond-order kinetics equations, respectively.

All kinetics parameters, correlation coefficients, and experimental adsorption capacities are listed in Table 1. It can be clearly seen that the result presented an ideal fit to the pseudosecond-order model with an extremely high R^2 (0.9905–0.9978). Moreover, a good agreement can be supported by the consistency of the calculated value Q_{2e} and experimental value Q_{exp} , indicating that pseudo-second-order kinetics can reasonably describe the adsorption process.

Adsorption isotherm. As shown in Fig. 8a, the adsorption capacity at equilibrium for each adsorbate rises dramatically with an increase in the initial concentration from 25 to 800 mg L^{-1} at first and then tends to level off, which can be ascribed to the increasing driving force coming from the concentration gradient.³⁶

Adsorption isotherm models are commonly used to describe adsorption process and investigate its mechanism. In this study, two important isotherm equations, namely Langmuir and Freundlich isotherms, were employed to investigate the adsorption process. The Langmuir isotherm (Fig. 8b) assumes

Fig. 8 (a) Effect of initial concentrations on the absorption capacity of C-MHCs for Cu^{2+} , Pb²⁺, CR and MB. (b) Langmuir and (c) Freundlich isotherm plots of C-MHCs (adsorption condition: 4 h, pH = 5.5, 5.4, 5.0 and 10.0 for Cu²⁺, Pb²⁺, CR and MB).

Table 2 Langmuir and Freundlich parameters for Cu^{2+} , Pb²⁺, CR and MB by C-MHCs

Adsorbates	Langmuir			Freundlich				
	Q_{max} (mg g^{-1})	$k_{\rm L}$ (L mg ⁻¹)	R^2	$R_{\rm L}$	$k_{\rm F}$ (L mg ⁻¹)	\boldsymbol{n}	R^2	
$Cu2+$	68.3	0.0180	0.9978	$0.0649 - 0.6897$	7.9799	2.9323	0.8423	
Pb^{2+}	174.2	0.0078	0.9919	0.1381-0.8368	6.3105	1.9562	0.9158	
CR	109.4	0.0134	0.9943	0.0853-0.7491	7.7868	2.3890	0.8577	
MВ	247.0	0.0073	0.9923	$0.1462 - 0.8457$	9.2159	1.9881	0.9395	
	that the adsorption occurs at specific homogenous sites of the adsorbent, ³⁷ and the equation is given as follows: $\frac{C_{\rm e}}{Q_{\rm e}} = \frac{C_{\rm e}}{Q_{\rm max}} + \frac{1}{k_{\rm L}Q_{\rm max}}$ where C_e (mg L ⁻¹) is the equilibrium concentration, Q_e (mg g ⁻¹) is the adsorption amount at equilibrium, Q_{max} (mg g^{-1}) repre- sents the maximum monolayer capacity of adsorbent, and k_L (L mg^{-1}) is the Langmuir constant that denotes the energy of the adsorption process. In order to determine whether the adsorption is favorable, a dimensionless constant separation factor or equilibrium parameter is defined based on eqn (6): $R_{\rm L} = \frac{1}{1 + k_{\rm L} C_{\rm g}}$		(5) (6)	where k_F and n are Freundlich constant and heterogeneity factor determined by the intercept and slope of the linear fitting, respectively (Fig. 8c). All corresponding parameters are summarized in Table 2. Comparing their linear correlation coefficients R^2 , it is concluded that the adsorption for Cu^{2+} , Pb^{2+} , CR and MB on C- MHCs was well fitted to the Langmuir isotherm equation. In addition, the suitable Langmuir constant $(k_L > 0)$ and reason- able separation factor ($0 < R_L < 1$) also demonstrate the feasi- bility of the Langmuir isotherm, illuminating the monolayer homogeneous adsorption of C-MHCs. As shown in Table 2, Q_{max} of C-MHCs is 68.3, 174.2, 109.4 and 247.0 mg g^{-1} for Cu ²⁺ , Pb ²⁺ , CR and MB, respectively.				
	where $R_{\rm L}$ indicates the type of the isotherm favorable $(0 \le R_{\rm L} \le 1)$, unfavorable $(R_L > 1)$, linear $(R_L = 1)$, or irreversible $(R_L = 0)$. In the present case in Table 2, RL is over the range 0-1 and, therefore, indicates a favorable adsorption. Freundlich isotherm equation, the most widely used adsorption isotherm for heterogeneous surface of adsorbent, is an empirical relationship as eqn (7) describes. $\ln Q_e = \ln k_F + \frac{1}{2} \ln C_e$		(7)	Compared with representative studies about MnO_x and MnO_x composite adsorbents in Table 3, ^{6,29,38-43} the C-MHCs show improved adsorption capacities. This excellent adsorption performance directly benefits from the hollow and flat fiber structure and high hydrophilicity of native cotton fibers. Moreover, the two-dimensional lamina-stacked birnessite- MnO ₂ granules with a uniform distribution provide more additive sites for adsorption, suggesting that the C-MHCs is a promising candidate for applications in wastewater treatment.				

$$
\frac{C_{\rm e}}{Q_{\rm e}} = \frac{C_{\rm e}}{Q_{\rm max}} + \frac{1}{k_{\rm L}Q_{\rm max}}\tag{5}
$$

$$
R_{\rm L} = \frac{1}{1 + k_{\rm L} C_{\rm o}} \tag{6}
$$

$$
\ln Q_{\rm e} = \ln k_{\rm F} + \frac{1}{n} \ln C_{\rm e} \tag{7}
$$

Table 3 Previous representative studies of MnO_x and MnO_y composites in the application for metal ions and dyes removal

	Adsorption capacity (mg g^{-1})						
Adsorbent	Cu^{2+}	Pb^{2+} CR.		MB	Reference		
MnO ₂ /CNTs		78.7			38		
Manganese oxide nanostructure				68.4	6		
α -MnO ₂ hierarchical hollow microspheres			96.0		39		
Hollow $MnO2$ nanostructure			60.0		40		
MWCNTs/MnO ₂		19.9			41		
Manganese oxide coated sand	2.1	1.8			42		
Cellulose-manganese oxide		80.1			29		
Manganese oxide coated zeolite	10.2	75.8			43		
C-MHCs	68.3	174.2	109.4	247.0	This work		

Regeneration of C-MHCs

Regeneration ability is a vital factor to evaluate the performance of an adsorbent, and desorption process aims to refresh the adsorption capacity of the adsorbent at the maximum extent for effective reuse. As shown in Fig. 9, the Q_{e} for all pollutants can

Fig. 9 Adsorption capacity of regenerated C-MHCs at different cycle numbers.

still keep above 85% of the initial adsorbability at the fifth cycle, indicating a benign renewable adsorbent. Furthermore, the phenomenon that the adsorbates can be desorbed by strong mineral acids or bases demonstrates that the electrostatic interaction and chemisorption contribute to a large proportion of adsorption capacity.⁴⁴ This desorption process shows a similar correlation and mutual correspondence with the pHdependent adsorbability of C-MHCs.

Conclusions

This study reported the fabrication of the C-MHCs via a new and efficient "ion exchange–redox reaction" strategy, in which cotton fibers worked as nanoreactor and macroscopic support for a straightforward separation of pollutants. A series of characterizations demonstrate that the C-MHCs are equipped with homogeneous monolayer coverage of $MnO₂$ nanoparticles formed by lamella-stacked birnessite- $MnO₂$ granules with high reactivity. Compared with the adsorbability of representative studies, the C-MHCs show improved adsorption capacity for cationic and anionic pollutants. The adsorption behavior follows pseudo-second-order kinetics and Langmuir isotherm, with the Langmuir monolayer capacity of 68.3, 174.2, 109.4 and 247.0 mg $\rm g^{-1}$ for $\rm Cu^{2+},\rm Pb^{2+},\rm CR$ and MB, respectively. In terms of advantageous straightforward separation after adsorption, the C-MHCs were regenerated and the adsorption amounts could be retained above 85% at the 5th adsorption-desorption cycle for all pollutants, demonstrating that the C-MHCs are versatile and renewable candidates for wastewater treatment. Paper

SEA devented on 19 Seconds Articles. The electrostatic studies Article. The second of the commonstration and the electrostatic 12 A. This area, 200, 113, Case and Creative Commonstration-Noncommercial and the elect

Acknowledgements

This study was supported by the Graduate Student Innovation Project of Jiangsu Province (No. KYLX16_0134), and the Natural Science Foundation of Jiangsu Province (No. BK20140347).

Notes and references

- 1 A. Salama, J. Colloid Interface Sci., 2017, 487, 348–353.
- 2 I. Michael, L. Rizzo, C. McArdell, C. Manaia, C. Merlin, T. Schwartz, C. Dagot and D. Fatta-Kassinos, Water Res., 2013, 47, 957–995.
- 3 M. S. Sajab, C. H. Chia, S. Zakaria, S. M. Jani, M. K. Ayob, K. L. Chee, P. S. Khiew and W. S. Chiu, Bioresour. Technol., 2011, 102, 7237–7243.
- 4 W. W. Ngah, L. Teong and M. Hanafiah, Carbohydr. Polym., 2011, 83, 1446–1456.
- 5 A. Z. Aroguz, J. Gulen and R. Evers, Bioresour. Technol., 2008, 99, 1503–1508.
- 6 H. Chen and J. He, J. Phys. Chem. C, 2008, 112, 17540–17545.
- 7 L. Espinal, S. L. Suib and J. F. Rusling, J. Am. Chem. Soc., 2004, 126, 7676–7682.
- 8 Y. Ren, N. Yan, Q. Wen, Z. Fan, T. Wei, M. Zhang and J. Ma, Chem. Eng. J., 2011, 175, 1–7.
- 9 L. Dong, Z. Zhu, H. Ma, Y. Qiu and J. Zhao, J. Environ. Sci., 2010, 22, 225–229.
- 10 E. Deliyanni, E. Peleka and K. Matis, J. Hazard. Mater., 2009, 172, 550–558.
- 11 T. Pradeep, Thin Solid Films, 2009, 517, 6441–6478.
- 12 B. Pan, B. Pan, W. Zhang, L. Lv, Q. Zhang and S. Zheng, Chem. Eng. J., 2009, 151, 19–29.
- 13 X. Pang, Y. He, J. Jung and Z. Lin, Science, 2016, 353, 1264– 1272.
- 14 D. Dutta, R. Hazarika, P. D. Dutta, T. Goswami, P. Sengupta and D. K. Dutta, RSC Adv., 2016, 6, 85173–85181.
- 15 A. Fukuoka and P. L. Dhepe, Angew. Chem., Int. Ed., 2006, 45, 5161–5163.
- 16 X. Zhang, H. Yu, H. Yang, Y. Wan, H. Hu, Z. Zhai and J. Qin, J. Colloid Interface Sci., 2015, 437, 277–282.
- 17 L. Zhou, J. He, J. Zhang, Z. He, Y. Hu, C. Zhang and H. He, J. Phys. Chem. C, 2011, 115, 16873–16878.
- 18 M. L. Chacón-Patiño, C. Blanco-Tirado, J. P. Hinestroza and M. Y. Combariza, Green Chem., 2013, 15, 2920.
- 19 Y. Wang, X. Zhang, X. He, W. Zhang, X. Zhang and C. Lu, Carbohydr. Polym., 2014, 110, 302–308.
- 20 J.-S. Hu, L.-S. Zhong, W.-G. Song and L.-J. Wan, Adv. Mater., 2008, 20, 2977–2982.
- 21 J. Fei, Y. Cui, J. Zhao, L. Gao, Y. Yang and J. Li, J. Mater. Chem., 2011, 21, 11742.
- 22 H. Wang, D. Ma, X. Huang, Y. Huang and X. Zhang, Sci. Rep., 2012, 2, 701.
- 23 J.-H. Lee, Sens. Actuators, B, 2009, 140, 319–336.
- 24 R. H. Setyanto, K. Diharjo, P. Setyono and I. M. Miasa, J. Mater. Sci. Res., 2013, 2, 80–88.
- 25 A. bin Jusoh, W. H. Cheng, W. M. Low, A. Nora'aini and M. J. Megat Mohd Noor, Desalination, 2005, 182, 347–353.
- 26 S. Liang, F. Teng, G. Bulgan, R. Zong and Y. Zhu, J. Phys. Chem. C, 2008, 112, 5307–5315.
- 27 C.-H. Kuo and C.-K. Lee, Carbohydr. Polym., 2009, 77, 41–46.
- 28 M. L. Nelson and R. T. O'Connor, J. Appl. Polym. Sci., 1964, 8, 1325–1341.
- 29 S. M. Maliyekkal, K. P. Lisha and T. Pradeep, J. Hazard. Mater., 2010, 181, 986–995.
- 30 Q. Lu, L. Tang, F. Lin, S. Wang, Y. Chen, X. Chen and B. Huang, Cellulose, 2014, 21, 3497–3506.
- 31 Y. Hu, J. Wang, X. Jiang, Y. Zheng and Z. Chen, Appl. Surf. Sci., 2013, 271, 193–201.
- 32 J. Xiong, C. Jiao, C. Li, D. Zhang, H. Lin and Y. Chen, Cellulose, 2014, 21, 3073–3087.
- 33 B. Zhu, P. Xia, W. Ho and J. Yu, Appl. Surf. Sci., 2015, 344, 188–195.
- 34 A. P. Vieira, S. A. Santana, C. W. Bezerra, H. A. Silva, J. A. Chaves, J. C. de Melo, E. C. da Silva Filho and C. Airoldi, J. Hazard. Mater., 2009, 166, 1272–1278.
- 35 Y. Aldegs, M. Elbarghouthi, A. Elsheikh and G. Walker, Dyes Pigm., 2008, 77, 16–23.
- 36 J. Tao, J. Xiong, C. Jiao, D. Zhang, H. Lin and Y. Chen, ACS Sustainable Chem. Eng., 2016, 4, 60–68.
- 37 I. Langmuir, J. Am. Chem. Soc., 1918, 40, 1361–1403.
- 38 S. Wang, W. Gong, X. Liu, Y. Yao, B. Gao and Q. Yue, Sep. Purif. Technol., 2007, 58, 17–23.
- 39 J. Wang, J. Liu, Y. Zhou, P. Hodgson and Y. Li, RSC Adv., 2013, 3, 25937.
- 40 J. B. Fei, Y. Cui, X. H. Yan, W. Qi, Y. Yang, K. W. Wang, Q. He and J. B. Li, Adv. Mater., 2008, 20, 452–456.
- 41 M. A. Salam, Colloids Surf., A, 2013, 419, 69–79.
- 42 R. Han, W. Zou, Z. Zhang, J. Shi and J. Yang, J. Hazard. Mater., 2006, 137, 384–395.
- 43 W. Zou, R. Han, Z. Chen, J. Shi and L. Hongmin, J. Chem. Eng. Data, 2006, 51, 534–541.
- 44 A. Roy, B. Adhikari and S. Majumder, Ind. Eng. Chem. Res., 2013, 52, 6502–6512.