Journal of Materials Chemistry A



View Article Online

CORRECTION



Cite this: J. Mater. Chem. A, 2017, 5, 852

Correction: A-site deficient perovskite: the parent for *in situ* exsolution of highly active, regenerable nano-particles as SOFC anodes

Yifei Sun,^a Jianhui Li,^{*bc} Yimin Zeng,^d Babak Shalchi Amirkhiz,^d Mengni Wang,^a Yashar Behnamian^a and Jingli Luo^{*a}

DOI: 10.1039/c6ta90256a

www.rsc.org/MaterialsA

Correction for 'A-site deficient perovskite: the parent for *in situ* exsolution of highly active, regenerable nano-particles as SOFC anodes' by Yifei Sun *et al.*, *J. Mater. Chem. A*, 2015, **3**, 11048–11056.

The authors wish to replace Fig. 4(e) of the above manuscript with the correct version shown below as the ohmic resistance in the original Fig. 4(e) is incorrect. The YSZ composition for Fig. 4(e) is 8YSZ – with 8 mol% Y_2O_3 fully stabilized ZrO_2 .

The authors also wish to clarify that, in the redox test (Fig. 4d), the metallic Ni nanoparticles were transformed to NiS in 5000 ppm H_2S-H_2 . However, this is recoverable since NiS can be reoxidized to NiO during the redox process.

"Department of Chemical and Materials Engineering, University of Alberta, Alberta, T6G 2V4, Canada. E-mail: Jingli.Luo@ualberta.ca

^cDepartment of Chemistry and Applied Chemistry, University of Changji, Changji, 831100, China ^dCanmet MATERIALS. Natural Resources Canada. Hamilton. Ontario. L8P 0A5. Canada

^bNational Engineering Laboratory for Green Chemical Productions of Alcohols-Ethers-Esters, College of Chemistry and Chemical Engineering, Xiamen University, Xiamen, 361005, China. E-mail: jhli@xmu.edu.cn



Open Access Article. Published on 15 December 2016. Downloaded on 7/28/2025 7:07:37 PM.

Fig. 4 Fuel cell performances with the various anodes in H_2 or 5000 ppm H_2S-H_2 . Current density-voltage and power density curves for fuel cells with 63LSCNi-15 and 73LSCNi-15 anodes using (a) pure H_2 fuel and (b) 5000 ppm H_2S-H_2 fuel at 800 °C. (c) EIS for the cells with 63LSCNi-15 and 73LSCNi-15 anodes fueled with 5000 ppm H_2S-H_2 at 800 °C. (d) The redox test results for the 63LSCNi-15-YSZ/YSZ/YSZ-LSM fuel cell at 800 °C during four 26 h-cycles. In each cycle, the cell was treated with 5000 ppm H_2S-H_2 for 24 h and then recovered *via* the *in situ* treatment of 5% O_2/N_2 for 2 h (hatching period). Then the fuel was introduced again and the power density was measured after the introduction of fuel for 30 min. (e) The comparison of EIS results for the cell using the 63LSCNi-15 anode before and after 4 redox cycle tests in (d).

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.