Cite this: *Phys. Chem. Chem. Phys.*, 2018, 20, 1294

DOI: 10.1039/c7cp90275a

rsc.li/pccp

Correction: *Geobacter sulfurreducens* pili support ohmic electronic conduction in aqueous solution

Nicole L. Ing,^a Tyler D. Nusca^a and Allon I. Hochbaum^{*ab}

Correction for '*Geobacter sulfurreducens* pili support ohmic electronic conduction in aqueous solution' by Nicole L. Ing et al., *Phys. Chem. Chem. Phys.*, 2017, **19**, 21791–21799.

The range of values in the Y-axes labels of Fig. 4 panels A (I_{DS}) and B ($\ln[G]$) were incorrect in the published version of this manuscript. The correct axis labels for both panels are as shown below.

Fig. 4 Electronic transport in purified *G. sulfurreducens* pili in aqueous buffered conditions. (A) Electrochemical transfer characteristics of the pili film, at different V_{DS} values according to the color scale at the right, in phosphate–citrate buffer at pH 7.0. (B) Temperature-dependent conductance (G) of the pili film at $V_{DS} = 60$ mV and $V_S = 0$ vs. Ag/AgCl in phosphate–citrate buffer pH 7.0. Dashed red and blue lines indicate linear regimes in the Arrhenius plot above and below room temperature ($1000/T = 3.39 K^{-1}$), respectively. Electrode spacing = 5 μm .

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

^a Department of Chemical Engineering and Materials Science, University of California, Irvine, Irvine, CA 92697, USA. E-mail: hochbaum@uci.edu; Tel: +1-(949) 824-1194

^b Department of Chemistry, University of California, Irvine, Irvine, CA 92697, USA