Nanoscale



CORRECTION

View Article Online



Cite this: Nanoscale, 2018, 10, 14771

Correction: Lithographically fabricated gold nanowire waveguides for plasmonic routers and logic gates

Long Gao, a,b Li Chen, a Hong Wei*a and Hongxing Xuc

DOI: 10.1039/c8nr90158a

rsc.li/nanoscale

Correction for 'Lithographically fabricated gold nanowire waveguides for plasmonic routers and logic gates' by Long Gao et al., Nanoscale, 2018, **10**, 11923–11929.

The authors have noticed an error in Fig. 6 in the published paper, in which Fig. 6b and Fig. 5c are identical due to an error that occurred in the production stage of the paper. The correct version of Fig. 6 is shown below, and the caption of the figure remains the same. This error does not affect the conclusions of the paper.




Fig. 6 Interference of SPs in a gold NW network with three inputs for the XNOR gate. (a) Output intensity for single inputs (red) and multiple inputs (black) with the phase difference changing over time. The plateaus on the sides of the oscillating curves correspond to the minimum or maximum output intensity for fixed phases. (b) (i–iii) Scattering images for single inputs. (iv–vii) Scattering images for two or three inputs. The scattering images outlined by yellow boxes show the working states corresponding to the XNOR operations. The red arrows indicate the polarization of incident light. The scale bar is 1 μm. (c) Inputs and outputs of the XNOR logic gate.

The Royal Society of Chemistry apologises for this error and any consequent inconvenience to authors and readers.

^aBeijing National Laboratory for Condensed Matter Physics, Institute of Physics, Chinese Academy of Sciences, Beijing 100190, China. E-mail: weihong@iphy.ac.cn

^bSchool of Physical Sciences, University of Chinese Academy of Sciences, Beijing 100049, China

^cSchool of Physics and Technology, and Institute for Advanced Studies, Wuhan University, Wuhan 430072, China