



## Correction: Perovskite photodetectors and their application in artificial photonic synapses

Cite this: *Chem. Commun.*, 2021, 57, 11871

Xin Huang, Yunlong Guo\* and Yunqi Liu\*

Correction for 'Perovskite photodetectors and their application in artificial photonic synapses' by Xin Huang *et al.*, *Chem. Commun.*, 2021, DOI: 10.1039/d1cc04447h.

DOI: 10.1039/d1cc90380b

[rsc.li/chemcomm](https://rsc.li/chemcomm)

The authors regret that there was an error in formulae 2 and 3 of section 2. The corrected formulae are given below:

(2) Responsivity ( $R$ ) refers to the ratio of the photocurrent generated by the PDs to the intensity of the incident light under light illumination and is defined as follows:

$$R = \frac{I_l - I_d}{P_{in}A} = \frac{I_{ph}}{P_{in}A}$$

where  $I_l$  and  $I_d$  are the currents measured under light/in darkness, respectively,  $P_{in}$  is the power density of the incident light and  $A$  is the active area of a PD.

(3) Photosensitivity refers to the ratio of the photocurrent generated by the PDs to the dark current of the PDs in the dark.

$$P = \frac{I_l - I_d}{I_d}$$

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

