Volume 11 Number 20 21 October 2021 Pages 6581–6892

**Catalysis
Science &** Technolog rsc.li/catalysis

rsc.li/catalysis

ISSN 2044-4761

MINIREVIEW Matteo Maestri *et al.* Mechanistic and multiscale aspects of thermo-catalytic $CO₂$ conversion to $C₁$ products

**Catalysis
Science & Technology** Technology (SS)

MINI REVIEW

Cite this: Catal. Sci. Technol., 2021, 11, 6601

Received 23rd May 2021, Accepted 26th August 2021

DOI: 10.1039/d1cy00922b

rsc.li/catalysis

1. Introduction

Energy and materials are key requirements of our society and economy. 84% of the primary energy consumed in 2020 was provided by fossil fuels.¹ Long geological processes $(10^6$ - 10^8 years) brought about the formation of coal and hydrocarbons from organic materials that originally stored solar energy in their chemical bonds via the photosynthesis process from water and $CO₂$. Today, while burning hydrocarbons, we make available the energy stored in their chemical bonds with the concomitant re-emission into the atmosphere of the $CO₂$ originally consumed in the photosynthesis process. For instance, approximately 22 million tons of coal, 12 million tons of oil (85 million barrels), and 10 billion $m³$ of natural gas are consumed per day to fulfill ∼82% of the total energy demand, resulting in about 30 billion tons of $CO₂$ emission

Laboratory of Catalysis and Catalytic Processes, Dipartimento di Energia, Politecnico di Milano, Via La Masa 34, 20156, Milano, Italy.

E-mail: matteo.maestri@polimi.it

† All authors contributed equally to this work.

Mechanistic and multiscale aspects of thermocatalytic $CO₂$ conversion to $C₁$ products

Md. Imteya[z](http://orcid.org/0000-0002-5677-3163) [A](http://orcid.org/0000-0002-5677-3163)lam, D[†](http://orcid.org/0000-0002-0729-9389) Raffaele Ch[eula](http://orcid.org/0000-0002-8925-3869), D† Gianluca Moroni, D† Luca Nardi \mathbf{D} † and Matteo Maestri \mathbf{D} †*

The increasing environmental concerns due to anthropogenic $CO₂$ emissions have called for an alternate sustainable source to fulfill rising chemical and energy demands and reduce environmental problems. The thermo-catalytic activation and conversion of abundantly available CO₂, a thermodynamically stable and kinetically inert molecule, can significantly pave the way to sustainably produce chemicals and fuels and mitigate the additional $CO₂$ load. This can be done through comprehensive knowledge and understanding of catalyst behavior, reaction kinetics, and reactor design. This review aims to catalog and summarize the advances in the experimental and theoretical approaches for $CO₂$ activation and conversion to $C₁$ products via heterogeneous catalytic routes. To this aim, we analyze the current literature works describing experimental analyses (e.g., catalyst characterization and kinetics measurement) as well as computational studies (e.g., microkinetic modeling and first-principles calculations). The catalytic reactions of $CO₂$ activation and conversion reviewed in detail are: (i) reverse water-gas shift (RWGS), (ii) $CO₂$ methanation, (iii) CO₂ hydrogenation to methanol, and (iv) dry reforming of methane (DRM). This review is divided into six sections. The first section provides an overview of the energy and environmental problems of our society, in which promising strategies and possible pathways to utilize anthropogenic $CO₂$ are highlighted. In the second section, the discussion follows with the description of materials and mechanisms of the available thermo-catalytic processes for $CO₂$ utilization. In the third section, the process of catalyst deactivation by coking is presented, and possible solutions to the problem are recommended based on experimental and theoretical literature works. In the fourth section, kinetic models are reviewed. In the fifth section, reaction technologies associated with the conversion of $CO₂$ are described, and, finally, in the sixth section, concluding remarks and future directions are provided. **MINIREVIEW We are the contract and multiscale aspects of thermo-

The methanistic and multiscale aspects of thermo-

Engine and the methanistic and multiscale aspects of thermo-

Material CO₂ conversion to** C_1 **produc**

Md. Imteyaz Alam obtained his master's and Ph. D. degree in Chemistry from the University of Delhi, India in 2009 and 2015, respectively. After a brief research experience at SC Johnson Products Pvt. Ltd. (Delhi), Indian Agricultural Research Institute (Delhi) and Indian Institute of technology Delhi (2014–2019), he joined Prof. Matteo Maestri's group in 2019 as a Marie Sklodowska-Curie (MSCA) Postdoctoral fellow at Politecnico

di Milano (Italy). His research interests are focused on heterogeneous catalysis and sustainable chemistry to key energy conversion technologies including biomass transformation and $CO₂$ conversion for fuels, chemicals and materials.

Gianluca Moroni has been a Ph. D. student in Chemical Engineering and Industrial Chemistry at Politecnico di Milano since 2017. He received his Master's degree in Chemical Engineering in 2015 from Politecnico di Milano with a thesis on the study of the support structure effect on the DeNOx activity of SCR Cu-based catalysts. He is mainly interested

every year.² Moreover, today the average power consumption on Earth is expected to increase to 27.6 terawatts by 2050 with an increased population of \sim 9.1 billion.³ Also, industrial sectors such as steel, iron, and cement industries emit tens to hundreds of tons of $CO₂$ annually in a localized and concentrated form for the production of materials essential to our economy. For instance, in 2018 in the European Union, $CO₂$ accounted for 81% of total green-house gas

emissions, which was 3970 million tons of $CO₂$ equivalent, 22.4% of which was from industrial processes, agriculture, and waste management sectors.⁴ As such, all these anthropogenic activities are causing an accumulation of carbon dioxide in the atmosphere.⁵ The average $CO₂$ concentration in the atmosphere has been stable for hundred-thousand years in the range of 200–300 ppm, while in the last two centuries it has started to steeply increase, Nini review Cotalysis Science & Technology

on Earth Responses Articles Artic

Raffaele Cheula is a postdoctoral fellow at Politecnico di Milano. He has been a member of Prof. Matteo Maestri's group since 2016. He obtained his PhD in Chemical Engineering and Industrial Chemistry from Politecnico di Milano in 2020. His work focuses on the development of a multiscale and multidisciplinary approach in the analysis and simulation of heterogeneous catalytic processes, focusing especially on

microkinetic modeling based on density functional theory calculations. He developed and applied a framework for the concerted simulation of surface reactions and morphological modifications of catalyst materials inside chemical reactors. His primary interests are related to the modeling of catalytic processes for the interpretation of the experimental evidence and the discovery and engineering of catalytic materials.

Gianluca Moroni in heterogeneous catalysis and structure-dependent microkinetic analysis of catalytic processes. As a Ph.D. student, he has been a member of Prof. Matteo Maestri's group since November 2017. His main work focuses on the investigation of metal-based catalyst deactivation in methane steam and dry reforming reactions with operando spectroscopic techniques.

Luca Nardi

Luca Nardi has been a Ph.D. student in Chemical Engineering and Industrial Chemistry at Politecnico di Milano since November 2019 in Prof. Matteo Maestri's group. He received his bachelor's degree and master's degree in Chemical Engineering from Politecnico di Milano in 2017 and 2019, respectively. His research is focused on heterogeneous catalysis and structure-dependent microkinetic analysis of $CO₂$ transformation

into valuable products on metal-based catalysts.

Matteo Maestri

Matteo Maestri is a full professor of Chemical Engineering at Politecnico di Milano, Italy. He received his Ph.D. in Chemical Engineering from Politecnico di Milano in 2008. He was a visiting scholar at the Center for Catalytic Science and Technology of the Department of Chemical Engineering of the University of Delaware, USA (2006–2007); Alexander von Humboldt Fellow at the Fritz-Haber-Institut der Max-Planck-Gesellschaft in

Berlin, Germany (2009–2010); and at the Catalysis Research Center (CRC)–Department of Chemistry of the Technische Universität München, Germany (2011). He has received several awards, including the ERC Starting Grant from the European Research Council. His main research interests are fundamental analysis of catalytic kinetics and multiscale modeling of catalytic processes, by applying and developing methods that span from atomistic (DFT) calculations to CFD, and from kinetic analysis to operando-spectroscopy.

exceeding nowadays 400 ppm. $6,7$ On the one hand, the presence of $CO₂$ in the atmosphere is crucial for life on Earth, being involved in the C-cycle and in the regulation of the temperature of the Earth. Without $CO₂$, life on Earth would not be possible.⁸ On the other hand, the actual value of the $CO₂$ concentration in the atmosphere matters in maintaining the ecosystem compatible with our life. For instance, the increase of the average temperature on Earth causes a wide variety of problems such as more frequent droughts, more intense hurricanes, and the rising sea level.⁹⁻¹¹ The Intergovernmental Panel on Climate Change (IPCC) has shown a strict link between the rise of $CO₂$ concentration in the atmosphere due to anthropogenic activities and the increase of the average temperature on Earth.⁶ Hence, the IPCC stressed that more than 1000 Gt of $CO₂$ should not be emitted from 2000 to 2050 to limit the temperature rise to 2 $^{\circ}$ C.¹² Moreover, the Paris Agreement in 2015 suggested holding the increasing global temperature below 2 °C compared to preindustrial levels and pursuing efforts to limit the temperature increase to 1.5 °C above the preindustrial level.¹² Therefore, policymakers are taking action to achieve net-zero $CO₂$ emissions. The European Union and other countries such as New Zealand and South Korea are taking action to achieve $CO₂$ neutrality by 2050, while China is moving towards the idea of achieving carbon neutrality by 2060. Research and Development (R&D) efforts are required not only to circumvent the $CO₂$ problem but to turn it into opportunities by developing resource and energy-efficient processes towards net-zero $CO₂$ emissions without compromising the nature, economics, and environment.¹³⁻¹⁷ Catalysis Science & Technology

While two weakenbane CC (an the standard life is one standard life is one standard access Archar, and results consider the standard commons are the standard commons are the standard commons

Solving the problem by eliminating the need for fossil fuels as an energy source is not straightforward since fossil resources are the basis of our current chemical industry.¹⁸ From a technological point of view, fossil-carbon fuels are also very hard to replace as the main energy vector in our society for three main reasons: (i) they are characterized by huge energy densities; (ii) they are chemically stable under normal conditions; (iii) they are easy to store and transport. A promising concept would be replacing the fossil feedstocks currently used in the chemical and energy industry with sustainably produced chemicals and fuels by reducing $CO₂$ using renewable energy. In this view, renewable H_2 (e.g., water electrolysis with electricity from wind or solar energy) or renewable electricity can be combined with the undesired and highly available $CO₂$ for the production of commercially important fuels and chemicals, resulting in a carbon-neutral technology of energy transformation and storage.

Such transformation can be done via electrocatalysis, photocatalysis, and thermal catalysis that are essential components in any sustainable energy and chemical production.19,20 With the highest oxidized state (+4) and extreme heat of formation (ΔH_f° = −393.5 kJ mol⁻¹ at 25 °C), CO₂ is thermodynamically a highly stable molecule ($\Delta G_{\rm f}^{\circ}$ = −394.4 kJ mol⁻¹ at 25 °C), with a very strong C=O bond energy (799 kJ mol⁻¹). As a result, the activation and

transformation of $CO₂$ need very high temperatures or a catalytic process working under suitable operating conditions. For the process of $CO₂$ activation and conversion, different technologies have been proposed and developed, 2^{1-38} including bioconversion (e.g. enzyme catalysis), $21,22,28$ electrocatalysis, $31-36$ photochemical reduction,^{23–27,37–39} thermochemical processes,40–⁴² and their combination. This review is focused on thermo-catalytic CO_2 activation⁴³⁻⁴⁶ to provide clean, affordable, and secure energy and chemicals by substituting conventional feedstocks.47 Furthermore, major attention is paid to the importance of using earth-abundant catalytic materials for $CO₂$ activation, which has been widely studied and highlighted in several literature works.⁴⁸⁻⁵⁴

State-of-the-art experiments have shown the potential of $CO₂$ in making chemical intermediates such as syngas, $55,56$ carbon monoxide,⁵⁷ formic acid,⁴¹ methanol,⁵⁸ methane,⁵⁹ dimethyl ether, 60 olefins, 61 carbamates, carbonates, hydrocarbons (alkanes and aromatics) 62 and higher alcohols, 63 which can subsequently be transformed into a myriad of high-value products including chemical process intermediates and fuels. Despite the multitude of fundamental research studies on $CO₂$ conversion and its potential to yield important chemical compounds, very few processes have been demonstrated so far with their commercial viability.⁶⁴ The main technological challenges associated with the catalytic conversion of $CO₂$ are (i) requirement of significant energy input from carbon-neutral sources to prevent further $CO₂$ emission, (ii) need for high temperature and/or pressure processes to achieve good process performances, (iii) requirement of stable and active catalysts to prevent continuous waste of the catalytic material, (iv) poisoning of catalysts by residual water, 65 (v) sintering of catalyst particles, $66-74$ (vi) coke formation during the reaction, $75,76$ (vii) overoxidation to toxic metal carbonyl $(e.g., Ni(CO)₄),^{77–84}$ and (viii) waste generation by undesired side reactions.

In this review, we present an overview of the state-ofthe-art thermally-catalyzed approaches to utilize captured $CO₂$ directly by making fuels and chemicals. In particular, we focus on the analysis of four main chemical reactions: (i) reverse water-gas shift (RWGS), (ii) $CO₂$ methanation, (iii) CO₂ hydrogenation to methanol, and (iv) dry reforming of methane (DRM). These reactions are illustrated in Fig. 1. In the analysis and description of the current literature on the selected reaction systems, major attention is paid to (i) catalyst materials employed, (ii) information on the reaction mechanisms gained from experiments and first-principles calculations, (iii) kinetic experiments and corresponding rate equations, (iv) most important challenges and possible solutions, and (v) available reactor technologies.

2. Materials and mechanisms

The reaction mechanism of $CO₂$ activation and conversion can vary over different catalysts and reaction conditions (e.g.,

temperature, pressure), and it involves the formation of several different reaction intermediates. The key steps of the reaction scheme are (i) chemical adsorption of $CO₂$ and coreactants (e.g., H_2 , CH₄), which dissociate over the catalyst surface into reaction intermediates, (ii) surface diffusion and reaction of the intermediates at the catalyst active sites, and (iii) desorption of product species (e.g., CO, CH_4 , CH_3OH , $H₂O$) from the catalyst surface. The information on the reaction kinetics and mechanisms is crucial for the understanding of the pathways of $CO₂$ activation and conversion, the identification of the rate-determining steps (RDSs), and the elucidation of the active sites of the catalyst. Such information is fundamental for the optimization of existing processes and the discovery of new catalytic materials, by guiding new experiments or by in silico catalyst design. An important concept to take into account when analyzing catalytic systems is that the reaction mechanism and the distribution of the active sites of a catalyst evolve under reaction conditions.^{85,86} Indeed, the local reaction environment that forms during the reaction highly affects the reaction rates, 87 and catalyst materials can also undergo morphological transformation such as surface reconstruction, phase transition, and deactivation by sintering or coking. These are multiscale phenomena, which need a proper description based on the combination of experimental and theoretical analyses representing the different time and length scales (i.e., from the atomic scale to the reactor scale).

2.1 Mechanism of $CO₂$ activation and conversion to $C₁$ products

The reactions of transformation of $CO₂$ into $C₁$ products (CO, CH_4 , and CH_3OH) proceed through a complex reaction scheme.88–¹⁰⁷ A simplified version of the scheme is represented in Fig. 2. For illustrative purposes, four main reaction paths^{98,99} are identified in the reaction mechanism

and their reaction intermediates are highlighted with different colours. The paths are (i) RWGS redox path, in orange, (ii) CO* methanation path, in grey, (iii) carboxyl path, in yellow, and (iv) formate path, in light blue. In the RWGS redox path, adsorbed CO^{*} dissociates into CO^{*} and O*. Then, CO* can desorb as gaseous CO, or it can further react. This path is called "redox" because in RWGS it is accompanied by the oxidation of H^* to H_2O . The dissociation of CO* to C* and O* is the first step of the CO* methanation mechanism, and it is followed by the successive reduction of C^* to CH^* , CH_2^* , CH_3^* , and gaseous CH_4 , by the addition of H* species. The carboxyl (COOH*) path involves the formation of a COOH* molecule by the addition of an H^* to the O atom of CO_2^* . In the successive steps, $COOH^*$ then loses an O* atom, producing COH*, which is successively hydrogenated to HCOH*, and H_2COH^* . The further reduction of H_2COH^* produces CH_3OH in the gas phase. Similarly, the formate (HCOO*) path involves the reaction of CO^{*}₂ with an H^{*} atom. However, an HCOO^{*} molecule is formed when H^* binds to the C atom of CO_2^* . The formate path continues with the removal of an O* from HCOO* to give HCO*, which is hydrogenated to H_2CO^* , H_3CO^* , and eventually to CH₃OH. The CO₂^{*} dissociation, methanation, carboxyl, and formate reaction paths are interconnected by several elementary reactions; indeed, CO and $CH₄$ can be formed also from intermediates of COOH $*$ and HCOO* paths. The elementary reactions in the kinetic mechanism involve the addition or the removal of H*, O*, and OH* species. Those adsorbed species are provided by either other elementary steps depicted in Fig. 2 or by the dissociative adsorption of H_2 , and they are precursors for the formation of H_2O . In DRM, the reaction paths in Fig. 2 which link $CH₄$ to CO are followed backwards. Indeed, the adsorption and oxidation of CH_4 produce CO^* and H^* species, which are the precursors of syngas (mixture of CO and H2). During DRM, carboxyl and formate pathways can also produce $CH₃OH$ as a side product. Besides the main

Fig. 2 Simplified reaction mechanism of CO₂ reduction to CO, CH₄, and CH₃OH, in which four main reaction paths are highlighted: RWGS redox path (orange), CO* methanation path (grey), formate path (yellow), and carboxyl path (light blue). On the right hand side, the structures of the reaction intermediates⁹⁹ are highlighted with the colors of the corresponding reaction path.

intermediates and pathways reported in Fig. 2, other reaction intermediates can participate in the overall reaction mechanism. For example, in the carboxyl path, COH* can be formed from COOH* through a $C(OH)_2^*$ intermediate. In the formate path, the formation of H_2CO^* from HCOO* can proceed with H₂COO* or HCOOH* as an intermediate instead of HCO*. Other possible reaction intermediates include CO^{*} and species adsorbed onto the catalyst support. Moreover, $CO₂$ can also react directly from the gas phase to give HCOO*, COOH*, or CO* and O* species, without being first adsorbed.

In heterogeneous catalysis, $CO₂$ activation consists of the interaction of the molecule with a catalytic surface, which usually consists of the chemical adsorption of $CO₂$ (the first step of Fig. 2) to give the activated reaction intermediate CO* ². Usually, the adsorption on the active sites of a surface implies the bending of the $CO₂$ molecule. This bending lowers the energy level of the in-plane contribution of the 2π orbital (the lowest unoccupied molecular orbital, LUMO), which makes the carbon atom electrophilic. On metallic surfaces, $CO₂$ activation usually consists of electronic charge transfer from the metal to CO_2 .¹⁰⁸⁻¹¹⁰ On metal oxides, on the other hand, the adsorption exploits the amphoteric nature of $CO₂$, which has a partial positive charge on the C atom (+0.37 e from Mulliken's population analysis) and negative charges on the two O atoms (-0.18 e) .⁴⁰ During the adsorption, the electron-deficient C atom and the more electron-rich O atoms can be attacked by either electron-rich or electron-deficient active sites, respectively.⁴⁰ Typically, the carbon atom of $CO₂$ interacts through O^{2-} lattice atoms, and the oxygen atoms of $CO₂$ interact with the metal cations (e.g., Mn²⁺).

The group of Mpourmpakis studied with DFT the $CO₂$ activation on monometallic, core-shell, and decorated icosahedral CuNi (ref. 108) and CuZr (ref. 109 and 110) nanoparticles. For the case of CuNi, it is reported that the presence of surface Ni is key in strongly adsorbing the $CO₂$ molecule, which occurs through a charge transfer from the nanoparticles to the $CO₂$ molecule, where the local metal

d-orbital density localization on surface Ni plays a pivotal role. Additionally, they found a linear relationship between the local-site d-band center and the $CO₂$ adsorption energy and observed that the active sites of strong adsorption localize the HOMO (highest occupied molecular orbital) orbitals with increased d-character.¹⁰⁸ For the case of CuZr nanoparticles, they observed that $CO₂$ activation is endothermic on metallic Cu, whereas it becomes barrierless and exothermic on the Zr-decorated Cu nanoparticles, and that the rate of $CO₂$ dissociation to $CO[*]$ and $O[*]$ is much higher on CuZr than Cu.¹⁰⁹ Moreover, they showed that Zr sites can be oxidized because of their high oxophilicity; however, they are still able to adsorb and activate $CO₂$ easily.¹¹⁰ Dixit et al.¹¹¹ investigated CO_2 adsorption on molybdenum carbide $(Mo₂C)$, showing an important influence of the O^* coverage on the $CO₂$ adsorption energy and the $CO₂$ dissociation barrier. They explained this by showing an electronic modification on the catalyst surface (e.g., d-band shift on Mo atoms) with increasing oxygen coverage. **Mini review**

Catalysis Science & Technology

noids. Additionally allow the minimization is linear relationship between the

noid calibration is linear relationship between the "new matricles. The

introduction of the mi

The adsorption configuration of CO_2^* changes with the structure and composition of the catalyst surface.^{99,108-114} Usually, the C atom and one O atom of CO_2^* bind to one or two metal atoms^{108-110,112} (on the "top" or "bridge" adsorption sites). The other O atom of CO^{*}₂ may interact with the surface.^{99,111} Particularly relevant is the interaction of CO* ² with the (100) facets of metal catalysts. Indeed, the square geometry of such facets allows for a CO₂^{*} adsorption configuration in which C and O interact with two metal atoms each, which promotes the breaking of the $C=O$ bond of CO₂^{*}. This yields low activation barriers for CO₂^{*}</sup> dissociation to CO* and O* on (100) facets, representing an example of a structure-sensitive elementary step. $112,115$ Regarding the elementary steps needed in the production of hydrocarbons (e.g., CH₄) from CO $_2^*$ (Fig. 2), other structuresensitive effects are reported in the literature.^{86,99,116-118} In those processes, the slow steps are related to the breaking of the triple bond in the CO* molecule $(C=0)$,¹¹⁸ which can occur by direct CO^* dissociation^{86,116,117} or by hydrogenassisted dissociation (via a HCO* intermediate). ^{99,118} For those reactions, the highest rates are usually provided by the stepped sites available on, e.g., (211) , 116,117 (311) , 86,112 and $(110)^{99}$ facets.

2.2 Reverse water-gas shift (RWGS)

RWGS is a reversible and endothermic reaction ($\Delta H_{\rm R}^0$ = +41.2 kJ mol⁻¹ at 25 °C), in which CO₂ reacts with H₂ to give CO and $H_2O^{93,119,120}$ It is an equimolar reaction, so its chemical equilibrium is independent of the pressure. At low temperatures, it is usually accompanied by side production of CH₄ via CO₂ methanation.^{121,122} This is because the production of CH4 is favored by thermodynamics below ∼400 °C. As a result, high CO selectivity can be achieved by flowing $CO₂$ and $H₂$ at elevated temperatures.

\mathcal{L} and \mathcal{L} review \mathcal{L} review \mathcal{L} . The contract of technology is \mathcal{L}

Several supported metals including Pd,^{123,124} Pt,^{100,125-127} Rh,^{128–130} Au,^{122,131,132} Fe,^{133,134} Ni,^{47,94,135} and Cu,^{136,137} have been reported as active catalysts for the RWGS reaction. In addition, supported metal alloys, such as $Pd-In/SiO₂,¹³⁸ Co-$ Fe/Al₂O₃,¹³⁹ Fe–Cu/Al₂O₃,¹⁴⁰ and Fe–Cu–Cs/Al₂O₃,¹⁴⁰ were employed as catalyst materials, showing high CO selectivity (90-100%) and $CO₂$ conversion ranging from 20 to 55%. Among supported metals, high catalytic performances were shown by Cu/CeO₂ (ref. 137) (25 g_{CO} g_{cat}^{-1} h⁻¹), Pt/TiO₂ (ref. 100) (51 $g_{CO} g_{cat}^{-1} h^{-1}$), and Rh supported on silicalite-1 (ref. 130) (76 $g_{CO} g_{cat}^{-1} h^{-1}$) at 400–450 °C. At the same reaction temperatures, K-Mo₂C/ γ -Al₂O₃ (ref. 141) demonstrated also a good catalytic activity (50 $g_{\text{co}} g_{\text{cat}}^{-1} h^{-1}$), with a catalyst cost much lower than that of noble metals. At a higher temperature (600 °C), Cu/β-Mo₂C (ref. 136) showed high catalytic activity (40% $CO₂$ conversion, 99% CO selectivity) and very good catalyst stability provided by the support that prevents the sintering of Cu nanoparticles.

Based on experimental and theoretical observations, two kinds of mechanisms have been proposed, 125 namely the redox mechanism^{142–144} and carboxyl $(COOH^*)$ mechanism.145–¹⁴⁷ Formate species, which can form under reaction conditions, $148-150$ are usually reported as spectator molecules that do not participate actively in the reaction. In the redox mechanism, CO_2^* dissociates to CO^* and O^* , and the latter reacts with H^* (produced by H_2 adsorption) to give OH* and then H_2O^* .¹¹⁴ In the carboxyl mechanism, CO_2^* reacts with H* to give COOH*, which dissociates into CO* and OH * .^{151,152} Maestri and co-workers¹⁵³ studied with DFT calculations the two mechanisms on the (111) surfaces of Pt, Rh, Ni, Cu, Ag, and Pd, showing different reaction paths on the different metals. Indeed, they showed that the redox mechanism is preferred on Rh(111), Ni(111), and Cu(111), whereas the COOH* mechanism is favored on $Pt(111)$, Pd(111), and Ag(111). Brønsted–Evans–Polanyi (BEP) relations for CO^{*} dissociation and hydrogenation were derived, and

Fig. 3 Linear correlation between the O* binding energy and the difference in the activation energies of CO_2^* dissociation ($E_{\text{act}}^{\text{Diss}}$) and CO_2^* hydrogenation (E_{act}^{Hydr}). Adapted with permission from ref. 153. Copyright 2015 American Chemical Society.

the occurrence of different reaction mechanisms was correlated with the oxophilicity of the metals, thus explaining that the stronger the interaction of O* with the metal, the lower the activation energy of CO_2^* dissociation, which results in a preferred redox mechanism over the competing COOH* path (Fig. 3).

Several theoretical and experimental observations reported a strong structure-sensitive character of the reactions of $CO₂$ conversion,99,113,154 including RWGS.114,155 For example, Cai et al.¹¹³ investigated the interaction of CO_2 (and H₂O) on Ni(111) and Ni(100) surfaces using ambient pressure X-ray photoelectron spectroscopy and theoretical DFT calculations and observed a very different distribution of dissociation products on the two Ni facets in the presence of 0.2 Torr of $CO₂$. On Ni(111), more than 90% of the adsorbed surface species are carbonate (CO_3^*) , whereas Ni(100) is mainly covered by adsorbed CO* and graphitic C*. Moreover, they observed with DFT a very high difference in the activation energy of the $CO₂$ dissociation reaction on the two facets: 0.33 eV on $Ni(100)$ and 1.34 eV on $Ni(111)$. This is explained by the geometry of Ni(100), which stabilizes the transition state of $CO₂$ dissociation by interaction with four Ni atoms interacting with the π orbitals of CO₂.¹¹⁵ Along with this, they showed that the conversion of $CO₂$ on Ni(111) and Ni(100) tends to follow different reaction paths, in agreement with their experimental observations. Zhang et $al.^{114}$ investigated the RWGS redox mechanism on Ni(111) and Ni(311), showing that the stepped (311) surface has higher catalytic activity than the flat (111) surface. Lin et al .¹⁵⁵ investigated redox and carboxyl mechanisms on Ni(110) in the presence of a high density of subsurface hydrogen, showing that subsurface H atoms can play an important role in RWGS, by both lowering the energy barriers of the kinetic mechanism and participating actively in the hydrogenation elementary steps. They also concluded that, in their system, the redox mechanism is the most favorable RWGS pathway. Wang et $al.^{156}$ investigated with transient quantitative temporal analysis of products (TAP) the ability of $CO₂$ to re-oxidize a pre-reduced $Au/CeO₂$ catalyst. They observed that the reduced catalyst is partially oxidized by $CO₂$, suggesting that the redox path is possible on $Au/CeO₂$. Wang and Nakamura¹⁵⁷ performed DFT calculations on different Cu surfaces and revealed a strong structure-sensitivity of CO_2^* and H_2O^* dissociation reactions. They calculated activation energies in the following order Cu(110) \langle Cu(100) \langle Cu(111) for both elementary dissociation reactions. They reported a "late" nature of the transition states, which resemble the geometry of dissociation products, and they concluded that the activation energies of CO_2^* and H_2O^* dissociation are influenced significantly by the binding energies of OH* and O^* , respectively. Liu et al.¹⁵⁸ investigated the redox mechanism on the (100) surfaces of Fe, Ni, Co, and Cu. They reported that Fe(100) shows the highest $CO₂$ adsorption energy, which, however, does not facilitate the reaction, but causes a thermodynamic sink on the reaction coordinate. $Co(100)$ and Ni (100) , on the other hand, are more favorable Catalysis Science & Technology

While exongulation the constraints are considered to the function of the method on a standard on the the consideration of the common and the common and the common and the common and the com

in terms of a smaller fluctuation in reaction energies and barriers. They also studied $CO₂$ adsorption on Fe bcc(100) and Co hcp(1010) surfaces and suggested that that not only metals but also the surface structures significantly affect the reaction kinetics.

A widely accepted concept is that in the redox mechanism, the RDS is CO_2^* dissociation.^{153,155-158} In the COOH^{*} mechanism, on the other hand, COOH* formation is usually the limiting step.¹⁵³ The reactions of water formation, *i.e.*, $OH^* + H^* \rightarrow H_2O^*$ (and also $O^* + H^* \rightarrow OH^*$ in the redox mechanism), can also be relevant for the kinetics of the RWGS reaction. Experimental^{159,160} and theoretical^{112,161,162} observations on an Rh/Al_2O_3 catalyst suggested that direct WGS and RWGS can follow different reaction mechanisms, where the H_2O^* formation steps are pseudo-equilibrated for RWGS, but they are the slow steps for direct WGS. Maestri and co-workers^{161,162} suggested that the RWGS reaction proceeds through CO_2^* dissociation over Rh/Al_2O_3 , whereas direct WGS proceeds with a COOH* intermediate. They calculated that H_2O^* dissociation and CO_2^* dissociation are the RDSs for direct and reverse WGS, respectively, in agreement with the experimental reaction orders of Donazzi et al.^{159,160} Cheula and Maestri¹¹² derived a structuredependent microkinetic model of direct and reverse WGS on $Rh/Al₂O₃$, which describes the morphological evolution of the catalyst along with the surface reactions on five different Rh facets: (100), (110), (111), (311), and (331). Their study allowed to rationalize that far from equilibrium the two different reacting systems not only follow different reaction pathways but also show that the active sites are different for WGS and RWGS. Indeed, the WGS reaction occurs mainly on the Rh(111) facet, whereas RWGS proceeds on the active sites of Rh(100), which promotes the CO_2^* dissociation elementary step thanks to its structural arrangement.

2.3 CO2 methanation

 $CO₂$ methanation, called also the Sabatier reaction,¹⁶³ is an exothermic reaction ($\Delta H_{\rm r}^0$ = -165.0 kJ mol⁻¹ at 25 °C) favored at low temperatures, in which $CO₂$ reacts with 4 molecules of H_2 to give CH₄ and 2 molecules of H₂O. The production of $CH₄$ from $CO₂$ and $H₂$ is advantageous due to the high energy density of $CH₄$ and its easiness to be fed into conventional natural gas infrastructure.¹⁶⁴ Moreover, because of the possibility to convert the Martian $CO₂$ atmosphere into methane and water for the fuels and life support of astronauts,¹⁶⁵ the National Aeronautics and Space Administration (NASA) is spending its efforts to apply this reaction for space colonization on Mars.¹⁶⁵ The catalysts are typically based on Ni, Ru, Rh, and Co as active phases, with Ni being the most used due to its activity, selectivity, and low cost.166–¹⁷² The temperature is usually between 100 and 350 °C, as at higher temperatures, the production of CO by RWGS is favored by thermodynamics.¹⁷³

Ni has been the most studied material for industrial $CO₂$ methanation applications.¹⁷⁴⁻¹⁷⁶ High CO₂ conversion (5560%) and selectivity to methane (80–90%) were obtained on supported Ni catalysts.^{135,177} However, Ni presents severe deactivation and loss of activity due to carbon formation,¹⁷⁸ metal sintering, $179,180$ and formation of Ni carbonyls. $181,182$ Alternatively, Rh, Ru, Pd, Pt, and Re on different oxide supports were studied.^{130,183-186} Among them, Ru and Rh showed very high catalytic performances (up to 95% selectivity to CH₄ and 65–80% CO₂ conversion).^{130,135,187} Cheaper materials, such as $Co_{188,189} Fe₁₉₀₋₁₉₄$ and Mn,^{166,189} and bimetallic particles containing noble metals, Ni and Fe (ref. 194 and 195), were also investigated.

 $CO₂$ methanation was reported to be highly dependent on metal–support interaction.^{98,196–200} This phenomenon was related to the ability of $CO₂$ to adsorb on the support materials. For instance, Pandey and $Deo¹⁹⁴$ studied the reaction on Ni–Fe supported on different materials (i.e., Al_2O_3 , ZrO_2 , TiO_2 , SiO_2 , and Nb_2O_5) and observed that the support yielding the highest activity, Al_2O_3 , is the one that more favorably adsorbs $CO₂$. Martin et al.¹⁹⁷ studied $CO₂$ methanation over $Rh/CeO₂$ and $Ni/CeO₂$ using spectroscopic analyses and demonstrated that $Rh/CeO₂$ exhibits higher methane selectivity than the $Ni/CeO₂$ catalyst with the same loading. This was explained by the lower Rh particle sizes resulting from the strong metal–support interaction. Moreover, they argued that the $CeO₂$ support can influence the reaction rates by getting partially reduced during the reaction and producing Ce^{3+} , which can facilitate the activation of CO₂. Ocampo *et al.*¹⁷⁰ investigated the Ni/Ce_{0.72}- $Zr_{0.28}O_2$ system and reported excellent activity and selectivity of $CO₂$ methanation as well as good catalyst stability. The good performances of their catalyst were attributed to the good ability to store active oxygen and to the high Ni dispersibility.²⁰¹⁻²⁰³

The proposed reaction mechanisms of $CO₂$ methanation are mainly three: (i) carbide pathway, $204-206$ (ii) COOH* pathway,^{207,208} and (iii) HCOO* pathway,^{209,210} as illustrated in Fig. 4.b. Several authors proposed that a part of the reaction mechanisms can occur on the support $207,211-213$ or at the interfacial sites between the metal and support, 103 while $H₂$ is always supposed to dissociate on the metal. Particularly

on the support, the formation of CO_3^* by the oxidation of CO_2 is also observed, which can be reduced to bicarbonate $(HCO[*])$ and participate in the reaction mechanism^{211,212} by producing HCOO* species. Qin et al.²¹³ achieved high conversion and methane selectivity at 280 °C and over bimetallic catalysts containing Ni, and they suggested bicarbonate, carbonate, and formate as intermediates based on their in situ FTIR analyses. Falbo et al.²¹⁴ investigated $CO₂$ methanation on $Rh/Al₂O₃$ at low and high temperatures and observed higher catalyst stability when CO was added to the inlet. Their spectroscopic analyses were consistent with a path where CO_2 is adsorbed as bicarbonate on Al_2O_3 and it is successively hydrogenated to $CH₄$ on Ru, passing through formate and carbonyl intermediates. Aldana et $al.^{207}$ studied the reaction on strong and weak basic sites of $Ni/Ce_{0.5}Zr_{0.5}O_2$ and Ni/γ -Al₂O₃ and showed that the weak basic sites result in monodentate carbonate, which is more prone to hydrogenation, while the strong basic sites form bidentate carbonates, which do not participate in the reaction mechanism. Yang et al.¹⁰³ studied with DFT the $CO₂$ methanation over a cluster of Rh supported on $TiO₂$, highlighting the role of the metal–support interface, which is a significant charge accumulation region and can provide electrons for $CO₂$ reduction. In their work, they showed that the interface active sites are more feasible for $CO₂$ activation than the Rh nanoparticle sites. Moreover, they calculated that the COOH* mechanism involving the formation of a COH* intermediate is the favorite reaction pathway of $CO₂$ methanation over the $Rh/TiO₂$ catalyst, while the redox WGS and the formate pathways show higher energy barriers. Such preferred pathways proceed with the intermediates CO_2^* , COOH*, CO*, COH*, HCOH*, H_2COH^* , CH_3^* , and CH_4^* , and show COOH* dissociation into CO* as the RDS. Mini review Catalysis Science & Technology

supposed by calculations of the stress article is article in the stress article is article in the reduction of the stress are the stress are the stress are the stress Article in

Vogt et $al.^{99,154}$ highlighted the strong structure-sensitive character of $CO₂$ methanation over Ni catalysts. They studied the effect of a $Ni/SiO₂$ nanocluster with particle size 1-7 nm and observed an optimum in the $CO₂$ methanation activity at a particle size of 2-3 nm (Fig. 4.a).¹⁵⁴ To understand such a particle size effect, they also studied $CO₂$ methanation on Ni catalysts supported on different metal oxide supports $(A₂O₃$,

Fig. 4 (a) The influence of Ni particle size on activity normalized to the Ni loading for CO₂ methanation on Ni/SiO₂, at 400 °C, 1 bar, and H₂/CO₂ $=$ 4. Reproduced with permission from ref. 154. (b) Proposed reaction mechanism of CO₂ methanation on Ni. Reproduced with permission from ref. 99.

 $CeO₂$, $ZrO₂$, $TiO₂$), and they developed a microkinetic model based on DFT calculations on the (100), (110), (111), and (211) facets of Ni (reaction mechanism shown in Fig. 4.b). The integration of their microkinetic model allowed them to select the most active Ni facet, i.e., Ni(110), and identify the dissociation of HCO* (HCO* \rightarrow CH* + O*) on such a facet as the RDS of the reaction mechanism. The maximum in the activity vs. size plot was explained by two phenomena: (i) the catalytic activity decreases with the particle size because big particles have a lower dispersion (*i.e.*, the fraction of metal atoms at the surface) and therefore a lower number of active sites per gram of catalyst, and (ii) particles with size lower than 2–3 nm have low turnover frequency (TOF), $(i.e.,$ the catalytic activity per active site) because they do not show the most active sites for the reaction.²¹⁵

The main phenomena that determine catalyst deactivation during $CO₂$ methanation are sintering and coking. To identify the nature of carbon formed during methanation reactions over $Ni/Al₂O₃$, Olesen et al.²¹⁶ performed temperature-programmed hydrogenation experiments and observed three major carbon peaks, attributed to carbide ($~\sim$ 650 K) and polymeric carbon ($~\sim$ 650 and $~\sim$ 775 K). Loss of activity with an increase in the carbon-to-nickel ratio was noticed, primarily due to polymeric carbon formation that resulted in catalyst deactivation. A linear correlation was observed between the amount of carbon formed and the degree of deactivation of the catalyst.²¹⁶ Barrientos et al.²¹⁷ investigated various $Ni/Al₂O₃$ catalysts promoted with MgO, CaO, BaO, and $ZrO₂$ under low-temperature conditions (300 °C), and they showed that the presence of Zn lowers the formation of polymeric carbon. Galhardo et al.,⁹² with in situ spectroscopic analyses, observed that the accumulation of carbon species on the surface of a $Ni/SiO₂$ catalyst at high temperatures leads to a $Ni₃C$ -like phase, which changes the process selectivity towards the formation of CO. After carbon depletion from the surface of the Ni particles by oxidation, the catalyst regains its high selectivity to $CH₄$ production. However, the selectivity readily shifts back toward CO formation after exposing the catalysts to a new temperatureprogrammed $CO₂$ hydrogenation cycle. The fraction of weakly adsorbed CO^* increases on the Ni₃C-like surface when compared to a clean nickel surface, explaining the higher selectivity to CO. Catalysis Science & Technology Www.2006

Velopi equity of the microsines content in the common content in the microsical content in the common content in the common content in the common content in the common content in t

2.4 Dry reforming of methane (DRM)

Syngas (a mixture of CO and H_2) is an important intermediate used as a building block molecule to manufacture high-value chemicals (e.g., methanol, olefins, and hydrocarbons), and it can be produced from $CO₂$ via DRM ,^{218,219} a reaction in which $CO₂$ combines with $CH₄$ to give 2 molecules of CO and 2 molecules of H_2 . As DRM is an endothermic reaction ($\Delta H_{\rm R}^0$ = +247.0 kJ mol⁻¹ at 25 °C), it is thermodynamically favorable at high temperature, so the reaction temperature is usually between 550 and 800 °C. On the surface of a catalyst, $CO₂$ and $CH₄$ dissociate into reaction intermediates (e.g., CO*, O*, H*, OH*, CH_x^* , $CH_xO_y^*$), which combine to give the final reaction products (CO and H_2). The most relevant unwanted side-product is coke, which can accumulate and deactivate the catalyst.

Nickel is the most important and utilized material for DRM, because of its high activity, high abundance, and low cost. High conversion of both $CO₂$ and $CH₄$ (80-95% at 700-800 °C) was obtained with Ni catalysts supported on different materials such as Al_2O_3 ,²²⁰ SiO₂,²²¹ and BN.²²² However, rapid coke deposition on the catalyst surfaces during the reaction limits the practical use of Ni-based catalysts. $217,223$ To cope with such challenges, noble metals like Rh Ru, Pt, Ir, and Pd were also investigated, because of their higher coking resistance.224–²²⁶ Good catalyst performances and resistance to deactivation by coking were showed by supported bimetallic catalysts such as Ni-Rh/LaAlO₃,²²⁷ Ni-Cu/MgO₂²²⁸ and Ni-Mn/Al₂O₃.²²⁹ Such hybrid materials have a lower cost than noble metal catalysts and show high catalytic performances (85–97% $CO₂$ and $CH₄$ conversion at 750–800 $\rm ^{o}C$).^{227–229}

Several researchers have attempted to understand the mechanism of DRM on supported metal catalysts.²³⁰⁻²³⁵ Bradford et al.²³⁵ performed kinetic studies on Ni supported on different materials $(SiO₂, TiO₂, MgO, and C)$ and suggested a reaction mechanism consistent with their experimental data. In their mechanism, $CO₂$ dissociates to CO^* and O^* , and CH_4 dissociates into CH^*_x and H^* . Then, OH* species are formed and act as an oxidant. Indeed, $CH_x[*]$ gets oxidized by OH* to form $\mathrm{CH}_x\mathrm{OH}^*$ species, which produce CO and H_2 upon subsequent reactions. Both CH₄ dissociation and CH_xOH decomposition were supposed as the slow steps of the mechanism. Múnera et al^{236} have concluded in their kinetic studies of DRM on $Rh/La_2O_3-SiO_2$ that $CH₄$ decomposition takes place on the metal, whereas $CO₂$ activation occurs on the support. Maestri et al.²³⁷ proposed CH₄ dissociation (CH₄ \rightarrow CH₃^{*} + H^{*}) as the RDS on an $Rh/Al₂O₃$ catalyst, from hierarchical microkinetic modeling. With their analysis, they show that CH4 dehydrogenates into atomic carbon (C*), which gets oxidized subsequently by OH* over Rh surfaces. Mark et al^{238} concluded that CH4 dissociation is the RDS for DRM also over Ir/Al₂O₃ at 700–850 °C and 1 atm. However, they reported that adsorbed carbon C* reacts via the reverse Boudouard reaction (BR) (C^* + CO_2^* \Rightarrow CO^*) to give the final products.²³⁹ CH₄ dissociation was further confirmed as the RDS in DRM by Iglesia and co-workers through conducting experiments over supported Ni, Pd, and Rh catalysts at temperatures lower than 600 °C using the CH₄/CD₄ isotope tracer method.^{239–241} Fan et al.²³⁰ derived a comprehensive microkinetic model based on DFT calculations on Ni(111), Ni(211), and Ni(100) facets, and showed that at low CH_4 and $CO₂$ partial pressures, both $CH₄$ dissociative adsorption and C* oxidation affect the overall reaction rate, whereas, at high pressures, C* oxidation is suggested as the only RDS for the DRM reaction, in agreement with previous experimental observations. Manavi and $Liu²⁴²$ investigated the reaction

Fig. 5 (a) DRM reaction network displaying the conversion routes of CH₄ (green arrows) and CO₂ (light blue arrows), including relevant reaction intermediates and elementary steps. (b) 2D volcano plot indicating the DRM catalytic activity (TOF) as a function of the binding energies of C* and O*. Adapted with permission from ref. 242.

mechanism of DRM on the (111) facet of Co_3Mo_3N , a catalyst that can activate easily both $C=O$ and $C-H$ bonds, and proposed a reaction network for DRM, as shown in Fig. 5.a. Moreover, they derived a 2D volcano plot illustrating the catalytic activity vs. the binding energy of C* and O* for different materials (shown in Fig. 5.b), highlighting the importance of mild adsorption energies for the highest catalytic activity.

Since carbon is miscible in Ni surfaces, it can diffuse through the surface and form carbide-like phases such as $Ni₃C^{243,244}$ To understand the role of Ni₃C in syngas production and catalyst deactivation, Wang et al^{245} investigated DRM over flat and stepped Ni and $Ni₃C$ surfaces with DFT calculations. They reported that, due to the high CH oxidation rate and low CO dissociation, the flat Ni(111) surface shows high catalytic activity for DRM and low coke formation. The flat $Ni₃C(001)$ shows good DRM catalytic activity, but it also produces coke. The stepped surfaces of both nickel – Ni(211) – and nickel carbide – Ni₃C(111) – show instead poor DRM performances and high coke formation.

The support material is another important factor that can modify the reactivity and stability of the catalyst under reaction conditions by changing its dispersion and its electronic properties.²⁴⁶ The role of different supports and additives in coke deposition and the durability of Ni-based catalysts has been extensively studied.^{194,247-249} Sokolov et al^{250} investigated the role of different supports in the activity of Ni at 400 °C. Their Ni/La₂O₃ZrO₂ catalyst was reported to be the most active and most stable. They also studied different structures of $La_2O_3ZrO_2$, *i.e.*, nonstructured, mesoporous, and microporous. The mesoporous support showed no change in activity over 180 h on-stream, whereas the others deactivated, by the formation of graphene-like coke layers and NiO shells over Ni particles. The enhanced stability of Ni on the mesoporous $La_2O_3ZrO_2$ was attributed to a pore confinement effect. Yavuz and co-workers²¹⁸ demonstrated very high stability of the Ni–Mo/MgO catalyst (up to 850 h) without coke formation at 800 °C under DRM conditions. This high stability was presumed to be due to the small particle size (2.9 nm) of the Ni–Mo/MgO nano-catalyst that may lead to better dispersibility and prevent coke formation.

2.5 $CO₂$ hydrogenation to methanol

Methanol is an important chemical compound that can be used as an additive for fuels or as a precursor of, e.g., dimethyl ether, gasoline, and diesel. $CO₂$ hydrogenation to methanol is an exothermic reaction ($\Delta H_{\rm r}^0$ = -49.5 kJ mol⁻¹ at 25 °C), favored at low temperatures and high pressures. A good catalyst for the production of methanol from $CO₂$ must have active sites for the activation of $CO₂$, dissociate $H₂$, and suppress competitive side reactions (e.g., RWGS, methanation).251–²⁵⁴ Usually, this implies the use of active metal-oxide materials, $52,253$ which can also be doped to change their surface electronic properties.²⁵⁵⁻²⁵⁸

Industrially, methanol is produced from synthesis gas mixtures $(CO/CO₂/H₂)$ at 200-300 °C and 50-100 bar (ref. 259) over $Cu/ZnO/Al₂O₃$ catalysts, selected because of the low cost of Cu and the good synergism between Cu and ZnO. For $CO₂$ conversion, the Cu/ZnO/Al₂O₃ catalyst displays lower activity towards methanol formation due to the competitive RWGS reaction²⁶⁰ and water-induced deactivation.^{261,262} The production of H_2O is higher when CO_2 is present in the feed because the $CO₂$ to methanol reaction stoichiometry ($CO₂$ + $3H_2$ \Rightarrow CH₃OH + H₂O) implies the formation of an H₂O molecule for every CO_2 molecule.^{261–263} The production of $H₂O$ enhances also the sintering of the catalyst.^{70-74,263} To overcome these challenges, different support materials, which can promote structural and electronic properties and stabilize smaller Cu particles,²⁶⁴ were investigated, including ZrO_2 ,^{265,266} La₂O₃,²⁶⁷ MoC₂,²⁶⁷ CeO₂,²⁶⁸ and La₂O₂CO₃ (ref. 267) and ZnO-ZrO₂.^{98,259,269-275} In particular, Cu/ZnO/ZrO₂ showed very high activity and selectivity at low temperatures (180–240 °C).^{276–279} This is likely due to the weak hydrophilic nature of $ZrO₂$, which may inhibit the poisoning effect of

water on the active sites $272,273$ and promote the activity by increasing Cu dispersion, which can strongly affect $CO₂$ adsorption and methanol selectivity.280,281 Other materials investigated for $CO₂$ hydrogenation to methanol are Au/CeO_x/ TiO₂,²⁸² In₂O₃,^{283–287} Ir-In₂O₃,²⁸⁸ Ni-In₂O₃,²⁸⁹ Mn-Co₂²⁹⁰ Ni-Ga,²⁹¹ ZnO–ZrO₂,²⁹² GaPd₂,²⁹³ and Co/SiO₂.⁹¹ In particular, In_2O_3 is attracting great interest in the scientific community²⁸³⁻²⁸⁷ because of its high catalyst stability^{265,286} and very high methanol selectivity.294–²⁹⁸ However, there is still a debate on the currently available best catalyst of methanol synthesis from $CO₂$, mainly because the performances of the catalysts strongly depend on the experimental conditions under which they are tested. An In_2O_3/ZrO_2 catalyst²⁸⁷ provided high methanol selectivity (99.8%), low $CO₂$ conversion (5.2%) and a productivity of 0.30 $g_{\text{MeOH}} g_{\text{cat}}^{-1} h^{-1}$ at 300 °C, 50 bar, with a gas hourly space velocity (GHSV) of 16 000 h^{−1}. Under similar experimental conditions (240 °C and 50 bar), a Cu/ZnO/ZrO₂ catalyst showed higher methanol productivity (1.2 $g_{\text{MeOH}} g_{\text{cat}}^{-1} h^{-1}$), a $CO₂$ conversion of 9.7% and a methanol selectivity of 62.0%.²⁹⁹ At 280 °C, 46 bar, and GHSW = 10 000 h⁻¹, Cu/ZnO/ Al_2O_3 (ref. 300) showed higher CO_2 conversion (23.8%) but lower methanol selectivity (22.8%) and a productivity of 0.15 $g_{\text{MeOH}}~{g_{\text{cat}}}^{-1}$ h $^{-1}$. The same Cu/ZnO/Al $_2$ O₃ catalyst at extreme pressure (442 bars) showed much better performances, i.e., a $CO₂$ conversion of 84.7%, a methanol selectivity 93.1% and a productivity of 2.18 $g_{\text{MeOH}} g_{\text{cat}}^{-1} h^{-1}$,³⁰⁰ highlighting the strong positive effect of the pressure on the thermodynamics and kinetics of the reaction. Open Access Article. Published on 30 September 2021. Downloaded on 7/31/2024 11:14:13 AM. This article is licensed under a [Creative Commons Attribution 3.0 Unported Licence.](http://creativecommons.org/licenses/by/3.0/) **[View Article Online](https://doi.org/10.1039/d1cy00922b)**

Three main pathways³⁰¹ have been proposed for $CO₂$ hydrogenation to methanol (Fig. 6), with a mechanism slightly different from the one represented in Fig. 2. In the formate $(HCOO^*)$ mechanism, 259,302,303 CO_2^* is hydrogenated to HCOO*, H_2COO^* (or HCOOH*), and to H_2COOH^* . Then, an OH* is removed, yielding H_2CO^* , which is hydrogenated to H_3CO^* and CH₃OH. In the RWGS mechanism, CO^* is formed from CO^{*}₂ through a COOH^{*} intermediate, then CO^{*} is hydrogenated to HCO*, H_2CO^* , H_3CO^* , and CH_3OH . In the hydroxycarbonyl mechanism, COH* is formed through a $\rm C(OH)_2^*$ intermediate, and then it is hydrogenated to $\rm HCOH^*,$ $H₂CO[*]$, $H₃CO[*]$, and CH₃OH.

Regarding the Cu/ZnO system, many hypotheses on the nature of the active sites were proposed.^{259,304,305} Fujita et al^{306} investigated the system with diffuse reflectance FT-IR spectroscopy and temperature-programmed desorption, showing that two types of formate species and zinc methoxide – $\text{Zn}(\text{CH}_3\text{O})_2$ – form during the reaction. Zinc methoxide was readily hydrolyzed to methanol, whereas H_2O formed through RWGS was suggested to be involved in the hydrolysis of zinc methoxide. In a recent communication, Muhler and co-workers³⁰⁷ investigated $CO₂$ hydrogenation to methanol on $Cu/ZnO/Al_2O_3$ with a surface-sensitive *operando* method using a high-pressure pulse experiment (HPPE) and proposed a mechanism for long-term catalyst deactivation, as illustrated in Fig. 7. In the beginning, reduced ZnO_x species migrate onto the metallic Cu^{0} nanoparticles and form Cu^{0} - Zn^0 alloys.³⁰⁵ Then, under CO_2 hydrogenation, different oxygen-containing adsorbates form, which partially oxidize Zn^0 to Zn^{δ^+} at the defective Cu⁰ site.²⁵⁹ The subsequent migration of Zn species leads to a graphitic-like ZnO_x layer on Cu⁰ surfaces,³⁰⁴ which ultimately turns into a stable and crystalline layer of $ZnO₃₀₄$ covering the Cu⁰ surface completely or partially.²⁶⁹ During the process, the highly active Cu⁰-Zn^{δ +} sites were found embedded in a constantly changing matrix provided by the $Cu/ZnO/Al_2O_3$ catalyst.

The reaction mechanism and RDS for methanol production over Cu are still under debate.³⁰⁸⁻³¹² Bowker et al.³¹⁰ suggested the hydrogenation of H_2CO^* to H_3CO^* as the rate-limiting step. Other authors $308,309$ reported instead the hydrogenation of HCOO* to H_2 COO* as the RDS over Cu(111). Zhao et al.³¹¹ showed that the HCOO* path is kinetically unfavorable compared to the COOH* route, especially in the presence of water. The isotope labeling experiment by Chinchen et al^{313} suggested that CO may not be an essential intermediate for methanol formation from $CO₂$. Mavrikakis and co-workers³¹² produced a microkinetic model based on DFT calculations which describes WGS and methanol synthesis from CO and $CO₂$ on Cu(111) and highlighted the role of HCOOH* as a reaction intermediate. They showed different sequences of intermediates in methanol production from CO (HCO*, CH_2O^* , and CH_3O^*) and CO₂ (HCOO*, HCOOH*, CH₃O^{*}, CH₂O*, CH₃O*). They

Fig. 6 Proposed reaction paths³⁰¹ of methanol synthesis via CO₂ hydrogenation over Cu-based catalysts.

Fig. 7 Long-term methanol production over the industrial Cu/ZnO/Al₂O₃ catalyst at 210 °C and 60 bar, under different controlled conditions. Black points refer to the recorded degrees of conversion of the reaction; the dashed red line describes the intra- and extrapolation of the experimental data. Illustrations from right to left: Cu^o–Zn^o surface alloy, Zn^{۶+} species at the defective Cu^o surface, and graphitic-like ZnO_x layer on Cu⁰. ZnO layer on Cu⁰ and ZnO on the top layer of Cu⁰. Reproduced with permission from ref. 307.

show that methanol synthesis rates are limited by methoxy $(CH₃O[*])$ formation in CO-rich environments and by $CH₃O[*]$ hydrogenation in CO₂-rich feeds. Higham et al.³¹⁴ have concluded in their DFT studies that Cu(110) and Cu(100) are more active facets for $CO₂$ dissociation and hydrogenation than the more abundant Cu(111) surface. Moreover, they showed that the synthesis of methanol on those Cu surfaces can follow also reaction paths with COOH* as an intermediate. Eventually, some experimental observations suggest that the formate mechanism should not be the preferred one, because (i) direct hydrogenation of formate on the Cu surface did not result in methanol in the absence of water;³⁰⁹ (ii) the experimentally observed formate (ii) the experimentally observed formate hydrogenation kinetics was inconsistent with that of methanol formation,³⁰⁸ and (iii) during methanol synthesis, formaldehyde, easily produced from H_2CO^* , has not been detected as a side product.^{315,316} Therefore, further theoretical studies, especially on the study of the active sites at the catalyst–support interface, are required.

Recent experimental studies demonstrated high performances of In_2O_3 catalysts for methanol synthesis from CO_2 .^{283–287} Martin et al.²⁸⁷ produced an In₂O₃/ZrO₂ catalyst showing 100% methanol selectivity at 200–300 °C and 1–5 MPa and high stability (1000 h on stream). The excellent selectivity of the catalyst was attributed to the formation of oxygen vacancies, promoted by both the $ZrO₂$ support and a co-feeding of CO. The group of Nørskov 317 investigated with DFT the methanol synthesis on $In_2O_3(111)$ and $In_2O_3(110)$. They produced a theoretical volcano plot illustrating a clear relationship between the number of reduced surface In layers and the catalytic activity of $In_2O_3(111)$. Moreover, they explained the positive effect on the catalytic activity of the $ZrO₂$ support, which influences the number of reduced In layers.

Following these findings, Zhou et $al.^{318}$ investigated with DFT analyses the reaction mechanism on $In_2O_3(111)$ and In₂O₃(110). They reported that CO production from CO₂ via both redox and COOH* routes is kinetically slower than methanol formation under typical steady-state conditions, in agreement with the experimental observations showing high methanol selectivity of In_2O_3 . They reported a formate mechanism of methanol synthesis in which H_2COO^* is produced from HCOO* and then dissociates to H_2CO^* and O*. The O* fills the oxygen vacancy site of In_2O_3 , and H_2CO^* is then hydrogenated to H_3CO^* and CH₃OH. Their calculated RDS is the homolytic H_2 dissociation and suggested that the reaction rate can be enhanced by introducing transition metal dopants which speed up H_2 dissociation. Dang et $al.^{319}$ investigated with DFT the cubic and hexagonal surfaces of In_2O_3 , showing that the hexagonal $In_2O_3(104)$ shows far superior catalytic performance. Moreover, they synthesized a novel hexagonal In_2O_3 nanomaterial that exhibits very high activity, methanol selectivity, and catalytic stability. On In_2O_3 , the formate mechanism is suggested as the most probable pathway, entailing cyclic creation and annihilation of oxygen vacancy active sites, and involving the reaction intermediates HCOO*, H_2COO^* , H_2CO^* , and H_3CO^* .³¹⁸

A major shortcoming of In_2O_3 catalysts is the long-term stability. To investigate morphological changes of the In_2O_3 catalyst during $CO₂$ hydrogenation to $CH₃OH$, Tsoukalou et al.²⁸⁵ performed combined time-resolved *operando* XAS– XRD and in situ TEM experiments. Their results show the reduction of In_2O_3 during the reaction by the formation of oxygen vacancy sites (In₂O_{3−x}), followed by the amorphization of In₂O₃ nanoparticles into a dynamic mixture of In⁰/In₂O_{3-x}, in which crystalline and amorphous phases coexist and continuously interconvert. The formation of metallic In^0 was reported to cause the deactivation of the catalyst.

3. Carbon formation and design for coke-tolerant catalysts

Catalyst deactivation due to carbon formation is one of the critical technological problems for $CO₂$ conversion processes.66,223 It is an inevitable process that can lead to a temporary or permanent catalyst deactivation via pore blockage, $320,321$ metal particle encapsulation, 322 or breakage of the catalyst pellets. 217 In the processes reviewed in this work, carbon is primarily produced by CO disproportionation $(2CO \rightarrow C^* + CO_2)$ and CH₄ dehydrogenation $(CH_4 \rightarrow C^* +$ $2H₂$). The latter reaction is favored at high temperature, while CO disproportionation is exothermic and thus thermodynamically favored at a temperature lower than 500 $^{\circ}C$

The carbon formed at the catalyst surface can assume various forms depending on the operating conditions, $323-325$ each form exhibiting unique features and different reactivities.^{244,326}

As shown in Fig. 8, CO and methane dissociate on the metal surface to form a highly reactive carbon species, C_{α} (probably an adsorbed atomic carbon), which can be gasified (to CH₄) or turned into the less reactive C_β and assume the form of polymeric carbon films or filaments.³²⁷ On exposure to high temperature ($T > 500-550$ °C), amorphous carbon

$$
CH_4(g) \longrightarrow C_{\alpha}(a) + 4H(a)
$$

\n
$$
CO(g) \longrightarrow C_{\alpha}(a) + O(a)
$$

\n
$$
\longrightarrow C \text{ in Ni} \longrightarrow C_{v}
$$

\n
$$
C_{\alpha}(a) \longrightarrow Ni_3C(s)
$$

\n
$$
\longrightarrow C_{\beta}(s) \longrightarrow C_{c}(s)
$$

\n
$$
\longrightarrow CH_4(g)
$$

Fig. 8 Various forms of carbon³²⁷ generated from CO over the Ni surface. (a), (g), and (s) refer to adsorbed, gaseous, and solid states, respectively.

 (C_{β}) is transformed into an even less reactive graphitic form (C_c) .³²⁷ Some of these carbon structures such as polymeric (C_{β}) and graphitic (C_c) films are responsible for deactivation due to encapsulation of the metal particles at the catalyst surface.³²⁸ Meanwhile, other forms such as filamentous carbon, generally do not deactivate metal surfaces but may plug catalyst pores and break up catalyst pellets.³²⁸ The growth of such carbon species depends on the possibility and the ease of the carbon C_{α} to dissolve through the metal particles.³²⁹ The dissolved carbon can diffuse through the metallic crystallite to nucleate and precipitate at the rear of the particles.244 This process leads to the formation of carbon whiskers, which lift the crystallite from the support surface and eventually result in the fragmentation of the catalyst.³²⁸ The driving force for intra-particle carbon diffusion and whisker growth is a gradient in carbon activity $(i.e.,$ concentration) across the metal particle. 244 Noble metals, except for palladium at 650 °C, do not form this carbon structure; the structure of the carbon formed on noble metals is difficult to distinguish from the catalyst structure, with few atomic layers of carbon covering almost completely the surface.³³⁰ Leung et $al.^{331}$ proposed that carbon formation rates and morphologies on Ni (i.e., filamentous or encapsulating) are solely determined by the pressure ratio $P_{\text{CH}_4}P_{\text{CO}}/P_{\text{CO}_2}$, which sets the thermodynamic carbon activity at the metal surface. Low values of this ratio lead to the formation of carbon filaments with a rate proportional to the ratio itself. Meanwhile, high values of carbon activity lead to the simultaneous nucleation of multiple carbon patches, with the consequent formation of carbon adlayers that brings about the encapsulation of Ni nanoparticles. In this sense, carbon formation rates decrease with decreasing metal particle size because of the lower stability and concomitant increase in activity of the smaller diameter carbon filaments formed on smaller metal nanoparticles. This phenomenon was reported also by other authors.^{332,333} Catalysis Science & Technology

A major shownloade of the solely as the solely constrained of the solely constrained on 2021. Solely solely are different and the solely constrained on a september 2021. Solely the set of t

> Under common industrial operative conditions ($T > 800$ $°C$), CH₄ decomposition is the main cause of carbon formation during DRM.³³³ For a given $CO₂/CH₄$ ratio, the temperature below which carbon deposits are formed decreases as the pressure decreases, while at constant pressure, this temperature limit increases as the $CO₂/CH₄$ ratio decreases.^{334,335} Thus, working with an excess of $CO₂$ in the feed may reduce carbon formation at lower temperatures. With stoichiometric feeds, a temperature higher than 800 °C should suppress carbon deposits where there is thermodynamic potential. 224 Catalyst deactivation due to carbon formation was observed during RWGS only when the reaction is conducted at low temperatures. Goguet et al , 336 observed a slow but continued catalyst deactivation due to carbon formation over 2% Pt/CeO₂ under RWGS conditions at 300 °C mainly due to CO disproportionation. Witte et al .³³⁷ experienced a loss in activity of a Ni catalyst during an 1100 h test at 350 °C under $CO₂$ methanation conditions. They proved the presence of carbon deposits through TPO with oxygen conducted over the spent Ni-based catalyst and

suggested the addition of steam into the reactor feed to prevent coking. Carbon deposits were also proved to form under the same conditions over noble metals catalysts by Solymosi et al.^{171,338,339}

Once formed, carbon may be removed from the catalyst surface to restore the initial activity. The alternatives are gasification with H_2 or H_2O or controlled oxidation with oxygen or oxygen-containing compounds (e.g., CO_2 itself).³⁴¹ Gasification with H_2O and H_2 occurs at significant rates from 500 to 700 °C once the encapsulated material has been removed, making the metallic particles available for the catalyzed reaction.³⁴² Moreover, the gasification of carbon with water was found to be faster than the one with hydrogen.³⁴² Indeed, the removal of carbonaceous deposits with H_2 , like the one with CO_2 , involves dissociative adsorption and a surface reaction with carbon. In this sense, it has been successfully demonstrated that the addition of different promoters such as alkali and alkaline-earth metals enhances the gasification of carbon species and increases the stability with time. These elements enhance the adsorption and dissociation of water and $CO₂$, increase the rate of gasification by H_2 and lower the carbon solubility in the active metal. ZrO_2 , commonly used as a metal support in heterogeneous catalysts, can be used as an additive to favor $CO₂$ activated adsorption, thus promoting higher levels of activity for the DRM reaction and the gasification of intermediate precursors in the carbon generation. 340 In particular, the combination of Al_2O_3 and ZrO_2 yields a reduction of catalyst deactivation by coking (Fig. 9). Although oxygen is the most effective in removing carbon deposits, a loss of activity following the regeneration process has been observed due to the oxidation of the active phase and to the loss of metallic atoms.³²⁷

For industrial applications, it is important to significantly improve the stability of the catalyst and make it resistant to coke. In this view, both active phase and support optimization is needed. Particle size, support defects, particle composition, and temperature-induced aggregation are the principal causes of catalyst instability. Precious metals (e.g.,

Ru, Rh) exhibit superior activity but are limited and expensive, and thus R&D efforts have been shifted towards abundant and active metals like Ni.^{92,94,96,222,343,344} To increase the catalyst performance while retaining its stability and resistance to coke formation, several approaches such as carbon gasification^{221,345-347} through introducing redox or basic materials, alloying active metals (e.g., Ni) with other metals,228,348–³⁵¹ and enhancing the thermal stability of active metal particles by strong interaction with the support or confinement inside stable structures $352-355$ have been attempted. In order to reduce coke formation and improve catalyst stability/activity, numerous strategies involving modification in the catalyst surface composition and metal– support interaction have been attempted.^{219,220,222,356-368} To develop a coke-resistant catalyst, approaches based on selective blockage of the defect sites of the active metal $(e.g.,$ Ni) nanoparticles by the use of inert elements such as $S₁$ ³³⁰, Sn,³⁶⁹ Au,³⁷⁰ and K (ref. 234 and 371) were attempted. Atoms of these elements are supposed to be favorably localized on the defect sites of the Ni surface. For instance, Juan-Juan et al^{371} have summarized the role of K in improving the stability of Ni metal with the following assumptions: (i) introduction of a small portion of K can increase the reducibility of Ni species as it enhances the interaction of NiO with the alumina support; (ii) K migrates from the support to the Ni metal surface and neutralizes a portion of active sites; (iii) coke formed during the reaction gets gasified by K without any change in its structure; (iv) K has no role in the modification of particle size or the structure of the catalyst. In an analogous study, elements such as K, S, and Au have shown improved catalytic activity by selectively blocking the active sites of the Ni stepped facet such as Ni $(211),$ ³³² which are responsible for coke formation.³⁷² Similarly, Chen et al^{373} observed a promotional role of a B-based catalyst with improved coking resistance during the experiment for partial oxidation of methane (POM). Moreover, boron was suggested for effectively blocking the subsurface sites and avoiding carbon diffusion into the bulk, which compels carbon atoms to remain on the surface and **Mini review**

Surface the distribution depends on stress are calor of top many constants, and this BaD. This case are compatible in

the compatible in the compatible in the compatibility of the compatibility of the stres

Fig. 9 (a) Catalyst deactivation in terms of the CH₄ activity coefficient (ratio between the CH₄ consumption rate and the initial consumption rate) during DRM over Ni-αAl₂O₃ (NiA), Ni-ZrO₂ (NiZ), and Ni-ZrO₂-Al₂O₃ (NiAZ) catalysts at 700 °C. (b) TEM image of the Ni-αAl₂O₃ catalyst after DRM deactivation at 700 °C. (c) TEM image of the Ni-ZrO₂-Al₂O₃ catalyst after the DRM deactivation test at 700 °C. Adapted with permission from ref. 340.

react.^{374,375} Most recently, Song et al.²¹⁸ developed a new technique for the preparation of Ni–Mo/MgO catalysts, wherein Mo doped Ni nano-crystallites move towards the edges of the MgO support, unite, and then stabilize at the step edges. Their catalyst exhibited high conversion and strong catalyst stability (850 hours) under DRM reaction conditions with anti-sintering and anti-coke properties.

4. Kinetic models

The data obtained from the reaction kinetics are applied in designing reactors, studying reaction mechanisms, and elucidating reaction–property relationships of catalyst materials. In general, the power law model is the simplest and can provide a satisfactory description of the process through a rough estimation of the required parameters.239,376 However, it does not account for the underlying reaction mechanisms. The Eley–Rideal (ER) model³⁷⁷ assumes that one reactant (e.g., CH₄ or CO₂ in DRM) adsorbs onto the catalyst surface, whereas the other one reacts from the gas phase. Then, the Langmuir Hinshelwood–Hougen–Watson (LHHW) model is the result of a reaction mechanism that implies (i) the adsorption of the reactants on the active sites, (ii) their reaction at the catalyst surface, and (iii) the desorption of the reaction products, and it is based on the hypothesis that there is one (or more) reaction step slow enough to be rate-limiting (*i.e.*, the RDS), while the other ones are pseudoequilibrated. More detailed modeling comes from microkinetic modeling (MKM), a powerful tool for the description of catalytic processes with an atomistic level of detail. A microkinetic model is a detailed kinetic model in which the single elementary steps of the reaction mechanism are characterized by their thermodynamic (e.g., binding energies of reaction intermediates) and kinetic properties (e.g., activation energies). The integration in time of a microkinetic model allows for the rational understanding of the reaction mechanisms occurring at the catalyst surfaces, the identification of preferred reaction paths, and corresponding active sites and RDSs. A great breakthrough was achieved with the possibility to combine DFT calculation with MKM.^{230,378-380} This powerful combination can elucidate different aspects of the reaction mechanism and the reaction kinetics without a priori assumptions compared with the traditional experimental kinetic methods.372,381

4.1 Reverse water-gas shift (RWGS)

The kinetics of the RWGS reaction has been widely investigated in the literature as a stand-alone process for the conversion of $CO₂$ to syngas^{151,382-384} and as an inevitable side reaction in reforming processes.^{144,160,385-389} The RWGS kinetics over $CuO/ZnO/Al₂O₃$ was studied by the use of both differential and integral plug flow reactors by Ginés et $al.^{390}$ A good agreement between the experimental and calculated data was obtained under different conditions by considering

a Langmuir–Hinshelwood redox mechanism on Cu. However, in agreement with other authors who studied Cu-based catalysts, they noticed that the activity and the order of reaction of $CO₂$ and $H₂$ depend strongly on the reactants' partial pressures. This is due to a recontraction process that affected the catalyst surface caused by H_2 -rich working conditions, as proposed by Campbell and $Ernst³⁹¹$ and then confirmed by many studies over Cu single-atom catalysts. Chen et al^{392} performed a kinetic study of the RWGS reaction over silica-supported Cu-nanoparticles and proposed a Langmuir–Hinshelwood model starting from a formate mechanism. Kim et al., 248 on the other hand, derived two different reaction rates for the conversion of $CO₂$ to $CO₂$ according to associative and redox mechanisms. The initial reaction rate of the two mechanisms was consistent with the experimental data under low and high H_2 partial pressures. However, only the redox-derived rate was able to fit the experimental data under moderate hydrogen partial pressures. Wolf et $al.^{393}$ used a commercial Ni catalyst to study the RWGS reaction and determine its intrinsic kinetics to design an industrial plant. The intrinsic kinetics was examined at low residence time in a differential packed bed reactor and then modified to consider pore and external diffusion limitations. Then, the kinetic model was used in the simulation of a 1D fixed-bed reactor and validated with experimental data. Several authors used microkinetic models already developed for other processes (*i.e.* steam reforming, $CO₂$ methanation, and $CO₂$ hydrogenation to methanol) to gain new insights into the RWGS reaction system.376,394 A detailed multi-step heterogeneous reaction mechanism developed for SRM, partial and total oxidation of methane, and RWGS, for Nibased catalysts was used by Benzinger et $al.^{395}$ to interpret the experimental data obtained from the RWGS reaction in a monolith reactor. The microkinetic model, which included 42 reactions, 7 gas-phase species, and 12 surface species, was adjusted for thermodynamic consistency in the temperature range used for the study and validated with data derived from isothermal experiments in a fixed bed reactor over a commercial $Ni/Al₂O₃$ catalyst. Maestri et al.^{161,162,237} refined their first microkinetic model on Rh guided by the DFT-based analysis of the WGS/RWGS pathways and based on a comprehensive set of isothermal experimental data. Their semiempirical microkinetic model refined with DFT calculations was used to quantitatively describe the roles of WGS and its reverse in catalytic partial oxidation of methane on a Rh-based catalyst and it was extensively validated with experiments. Catalysis Science & Technology

Young ceta¹²³ of the presentation of Ni-MoMago cultures.

Volume in the resultion of Ni-MoMago cultures, the methods of Ni-MoMago culture and

set of the presentation of Ni-MoMago culture

> The structure-dependent microkinetic model of Cheula and Maestri¹¹² describing WGS and RWGS on Rh/Al_2O_3 represents a novel methodology for the simulation of structure and activity of catalyst materials, allowing for the identification of the "nature" and "identity" of the active site in a self-consistent manner. In their model, the morphology of heterogeneous catalyst nanoparticles – that represents the "nature" of the active sites - is calculated using ab initio

thermodynamics and Wulff–Kaishew construction methods. The reaction rates – that determine the "identity" of the dominant active sites – are calculated by integrating a DFT-based microkinetic model describing the catalytic activity of the crystal facets exposed by the catalyst under reaction conditions. Their microkinetic model well reproduced experimental kinetic data and reaction orders and allowed for a concomitant description of the nature of the catalyst material under reaction conditions and of its catalytic consequences in terms of reactivity.

4.2 $CO₂$ methanation

 $CO₂$ methanation is thermodynamically favorable at low temperatures. However, it is limited by kinetics that strongly depends on the selected catalyst. Over the past few years, many kinetic expressions of $CO₂$ methanation over different catalysts have been published.^{394,396-401} Some of them were based on simple power law models, $402,403$ while others followed more complex kinetic models.⁴⁰⁴⁻⁴⁰⁷ Most of these models are empirical and do not take into account the approach to equilibrium. Moreover, their parameters were estimated at low $CO₂$ conversions and atmospheric pressure, thus far from the conditions of industrial interest. One of the first detailed mechanistic models was proposed by Weatherbee and Bartholomew⁴⁰⁸ for the kinetics of a 3% Ni/SiO₂ catalyst. However, in their experiments, the gas composition was highly diluted and far away from the one required for direct injection in the gas grid without further purification or separation steps. An important breakthrough was achieved by Kai et al .⁴⁰⁹ They performed kinetic studies at atmospheric pressure over a La_2O_3 promoted Ni on alumina catalyst by using both a differential and an integral reactor. With an integral reactor operating at high $CO₂$ conversion, they develop a Langmuir–Hinshelwood rate equation based on the mechanism proposed by Weatherbee and Bartholomew,408 resulting in a model able to describe in detail the influence of the reaction's products on the kinetics. Lunde and Kester¹⁶⁵ proposed an empirical model over a Ru-based catalyst potentially able to predict the catalyst activity from differential to thermodynamically limited $CO₂$ conversion. The original expression was derived using a fitting procedure made by the authors to data collected under differential conditions at atmospheric pressure. The same model had been used by other authors to fit experimental data collected in a larger range of $CO₂$ conversions and higher pressures by modifying the kinetic parameters. Falbo et $al.^{410}$ derived a novel kinetic rate equation from the one proposed by Lunde and Kester to account for the negative dependence on the partial pressure of water, improving the model capability to simulate the catalyst performance in a wide range of process conditions. The kinetics of $CO₂$ methanation over a 10% Ru/γ -Al₂O₃ catalyst were investigated by Duyar et $al.^{411}$ using a differential Miniteview Catalysis Science & Technology

methods. The line constraints are characterized on 2022 are characterized on 2021. The line constraint with an Expedibility and the common state are constraint with the material

reactor at atmospheric pressure to obtain an empirical rate equation consistent with an Eley–Rideal mechanism where gas phase H_2 reacts with surface species resulting from the adsorption of $CO₂$. This implies that excess H_2 would be required to boost the reaction rate. Avanesian et $al.^{412}$ developed a mean-field microkinetic model for the Sabatier reaction based on DFT calculation on Ru(0001) which consisted of 18 elementary steps and was able to successfully predict the experimental data at different temperatures and reactants' partial pressures. However, this model was not able to predict the thermodynamic equilibrium conversion at different temperatures. Raghu and Kaisare413 proposed a mean-field microkinetic model for CO2 methanation at atmospheric pressure over a Rubased catalyst by using a bottom-up modeling strategy. According to the authors, the model provided a reasonably good prediction of $CO₂$ conversion within the temperature range of interest for the methanation reaction as well as under equilibrium conditions.

4.3 CO2 hydrogenation to methanol

The kinetic modeling of methanol synthesis from $CO₂/H₂$ mixtures using industrial Cu-based catalysts had been widely studied in the literature.^{268,311,414-418} Although it is generally accepted that methanol is primarily formed via $CO₂$ hydrogenation (formate route), the role of the active sites and the effect of different catalyst components are still under debate. A variety of global kinetic models were published in the past years.317,419–⁴²² Power laws and LHHW models were widely used to describe methanol synthesis, first from CO and then from CO_2 as the main carbon source. Graaf et al.⁴²³ and Vanden Bussche and Froment^{424,425} were among the first authors to propose an LHHW kinetic model for $CO₂$ hydrogenation to methanol over a commercial $Cu/ZnO/Al₂O₃$ catalyst. The main difference between the two models was the active sites involved in the activation of reactants. According to Vanden Bussche and Froment, both H_2 and CO_2 adsorb on the same type of active site (Cu). The first microkinetic model was proposed by Askgaard et $al.^{426}$ from results obtained in surface science studies over a Cu(100) single-crystal catalyst and then successfully extrapolated for industrial conditions. Ovesen et $al.^{427}$ proposed a detailed microkinetic model for methanol synthesis based on the experimental evidence collected by in situ EXAFS. This "dynamic" model was able to describe the change in particle morphology with the change in reaction environment as well as the reaction rate over the three basal Cu surface planes of a Cu/ZnO catalyst, both crucial features to describe the kinetic data measured under industrial conditions. Grabow and Mavrikakis³¹² conducted an extensive set of periodic, self-consistent DFT calculations over the Cu(111) facet to fit a mean-field microkinetic model to published experimental methanol synthesis rate data under realistic conditions over a commercial ternary Cu catalyst. This model included novel

reaction intermediates which allowed for the formation of formic acid, formaldehyde, and methyl formate as byproducts. A statistical kinetic model was derived from firstprinciples density functional theory (DFT) calculations and kinetic Monte Carlo simulations by Tang et $al.^{121}$ over a Cu/ $ZrO₂$ catalyst. Despite the complexity of the reaction system, they were able to model the metal/oxide interface and demonstrate that methanol was produced through both RWGS and formate routes, assessing the contribution of each reaction channel in terms of the reaction rate. In agreement with Tang *et al.*, 121 Ye *et al.* 428 identified in the metal/oxide interface the most active site for $CO₂$ adsorption and hydrogenation. By combining DFT calculations and microkinetic modeling to study $CO₂$ to methanol conversion over a Pd_4/In_2O_3 model catalyst, they demonstrated the dynamical nature of the structure of the supported Pd_4 cluster, which transforms in response to the presence of OH in the reaction environment, modifying the main reaction pathway. Chiavassa et $al.^{429}$ modeled the synthesis of methanol from a $CO₂/H₂$ mixture on a $Ga₂O₃$ -Pd/SiO₂ catalyst by combining kinetic information with relevant spectroscopic FT-IR data. They proposed a detailed reaction scheme for the CO₂ hydrogenation bifunctional mechanism where reactants' activation occurred on two different active sites, serving as a basis for the development of an LHHW type kinetic model, able to predict the negative influence of CO due to the competitive adsorption with $H₂$ on Pd sites.

4.4 Dry reforming of methane (DRM)

Different kinetic mechanisms for the dry reforming reaction have been published in the last few years.^{224,430-435} Only a few reports are present in the literature employing the Eley– Rideal (ER) model for DRM on Ni-based catalysts.³⁷⁷ The Langmuir Hinshelwood–Hougen–Watson model (LHHW) has more extensive applications and reports in the literature.^{436,437} Mhadeshwar et al. and Maestri et al. developed a C_1 semiempirical microkinetic model for the conversion of $CH₄$ to syngas on a Rh-based catalyst applying a hierarchical multiscale approach and first-principles calculations.162,438 Both were able to quantitatively predict the behaviors of several C_1 reaction systems, including SR, DR, and CPO under different reaction conditions. Delgado et al.⁴³⁹ proposed a different multistep surface kinetic model on a Ni-based catalyst, consisting of 52 elementary steps with 14 surface and 6 gas-phase species. The mechanism was implemented into a 1D model of a fixed bed reactor that is able to describe the conversion of methane with oxygen, steam, and $CO₂$ as well as methanation, WGS, and carbon formation via the Boudouard reaction. Their model has been derived by comparison of numerical simulations with data derived from isothermal experiments in a packed bed reactor, using different inlet gas compositions and operating temperatures (up to 900 $^{\circ}$ C). Aparicio⁴⁴⁰ derived a microkinetic model for methane reforming over Ni catalysts with many parameters obtained either from the surface

science literature or from fitting the results of transient kinetic experiments. However, the model's predictions were not quantitative, as predicted rates can deviate from the experimental ones, but it could correctly predict activation energies, reaction orders, and the major trends for several reactions, such as steam and dry reforming, CO and $CO₂$ methanation, WGS and RWGS. Foppa et $al.^{225}$ presented an ab initio mechanistic study of DRM over the flat (111) surfaces of Ni, Pd, and Pt for the development of a microkinetic model made of 16 elementary steps. They provided new insights into intrinsic catalytic activity over the metallic surfaces and evaluated the interplay among all the competitive reactions that can occur under DRM experimental conditions (i.e., SRM, RWGS, methane cracking, and Boudouard reaction). Based on experiments conducted in an oscillating microbalance reactor, Chen et al^{441} were able to study the catalyst deactivation due to carbon formation during DRM and proposed an advanced microkinetic model for methane reforming, carbon formation, and deactivation over a Ni-based catalyst. A good agreement with the experimental kinetic data during dry reforming over fresh catalyst and with time on stream was obtained. However, the quantitative description of the deactivation process that affects reforming catalysts due to carbon formation is still an issue. The formulation of a structure-dependent microkinetic model able to simulate carbon formation under DRM conditions and its effect on the overall catalyst activity represents an intriguing challenge for heterogeneous catalysis and scientific research. Catalysis Science & Technology

YMin reviews Anti-Solution and Equilibrigation and Catalysis and September 2021. Downloads point and the september 2021. The most are the september 2021. Downloads are the september 2021. T

5. Reactor technologies

In CO₂ conversion technologies, the design of chemical reactors is very important for its key involvement in controlling both the thermodynamic and kinetic aspects of the processes. Significant efforts have been undertaken to enhance the catalytic activity on various reactor systems starting from fixed to fluidized beds and then to multistage reactors.57,442

The reactions considered in this work are both endothermic (e.g., DRM, RWGS) and exothermic (e.g., $CO₂$ methanation, $CO₂$ hydrogenation to methanol). Thus, the reactor design faces different problems depending on the reaction considered but presents similarities when dealing with heat management. Exothermic reactions present heat dissipation and possible hotspot problems. The classic design of fixed bed reactors utilized in industry for several years, such as multistage adiabatic reactors and multitubular fixed bed reactors, presents a convenient mechanical design, low maintenance cost, high productivity per unit of volume, and limited residence time distribution of reactants and products in the reactor, in addition to the secular knowhow in the construction and management. Nevertheless, such reactors present large axial and radial temperature gradients with possible hotspots, which are important issues.⁴⁴³ Recently, multi-tubular shell cooled reactors typically used in

industry have been studied for the methanation reaction, with interesting results concerning the optimization of the operating conditions.⁴⁴⁴ The interest in structured reactors is growing due to good heat management performances, high surface-to-volume ratio, and more efficient use of the catalyst. The use of microchannel reactors provides an interesting solution for the management of heat transfer and also for improved gas/solid contact compared to traditional reactor design.445,446 Packed bed foams show a promising role in intensifying processes and improve the heat management of strongly exothermic/endothermic reactions, with fundamental studies that are paving the way towards the improvement in the design of such reactors.^{447,448} The use of highly conductive $Ru/Ce_x/Ni$ foams has been investigated for the methanation reaction, demonstrating promise for the management of highly exothermic catalytic reactions.⁴⁴⁹ Depending on the materials used for the structure and/or for the catalysts, different techniques exist and should be approached to identify the best one, with possible clogging and material coating feasibility that must be taken into account.450 Fluidized bed reactors are another technology already used in some industrial processes, due to the almost perfect heat management, with small or even negligible temperature gradients, thanks to the fluidization of the bed. Nevertheless, such technology suffers from the intrinsic complexity of the management of fluidization and of the broad residence time distribution. In this view, several efforts are made to increase the know-how of such technology Mini review Catalysis Science & Technology

value and interesting case of the contribution of the design in control of the design in control of the control of th

employing advanced CFD simulations 451 and improve their design in $CO₂$ hydrogenation processes.^{452,453} Recently, plasma reactors have attracted attention in the hydrogenation of $CO₂$, mainly because of their capability to run the reaction at low temperatures. 187 This technology can involve electrically-based plasma 454 or the addition of plasma in the gas-phase.455,456

Endothermic reactions present heat supply problems, which can result in the formation of cold spots in the reactors and decrease the process performance. Such problems are usually addressed by technologies similar to the ones for exothermic reactions, where the heat is usually supplied by boilers. Recently, new solutions to provide heat to the chemical reactions have been proposed, including the use of microwaves⁴⁵⁷ and electrified reactors.^{458,459} The electrification of reactors is a very promising technology, and it has been investigated both for the steam and dry reforming of methane, $458,459$ showing good energetic efficiency, increasing catalyst utilization, and reducing the thermal gradient in the reactor. Steady and consistent power supply, thermo-mechanical and physical properties of materials, and energy efficiency represent the main challenges when considering electrified reactors.⁴⁵⁸⁻⁴⁶⁰

Besides heat management, thermodynamics is an intrinsic limit of some of these processes. To increase thermodynamic equilibrium yields, suitable pressure and temperature should be chosen, but convenient designs help to achieve good yields with less severe operating conditions (e.g., lower

Fig. 10 Possible solutions to suppress thermodynamic equilibrium limitations in CO₂ conversion reactions. (a) CAMERE process (carbon dioxide hydrogenation to form methanol via a reverse-water-gas-shift reaction). Reproduced with permission from ref. 88. (b) Membrane reactor. (c) Sorption enhanced reactor. Reproduced with permission from ref. 461.

pressure). Product removal is an increasingly feasible opportunity with several solutions proposed. The separation of CO production and subsequent methanol production has proven to be a feasible technology, with the intermediate separation of water with a separating unit (Fig. 10.a). $88,462$ Selective membranes^{187,463} are a promising technology to separate water to push the yield beyond thermodynamic limitations (Fig. 10.b). Polymeric membranes can be employed but suffer from problems at high temperatures and pressures.464 Zeolite membranes seem to offer a valid alternative, overcoming such problems, being stable at relatively high pressures and temperatures, and showing a relevant yield increase compared to traditional reactors.⁴⁶⁵⁻⁴⁶⁷ Stable and efficient materials for membranes at process temperatures, pressures, and compositions represent a challenge for membrane reactors.⁵⁸ Moreover, separating water is challenging due to the similar kinetic diameters of H₂O, CH₃OH, CO₂, and H₂ (0.30 nm, 0.38 nm, 0.33 nm, and 0.29 nm, respectively).⁴⁶⁸ Sorption enhanced processes (Fig. 10.c) are another breakthrough technology, allowing thermodynamic limitations to be overcome by the use of an adsorbent material that removes water from the reaction environment, and have applications either in methanol production or in higher alcohols production.^{469,470} The adsorption of water simulating a complete process proved to increase the methanol productivity by 15% under practically relevant operating conditions.⁴⁷¹ Recently, sorption enhanced methanol production from $CO₂$ hydrogenation has provided outlet methanol concentrations up to 290% of the one without the sorption enhancement effect at 60 bar. 472 To improve methanol production from carbon dioxide at low temperatures, magnetic field-assisted reactors are being investigated, showing positive effects on $CO₂$ conversion and selectivity towards methanol.^{187,473} The presence of carbonproducing reactants and/or intermediates and/or products is another trivial challenge for some of these reactions (e.g., DRM) as mentioned above. Even if catalyst design is the key to overcome such a problem, the operating conditions must be properly chosen to find the optimum between yield and catalyst deactivation, to maximize the profitability of the process. Catalysis Science & Technology

Whili everywhenology

operating with the signalization of the category of the signalization of the category of the category of the signalization of the signalization of the signalization of

6. Summary and outlook

 $CO₂$ is an essential molecule for our life on Earth. It plays a crucial role in the carbon-cycle which is at the basis of the mechanism of storing solar energy in chemical bonds. Moreover, thanks to its green-house properties, it affects the thermoregulation of the Earth. Without the presence of $CO₂$ in the atmosphere, the average temperature of the planet would be considerably lower than the values required for life and the environment as we know them. The intensive use of fossil fuels made in the last two centuries has allowed a dramatic improvement in the quality of life thanks to the availability of enormous quantities of energy at high energy and power densities. On the flip side of the same coin, the

exploitation of the energy "trapped" in the chemical bonds of the fossil fuels has released the $CO₂$ originally used in the photosynthesis process to store the solar energy in the chemical bonds. As a result of these processes and together with the rapid growth of production of materials such as cement, iron, and steel $(CO₂)$ intensive processes), a rapid increase of the concentration of the $CO₂$ in the atmosphere from 300 pm (in the pre-industrial period) to values higher than 400 ppm has been observed. The IPCC demonstrated that this higher concentration of $CO₂$ can be explained with 95% confidence only by accounting for the anthropogenic activities of the last two centuries. As such, the increase of the temperature of the Earth with all the consequent effects on our life and the environment is directly linked with human activities.

Therefore, policymakers are taking action to achieve netzero $CO₂$ emissions. Solving the problem by simply eliminating the need for fossil fuels as an energy source is not straightforward since fossil resources are the basis of our current chemical and energy industry. Moreover, they are difficult to replace due to their huge energy densities. A promising concept is to replace the fossil feedstocks currently used in the chemical and energy industry with sustainably produced base chemicals and fuels by reducing $CO₂$ using renewable energy (e.g., H_2 from water electrolysis with electricity from wind or solar energy – "green hydrogen") for the production of commercially important fuels and chemicals by means of electrocatalysis, photocatalysis, or thermal catalysis routes. This would result in a carbonneutral technology of energy transformation and storage, since CO₂ consumption and production would occur at comparable characteristic times.

In this review, we have reported an in-depth survey of the state-of-the-art mechanistic and multiscale aspects of $CO₂$ conversion to C_1 products *via* thermo-catalysis. Though there are many chemicals in the domain of $CO₂$ activation, hydrogenation products such as CO (RWGS and dry reforming routes), methane (methanation reaction) and methanol are industrially and economically highly relevant.

Catalyst design requires in-depth understanding of the reaction mechanism and surface characterization techniques. However, due to the formation of multiple products and lack in development of effective in situ probing techniques for thermocatalytic CO₂ hydrogenation, elucidating the reaction mechanism and separation of product mixtures are difficult. Insights from different techniques have been reported, spanning from theoretical calculations to spectroscopy studies and kinetic investigations. We reviewed the main materials used to thermo-catalytically activate $CO₂$ (a very thermodynamically stable molecule) and the main conclusions and hypothesis on the activation mechanisms and elementary pathways. The systematic understanding of the reaction mechanism with key intermediate formation and identification of surface-active sites of the catalysts are of great help in establishing the $CO₂$ activation process and obtained desired conversion. A significant role of the

catalyst's shape was also reported. This finding could lead to rational design of catalysts and judicious plans of new nanocatalysts for potential use in carbon dioxide hydrogenation. Particular attention has been paid to catalyst deactivation due to coke formation that is a major technological and scientific challenge, requiring innovations in materials and process design to combat. Deactivation is mainly caused by filamentous carbon as it has high mechanical strength that leads to mechanical deformation of the catalyst and blocks metal active sites. We then reviewed the main kinetic schemes reported in the literature (both detailed microkinetic models based on first-principles calculations and rate equations): the main open area of progress for kinetic modeling in this context is to couple the description of the kinetic events with coke formation and its kinetic consequences. Design, innovations, and engineering of catalytic materials including reactors and process technologies are vital solutions, but such approaches are yet to be established for commercial success. Integrating reactor design and developing more effective and selective catalysts may solve scientific and technological challenges by reducing the activation barrier in an energy efficient process. Open Access Article. Published on 30 September 2021. Downloaded on 7/31/2024 11:14:13 AM. This article is licensed under a [Creative Commons Attribution 3.0 Unported Licence.](http://creativecommons.org/licenses/by/3.0/) **[View Article Online](https://doi.org/10.1039/d1cy00922b)**

Conflicts of interest

There are no conflicts to declare.

Acknowledgements

The authors acknowledge funding under the European Union's Horizon 2020 research and innovation program from the European Research Council, ERC (Grant agreement No. 677423/SHAPE: "Structure Dependent Microkinetic Modelling of Heterogeneous Catalytic Processes") and from the MSCA-IF (Grant agreement No. 846255/Biogas2Syngas: "Rational Design for Coke-resistant Dry Reforming Catalyst using Combined Theory and Operando Raman Experiments").

References

- 1 Statistical Review of World Energy, 2020.
- 2 International Energy Outlook 2013, 2013.
- 3 M. I. Hoffert, K. Caldeira, A. K. J. Jain, E. F. Haites, L. D. D. D. Harvey, S. D. Potter, S. H. Schlesinger, R. G. Watts, T. M. L. Wigley and D. J. Wuebbles, Nature, 1998, 395, 881–884.
- 4 Annual European Union greenhouse gas inventory 1990– 2018 and inventory report 2020 Submission to the UNFCCC Secretariat 27 May 2020.
- 5 J. A. Martens, A. Bogaerts, N. De Kimpe and P. A. Jacobs, ChemSusChem, 2017, 10, 1039–1055.
- 6 T. F. Stocker, D. Qin, G.-K. Plattner, M. M. B. Tignor, S. K. Allen, J. Boschung, A. Nauels, Y. Xia, V. Bex and P. M. Midgley, IPCC 2013. Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change, Cambridge University Press, 2014, DOI: 10.1017/ CBO9781107415324.
- 7 A. W. Kleij, M. North and A. Urakawa, ChemSusChem, 2017, 10, 1036–1038.
- 8 G. Pacchioni, W la CO2. Possiamo trasformare il piombo in oro?, Il Mulino, 2021.
- 9 U.S. Global Change Research Program, Third Climate Assessment, 2014.
- 10 S. A. Kulp and B. H. Strauss, Nat. Commun., 2019, 10, 4844.
- 11 D. J. Wuebbles, D. W. Fahey, K. A. Hibbard, D. J. Dokken, B. C. Stewart and T. K. Maycock, USGCRP, 2017: Climate Science Special Report: Fourth National Climate Assessment, Volume I, U.S. Global Change Research Program, Washington, DC, USA, DOI: 10.7930/J0J964J6.
- 12 C. McGlade and P. Ekins, Nature, 2015, 517, 187–190.
- 13 M. Höök and X. Tang, Energy Policy, 2013, 52, 797–809.
- 14 U. Riebesell, in Encyclopedia of Earth Sciences Series, 2016, vol. Part 2, pp. 541–542.
- 15 E. R. H. Moore, M. R. Smith, D. Humphries, R. Dubrow and S. S. Myers, Challenges, 2020, 11, 4.
- 16 P. Akhter, M. A. Farkhondehfal, S. Hernández, M. Hussain, A. Fina, G. Saracco, A. U. Khan and N. Russo, J. Environ. Chem. Eng., 2016, 4, 3934–3953.
- 17 A. R. Brandt, A. Millard-Ball, M. Ganser and S. M. Gorelick, Environ. Sci. Technol., 2013, 47, 8031–8041.
- 18 S. Perathoner, K. M. Van Geem, G. B. Marin and G. Centi, Chem. Commun., 2021, DOI: 10.1039/d1cc03154f.
- 19 J. K. Nørskov, B. Weckhuysen, G. Centi, S. R. ChorkendorffI, G. Marin, A. Grimaud, J. Rossmeisl, P. Strasser, M. Koper and B. Roldan, Energy X.
- 20 G. Centi and S. Perathoner, Catal. Today, 2009, 148, 191–205.
- 21 H. Y. Yang, B. L. Bao, J. Liu, Y. Qin, Y. R. Wang, K. Z. Su, J. C. Han and Y. Mu, Bioelectrochemistry, 2018, 119, 180–188.
- 22 S. K. M. R. Rittmann, A. H. Seifert and S. Bernacchi, Appl. Energy, 2018, 216, 751–760.
- 23 J. J. Leung, J. Warnan, K. H. Ly, N. Heidary, D. H. Nam, M. F. Kuehnel and E. Reisner, Nat. Catal., 2019, 2, 354–365.
- 24 D. Yang, H. Yu, T. He, S. Zuo, X. Liu, H. Yang, B. Ni, H. Li, L. Gu, D. Wang and X. Wang, Nat. Commun., 2019, 10, $1 - 10$.
- 25 J. Chen, J. Yin, X. Zheng, H. Ait Ahsaine, Y. Zhou, C. Dong, O. F. Mohammed, K. Takanabe and O. M. Bakr, ACS Energy Lett., 2019, 4, 1279–1286.
- 26 X. Deng, R. Li, S. Wu, L. Wang, J. Hu, J. Ma, W. Jiang, N. Zhang, X. Zheng, C. Gao, L. Wang, Q. Zhang, J. Zhu and Y. Xiong, J. Am. Chem. Soc., 2019, 141, 10924–10929.
- 27 H. Y. Kang, D. H. Nam, K. D. Yang, W. Joo, H. Kwak, H. H. Kim, S. H. Hong, K. T. Nam and Y. C. Joo, ACS Nano, 2018, 12, 8187–8196.
- 28 B. B. Cardias, M. G. de Morais and J. A. V. Costa, Bioresour. Technol., 2018, 267, 77–83.
- 29 M. Aresta and A. Dibenedetto, Dalton Trans., 2007, 2975–2992.
- 30 M. Aresta, A. Dibenedetto and E. Quaranta, J. Catal., 2016, 343, 2–45.

- 31 S. Zhang, Q. Fan, R. Xia and T. J. Meyer, Acc. Chem. Res., 2020, 53, 255–264.
- 32 A. Hasani, M. A. Teklagne, H. H. Do, S. H. Hong, Q. Van Le, S. H. Ahn and S. Y. Kim, Carbon Energy, 2020, 2, 158–175.
- 33 L. Fan, C. Xia, P. Zhu, Y. Lu and H. Wang, Nat. Commun., 2020, 11, 1–9.
- 34 M. Wang, K. Torbensen, D. Salvatore, S. Ren, D. Joulié, F. Dumoulin, D. Mendoza, B. Lassalle-Kaiser, U. Işci, C. P. Berlinguette and M. Robert, Nat. Commun., 2019, 10, 1-8.
- 35 M. D. Hossain, Y. Huang, T. H. Yu, W. A. Goddard and Z. Luo, Nat. Commun., 2020, 11, 1–14.
- 36 F. P. García de Arquer, C. T. Dinh, A. Ozden, J. Wicks, C. McCallum, A. R. Kirmani, D. H. Nam, C. Gabardo, A. Seifitokaldani, X. Wang, Y. C. Li, F. Li, J. Edwards, L. J. Richter, S. J. Thorpe, D. Sinton and E. H. Sargent, Science, 2020, 367, 661–666. Catalysis Science & Technology Www. Will review Access Articles. 2021. Although Commons Articles. 2021. Downloaded on 2021. Downloaded on 2021. Downloaded under a Creative Commons Articles. 2021. Although Commons Articles
	- 37 J. L. White, M. F. Baruch, J. E. Pander, Y. Hu, I. C. Fortmeyer, J. E. Park, T. Zhang, K. Liao, J. Gu, Y. Yan, T. W. Shaw, E. Abelev and A. B. Bocarsly, Chem. Rev., 2015, 115, 12888–12935.
	- 38 S. Cao, Y. Wang, B. Zhu, G. Xie, J. Yu and J. R. Gong, J. Mater. Chem. A, 2020, 8, 7671–7676.
	- 39 T. Baran, S. Wojtyła, A. Dibenedetto, M. Aresta and W. Macyk, ChemSusChem, 2016, 9, 2933–2938.
	- 40 A. Álvarez, M. Borges, J. J. Corral-Pérez, J. G. Olcina, L. Hu, D. Cornu, R. Huang, D. Stoian and A. Urakawa, ChemPhysChem, 2017, 18, 3135–3141.
	- 41 X. Dong, X. Liu, Y. Chen and M. Zhang, J. CO2 Util., 2018, 24, 64–72.
	- 42 W. Tu, M. Ghoussoub, C. V. Singh and Y. H. C. Chin, J. Am. Chem. Soc., 2017, 139, 6928–6945.
	- 43 D. L. Tomasko, H. Li, D. Liu, X. Han, M. J. Wingert, L. J. Lee and K. W. Koelling, Ind. Eng. Chem. Res., 2003, 42, 6431–6456.
	- 44 D. Roberts, These uses of CO2 could cut emissions—and make trillions of dollars.
	- 45 D. Y. C. Leung, G. Caramanna and M. M. Maroto-Valer, Renewable Sustainable Energy Rev., 2014, 39, 426–443.
	- 46 G. C. Nelson, Agric. Trade, Environ. Discov. Meas. Crit. Linkages, 2019, pp. 295–299.
	- 47 S. G. Wang, X. Y. Liao, J. Hu, D. B. Cao, Y. W. Li, J. Wang and H. Jiao, Surf. Sci., 2007, 601, 1271–1284.
	- 48 L. Wang, W. Chen, D. Zhang, Y. Du, R. Amal, S. Qiao, J. Wu and Z. Yin, Chem. Soc. Rev., 2019, 48, 5310–5349.
	- 49 R. W. Dorner, D. R. Hardy, F. W. Williams and H. D. Willauer, Energy Environ. Sci., 2010, 3, 884–890.
	- 50 K. Damen, M. Van Troost, A. Faaij and W. Turkenburg, Prog. Energy Combust. Sci., 2006, 32, 215–246.
	- 51 X. M. Liu, G. Q. Lu, Z. F. Yan and J. Beltramini, Ind. Eng. Chem. Res., 2003, 42, 6518–6530.
	- 52 J. A. Rodriguez, P. Liu, D. J. Stacchiola, S. D. Senanayake, M. G. White and J. G. Chen, ACS Catal., 2015, 5, 6696–6706.
	- 53 E. V. Kondratenko, G. Mul, J. Baltrusaitis, G. O. Larrazábal and J. Pérez-Ramírez, Energy Environ. Sci., 2013, 6, 3112–3135.
- 54 A. Goeppert, M. Czaun, J. P. Jones, G. K. Surya Prakash and G. A. Olah, Chem. Soc. Rev., 2014, 43, 7995–8048.
- 55 D. Qin and J. Lapszewicz, Catal. Today, 1994, 21, 551–560.
- 56 W. Zhou, K. Cheng, J. Kang, C. Zhou, V. Subramanian, Q. Zhang and Y. Wang, Chem. Soc. Rev., 2019, 48, 3193–3228.
- 57 S. Roy, A. Cherevotan and S. C. Peter, ACS Energy Lett., 2018, 3, 1938–1966.
- 58 X. Jiang, X. Nie, X. Guo, C. Song and J. G. Chen, Chem. Rev., 2020, 120, 7984–8034.
- 59 W. Wang and J. Gong, Front. Chem. Sci. Eng., 2011, 5, 2–10.
- 60 K. Saravanan, H. Ham, N. Tsubaki and J. W. Bae, Appl. Catal., B, 2017, 217, 494–522.
- 61 Z. Li, J. Wang, Y. Qu, H. Liu, C. Tang, S. Miao, Z. Feng, H. An and C. Li, ACS Catal., 2017, 7, 8544–8548.
- 62 J. Wei, Q. Ge, R. Yao, Z. Wen, C. Fang, L. Guo, H. Xu and J. Sun, Nat. Commun., 2017, 8, 1–8.
- 63 C. Yang, R. Mu, G. Wang, J. Song, H. Tian, Z. J. Zhao and J. Gong, Chem. Sci., 2019, 10, 3161–3167.
- 64 E. Alper and O. Yuksel Orhan, Petroleum, 2017, 3, 109–126.
- 65 O. Martin and J. Pérez-Ramírez, Catal. Sci. Technol., 2013, 3, 3343–3352.
- 66 J. T. Sun, I. S. Metcalfe and M. Sahibzada, Ind. Eng. Chem. Res., 1999, 38, 3868–3872.
- 67 E. D. Goodman, J. A. Schwalbe and M. Cargnello, ACS Catal., 2017, 7, 7156–7173.
- 68 Y. Dai, P. Lu, Z. Cao, C. T. Campbell and Y. Xia, Chem. Soc. Rev., 2018, 47, 4314–4331.
- 69 J. Sehested, J. A. P. Gelten and S. Helveg, Appl. Catal., A, 2006, 309, 237–246.
- 70 B. Dargatz, J. Gonzalez-Julian, M. Bram, P. Jakes, A. Besmehn, L. Schade, R. Röder, C. Ronning and O. Guillon, J. Eur. Ceram. Soc., 2016, 36, 1207–1220.
- 71 T. W. Hansen, A. T. Delariva, S. R. Challa and A. K. Datye, Acc. Chem. Res., 2013, 46, 1720–1730.
- 72 M. V. Twigg and M. S. Spencer, Top. Catal., 2003, 22, 191–203.
- 73 M. B. Fichtl, D. Schlereth, N. Jacobsen, I. Kasatkin, J. Schumann, M. Behrens, R. Schlögl and O. Hinrichsen, Appl. Catal., A, 2015, 502, 262–270.
- 74 S. R. Challa, A. T. Delariva, T. W. Hansen, S. Helveg, J. Sehested, P. L. Hansen, F. Garzon and A. K. Datye, J. Am. Chem. Soc., 2011, 133, 20672–20675.
- 75 J. H. Bitter, W. Hally, K. Seshan, J. G. Van Ommen and J. A. Lercher, Catal. Today, 1996, 29, 349–353.
- 76 J. H. Bitter, K. Seshan and J. A. Lercher, J. Catal., 1999, 183, 336–343.
- 77 M. Jacquemin, A. Beuls and P. Ruiz, Catal. Today, 2010, 157, 462–466.
- 78 W. M. Shen, J. A. Dumesic and C. G. Hill, J. Catal., 1981, 68, 152–165.
- 79 M. Agnelli, M. Kolb and C. Mirodatos, J. Catal., 1994, 148, 9–21.
- 80 M. Agnelli, H. M. Swaan, C. Marquez-Alvarez, G. A. Martin and C. Mirodatos, J. Catal., 1998, 175, 117–128.
- 81 M. Mihaylov, K. Hadjiivanov and H. Knözinger, Catal. Lett., 2001, 76, 59–63.
- 82 P. Munnik, M. E. Z. Velthoen, P. E. de Jongh, K. P. de Jong and C. J. Gommes, Angew. Chem., 2014, 126, 9647–9651.
- 83 K. S. Park, K. Saravanan, S. J. Park, Y. J. Lee, K. W. Jeon and J. W. Bae, Catal. Sci. Technol., 2017, 7, 4079–4091.
- 84 S. M. Kim, J. W. Bae, Y. J. Lee and K. W. Jun, Catal. Commun., 2008, 9, 2269–2273.
- 85 R. Cheula, A. Soon and M. Maestri, Catal. Sci. Technol., 2018, 8, 3493–3503.
- 86 R. Cheula, M. Maestri and G. Mpourmpakis, ACS Catal., 2020, 10, 6149–6158.
- 87 M. Vyshnepolsky, Z.-B. Ding, P. Srivastava, P. Tesarik, H. Mazhar, M. Maestri and K. Morgenstern, Angew. Chem., Int. Ed., 2021, 133, 18365–18370.
- 88 G. Centi, E. A. Quadrelli and S. Perathoner, Energy Environ. Sci., 2013, 6, 1711–1731.
- 89 E. S. Gutterød, A. Lazzarini, T. Fjermestad, G. Kaur, M. Manzoli, S. Bordiga, S. Svelle, K. P. Lillerud, E. Skúlason, S. Øien-ØDegaard, A. Nova and U. Olsbye, J. Am. Chem. Soc., 2020, 142, 999–1009. **Nini review Catalysis Science Station Access Commons.** Access Articles. The Mondo, K. Older and A. American, A. Am
	- 90 F. Jiang, B. Liu, S. Geng, Y. Xu and X. Liu, Catal. Sci. Technol., 2018, 8, 4097–4107.
	- 91 L. Wang, E. Guan, Y. Wang, L. Wang, Z. Gong, Y. Cui, X. Meng, B. C. Gates and F. S. Xiao, Nat. Commun., 2020, 11, 1–9.
	- 92 T. S. Galhardo, A. H. Braga, B. H. Arpini, J. Szanyi, R. V. Gonc, B. F. Zornio, C. R. Miranda and L. M. Rossi, J. Am. Chem. Soc., 2021, 143, 4268–4280.
	- 93 R. V. Gonçalves, L. L. R. Vono, R. Wojcieszak, C. S. B. Dias, H. Wender, E. Teixeira-Neto and L. M. Rossi, Appl. Catal., B, 2017, 209, 240–246.
	- 94 M. M. Millet, G. Algara-Siller, S. Wrabetz, A. Mazheika, F. Girgsdies, D. Teschner, F. Seitz, A. Tarasov, S. V. Levchenko, R. Schlögl and E. Frei, J. Am. Chem. Soc., 2019, 141, 2451–2461.
	- 95 M. C. Silaghi, A. Comas-Vives and C. Copéret, ACS Catal., 2016, 6, 4501–4505.
	- 96 M. Roiaz, E. Monachino, C. Dri, M. Greiner, A. Knop-Gericke, R. Schlögl, G. Comelli and E. Vesselli, J. Am. Chem. Soc., 2016, 138, 4146–4154.
	- 97 J. R. Rostrup-Nielsen, J. Sehested and J. K. Nørskov, Adv. Catal., 2002, 47, 65–139.
	- 98 S. Kattel, P. Liu and J. G. Chen, J. Am. Chem. Soc., 2017, 139, 9739–9754.
	- 99 C. Vogt, M. Monai, E. B. Sterk, J. Palle, A. E. M. Melcherts, B. Zijlstra, E. Groeneveld, P. H. Berben, J. M. Boereboom, E. J. M. Hensen, F. Meirer, I. A. W. Filot and B. M. Weckhuysen, Nat. Commun., 2019, 10, 1–10.
	- 100 X. Chen, X. Su, H. Duan, B. Liang, Y. Huang and T. Zhang, Catal. Today, 2017, 281, 312–318.
	- 101 E. S. Gutterød, S. Øien-ØDegaard, K. Bossers, A. E. Nieuwelink, M. Manzoli, L. Braglia, A. Lazzarini, E. Borfecchia, S. Ahmadigoltapeh, B. Bouchevreau, B. T. Lønstad-Bleken, R. Henry, C. Lamberti, S. Bordiga, B. M. Weckhuysen, K. P. Lillerud and U. Olsbye, Ind. Eng. Chem. Res., 2017, 56, 13206–13218.
- 102 H. Kusama, K. K. Bando, K. Okabe and H. Arakawa, Appl. Catal., A, 2001, 205, 285–294.
- 103 Y. Yang, J. Liu, F. Liu and D. Wu, Fuel, 2020, 276, 118093.
- 104 J. H. Kwak, L. Kovarik and J. Szanyi, ACS Catal., 2013, 3, 2449–2455.
- 105 A. Aitbekova, L. Wu, C. J. Wrasman, A. Boubnov, A. S. Hoffman, E. D. Goodman, S. R. Bare and M. Cargnello, J. Am. Chem. Soc., 2018, 140, 13736–13745.
- 106 S. Tada, O. J. Ochieng, R. Kikuchi, T. Haneda and H. Kameyama, Int. J. Hydrogen Energy, 2014, 39, 10090–10100.
- 107 X. Shao, X. Yang, J. Xu, S. Liu, S. Miao, X. Liu, X. Su, H. Duan, Y. Huang and T. Zhang, Chem, 2019, 5, 693–705.
- 108 N. Austin, B. Butina and G. Mpourmpakis, Prog. Nat. Sci.: Mater. Int., 2016, 26, 487–492.
- 109 N. Austin, J. Ye and G. Mpourmpakis, Catal. Sci. Technol., 2017, 7, 2245–2251.
- 110 J. Dean, Y. Yang, N. Austin, G. Veser and G. Mpourmpakis, ChemSusChem, 2018, 11, 1169–1178.
- 111 M. Dixit, X. Peng, M. D. Porosoff, H. D. Willauer and G. Mpourmpakis, Catal. Sci. Technol., 2017, 7, 5521–5529.
- 112 R. Cheula and M. Maestri, Catal. Today, 2021, DOI: 10.1016/j.cattod.2021.05.016.
- 113 J. Cai, Y. Han, S. Chen, E. J. Crumlin, B. Yang, Y. Li and Z. Liu, J. Phys. Chem. C, 2019, 123, 12176–12182.
- 114 M. Zhang, B. Zijlstra, I. A. W. Filot, F. Li, H. Wang, J. Li and E. J. M. Hensen, Can. J. Chem. Eng., 2020, 98, 740–748.
- 115 R. A. Van Santen, Acc. Chem. Res., 2009, 42, 57–66.
- 116 I. A. W. Filot, S. G. Shetty, E. J. M. Hensen and R. A. Van Santen, J. Phys. Chem. C, 2011, 115, 14204–14212.
- 117 M. Mavrikakis, M. Bäumer, H. J. Freund and J. K. Nørskov, Catal. Lett., 2002, 81, 153–156.
- 118 H. Mansour and E. Iglesia, J. Am. Chem. Soc., 2021, 143, 11582–11594.
- 119 M. Zhu, Q. Ge and X. Zhu, Trans. Tianjin Univ., 2020, 26, 172–187.
- 120 M. González-Castaño, B. Dorneanu and H. Arellano-García, React. Chem. Eng., 2021, 6, 954–976.
- 121 Q. L. Tang, Q. J. Hong and Z. P. Liu, J. Catal., 2009, 263, 114–122.
- 122 N. Ishito, K. Hara, K. Nakajima and A. Fukuoka, J. Energy Chem., 2016, 25, 306–310.
- 123 D. J. Pettigrew and N. W. Cant, Catal. Lett., 1994, 28, 313–319.
- 124 N. C. Nelson, L. Chen, D. Meira, L. Kovarik and J. Szanyi, Angew. Chem., Int. Ed., 2020, 59, 17657–17663.
- 125 A. Goguet, S. O. Shekhtman, R. Burch, C. Hardacre, F. C. Meunier and G. S. Yablonsky, J. Catal., 2006, 237, 102–110.
- 126 S. S. Kim, K. H. Park and S. C. Hong, Fuel Process. Technol., 2013, 108, 47–54.
- 127 Z. Zhao, M. Wang, P. Ma, Y. Zheng, J. Chen, H. Li, X. Zhang, K. Zheng, Q. Kuang and Z. X. Xie, Appl. Catal., B, 2021, 291, 120101.
- 128 X. Chen, Y. Chen, C. Song, P. Ji, N. Wang, W. Wang and L. Cui, Front. Chem., 2020, 8, 1–21.
- 129 M. M. Kauppinen, M. M. Melander, A. S. Bazhenov and K. Honkala, ACS Catal., 2018, 8, 11633–11647.

- 130 C. Wang, E. Guan, L. Wang, X. Chu, Z. Wu, J. Zhang, Z. Yang, Y. Jiang, L. Zhang, X. Meng, B. C. Gates and F. S. Xiao, J. Am. Chem. Soc., 2019, 141, 8482–8488.
- 131 Z. Zheng, C. Sun, R. Dai, S. Wang, X. Wu, X. An and X. Xie, Catal. Sci. Technol., 2015, 5, 2590–2601.
- 132 L. F. Bobadilla, J. L. Santos, S. Ivanova, J. A. Odriozola and A. Urakawa, ACS Catal., 2018, 8, 7455–7467.
- 133 M. Wenzel, N. V. R. Aditya Dharanipragada, V. V. Galvita, H. Poelman, G. B. Marin, L. Rihko-Struckmann and K. Sundmacher, J. CO2 Util., 2017, 17, 60–68.
- 134 D. H. Kim, S. W. Han, H. S. Yoon and Y. D. Kim, J. Ind. Eng. Chem., 2015, 23, 67–71.
- 135 R. Mutschler, E. Moioli, W. Luo, N. Gallandat and A. Züttel, J. Catal., 2018, 366, 139–149.
- 136 X. Zhang, X. Zhu, L. Lin, S. Yao, M. Zhang, X. Liu, X. Wang, Y. W. Li, C. Shi and D. Ma, ACS Catal., 2017, 7, 912–918.
- 137 S. C. Yang, S. H. Pang, T. P. Sulmonetti, W. N. Su, J. F. Lee, B. J. Hwang and C. W. Jones, ACS Catal., 2018, 8, 12056–12066.
- 138 J. Ye, Q. Ge and C. J. Liu, Chem. Eng. Sci., 2015, 135, 193–201.
- 139 S. Sengupta, A. Jha, P. Shende, R. Maskara and A. K. Das, J. Environ. Chem. Eng., 2019, 7, 102911.
- 140 L. Pastor-Pérez, F. Baibars, E. Le Sache, H. Arellano-García, S. Gu and T. R. Reina, J. CO2 Util., 2017, 21, 423–428.
- 141 M. Juneau, M. Vonglis, J. Hartvigsen, L. Frost, D. Bayerl, M. Dixit, G. Mpourmpakis, J. R. Morse, J. W. Baldwin, H. D. Willauer and M. D. Porosoff, Energy Environ. Sci., 2020, 13, 2524–2539. Catalysis Science & Technology Www.2006. Waveloness Article is the Unported Unported Unit (1998), μ 1212. The Catalogy Commons Article is licensed under the Creative Commons Article is licensed under a Creative Commons
	- 142 J. Nakamura, J. M. Campbell and C. T. Campbell, J. Chem. Soc., Faraday Trans., 1990, 86, 2725–2734.
	- 143 C. V. Ovesen, P. Stoltze, J. K. Nørskov and C. T. Campbell, J. Catal., 1992, 134, 445–468.
	- 144 J. Yoshihara and C. T. Campbell, J. Catal., 1996, 161, 776–782.
	- 145 P. Liu and J. A. Rodriguez, J. Chem. Phys., 2007, 126, 164705.
	- 146 Q. L. Tang, Z. X. Chen and X. He, Surf. Sci., 2009, 603, 2138–2144.
	- 147 A. A. Gokhale, J. A. Dumesic and M. Mavrikakis, J. Am. Chem. Soc., 2008, 130, 1402–1414.
	- 148 G. Peng, S. J. Sibener, G. C. Schatz and M. Mavrikakis, Surf. Sci., 2012, 606, 1050–1055.
	- 149 C.-S. Chen, W.-H. Cheng and S. Lin, Catal. Lett., 2000, 68, 45–48.
	- 150 E. Vesselli, M. Rizzi, L. de Rogatis, X. Ding, A. Baraldi, G. Comelli, L. Savio, L. Vattuone, M. Rocca, P. Fornasiero, A. Baldereschi and M. Peressi, J. Phys. Chem. Lett., 2010, 1, 402–406.
	- 151 A. Goguet, F. C. Meunier, D. Tibiletti, J. P. Breen and R. Burch, J. Phys. Chem. B, 2004, 108, 20240–20246.
	- 152 X. Su, X. Yang, B. Zhao and Y. Huang, J. Energy Chem., 2017, 26, 854–867.
	- 153 L. Dietz, S. Piccinin and M. Maestri, J. Phys. Chem. C, 2015, 119, 4959–4966.
- 154 C. Vogt, E. Groeneveld, G. Kamsma, M. Nachtegaal, L. Lu, C. J. Kiely, P. H. Berben, F. Meirer and B. M. Weckhuysen, Nat. Catal., 2018, 1, 127–134.
- 155 W. Lin, K. M. Stocker and G. C. Schatz, J. Phys. Chem. C, 2016, 120, 23061–23068.
- 156 L. C. Wang, M. Tahvildar Khazaneh, D. Widmann and R. J. Behm, J. Catal., 2013, 302, 20–30.
- 157 G. C. Wang and J. Nakamura, J. Phys. Chem. Lett., 2010, 1, 3053–3057.
- 158 C. Liu, T. R. Cundari and A. K. Wilson, J. Phys. Chem. C, 2012, 116, 5681–5688.
- 159 A. Donazzi, A. Beretta, G. Groppi and P. Forzatti, J. Catal., 2008, 255, 241–258.
- 160 A. Donazzi, A. Beretta, G. Groppi and P. Forzatti, J. Catal., 2008, 255, 259–268.
- 161 M. Maestri and K. Reuter, Chem. Eng. Sci., 2012, 74, 296–299.
- 162 M. Maestri, D. Livio, A. Beretta and G. Groppi, Ind. Eng. Chem. Res., 2014, 53, 10914–10928.
- 163 P. Sabatier and J. B. Senderens, J. Chem. Soc., 1902, 82, 333.
- 164 W. Wang, S. Wang, X. Ma, J. Gong and W. Wang, Chem. Soc. Rev., 2011, 40, 3703–3727.
- 165 P. J. Lunde and F. L. Kester, Ind. Eng. Chem. Process Des. Dev., 1974, 13, 27–33.
- 166 Y. Wu, J. Lin, Y. Xu, G. Ma, J. Wang and M. Ding, ChemCatChem, 2020, 12, 3553–3559.
- 167 K. Ravindranathan Thampi, L. Lucarelli and J. Kiwi, Langmuir, 1991, 7, 2642–2648.
- 168 A. Karelovic and P. Ruiz, ACS Catal., 2013, 3, 2799–2812.
- 169 H. Y. Kim, H. M. Lee and J. N. Park, J. Phys. Chem. C, 2010, 114, 7128–7131.
- 170 F. Ocampo, B. Louis and A. C. Roger, Appl. Catal., A, 2009, 369, 90–96.
- 171 F. Solymosi and A. Erdöhelyi, Stud. Surf. Sci. Catal., 1981, 7, 1448–1449.
- 172 X. Dong, B. Jin, S. Cao, F. Meng, T. Chen, Q. Ding and C. Tong, Waste Manage., 2020, 107, 244–251.
- 173 J. Gao, Y. Wang, Y. Ping, D. Hu, G. Xu, F. Gu and F. Su, RSC Adv., 2012, 2, 2358–2368.
- 174 S. Rönsch, J. Schneider, S. Matthischke, M. Schlüter, M. Götz, J. Lefebvre, P. Prabhakaran and S. Bajohr, Fuel, 2016, 166, 276–296.
- 175 G. Xu, K. Shi, Y. Gao, H. Xu and Y. Wei, J. Mol. Catal. A: Chem., 1999, 147, 47–54.
- 176 S. Wang and G. Q. M. Lu, Appl. Catal., B, 1998, 16, 269–277.
- 177 M. González-Castaño, J. C. N. de Miguel, A. Penkova, M. A. Centeno, J. A. Odriozola and H. Arellano-Garcia, Appl. Mater. Today, 2021, 23, 27–30.
- 178 Y. Yan, Y. Dai, Y. Yang and A. A. Lapkin, Appl. Catal., B, 2018, 237, 504–512.
- 179 X. Bai, S. Wang, T. Sun and S. Wang, React. Kinet., Mech. Catal., 2014, 112, 437–451.
- 180 J. R. Rostrup-Nielsen, K. Pedersen and J. Sehested, Appl. Catal., A, 2007, 330, 134–138.
- 181 W. Gac, W. Zawadzki, M. Rotko, G. Słowik and M. Greluk, Top. Catal., 2019, 62, 524–534.
- 182 C. Mirodatos, H. Praliaud and M. Primet, J. Catal., 1987, 107, 275–287.
- 183 J. Cored, A. García-Ortiz, S. Iborra, M. J. Climent, L. Liu, C. H. Chuang, T. S. Chan, C. Escudero, P. Concepción and A. Corma, J. Am. Chem. Soc., 2019, 141, 19304–19311.
- 184 J. Ashok, S. Pati, P. Hongmanorom, Z. Tianxi, C. Junmei and S. Kawi, Catal. Today, 2020, 356, 471–489.
- 185 Y. Chen, J. Long and Z. Li, Trends Chem., 2019, 1, 459–460.
- 186 S. Navarro-Jaén, J. C. Navarro, L. F. Bobadilla, M. A. Centeno, O. H. Laguna and J. A. Odriozola, Appl. Surf. Sci., 2019, 483, 750–761.
- 187 S. Saeidi, S. Najari, V. Hessel, K. Wilson, F. J. Keil, P. Concepción, S. L. Suib and A. E. Rodrigues, Prog. Energy Combust. Sci., 2021, 85, 100905.
- 188 B. Alrafei, I. Polaert, A. Ledoux and F. Azzolina-Jury, Catal. Today, 2020, 346, 23–33.
- 189 T. A. Le, J. Kim, J. K. Kang and E. D. Park, Catal. Today, 2020, 348, 80–88.
- 190 C. Mebrahtu, F. Krebs, S. Perathoner, S. Abate, G. Centi and R. Palkovits, Catal. Sci. Technol., 2018, 8, 1016–1027.
- 191 M. A. Serrer, A. Gaur, J. Jelic, S. Weber, C. Fritsch, A. H. Clark, E. Saraçi, F. Studt and J. D. Grunwaldt, Catal. Sci. Technol., 2020, 10, 7542–7554.
- 192 T. Franken and A. Heel, J. CO2 Util., 2020, 39, 101175.
- 193 A. I. Tsiotsias, N. D. Charisiou and I. V. Yentekakis, Nanomaterials, 2021, 21, 1–34.
- 194 D. Pandey and G. Deo, J. Ind. Eng. Chem., 2016, 33, 99–107.
- 195 H. H. Shin, L. Lu, Z. Yang, C. J. Kiely and S. McIntosh, ACS Catal., 2016, 6, 2811–2818.
- 196 A. Jangam, S. Das, N. Dewangan, P. Hongmanorom, W. M. Hui and S. Kawi, Catal. Today, 2020, 358, 3–29.
- 197 N. M. Martin, F. Hemmingsson, A. Schaefer, M. Ek, L. R. Merte, U. Hejral, J. Gustafson, M. Skoglundh, A. C. Dippel, O. Gutowski, M. Bauer and P. A. Carlsson, Catal. Sci. Technol., 2019, 9, 1644–1653.
- 198 A. Trovarelli, C. de Leitenburg, G. Dolcetti and J. L. Lorca, J. Catal., 1995, 151, 111–124.
- 199 C. De Leitenburg, A. Trovarelli and J. Kašpar, J. Catal., 1997, 166, 98–107.
- 200 C. De Leitenburg and A. Trovarelli, J. Catal., 1995, 156, 171–174.
- 201 Q. Pan, J. Peng, T. Sun, S. Wang and S. Wang, Catal. Commun., 2014, 45, 74–78.
- 202 F. Ocampo, B. Louis, A. Kiennemann and A. C. Roger, IOP Conf. Ser.: Mater. Sci. Eng., 2011, 19, 012007.
- 203 F. Ocampo, B. Louis, L. Kiwi-Minsker and A. C. Roger, Appl. Catal., A, 2011, 392, 36–44.
- 204 S. Eckle, H. G. Anfang and R. J. Behm, J. Phys. Chem. C, 2011, 115, 1361–1367.
- 205 A. Beuls, C. Swalus, M. Jacquemin, G. Heyen, A. Karelovic and P. Ruiz, Appl. Catal., B, 2012, 113–114, 2–10.
- 206 A. Karelovic and P. Ruiz, J. Catal., 2013, 301, 141–153.
- 207 P. A. U. Aldana, F. Ocampo, K. Kobl, B. Louis, F. Thibault-Starzyk, M. Daturi, P. Bazin, S. Thomas and A. C. Roger, Catal. Today, 2013, 215, 201–207.
- 208 D. C. Upham, A. R. Derk, S. Sharma, H. Metiu and E. W. McFarland, Catal. Sci. Technol., 2015, 5, 1783–1791.
- 209 W. Li, H. Wang, X. Jiang, J. Zhu, Z. Liu, X. Guo and C. Song, RSC Adv., 2018, 8, 7651–7669.
- 210 E. Baraj, S. Vagaský, T. Hlinčik, K. Ciahotný and V. Tekáč, Chem. Pap., 2016, 70, 395–403.
- 211 J. A. H. Dreyer, P. Li, L. Zhang, G. Khai, R. Zhang, P. H. Sit and W. Yang, Appl. Catal., B, 2017, 219, 715–726.
- 212 A. Quindimil, U. De-la-torre, B. Pereda-ayo and A. Davóquiñonero, Catal. Today, 2020, 356, 419–432.
- 213 D. Qin, D. Xie, H. Zheng, Z. Li, J. Tang and Z. Wei, Catal. Lett., 2021, 151, 2894–2905.
- 214 L. Falbo, C. G. Visconti, L. Lietti and J. Szanyi, Appl. Catal., B, 2019, 256, 117791.
- 215 C. Vogt, M. Monai, G. J. Kramer and B. M. Weckhuysen, Nat. Catal., 2019, 2, 188–197.
- 216 S. E. Olesen, K. J. Andersson, C. D. Damsgaard and I. Chorkendorff, J. Phys. Chem. C, 2017, 121, 15556–15564.
- 217 J. Barrientos, N. Gonzalez, M. Boutonnet and S. Järås, Top. Catal., 2017, 60, 1276–1284.
- 218 Y. Song, E. Ozdemir, S. Ramesh, A. Adishev, S. Subramanian, A. Harale, M. Albuali, B. A. Fadhel, A. Jamal, D. Moon, S. H. Choi and C. T. Yavuz, Science, 2020, 781, 777–781.
- 219 M. Akri, S. Zhao, X. Li, K. Zang, A. F. Lee, M. A. Isaacs, W. Xi, Y. Gangarajula, J. Luo, Y. Ren, Y. T. Cui, L. Li, Y. Su, X. Pan, W. Wen, Y. Pan, K. Wilson, L. Li, B. Qiao, H. Ishii, Y. F. Liao, A. Wang, X. Wang and T. Zhang, Nat. Commun., 2019, 10, 1–10. **Mini review Catalysis Science** & Technology Catalysis Science & Technology (2021. 2022.
	- 220 W. Y. Kim, Y. H. Lee, H. Park, Y. H. Choi, M. H. Lee and J. S. Lee, Catal. Sci. Technol., 2016, 6, 2060–2064.
	- 221 S. Das, A. Jangam, S. Xi, A. Borgna, K. Hidajat and S. Kawi, ACS Appl. Energy Mater., 2020, 3, 7719–7735.
	- 222 K. Bu, J. Deng, X. Zhang, S. Kuboon, T. Yan, H. Li, L. Shi and D. Zhang, Appl. Catal., B, 2020, 267, 118692.
	- 223 Z. Yao, J. Jiang, Y. Zhao, F. Luan, J. Zhu, Y. Shi, H. Gao and H. Wang, RSC Adv., 2016, 6, 19944–19951.
	- 224 M. C. J. Bradford and M. A. Vannice, Catal. Rev.: Sci. Eng., 1999, 41, 1–42.
	- 225 L. Foppa, M. C. Silaghi, K. Larmier and A. Comas-Vives, J. Catal., 2016, 343, 196–207.
	- 226 R. K. Singha, A. Yadav, A. Shukla, M. Kumar and R. Bal, Catal. Commun., 2017, 92, 19–22.
	- 227 H. Arandiyan, Y. Wang, J. Scott, S. Mesgari, H. Dai and R. Amal, ACS Appl. Mater. Interfaces, 2018, 10, 16352–16357.
	- 228 K. Song, M. Lu, S. Xu, C. Chen, Y. Zhan, D. Li, C. Au, L. Jiang and K. Tomishige, Appl. Catal., B, 2018, 239, 324–333.
	- 229 W. L. Vrijburg, G. Garbarino, W. Chen, A. Parastaev, A. Longo, E. A. Pidko and E. J. M. Hensen, J. Catal., 2020, 382, 358–371.
	- 230 C. Fan, Y. A. Zhu, M. L. Yang, Z. J. Sui, X. G. Zhou and D. Chen, Ind. Eng. Chem. Res., 2015, 54, 5901–5913.
	- 231 S. G. Wang, D. B. Cao, Y. W. Li, J. Wang and H. Jiao, J. Phys. Chem. B, 2006, 110, 9976–9983.
	- 232 J. Niu, X. Du, J. Ran and R. Wang, Appl. Surf. Sci., 2016, 376, 79–90.

- 233 A. Nandini, K. K. Pant and S. C. Dhingra, Appl. Catal., A, 2006, 308, 119–127.
- 234 T. Osaki and T. Mori, J. Catal., 2001, 204, 89–97.
- 235 M. C. J. Bradford and M. A. Vannice, Appl. Catal., A, 1996, 142, 97–122.
- 236 J. F. Múnera, L. M. Cornaglia, D. V. Cesar, M. Schmal and E. A. Lombardo, Ind. Eng. Chem. Res., 2007, 46, 7543–7549.
- 237 M. Maestri, D. G. Vlachos, A. Beretta, G. Groppi and E. Tronconi, J. Catal., 2008, 259, 211–222.
- 238 M. F. Mark, F. Mark and W. F. Maier, Chem. Eng. Technol., 1997, 20, 361–370.
- 239 J. Wei and E. Iglesia, J. Catal., 2004, 224, 370–383.
- 240 A. Yamaguchi and E. Iglesia, J. Catal., 2010, 274, 52–63.
- 241 J. Wei and E. Iglesia, J. Catal., 2004, 225, 116–127.
- 242 N. Manavi and B. Liu, Catal. Sci. Technol., 2021, 11, 3724–3736.
- 243 D. L. Trimm, Catal. Today, 1999, 49, 3–10.
- 244 J. Rostrup-Nielsen and D. L. Trimm, J. Catal., 1977, 48, 155–165.
- 245 Z. Wang, X. M. Cao, J. Zhu and P. Hu, J. Catal., 2014, 311, 469–480.
- 246 M. A. A. Aziz, A. A. Jalil, S. Wongsakulphasatch and D. V. N. Vo, Catal. Sci. Technol., 2020, 10, 35–45.
- 247 R. J. Zhang, G. F. Xia, M. F. Li, Y. Wu, H. Nie and D. D. Li, Ranliao Huaxue Xuebao, 2015, 43, 1359–1365.
- 248 S. S. Kim, H. H. Lee and S. C. Hong, Appl. Catal., A, 2012, 423–424, 100–107.
- 249 M. Ferrandon and T. Krause, Appl. Catal., A, 2006, 311, 135–145.
- 250 S. Sokolov, E. V. Kondratenko, M. Pohl, A. Barkschat and U. Rodemerck, Appl. Catal., B, 2012, 113–114, 19–30.
- 251 J. Zhong, X. Yang, Z. Wu, B. Liang, Y. Huang and T. Zhang, Chem. Soc. Rev., 2020, 49, 1385–1413.
- 252 F. Calaza, C. Stiehler, Y. Fujimori, M. Sterrer, S. Beeg, M. Ruiz-oses, N. Nilius, M. Heyde, T. Parviainen, K. Honkala, H. Häkkinen and H. Freund, Angew. Chem., Int. Ed., 2015, 54, 12484–12487.
- 253 J. Graciani, K. Mudiyanselage, F. Xu, A. E. Baber, J. Evans, S. D. Senanayake, D. J. Stacchiola, P. Liu, J. Hrbek, J. Fernández Sanz and J. A. Rodriguez, Science, 2014, 345, 546–550.
- 254 J. C. Frost, Nature, 1988, 334, 577–580.
- 255 F. Abild-pedersen, F. Studt and T. Bligaard, Proc. Natl. Acad. Sci. U. S. A., 2011, 108, 937–943.
- 256 J. Xiao and T. Frauenheim, J. Phys. Chem. C, 2013, 117, 1804–1808.
- 257 N. Acerbi, S. C. E. Tsang, G. Jones, S. Golunski and P. Collier, Angew. Chem., Int. Ed., 2013, 52, 7737–7741.
- 258 M. U. Khan, L. Wang, Z. Liu, Z. Gao, S. Wang, H. Li, W. Zhang, M. Wang, Z. Wang, C. Ma and J. Zeng, Angew. Chem., Int. Ed., 2016, 55, 9548–9552.
- 259 M. Behrens, F. Studt, I. Kasatkin, S. Kühl, M. Hävecker, F. Abild-pedersen, S. Zander, F. Girgsdies, P. Kurr, B. Kniep, M. Tovar, R. W. Fischer, J. K. Nørskov and R. Schlögl, Science, 2012, 759, 893–898.
- 260 M. Behrens, Angew. Chem., Int. Ed., 2016, 55, 14906–14908.
- 261 B. Liang, J. Ma, X. Su, C. Yang, H. Duan, H. Zhou, S. Deng, L. Li and Y. Huang, Ind. Eng. Chem. Res., 2019, 58, 9030–9037.
- 262 J. Wu, M. Saito, M. Takeuchi and T. Watanabe, Appl. Catal., A, 2001, 218, 235–240.
- 263 A. Prašnikar, A. Pavlišič, F. Ruiz-Zepeda, J. Kovač and B. Likozar, Ind. Eng. Chem. Res., 2019, 58, 13021–13029.
- 264 A. Parastaev, V. Muravev, E. Huertas Osta, A. J. F. van Hoof, T. F. Kimpel, N. Kosinov and E. J. M. Hensen, Nat. Catal., 2020, 3, 526–533.
- 265 E. Lam, J. J. Corral-Pérez, K. Larmier, G. Noh, P. Wolf, A. Comas-Vives, A. Urakawa and C. Copéret, Angew. Chem., 2019, 131, 14127–14134.
- 266 I. A. Fisher, H. C. Woo and A. T. Bell, Catal. Lett., 1997, 44, 11–17.
- 267 Z. Shi, Q. Tan, C. Tian, Y. Pan, X. Sun, J. Zhang and D. Wu, J. Catal., 2019, 379, 78–89.
- 268 K. Larmier, W. C. Liao, S. Tada, E. Lam, R. Verel, A. Bansode, A. Urakawa, A. Comas-Vives and C. Copéret, Angew. Chem., Int. Ed., 2017, 56, 2318–2323.
- 269 J. Nakamura, T. Fujitani, S. Kuld, S. Helveg, I. Chorkendorff and J. Sehested, Science, 2017, 357, 1296–1299.
- 270 R. Van Den Berg, G. Prieto, G. Korpershoek, L. I. Van Der Wal, A. J. Van Bunningen, S. Lægsgaard-Jørgensen, P. E. De Jongh and K. P. De Jong, Nat. Commun., 2016, 7, DOI: 10.1038/ncomms13057. Open Access Article. Published on 30 September 2021. Downloaded on 7/31/2024 11:14:13 AM. This article is licensed under a [Creative Commons Attribution 3.0 Unported Licence.](http://creativecommons.org/licenses/by/3.0/) **[View Article Online](https://doi.org/10.1039/d1cy00922b)**
	- 271 Y. Wang, S. Kattel, W. Gao, K. Li, P. Liu, J. G. Chen and H. Wang, Nat. Commun., 2019, 1166.
	- 272 Y. Wang, W. Gao, K. Li, W. Na, J. G. Chen, H. Wang, Y. Wang, W. Gao, K. Li, Y. Zheng, Z. Xie and W. Na, Chem, 2019, 10, 1–12.
	- 273 F. Arena, K. Barbera, G. Italiano, G. Bonura, L. Spadaro and F. Frusteri, J. Catal., 2007, 249, 185–194.
	- 274 X. Guo, D. Mao, G. Lu, S. Wang and G. Wu, J. Catal., 2010, 271, 178–185.
	- 275 T. Phongamwong, U. Chantaprasertporn, T. Witoon, T. Numpilai, Y. Poo-arporn, W. Limphirat, W. Donphai, P. Dittanet, M. Chareonpanich and J. Limtrakul, Chem. Eng. J., 2017, 316, 692–703.
	- 276 L. Angelo, K. Kobl, L. M. M. Tejada, Y. Zimmermann, K. Parkhomenko and A. C. Roger, C. R. Chim., 2015, 18, 250–260.
	- 277 F. Arena, G. Italiano, K. Barbera, S. Bordiga, G. Bonura, L. Spadaro and F. Frusteri, Appl. Catal., A, 2008, 350, 16–23.
	- 278 T. Witoon, N. Kachaban, W. Donphai, P. Kidkhunthod, K. Faungnawakij, M. Chareonpanich and J. Limtrakul, Energy Convers. Manage., 2016, 118, 21–31.
	- 279 C. Yang, Z. Ma, N. Zhao, W. Wei, T. Hu and Y. Sun, Catal. Today, 2006, 115, 222–227.
	- 280 P. Gao, F. Li, H. Zhan, N. Zhao, F. Xiao, W. Wei, L. Zhong, H. Wang and Y. Sun, J. Catal., 2013, 298, 51–60.
	- 281 G. Bonura, M. Cordaro, C. Cannilla, F. Arena and F. Frusteri, Appl. Catal., B, 2014, 152–153, 152–161.
- 282 X. Yang, S. Kattel, S. D. Senanayake, J. A. Boscoboinik, X. Nie, J. Graciani, J. A. Rodriguez, P. Liu, D. J. Stacchiola and J. G. Chen, J. Am. Chem. Soc., 2015, 137, 10104–10107.
- 283 A. Cao, Z. Wang, H. Li and J. K. Nørskov, ChemSusChem, 2020, 13, 6160–6181.
- 284 M. Dou, M. Zhang and Y. Chen, New J. Chem., 2018, 42, 3293–3300.
- 285 A. Tsoukalou, P. M. Abdala, D. Stoian, X. Huang, M. Willinger, A. Fedorov and C. R. Mu, J. Am. Chem. Soc., 2019, 141, 13497–13505.
- 286 J. Ye, C. Liu, D. Mei and Q. Ge, ACS Catal., 2013, 3, 1296–1306.
- 287 O. Martin, A. J. Martín, C. Mondelli, S. Mitchell, T. F. Segawa, R. Hauert, C. Drouilly, D. Curulla-Ferré and J. Pérez-Ramírez, Angew. Chem., Int. Ed., 2016, 55, 6261–6265. **Mini review Catalysis Science Commons Access Article Catalysis Articles Articles and Street Commons Articles Articles. Published and Street Commons Articles Articles. Article is licensed under a Creative Commons Articles**
	- 288 C. Shen, K. Sun, Z. Zhang, N. Rui, X. Jia, D. Mei and C. Liu, ACS Catal., 2021, 11, 4036–4046.
	- 289 M. S. Frei, C. Mondelli, O. V. Safonova, N. López, R. Garcíamuelas, J. Morales-vidal, M. Philipp, J. A. Stewart, D. C. Ferré and J. Pérez-ramírez, Nat. Commun., 2021, 1–9.
	- 290 C. S. Li, G. Melaet, W. T. Ralston, K. An, C. Brooks, Y. Ye, Y. S. Liu, J. Zhu, J. Guo, S. Alayoglu and G. A. Somorjai, Nat. Commun., 2015, 6, 1–5.
	- 291 F. Studt, I. Sharafutdinov, F. Abild-Pedersen, C. F. Elkjær, J. S. Hummelshøj, S. Dahl, I. Chorkendorff and J. K. Nørskov, Nat. Chem., 2014, 6, 320–324.
	- 292 J. Wang, G. Li, Z. Li, C. Tang, Z. Feng, H. An, H. Liu, T. Liu and C. Li, Sci. Adv., 2017, 3, 1–11.
	- 293 E. M. Fiordaliso, I. Sharafutdinov, H. W. P. Carvalho, J. D. Grunwaldt, T. W. Hansen, I. Chorkendorff, J. B. Wagner and C. D. Damsgaard, ACS Catal., 2015, 5, 5827–5836.
	- 294 J. Ye, Q. Ge and C. Liu, J. Phys. Chem. C, 2012, 116, 7817–7825.
	- 295 G. Korotcenkov, I. Boris, V. Brinzari, V. Golovanov, Y. Lychkovsky, G. Karkotsky, A. Cornet, E. Rossinyol, J. Rodrigue and A. Cirera, Sens. Actuators, B, 2004, 103, 13–22.
	- 296 K. Soulantica, L. Erades, M. Sauvan, F. Senocq, A. Maisonnat and B. Chaudret, Adv. Funct. Mater., 2003, 13, 553–557.
	- 297 K. Sun, Z. Fan, J. Ye, J. Yan, Q. Ge, Y. Li, W. He, W. Yang and C. J. Liu, J. CO2 Util., 2015, 12, 1–6.
	- 298 M. Zhang, M. Dou and Y. Yu, Appl. Surf. Sci., 2018, 433, 780–789.
	- 299 F. Arena, G. Mezzatesta, G. Zafarana, G. Trunfio, F. Frusteri and L. Spadaro, J. Catal., 2013, 300, 141–151.
	- 300 R. Gaikwad, A. Bansode and A. Urakawa, J. Catal., 2016, 343, 127–132.
	- 301 Z. Wu, J. Cole, H. L. Fang, M. Qin and Z. He, Journal of Advances in Nanomaterials, 2017, 2, 1–10.
	- 302 Y. Yang, J. Evans, J. A. Rodriguez, M. G. White and P. Liu, Phys. Chem. Chem. Phys., 2010, 12, 9909–9917.
	- 303 J. Zhu, Y. Su, J. Chai, V. Muravev, N. Kosinov and E. J. M. Hensen, ACS Catal., 2020, 10, 11532–11544.
	- 304 T. Lunkenbein, J. Schumann, M. Behrens, R. Schlögl and M. G. Willinger, Angew. Chem., 2015, 127, 4627–4631.
- 305 J. Nakamura, Y. Choi and T. Fujitani, Top. Catal., 2003, 22, 277–285.
- 306 S. Fujita, M. Usui, E. Ohara and N. Takezawa, Catal. Lett., 1992, 13, 349–358.
- 307 D. Laudenschleger, H. Ruland and M. Muhler, Nat. Commun., 2020, 11, 3898.
- 308 P. A. Taylor, P. B. Rasmussen and I. Chorkendorff, J. Chem. Soc., Faraday Trans., 1995, 91, 1267–1269.
- 309 Y. Yang, C. A. Mims, R. S. Disselkamp, J. H. Kwak, C. H. F. Peden and C. T. Campbell, J. Phys. Chem. C, 2010, 114, 17205–17211.
- 310 M. Bowker, R. A. Hadden, H. Houghton, J. N. K. Hyland and K. C. Waugh, J. Catal., 1988, 109, 263–273.
- 311 Y. F. Zhao, Y. Yang, C. Mims, C. H. F. Peden, J. Li and D. Mei, J. Catal., 2011, 281, 199–211.
- 312 L. C. Grabow and M. Mavrikakis, ACS Catal., 2011, 1, 365–384.
- 313 G. C. Chinchen, C. Plant, M. S. Spencer and D. A. Whan, Surf. Sci., 1987, 184, L370–L374.
- 314 M. D. Higham, M. D. Higham, M. G. Quesne, M. G. Quesne, C. R. A. Catlow, C. R. A. Catlow and C. R. A. Catlow, Dalton Trans., 2020, 49, 8478–8497.
- 315 P. B. Rasmussen, P. M. Holmblad, T. Askgaard, C. V. Ovesen, P. Stoltze, J. K. Nørskov and I. Chorkendorff, Catal. Lett., 1994, 26, 373–381.
- 316 P. B. Rasmussen, M. Kazuta and I. Chorkendorff, Surf. Sci., 1994, 318, 267–280.
- 317 A. Cao, Z. Wang, H. Li and J. K. Nørskov, ACS Catal., 2021, 11, 1780–1786.
- 318 Z. Zhou, B. Qin, S. Li and Y. Sun, Phys. Chem. Chem. Phys., 2021, 23, 1888–1895.
- 319 S. Dang, B. Qin, Y. Yang, H. Wang, J. Cai, Y. Han, S. Li, P. Gao and Y. Sun, Sci. Adv., 2020, 6, DOI: 10.1126/sciadv.aaz2060.
- 320 M. Yang, Z. Lingjun, Z. Xiaonan, R. Prasert and W. Shurong, J. CO2 Util., 2020, 42, 101304.
- 321 W. A. Wan Abu Bakar, R. Ali and N. S. Mohammad, Arabian J. Chem., 2015, 8, 632–643.
- 322 B. R. Powell and S. E. Whittington, J. Catal., 1983, 81, 382–393.
- 323 S. De Llobet, J. L. Pinilla, M. J. Lazaro, R. Moliner and I. Suelves, Fuel, 2013, 111, 778–783.
- 324 V. Pawar, D. Ray, C. Subrahmanyam and V. M. Janardhanan, Energy Fuels, 2015, 29, 8047–8052.
- 325 P. G. Menon, J. Mol. Catal., 1990, 59, 207–220.
- 326 J. G. McCarty, P. Y. Hou, D. Sheridan and H. Wise, ACS Symp. Ser., 1982, 253–282.
- 327 C. H. Bartholomew, Catal. Rev.: Sci. Eng., 1982, 24, 67–112.
- 328 D. L. Trimm, Catal. Today, 1997, 37, 233–238.
- 329 J. R. Rostrup-Nielsen, Catal. Today, 1993, 18, 305–324.
- 330 J. R. Rostrup-Nielsen and J. H. Bak Hansen, J. Catal., 1993, 144, 38–49.
- 331 S. L. Leung, J. Wei, W. L. Holstein, M. Avalos-Borja and E. Iglesia, J. Phys. Chem. C, 2020, 124, 20143–20160.
- 332 H. S. Bengaard, J. K. Nørskov, J. Sehested, B. S. Clausen, L. P. Nielsen, A. M. Molenbroek and J. R. Rostrup-Nielsen, J. Catal., 2002, 209, 365–384.

- 333 L. Guczi and A. Erdöhelyi, Catalysis for alternative energy generation, 2011, vol. 9781461403.
- 334 S. Wang, G. Q. Lu and G. J. Millar, Energy Fuels, 1996, 10, 896–904.
- 335 A. M. Gadalla and M. E. Sommer, Chem. Eng. Sci., 1989, 44, 2825–2829.
- 336 A. Goguet, F. Meunier, J. P. Breen, R. Burch, M. I. Petch and A. Faur Ghenciu, J. Catal., 2004, 226, 382–392.
- 337 J. Witte, A. Calbry-Muzyka, T. Wieseler, P. Hottinger, S. M. A. Biollaz and T. J. Schildhauer, Appl. Energy, 2019, 240, 359–371.
- 338 A. Erdöhelyi, M. Pásztor and F. Solymosi, J. Catal., 1986, 98, 166–177.
- 339 F. Solymosi, A. Erdöhelyi and M. Kocsis, J. Chem. Soc., Faraday Trans. 1, 1981, 77, 1003–1012.
- 340 F. Pompeo, N. N. Nichio, O. A. Ferretti and D. Resasco, Int. J. Hydrogen Energy, 2005, 30, 1399–1405.
- 341 J. L. Figueiredo and D. L. Trimm, J. Catal., 1975, 40, 154–159.
- 342 D. L. Trimm, Catal. Rev.: Sci. Eng., 1977, 16, 155–189.
- 343 M. Zhu, P. Tian, M. E. Ford, J. Chen, J. Xu, Y.-F. Han and I. E. Wachs, ACS Catal., 2020, 10, 7857–7863.
- 344 J. Gödde, M. Merko, W. Xia and M. Muhler, J. Energy Chem., 2021, 54, 323–331.
- 345 X. Yan, T. Hu, P. Liu, S. Li, B. Zhao, Q. Zhang, W. Jiao, S. Chen, P. Wang, J. Lu, L. Fan, X. Deng and Y. X. Pan, Appl. Catal., B, 2019, 246, 221–231. Catalysis Science & Technology Www.com Mill every Weight on 30 September 2021. Downloaded on 1, 8th article is a super-

Min provide a super-state on 2011, 0.2012. Downloaded a super-state and 1, 8th access Article is lik
	- 346 G. H. Lai, J. H. Lak and D. H. Tsai, ACS Appl. Energy Mater., 2019, 2, 7963–7971.
	- 347 S. Kawi, Y. Kathiraser, J. Ni, U. Oemar and Z. Li, ChemSusChem, 2015, 8, 3556–3575.
	- 348 K. Tomishige, D. Li, M. Tamura and Y. Nakagawa, Catal. Sci. Technol., 2017, 7, 3952–3979.
	- 349 Z. Bian, S. Das, M. H. Wai, P. Hongmanorom and S. Kawi, ChemPhysChem, 2017, 18, 3117–3134.
	- 350 P. Djinović and A. Pintar, Appl. Catal., B, 2017, 206, 675–682.
	- 351 D. Li, Y. Nakagawa and K. Tomishige, Appl. Catal., A, 2011, 408, 1–24.
	- 352 J. Dou, R. Zhang, X. Hao, Z. Bao, T. Wu, B. Wang and F. Yu, Appl. Catal., B, 2019, 254, 612–623.
	- 353 A. P. Tathod, N. Hayek, D. Shpasser, D. S. A. Simakov and O. M. Gazit, Appl. Catal., B, 2019, 249, 106–115.
	- 354 Z. Li, S. Das, P. Hongmanorom, N. Dewangan, M. H. Wai and S. Kawi, Catal. Sci. Technol., 2018, 8, 2763–2778.
	- 355 H. Peng, X. Zhang, X. Han, X. You, S. Lin, H. Chen, W. Liu, X. Wang, N. Zhang, Z. Wang, P. Wu, H. Zhu and S. Dai, ACS Catal., 2019, 9, 9072–9080.
	- 356 Z. Li, Z. Wang and S. Kawi, ChemCatChem, 2019, 11, 202–224.
	- 357 Z. Bian, I. Y. Suryawinata and S. Kawi, Appl. Catal., B, 2016, 195, 1–8.
	- 358 R. K. Singha, A. Yadav, A. Agrawal, A. Shukla, S. Adak, T. Sasaki and R. Bal, Appl. Catal., B, 2016, 191, 165–178.
	- 359 L. Li, L. Zhou, S. Ould-Chikh, D. H. Anjum, M. B. Kanoun, J. Scaranto, M. N. Hedhili, S. Khalid, P. V. Laveille, L.

D'Souza, A. Clo and J. M. Basset, ChemCatChem, 2015, 7, 819–829.

- 360 X. Du, D. Zhang, L. Shi, R. Gao and J. Zhang, Nanoscale, 2013, 5, 2659–2663.
- 361 C. Zhang, W. Zhu, S. Li, G. Wu, X. Ma, X. Wang and J. Gong, Chem. Commun., 2013, 49, 9383–9385.
- 362 J. Wang, Y. Fu, W. Kong, F. Jin, J. Bai, J. Zhang and Y. Sun, Appl. Catal., B, 2021, 282, 119546.
- 363 M. Lu, X. Zhang, J. Deng, S. Kuboon, K. Faungnawakij, S. Xiao and D. Zhang, Catal. Sci. Technol., 2020, 10, 4237–4244.
- 364 X. Wang, Y. Liu, K. Liu, J. Zhang and J. Wei, Int. J. Hydrogen Energy, 2020, 45, 28325–28336.
- 365 X. Chen, L. Yin, K. Long, H. Sun, M. Sun, H. Wang, Q. Zhang and P. Ning, J. Energy Inst., 2020, 93, 2255–2263.
- 366 W. Y. Kim, B. J. Lee, H. Park, Y. H. Choi, J. H. Kim and J. S. Lee, ChemCatChem, 2018, 10, 2214–2218.
- 367 T. Zhang, Z. Liu, Y. A. Zhu, Z. Liu, Z. Sui, K. Zhu and X. Zhou, Appl. Catal., B, 2020, 264, 118497.
- 368 R. Thakur, A. Vahidmohammadi, J. Smith, M. Hoffman, J. Moncada, M. Beidaghi and C. A. Carrero, ACS Catal., 2020, 10, 5124–5134.
- 369 E. Nikolla, A. Holewinski, J. Schwank and S. Linic, J. Am. Chem. Soc., 2006, 128, 11354–11355.
- 370 F. Besenbacher, I. Chorkendorff, B. S. Clausen, B. Hammer, A. M. Molenbroek, J. K. Nørskov and I. Stensgaard, Science, 1998, 279, 1913–1915.
- 371 J. Juan-Juan, M. C. Román-Martínez and M. J. Illán-Gómez, Appl. Catal., A, 2006, 301, 9–15.
- 372 F. Jalid, M. A. Haider, M. I. Alam and T. S. Khan, Catal. Sci. Technol., 2021, 11, 2130–2143.
- 373 L. Chen, Y. Lu, Q. Hong, J. Lin and F. M. Dautzenberg, Appl. Catal., A, 2005, 292, 295–304.
- 374 J. Xu and M. Saeys, J. Catal., 2006, 242, 217–226.
- 375 J. Xu and M. Saeys, Chem. Eng. Sci., 2007, 62, 5039–5041.
- 376 L. Maier, B. Schädel, K. H. Delgado, S. Tischer and O. Deutschmann, Top. Catal., 2011, 54, 845–858.
- 377 E. Akpan, Y. Sun, P. Kumar, H. Ibrahim, A. Aboudheir and R. Idem, Chem. Eng. Sci., 2007, 62, 4012–4024.
- 378 Y. A. Zhu, D. Chen, X. G. Zhou and W. K. Yuan, Catal. Today, 2009, 148, 260–267.
- 379 S. Chen, J. Zaffran and B. Yang, Appl. Catal., B, 2020, 270, 118859.
- 380 W.-Y. Wang and G.-C. Wang, Catal. Sci. Technol., 2021, 1395–1406.
- 381 Z. Xie, Q. Liao, M. Liu, Z. Yang and L. Zhang, Energy Convers. Manage., 2017, 153, 526–537.
- 382 K. H. Ernst, C. T. Campbell and G. Moretti, J. Catal., 1992, 134, 66–74.
- 383 C. S. Chen, W. H. Cheng and S. S. Lin, Appl. Catal., A, 2004, 257, 97–106.
- 384 L. Wang, S. Zhang and Y. Liu, J. Rare Earths, 2008, 26, 66–70.
- 385 M. C. J. Bradford and M. A. Vannice, J. Catal., 1998, 173, 157–171.
- 386 H. Purnama, T. Ressler, R. E. Jentoft, H. Soerijanto, R. Schlögl and R. Schomäcker, Appl. Catal., A, 2004, 259, 83–94. **Mini review Catalysis Science & Technology**

Soleh and R. Science Articles. Published and R. Science Article 2021. The CO2 CR, 2021. A Science Article is clear and R. Hermann Sole P. F. Contains, and D. H. King, Colled,
	- 387 J. K. Lee, J. B. Ko and D. H. Kim, Appl. Catal., A, 2004, 278, 25–35.
	- 388 K. Hou and R. Hughes, Chem. Eng. J., 2001, 82, 311–328.
	- 389 H. C. Wu, Y. C. Chang, J. H. Wu, J. H. Lin, I. K. Lin and C. S. Chen, Catal. Sci. Technol., 2015, 5, 4154–4163.
	- 390 M. J. L. Ginés, A. J. Marchi and C. R. Apesteguía, Appl. Catal., A, 1997, 154, 155–171.
	- 391 C. T. Campbell and K.-H. Ernst, Surface Science of Catalysis, American Chemical Society, 1992, vol. 482, pp. 130–142, DOI: 10.1021/bk-1992-0482.ch008.
	- 392 C. S. Chen, J. H. Wu and T. W. Lai, J. Phys. Chem. C, 2010, 114, 15021–15028.
	- 393 A. Wolf, A. Jess and K. Christoph, Chem. Eng. Technol., 2016, 298, 1040–1048.
	- 394 J. A. Hernandez Lalinde, P. Roongruangsree, J. Ilsemann, M. Bäumer and J. Kopyscinski, Chem. Eng. J., 2020, 390, 124629.
	- 395 W. Benzinger, E. Daymo, M. Hettel, L. Maier, C. Antinori, P. Pfeifer and O. Deutschmann, Chem. Eng. J., 2019, 362, 430–441.
	- 396 P. Marocco, E. A. Morosanu, E. Giglio, D. Ferrero, C. Mebrahtu, A. Lanzini, S. Abate, S. Bensaid, S. Perathoner, M. Santarelli, R. Pirone and G. Centi, Fuel, 2018, 225, 230–242.
	- 397 J. Lefebvre, S. Bajohr and T. Kolb, Fuel, 2019, 239, 896–904.
	- 398 Z. Bian, Y. M. Chan, Y. Yu and S. Kawi, Catal. Today, 2020, 347, 31–38.
	- 399 G. Garbarino, C. Wang, T. Cavattoni, E. Finocchio, P. Riani, M. Flytzani-Stephanopoulos and G. Busca, Appl. Catal., B, 2019, 248, 286–297.
	- 400 S. Rönsch, J. Köchermann, J. Schneider and S. Matthischke, Chem. Eng. Technol., 2016, 39, 208–218.
	- 401 F. Koschany, D. Schlereth and O. Hinrichsen, Appl. Catal., B, 2016, 181, 504–516.
	- 402 J. H. Chiang and J. R. Hopper, Ind. Eng. Chem. Prod. Res. Dev., 1983, 22, 225–228.
	- 403 J. K. Kesavan, I. Luisetto, S. Tuti, C. Meneghini, G. Iucci, C. Battocchio, S. Mobilio, S. Casciardi and R. Sisto, J. CO2 Util., 2018, 23, 200–211.
	- 404 J. Yang Lim, J. McGregor, A. J. Sederman and J. S. Dennis, Chem. Eng. Sci., 2016, 141, 28–45.
	- 405 O. Mohan, S. Shambhawi, X. Rong, A. A. Lapkin and S. H. Mushrif, ChemCatChem, 2021, 13, 2420–2433.
	- 406 A. Loder, M. Siebenhofer and S. Lux, J. Ind. Eng. Chem., 2020, 85, 196–207.
	- 407 X. Wang, Y. Hong, H. Shi and J. Szanyi, J. Catal., 2016, 343, 185–195.
	- 408 G. D. Weatherbee and C. H. Bartholomew, J. Catal., 1984, 87, 352–362.
	- 409 T. Kai, T. Takahashi and S. Furusaki, Can. J. Chem. Eng., 1988, 66, 343–347.
	- 410 L. Falbo, M. Martinelli, C. G. Visconti, L. Lietti, C. Bassano and P. Deiana, Appl. Catal., B, 2018, 225, 354–363.
- 411 M. S. Duyar, A. Ramachandran, C. Wang and R. J. Farrauto, J. CO2 Util., 2015, 12, 27–33.
- 412 T. Avanesian, G. S. Gusmão and P. Christopher, J. Catal., 2016, 343, 86–96.
- 413 A. K. Raghu and N. S. Kaisare, Ind. Eng. Chem. Res., 2020, 59, 16161–16169.
- 414 C. Seidel, A. Jörke, B. Vollbrecht, A. Seidel-Morgenstern and A. Kienle, Chem. Eng. Sci., 2018, 175, 130–138.
- 415 T. Fujitani, I. Nakamura, T. Uchijima and J. Nakamura, Surf. Sci., 1997, 383, 285–298.
- 416 M. Peter, M. B. Fichtl, H. Ruland, S. Kaluza, M. Muhler and O. Hinrichsen, Chem. Eng. J., 2012, 203, 480–491.
- 417 A. Karelovic, G. Galdames, J. C. Medina, C. Yévenes, Y. Barra and R. Jiménez, J. Catal., 2019, 369, 415–426.
- 418 J. F. Portha, K. Parkhomenko, K. Kobl, A. C. Roger, S. Arab, J. M. Commenge and L. Falk, Ind. Eng. Chem. Res., 2017, 56, 13133–13145.
- 419 K. Ahmad and S. Upadhyayula, Fuel, 2020, 278, 118296.
- 420 X. Jiang, X. Wang, X. Nie, N. Koizumi, X. Guo and C. Song, Catal. Today, 2018, 316, 62–70.
- 421 M. S. Frei, M. Capdevila-Cortada, R. García-Muelas, C. Mondelli, N. López, J. A. Stewart, D. Curulla Ferré and J. Pérez-Ramírez, J. Catal., 2018, 361, 313–321.
- 422 S. Ghosh, J. Sebastian, L. Olsson and D. Creaser, Chem. Eng. J., 2021, 416, 129120.
- 423 G. H. Graaf, E. J. Stamhuis and A. A. C. M. Beenackers, Chem. Eng. Sci., 1988, 43, 3185–3195.
- 424 K. M. V. Bussche and G. F. Froment, Appl. Catal., A, 1994, 112, 37–55.
- 425 K. M. Vanden Bussche and G. F. Froment, J. Catal., 1996, 161, 1–10.
- 426 T. S. Askgaard, J. K. Norskov, C. V. Ovesen and P. Stoltz, J. Catal., 1995, 156, 229–242.
- 427 C. V. Ovesen, B. S. Clausen, J. Schiøtz, P. Stoltze, H. Topsøe and J. K. Nørskov, J. Catal., 1997, 168, 133–142.
- 428 J. Ye, C. J. Liu, D. Mei and Q. Ge, J. Catal., 2014, 317, 44–53.
- 429 D. L. Chiavassa, S. E. Collins, A. L. Bonivardi and M. A. Baltanás, Chem. Eng. J., 2009, 150, 204–212.
- 430 D. Zambrano, J. Soler, J. Herguido and M. Menéndez, Top. Catal., 2019, 62, 456–466.
- 431 H. Zhou, T. Zhang, Z. Sui, Y. A. Zhu, C. Han, K. Zhu and X. Zhou, Appl. Catal., B, 2018, 233, 143–159.
- 432 G. D. Wehinger, T. Eppinger and M. Kraume, Chem. Eng. Sci., 2015, 122, 197–209.
- 433 D. Pakhare, V. Schwartz, V. Abdelsayed, D. Haynes, D. Shekhawat, J. Poston and J. Spivey, J. Catal., 2014, 316, 78–92.
- 434 U. Olsbye, T. Wurzel and L. Mleczko, Ind. Eng. Chem. Res., 1997, 36, 5180–5188.
- 435 J. Wei and E. Iglesia, J. Phys. Chem. B, 2004, 108, 4094–4103.
- 436 X. E. Verykios, Chem. Ind. Chem. Eng. Q., 2002, 8, 238–255.
- 437 M. M. B. Quiroga and A. E. C. Luna, Ind. Eng. Chem. Res., 2007, 46, 5265–5270.
- 438 A. B. Mhadeshwar and D. G. Vlachos, J. Phys. Chem. B, 2005, 109, 16819–16835.

- 439 K. H. Delgado, L. Maier, S. Tischer, A. Zellner, H. Stotz and O. Deutschmann, Catalysts, 2015, 5, 871–904.
- 440 L. M. Aparicio, J. Catal., 1997, 165, 262–274.
- 441 D. Chen, R. Lødeng, A. Anundskås, O. Olsvik and A. Holmen, Chem. Eng. Sci., 2001, 56, 1371–1379.
- 442 M. Younas, L. L. Kong, M. J. K. Bashir, H. Nadeem, A. Shehzad and S. Sethupathi, Energy Fuels, 2016, 30, 8815–8831. Catalysis Science & Technology Www.106000 MW (Weather Access Article 2021. 20
	- 443 H.-H. Greev, Ullmann's Encyclopedia of Industrial Chemistry, Wiley-VCH Verlag GmbH & Co. KGaA, 2000.
	- 444 E. Giglio, R. Pirone and S. Bensaid, Renewable Energy, 2021, 170, 1040–1051.
	- 445 S. Pérez, J. J. Aragón, I. Peciña and E. J. Garcia-Suarez, Top. Catal., 2019, 62, 518–523.
	- 446 K. P. Brooks, J. Hu, H. Zhu and R. J. Kee, Chem. Eng. Sci., 2007, 62, 1161–1170.
	- 447 M. Bracconi, M. Ambrosetti, M. Maestri, G. Groppi and E. Tronconi, Chem. Eng. Process., 2018, 129, 181–189.
	- 448 R. Balzarotti, M. Ambrosetti, A. Beretta, G. Groppi and E. Tronconi, Chem. Eng. J., 2020, 391, 123494.
	- 449 S. Cimino, E. M. Cepollaro, L. Lisi, S. Fasolin, M. Musiani and L. Vázquez-Gómez, Catalysts, 2021, 11, 1–15.
	- 450 V. Meille, Appl. Catal., A, 2006, 315, 1–17.
	- 451 R. Uglietti, M. Bracconi and M. Maestri, React. Chem. Eng., 2020, 5, 278–288.
	- 452 C. Jia, Y. Dai, Y. Yang and J. W. Chew, Particuology, 2020, 49, 55–64.
	- 453 H. Nam, J. H. Kim, H. Kim, M. J. Kim, S. G. Jeon, G. T. Jin, Y. Won, B. W. Hwang, S. Y. Lee, J. I. Baek, D. Lee, M. W. Seo and H. J. Ryu, Energy, 2021, 214, 118895.
	- 454 E. Jwa, S. B. Lee, H. W. Lee and Y. S. Mok, Fuel Process. Technol., 2013, 108, 89–93.
	- 455 M. Nizio, A. Albarazi, S. Cavadias, J. Amouroux, M. E. Galvez and P. Da Costa, Int. J. Hydrogen Energy, 2016, 41, 11584–11592.
	- 456 F. Azzolina-Jury, D. Bento, C. Henriques and F. Thibault-Starzyk, J. CO2 Util., 2017, 22, 97–109.
- 457 E. Meloni, M. Martino, A. Ricca and V. Palma, Int. J. Hydrogen Energy, 2021, 46, 13729–13747.
- 458 S. Renda, M. Cortese, G. Iervolino, M. Martino, E. Meloni and V. Palma, Catal. Today, 2020, DOI: 10.1016/j. cattod.2020.11.020.
- 459 K. De Ras, R. Van de Vijver, V. V. Galvita, G. B. Marin and K. M. Van Geem, Curr. Opin. Chem. Eng., 2019, 26, 81–87.
- 460 A. I. Stankiewicz and H. Nigar, React. Chem. Eng., 2020, 5, 1005–1016.
- 461 G. H. Xiu, P. Li and A. E. Rodrigues, Chem. Eng. Sci., 2003, 58, 3425–3437.
- 462 O. S. Joo, K. D. Jung, I. Moon, A. Y. Rozovskii, G. I. Lin, S. H. Han and S. J. Uhm, Ind. Eng. Chem. Res., 1999, 38, 1808–1812.
- 463 S. Saeidi, N. A. S. Amin and M. R. Rahimpour, J. CO2 Util., 2014, 5, 66–81.
- 464 R. P. W. J. Struis, M. Quintilii and S. Stucki, J. Membr. Sci., 2000, 177, 215–223.
- 465 F. Samimi, D. Karimipourfard and M. R. Rahimpour, Chem. Eng. Res. Des., 2018, 140, 44–67.
- 466 F. Gallucci and A. Basile, Int. J. Hydrogen Energy, 2007, 32, 5050–5058.
- 467 P. Rodriguez-Vega, A. Ateka, I. Kumakiri, H. Vicente, J. Ereña, A. T. Aguayo and J. Bilbao, Chem. Eng. Sci., 2021, 234, 116396.
- 468 K. I. Sawamura, T. Shirai, M. Takada, Y. Sekine, E. Kikuchi and M. Matsukata, Catal. Today, 2008, 132, 182–187.
- 469 S. Guffanti, C. G. Visconti, J. van Kampen, J. Boon and G. Groppi, Chem. Eng. J., 2021, 404, 126573.
- 470 S. Guffanti, C. G. Visconti and G. Groppi, Ind. Eng. Chem. Res., 2021, 60, 6767–6783.
- 471 A. Zachopoulos and E. Heracleous, J. CO2 Util., 2017, 21, 360–367.
- 472 P. Maksimov, A. Laari, V. Ruuskanen, T. Koiranen and J. Ahola, Chem. Eng. J., 2021, 418, 129290.
- 473 C. Sriakkarin, W. Umchoo, W. Donphai, Y. Poo-arporn and M. Chareonpanich, Catal. Today, 2018, 314, 114–121.