## **RSC Advances**



## CORRECTION

View Article Online
View Journal | View Issue



Cite this: RSC Adv., 2021, 11, 33661

## Correction: Comparative study of the extrinsic properties of poly(lactic acid)-based biocomposites filled with talc *versus* sustainable biocarbon

Michael R. Snowdon, ab Feng Wu, b Amar K. Mohanty\*ab and Manjusri Misra\*ab

DOI: 10.1039/d1ra90158c

rsc.li/rsc-advances

Correction for 'Comparative study of the extrinsic properties of poly(lactic acid)-based biocomposites filled with talc *versus* sustainable biocarbon' by Michael R. Snowdon *et al.*, *RSC Adv.*, 2019, **9**, 6752–6761, DOI: 10.1039/C9RA00034H.

The authors regret that the values given for oxygen and water vapor permeability in Table 1 were incorrect in the original article. The correct version of the table is shown here.

Table 1 Oxygen and water vapor permeability of the PLA composites and their diffusion path length with tortuosity factors

Sample	Oxygen permeability at 23 $^{\circ}$ C and 0% RH (cm $^{3}$ mm m $^{-2}$ day $^{-1}$ atm $^{-1}$ )	Water vapor permeability at 38 $^{\circ}$ C and 100% RH (g mm m <sup>-2</sup> day <sup>-1</sup> )	Total path of diffusing gas (μm)	Tortuosity factor
PLA	$7.37 \pm (0.39)$	$16.83 \pm (0.69)$	0.63	1.00
PLA/talc	$5.66 \pm (0.09)$	$12.50 \pm (0.67)$	0.78	1.23
PLA/BC	$8.50 \pm (0.25)$	$19.58 \pm (0.57)$	0.64	1.01
$PLA/BC_{24\ h}$	$8.38 \pm (0.17)$	$16.84 \pm (0.27)$	0.66	1.04

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

<sup>&</sup>quot;School of Engineering, Thornbrough Building, University of Guelph, 80 South Ring Rd E, Guelph, Ontario, N1G 1Y4, Canada. E-mail: mmisra@uoguelph.ca; mohanty@uoguelph.ca; snowdonm@uoguelph.ca

<sup>&</sup>lt;sup>b</sup>Bioproducts Discovery & Development Centre (BDDC), Department of Plant Agriculture, Crop Science Building, University of Guelph, 117 Reynolds Walk, Guelph, Ontario, N1G 1Y4, Canada. E-mail: fengwu@uoguelph.ca