RSC Advances



View Article Online

CORRECTION

Check for updates

Cite this: RSC Adv., 2021, 11, 33661

Correction: Comparative study of the extrinsic properties of poly(lactic acid)-based biocomposites filled with talc *versus* sustainable biocarbon

Michael R. Snowdon,^{ab} Feng Wu,^b Amar K. Mohanty^{*ab} and Manjusri Misra^{*ab}

DOI: 10.1039/d1ra90158c

rsc.li/rsc-advances

Correction for 'Comparative study of the extrinsic properties of poly(lactic acid)-based biocomposites filled with talc *versus* sustainable biocarbon' by Michael R. Snowdon *et al., RSC Adv.,* 2019, **9**, 6752–6761, DOI: 10.1039/C9RA00034H.

The authors regret that the values given for oxygen and water vapor permeability in Table 1 were incorrect in the original article. The correct version of the table is shown here.

Tahla 1	Ovugen and water vanor ne	α meability of the PLA c	omnosites and their diffusion	path length with tortuosity factors
Table I	Oxygen and water vapor pe		omposites and their unrusion	path tengen with tortuosity factors

Sample	Oxygen permeability at 23 °C and 0% RH (cm ³ mm m ⁻² day ⁻¹ atm ⁻¹)	Water vapor permeability at 38 °C and 100% RH (g mm m ⁻² day ⁻¹)	Total path of diffusing gas (μm)	Tortuosity factor
PLA	$7.37 \pm (0.39)$	$16.83 \pm (0.69)$	0.63	1.00
PLA/talc	$5.66 \pm (0.09)$	$12.50 \pm (0.67)$	0.78	1.23
PLA/BC	$8.50 \pm (0.25)$	$19.58 \pm (0.57)$	0.64	1.01
PLA/BC _{24 h}	$8.38 \pm (0.17)$	$16.84 \pm (0.27)$	0.66	1.04

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

[&]quot;School of Engineering, Thornbrough Building, University of Guelph, 80 South Ring Rd E, Guelph, Ontario, N1G 1Y4, Canada. E-mail: mmisra@uoguelph.ca; mohanty@ uoguelph.ca; snowdonm@uoguelph.ca

^bBioproducts Discovery & Development Centre (BDDC), Department of Plant Agriculture, Crop Science Building, University of Guelph, 117 Reynolds Walk, Guelph, Ontario, N1G 1Y4, Canada. E-mail: fengwu@uoguelph.ca