

CORRECTION

[View Article Online](#)
[View Journal](#) | [View Issue](#)

Cite this: *Mater. Adv.*, 2023, 4, 1202

DOI: 10.1039/d3ma90005c

rsc.li/materials-advances

Correction: Insulative wood materials templated by wet foams

Elisa S. Ferreira,^{ab} Elizabeth Dobrzanski,^{bc} Praphulla Tiwary,^d Prashant Agrawal,^d Richard Chen^d and Emily D. Cranston^{*ac}

Correction for 'Insulative wood materials templated by wet foams' by Elisa S. Ferreira *et al.*, *Mater. Adv.*, 2023, 4, 641–650, <https://doi.org/10.1039/d2ma00852a>.

The authors regret that the y-axis label in Fig. 6b was shown incorrectly in the original article. The correct version of Fig. 6b is shown here.




Fig. 6 Mechanical properties of wood foams prepared with wood/PVA ratios of 2, 3, and 4: (a) stress–strain diagrams under compressive strain showing three compressive regions: (I) elastic, (II) plateau, and (III) densification; (b) compressive strength at 10% compression according to ASTM Standard (D1621-16).

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

^a Department of Wood Science, University of British Columbia, Vancouver, BC, V6T 1Z4, Canada. E-mail: emily.cranston@ubc.ca

^b Bioproducts Institute, University of British Columbia, Vancouver, BC, V6T 1Z4, Canada

^c Department of Chemical and Biological Engineering, University of British Columbia, Vancouver, BC, V6T 1Z4, Canada

^d Plantee Bioplastics Inc., Vancouver, Canada