

## CORRECTION

[View Article Online](#)  
[View Journal](#) | [View Issue](#)Cite this: *J. Mater. Chem. A*, 2024, 12, 24703**Correction: Redox-active conductive metal–organic framework with high lithium capacities at low temperatures**Yogendra Kumar,<sup>a</sup> Tae Hyeong Kim,<sup>b</sup> Iyan Subiyanto,<sup>ID ac</sup> Winda Devina,<sup>ID a</sup> Segi Byun,<sup>ID a</sup> Subhajit Nandy,<sup>d</sup> Keun Hwa Chae,<sup>d</sup> Suim Lim,<sup>ID e</sup> Bumjin Kim,<sup>ID b</sup> Sanghui Kang,<sup>ID b</sup> Seong Ok Han,<sup>a</sup> Kanghoon Yim,<sup>ID \*e</sup> Jungjoon Yoo,<sup>ID \*b</sup> and Hyunuk Kim,<sup>ID \*ac</sup>

DOI: 10.1039/d4ta90157f

[rsc.li/materials-a](https://rsc.li/materials-a)Correction for 'Redox-active conductive metal–organic framework with high lithium capacities at low temperatures' by Yogendra Kumar *et al.*, *J. Mater. Chem. A*, 2024, <https://doi.org/10.1039/D4TA01779J>.

The authors regret that on the fifth page of the original article, the sentence beginning 'When the cycling performance of SKIER-5 was tested...' contained an error. The current density referred to should have been '2C (907 mA g<sup>−1</sup>)', rather than '200 mA g<sup>−1</sup>'. Similarly, the original caption of Fig. 2(d) referred to 'Cycling stability and coulombic efficiency at 200 mA g<sup>−1</sup>' for the SKIER-5 sample; this too should be corrected to 'Cycling stability and coulombic efficiency at 2C (907 mA g<sup>−1</sup>)'.

An error has also been corrected in the supplementary information (SI). In Table S2 on page 8 of the SI, the entry for SKIER-5 which read '700 mA h g<sup>−1</sup> after 1600 cycles at 200 mA g<sup>−1</sup>' previously has been updated to '600 mA h g<sup>−1</sup> after 1600 cycles at 2C (907 mA g<sup>−1</sup>)'. Please refer to the original article web page to access the supplementary information.

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

<sup>a</sup>Hydrogen Convergence Materials Laboratory, Korea Institute of Energy Research, 152 Gajeong-ro, Yuseong-gu, Daejeon 34129, Republic of Korea. E-mail: [hyunuk@kier.re.kr](mailto:hyunuk@kier.re.kr)<sup>b</sup>Energy Storage Research Department, Korea Institute of Energy Research, 152 Gajeong-ro, Yuseong-gu, Daejeon, Republic of Korea. E-mail: [jjyoo@kier.re.kr](mailto:jjyoo@kier.re.kr)<sup>c</sup>Energy Engineering, University of Science and Technology, 217 Gajeong-ro, Yuseong-gu, Daejeon, Republic of Korea<sup>d</sup>Advanced Analysis Center, Korea Institute of Science and Technology, 5, Hwarang-ro 14-gil, Seongbuk-gu, Seoul, Republic of Korea<sup>e</sup>Energy AI & Computational Science Laboratory, Korea Institute of Energy Research, 152 Gajeong-ro, Yuseong-gu, Daejeon 34129, Republic of Korea. E-mail: [khyim@kier.re.kr](mailto:khyim@kier.re.kr)