



## Introduction to Advances in nanophotonics, plasmonics, and nano-optics

Viktoriia E. Babicheva,<sup>ID</sup>\*<sup>a</sup> Yu-Jung Lu,<sup>ID</sup><sup>b</sup> Alexander Shalin<sup>c</sup> and Dattatray Late<sup>ID</sup><sup>d</sup>Cite this: *Nanoscale Adv.*, 2025, 7, 6674

DOI: 10.1039/d5na90067k

rsc.li/nanoscale-advances

Nanophotonics, plasmonics, and nano-optics have entered a transformative stage, where fundamental theories are rapidly translating into experimental advances and device-level realizations, enabling unprecedented control over light at the nanoscale. Recent progress encompasses the design of optical nano-antennas, novel nanostructures, and self-organized composites that significantly enhance light-matter interactions, leading to breakthroughs in near-field optics, nonlinear responses, and quantum photonics. These developments have expanded the possibilities of spectroscopy, microscopy, and advanced imaging, offering new means of probing material properties with high precision. Research has also uncovered anomalies in light scattering and transport in nanomaterials, deepening our understanding of optical response in complex systems. With advancements in nano-fabrication techniques, nano-optical trapping, and ultrafast optically induced magnetism, nanophotonics is pushing

the boundaries of sensing, information processing, and functional material design, establishing itself as a cornerstone of modern optical science.

Polarisation imaging extends conventional imaging by revealing surface and material properties that remain hidden to standard intensity or colour techniques, with full-Stokes measurements enabling advanced data processing for remote sensing. An ultra-thin topology-optimised diffractive metasurface that encodes polarisation states into five diffraction orders within a telescope pupil plane is introduced, allowing for single-shot full-Stokes acquisition on a single detector [<https://doi.org/10.1039/D5NA00298B>]. The design provides stitched wide-field coverage, simultaneous error monitoring, and a compact, lightweight solution that overcomes the size and weight constraints of small-satellite platforms.

Rare-earth-doped phosphors are widely investigated for their structural, optical, and catalytic properties, with a particular interest in their potential applications in solid-state lighting and photocatalysis. A Dy<sup>3+</sup>-doped sodium zinc molybdate phosphor has been synthesised *via* a green microwave-assisted route, confirmed by P-XRD to crystallise in a monoclinic *C2/m* structure [<https://doi.org/10.1039/D4NA00960F>].

Photoluminescence studies revealed a dominant excitation at 348 nm and

a sharp emission at 590 nm from the  ${}^4F_{9/2} \rightarrow {}^6H_{13/2}$  transition, with optimal intensity at 6 mol% Dy<sup>3+</sup>. The phosphor exhibited orangish chromaticity and enhanced UV-driven photocatalytic activity, demonstrating multifunctional performance.

Conventional microwave-based techniques face fundamental limitations in characterizing nano-antennas at frequencies above a few terahertz, restricting progress in the study and design of plasmonic antennas. A new methodology has been introduced that employs electron energy loss spectroscopy (EELS) to determine input impedance and scattering parameters from the mid-infrared to optical range. A theoretical framework has been developed to relate EEL probability to microwave scattering parameters, which has been validated through experiments and simulations on a single plasmonic dipole [<https://doi.org/10.1039/D4NA00960F>].

The approach enables the extraction of *S*-parameters and impedance across the 25–150 THz range, offering a non-contact alternative to VNA-like characterization at otherwise inaccessible frequencies.

Surface plasmon interference has long served as a basis for optical metrology and sensing. In [<https://doi.org/10.1039/D4NA00862F>], a novel interferometer has been presented that employs paired grating couplers to excite surface

<sup>a</sup>Department of Electrical and Computer Engineering, University of New Mexico, MSC01 11001, University of New Mexico, Albuquerque, New Mexico 87131, USA. E-mail: vbb@unm.edu

<sup>b</sup>Research Center for Applied Sciences, Academia Sinica, Taipei City 115201, Taiwan

<sup>c</sup>Suzhou City University, 1188 Wuzhong Blvd, Wuzhong District, Suzhou, Jiangsu, 215104, China

<sup>d</sup>Department of Physics, Federal University of Lavras, Campus Universitário, PO Box 3037, Lavras, Minas Gerais 37200-000, Brazil. E-mail: datta099@gmail.com



plasmon polaritons along a gold–air interface before their convergence at a nanoslit. The interference response has been controlled by tailoring nanoslit geometry to support multiple resonance modes. Experimental validation has confirmed that adjusting coupler and nanoslit parameters has enabled tunable transmission. Furthermore, grating-induced focusing and far-field interference patterns have been demonstrated.

Surface-enhanced Raman spectroscopy has been recognized as a powerful

technique for ultrasensitive molecular analysis, eliminating the need for selective binding. In [<https://doi.org/10.1039/d4na00742e>], a comprehensive workflow for SERS substrate development has been established using two-photon polymerization. Individual nanopillars with high aspect ratios have been fabricated by direct laser writing, enabling substantial field enhancement. The substrates have exhibited Raman signal amplification on the order of  $10^6$ , rivaling the performance of commercial devices. Prototyping has been completed within minutes to hours,

and reproducibility has been achieved through the uniform fabrication of nanostructure arrays.

Kagome metals have attracted attention as platforms for exploring correlated and topological charge dynamics. A systematic investigation of FeSn has been performed in [<https://doi.org/10.1039/D4NA00737A>], revealing that optical conductivity is governed by two Drude responses originating from Dirac and massive bands, with the Dirac channel dominating at low temperatures. Cooling has shifted the spectral weight



**Viktoriia E. Babicheva**

*Dr Viktoriia E. Babicheva has been an Assistant Professor at the University of New Mexico since 2019. She completed her postdoctoral training at the University of Arizona and previously worked at Purdue University and Georgia State University. Babicheva leads a research laboratory focused on nanophotonics, optics, and materials research. Babicheva is the lead author or co-author of over 80 peer-reviewed articles,*

*60 conference proceedings, two book chapters, one teaching handbook, and one monograph. She serves as an Associate Editor for Nano Select (Wiley) and SPIE Journal of Optical Microsystems, and is a Senior Member of IEEE, SPIE, and Optica.*



**Yu-Jung Lu**

*Dr Yu-Jung Lu is an associate research fellow at the Research Center for Applied Sciences, Academia Sinica, and an associate professor in the Department of Physics at the National Taiwan University. She earned her PhD in physics from the National Tsing Hua University, Taiwan, in 2013, and later joined Prof. Harry Atwater's research group at Caltech as a postdoctoral researcher from 2015 to 2017. Lu is a renowned*

*materials physicist who specializes in nitride-based plasmonics, nanophotonics, and metasurfaces. Her research focuses on plasmonic nanodevices that enable the harvesting, generation, and manipulation of light at the nanoscale.*



**Alexander Shalin**

*Prof. Alexander S. Shalin (Doctor of Sciences, Habil.) is an expert in nanophotonics and optomechanics, recognized for pioneering work in super-scattering, hybrid anapole states, and optomechanical light–matter interaction at the nanoscale. He is Professor at Suzhou City University and Beijing Institute of Technology, leading international projects on all-dielectric nanophotonics, metasurfaces, non-Hermitian*

*photonics, and optical tweezers. Author of 200+ peer-reviewed papers (5000+ citations, h-index 50/46), three monographs, and patents, he has organized major conferences, including MOST2024, and edited special issues in top journals. He has supervised 10+ PhDs, fostering global careers, and continues advancing next-generation photonic technologies.*



**Dattatray Late**

*Dr Dattatray Late obtained a PhD in Physics from University of Pune in 2008. He worked as a postdoctoral fellow at JNCASR and at Northwestern University (USA). He was awarded the highly prestigious Ramanujan Fellowship at the CSIR-NCL. Currently working as visiting Professor at Federal University of Lavras. He has published 270 research papers with 22800 citations, h-index of 70 and i-10 index of 205. He has edited 04*

*books, filed several patents, and is a Fellow of Royal Society of Chemistry, listed as the top 2% scientist by Stanford University in Applied Physics and top materials scientists by research.com.*



to lower frequencies as Dirac carrier mobility has risen due to reduced electron–phonon scattering. Interband dielectric measurements have matched density functional calculations, and the charge response of FeSn has been fully characterized for prospective photonic and plasmonic applications.

Metallenses have emerged as flat optical components capable of replacing conventional curved lenses by offering precise light control in a compact form. An artificial intelligence framework has been developed in [<https://doi.org/10.1039/D5NA00550G>] to predict the transmission and phase behavior of nanorod-based metasurfaces. Transfer learning has been applied using datasets of gallium nitride and titanium dioxide nanopillars on silica, with accuracy confirmed through experimental validation. The method has achieved low mean squared errors across the visible range, and focusing tests with two flat lenses have demonstrated practical viability. Angle-dependent response has also been assessed, showing potential for broader optical device design.

Surface-enhanced Raman scattering is renowned for its sensitivity; however, its reliability has often been limited by signal fluctuations related to substrate quality, polarization, and molecular distribution. A plasmonic chip has been fabricated in [<https://doi.org/10.1039/D4NA00387J>] to overcome these constraints by combining a periodic metallic grating with gold nanocubes, forming a 3D metasurface. Polarization-independent ultrahigh enhancement has been achieved, while signal averaging and normalization have reduced variability. The platform has enabled multimodal sensing through SERS, SEF, and SPR. Tests with rhodamine 6G and picric acid have demonstrated strong enhancement factors and a detection limit down to 3 nM.

Artificial intelligence has become a key enabler in the development of advanced photonic materials, offering unprecedented possibilities for

manipulating light. Photonic crystals, plasmonic structures, and metamaterials have been engineered to achieve tailored optical responses, with PhCs drawing particular attention due to their self-assembly capabilities and distinctive properties such as bandgaps, reflectance, and visible-range lasing [<https://doi.org/10.1039/D5NA00449G>]. Recent works have reported progress in cost-effective fabrication of 3D nano-PhCs, where AI has been utilized to optimize design and manufacturing. Enhanced lasing performance and miniaturized optoelectronic devices have been demonstrated, highlighting promising applications in energy harvesting and intelligent systems.

Two-dimensional semiconductors have been widely explored as building blocks for next-generation light-emitting devices due to their tunable optical properties. A dual-colored emitter has been realized by applying AC carrier injection through separate electrodes with a controlled phase delay, allowing balanced output from WSe<sub>2</sub> and WS<sub>2</sub> monolayers [<https://doi.org/10.1039/D5NA00623F>]. This method has provided stable, spectrally distinct emissions with dynamic controllability. A balanced operation between the two materials has been achieved, and the approach has expanded opportunities for compact, multicolor optoelectronics, with implications for integrated photonic circuits and high-resolution display technologies.

Surface-enhanced Raman scattering has remained a subject of active investigation since its discovery more than five decades ago, with several fundamental aspects still under exploration. Recent experiments have revealed distinctive axial variations of SERS profiles by scanning the laser focus relative to a planar nanostructured substrate. Signal strength has exhibited Lorentzian behavior along the *Z* axis, with maxima consistently occurring above the surface [<https://doi.org/10.1039/D4NA00982G>]. Ratios between spectral components have also varied with axial position.

Finite-difference time-domain simulations have attributed these effects to plasmonic near-field interactions, underscoring the importance of focus precision in quantitative SERS measurements.

Flexible sensing platforms have garnered interest due to their lightweight, adaptable nature and ability to conform to complex surfaces, providing advantages for detection in diverse environments. A plasmonic metamaterial sensor has been fabricated by nano-imprinting silver-coated polyvinylidene fluoride film, producing nanoscale arrays that act as polarization channels to support resonant enhancement [<https://doi.org/10.1039/D4NA00942H>]. These structures have significantly amplified SERS signals while improving reproducibility. Mechanical deformation of the piezoelectric substrate has further boosted Raman responses. Tests at 532 nm have demonstrated over an order of magnitude enhancement across multiple analytes, indicating strong potential for diagnostic, environmental, and trace detection applications.

As Guest Editors of this themed issue, we warmly thank the authors for their excellent contributions, the anonymous reviewers for their careful evaluation and time commitment, and the *Nanoscale Advances* editorial team, especially Dr Hannah Kerr, for their consistent guidance and support in bringing this collection to completion.

## Acknowledgements

V. E. B. is partly supported by the National Science Foundation under Award 2418519 and the Center for Integrated Nanotechnologies, an Office of Science User Facility operated for the U.S. Department of Energy (DOE) Office of Science by Los Alamos National Laboratory (Contract 89233218CNA000001) and Sandia National Laboratories (Contract DE-NA-0003525).

