



Cite this: *Nanoscale*, 2025, **17**, 7511

Correction: Simulation of the resistance switching performance and synaptic behavior of TiO₂-based RRAM devices with CoFe₂O₄ insertion layers

Fei Yang,* Bo Hu, Zijian He, Bingkun Liu, Shilong Lou, Duogui Li and Wentao Wang

DOI: 10.1039/d5nr90044a

rsc.li/nanoscale

Correction for 'Simulation of the resistance switching performance and synaptic behavior of TiO₂-based RRAM devices with CoFe₂O₄ insertion layers' by Fei Yang *et al.*, *Nanoscale*, 2024, **16**, 6729–6738, <https://doi.org/10.1039/D3NR05935A>.

The authors regret that in the original article, eqn (6), (7), (9) and (10) in section 2.1 were given incorrectly. The correct versions of equations (6), (7), (9) and (10) are shown below.

$$\frac{\partial n_D}{\partial t} = -\nabla \cdot j + G - R = \nabla \cdot (D\nabla n_D - vn_D) + G - R \quad (6)$$

$$\nabla \cdot \sigma \nabla \psi = 0 \quad (7)$$

$$\rho C_p \frac{\partial T}{\partial t} - \nabla \cdot K_{th} \nabla T = Q = J \cdot E = \sigma |\nabla \psi|^2 \quad (9)$$

$$-\nabla \cdot K_{th} \nabla T = \sigma |\nabla \psi|^2 \quad (10)$$

The Royal Society of Chemistry apologises for these errors and any consequent inconvenience to authors and readers.

School of Integrated Circuits, Anhui University, Hefei 230601, China. E-mail: feiyang-0551@163.com

