ChemComm

Accepted Manuscript



This is an *Accepted Manuscript*, which has been through the Royal Society of Chemistry peer review process and has been accepted for publication.

Accepted Manuscripts are published online shortly after acceptance, before technical editing, formatting and proof reading. Using this free service, authors can make their results available to the community, in citable form, before we publish the edited article. We will replace this Accepted Manuscript with the edited and formatted Advance Article as soon as it is available.

You can find more information about *Accepted Manuscripts* in the **Information for Authors**.

Please note that technical editing may introduce minor changes to the text and/or graphics, which may alter content. The journal's standard <u>Terms & Conditions</u> and the <u>Ethical guidelines</u> still apply. In no event shall the Royal Society of Chemistry be held responsible for any errors or omissions in this *Accepted Manuscript* or any consequences arising from the use of any information it contains.



Journal Name

RSCPublishing

COMMUNICATION

Electrochemical Flow-Reactor for Expedient Synthesis of Copper-N-Heterocyclic Carbene Complexes

Cite this: DOI: 10.1039/x0xx00000x

Michael R. Chapman, Yarseen M. Shafi, Nik Kapur, *Bao N. Nguyen* and Charlotte E. Willans*

Received ooth January 2012, Accepted ooth January 2012

DOI: 10.1039/x0xx00000x

www.rsc.org/

An electrochemical flow-cell for highly efficient and selective generation of Cu^I-N-heterocyclic carbene complexes under neutral and ambient conditions is reported. The feasibility of the flow-cell is demonstrated through the electrochemical synthesis of [Cu(IMes)Cl] and subsequent *in situ* flow directly into hydrosilylation reactions, with equal efficiency to the purified catalyst.

Since their isolation in 1991, 1 N-heterocyclic carbenes (NHCs) have become ubiquitous in organometallic chemistry and catalysis, including hydrogenation, hydrosilylation, crosscoupling reactions and olefin metathesis.²⁻⁵ In recent years, metal-NHCs have also shown significant promise in biomedicine, particularly within the fields of antimicrobials and cancer chemotherapy. 6-8 The most common synthetic methods to prepare metal-NHCs use imidazolium salt precursors and often require the use of strong bases and strict inert conditions, or the use of basic metal precursors (e.g. Ag₂O). 9-12 The major disadvantages of these routes include the generation of unstable intermediates, formation of undesirable side-products and incompatibility with base-sensitive substituents. Chen and coworkers reported a simple and practical procedure for the production of metal-NHCs using N-pyridine or N-pyrimidine substituted imidazolium salts and metal plates. 13 We reported a valuable extension to this model by using ligands that do not comprise a pendant donor arm, to produce selectively both neutral and cationic complexes. 14 As basic conditions are not necessary, the route was found to be compatible with basesensitive substituents, thus significantly widening the range of NHCs that may be developed. During the electrochemical reaction, an imidazolium ion (electrolyte) is reduced at the cathode, releasing H₂ to form a free NHC. Concomitantly, oxidation of the sacrificial copper anode occurs, liberating Cu⁺ ions into solution. These two species combine to deliver the desired Cu-NHC complex (Scheme 1).

(a)
$$R^1 + N - R^2 = \frac{e^-}{-\frac{1}{2}H_2} R^1 + N - R^2$$

$$R^3 + R^3 = \frac{e^-}{N - N - R^2} R^1 + N - R^2$$
(b) $M(s) = \frac{-ne^-}{N - N - R^2} R^1 + N - R^2$

Scheme 1 Electrochemical synthesis of metal-NHC complexes: (a) reduction of imidazolium to a free NHC; (b) oxidation of metal; (c) combination of NHC and metal.

Practical issues associated with the electrochemical batch process exist: (i) a large overpotential is required due to inefficient mass-transfer between the electrode surfaces; (ii) Faradaic efficiency tends to be low (Q generally >2). These problems can be overcome by moving into continuous mode, making the technology more accessible for academic, industrial and clinical use. An electrochemical microreactor for the synthesis of organic compounds in flow has previously been reported. Herein, we report the design, construction and optimisation of an electrochemical flow-reactor for the synthesis of both neutral heteroleptic and cationic homoleptic Cu^I-NHC complexes. To the best of our knowledge, this is the first example of the electrochemical synthesis of metal complexes in continuous flow.

Our first prototype consists of a PTFE linear flow-channel (190 x 4 x 3.5 mm), which supports two parallel copper electrodes (190 x 4 x 0.5 mm) at a separation distance of 2.5 mm (see Supporting Information). The effective volume of the flow-channel is 1.9 cm^3 . Preliminary experiments in MeCN under a N₂ atmosphere indicated that a significant amount of undesired [Cu(NHC)₂][CuCl₂] (3) was formed, likely due to the large distance between electrodes and consequently poor mixing between the carbene and [Cu(NCMe)₄]⁺ (Scheme 2). Glass beads (dia. 2.0 mm) were packed into the flow channel in

ChemComm Page 2 of 4

staggered formation to reduce the effective volume of the reactor to 1.05 cm³ and increase flow velocity. Residence time inside the cell was reduced and the formation of **3** was completely suppressed. All subsequent data recorded in the first flow-cell was therefore with the use of glass beads.

COMMUNICATION

Mes
$$\stackrel{+}{\underset{N-Mes}{\bigvee}}$$
 CI $\stackrel{-}{\underset{N-Mes}{\bigvee}}$ Mes $\stackrel{-}{\underset{N-Mes}{\bigvee}}$

Scheme 2 Concomitant electrochemical reduction/complexation of [IMesH]Cl 1 in flow.

Flow-rate and applied potential were optimised for efficiency and selectivity using a solution of [IMesH]Cl (6.6 mM) in MeCN (Fig. 1). The reduction potential of [IMesH]Cl in MeCN was determined to be -2.32 V (versus Fc/Fc⁺) by cyclic voltammetry (see ESI). Maximum conversion in singlepass mode was achieved with an applied potential of 2.5 V and flow-rate of 0.5 mL min⁻¹ (residence time = 126 seconds), giving Cu(IMes)Cl (2) in 36% yield. An insoluble copper species was formed when a voltage ≥ 3 V was applied, with the current density at 2.5 V being calculated as 0.36 mA cm⁻² (Table 1). When the concentration of [IMesH]Cl was increased five-fold, a decrease in conversion (25% yield) was observed, indicating that the surface area of the electrode is the limiting factor. Recirculation of the 6.6 mM solution (20 mL, 0.132 mmol) allowed full conversion of 1 to give complex 2 in 92% yield after 80 minutes, a significant improvement on the yield in batch (59%). 14 A small amount of imidazolinone 4 (8%) was observed, presumably as a consequence of air being introduced into the reactor during recirculation. Oxo-adducts of related NHCs have previously been observed, and can be induced from the imidazolium salt using CsOH.16 The overall Faradaic efficiency of the cell was 98%.




Fig. 1 Schematic diagram for the electrochemical synthesis of 2 in continuous mode.

To further increase the electrode surface area, a second modular reactor design was developed. Six square copper plates (50 x 50 x 1 mm), separated by five PTFE spacers (1 mm thickness cut with a 4 mm wide and 200 mm long flow

channel) were assembled as shown in Fig. 2. The copper plates alternate between cathode and anode to provide five consecutive parallel-plate electrochemical flow-reactors. This design allows reactor metrics (channel length, width, electrode separation, interfacial area and reactor volume) to be optimised as required. The short distance between electrodes and the tailored channel shape minimise the diffusive ion path-length and cell resistivity, whilst optimising current density. The second flow-cell had a total volume of 4.0 mL, and the surface areas of the anode and cathode electrodes were 40 cm² each.

Journal Name




Fig. 2 Photograph of the second-generation electrochemical flow-reactor (left) and the shape of the reactor channel through a 1 mm thick Teflon spacer (right).

Experimental evaluation of the revised flow-cell provided significant improvements in both the electrochemical output and selectivity. At 1.94 V and 0.67 mL min⁻¹ (residence time = 360 seconds), a yield of 94% of complex 2 was achieved in single-pass mode. Imidazolinone 4 was reduced to 3%, presumably due to reduced distance between the electrodes increasing the rate of formation of Cu(IMes)Cl 2. The lower potential required highlights the improved efficiency of the second flow-cell, and its capacity to selectively form desired complexes in the presence of redox sensitive functional groups. The overall reaction time to convert 0.132 mmol of [IMesH]Cl to complex 2 was reduced to 29.9 minutes (20 mL, 0.67 mL min⁻¹, single-pass). A comparison between the performance of the two electrochemical flow-cells is summarised in Table 1.

Table 1 Comparison of the electrochemical synthesis of Cu(IMes)Cl (2) in first- and second-generation flow-reactors.

	1st Flow-	2nd Flow-
	cell	cell
Single electrode surface area (cm ²)	7.6	40
Distance between electrodes (mm)	2.5	1.0
Applied potential (V)	2.50	1.94
Observed current (mA) ^a	2.7	10.0
Current density (mA·cm ⁻²)	0.36	0.25
Residence time (s)	126	360
Time to convert 0.132 mmol of 1 to 2 (mins)	$80.0~(92\%)^b$	29.9 (97%) ^c

a registered at steady-state; b in recirculation mode; c in single-pass mode.

The versatility of the second-generation flow-cell was examined using a variety of imidazolium precursors (Table 2). These included *N*-substituents with decreased steric bulk (entries 3-6), in addition to base-sensitive allyl and ester *N*-substituents (entries 3-4) and a macrocyclic imidazolium salt (entry 6). Furthermore, imidazolium hexafluorophosphate salts

Journal Name COMMUNICATION

ChemComm

were assessed (entries 2, 5-6), which form exclusively cationic homoleptic complexes. A variety of Cu^I-NHC complexes were prepared selectively and in high yields, validating that the optimised cell is suitable for the efficient synthesis of a broad range of Cu^I-NHCs.

Table 2 Scope of Cu^I-NHC complexes prepared under continuous electrochemical conditions in the second-generation flow-cell.

$$R \xrightarrow{X} Cu_{(s)} X \xrightarrow{Cu_{(s)}} Or R \xrightarrow{X} Or R \xrightarrow{X} Cu \xrightarrow{X} Or Cu \xrightarrow{X} Cu \xrightarrow{X} Or Cu \xrightarrow{X$$

	R	R'	X-	E_{appl}	I	τ_{R}	Yield
				(V)	$(mA)^c$	(mins)	$(\%)^d$
1	mesityl ^a	mesityl	Cl	1.94	10.0	29.9	94
2	mesityl ^a	mesityl	PF_6	2.54	20.1	20.0	93
3	picolyl ^a	allyl	Br	2.20	19.3	6.7	91
4	methyl ^a	CH ₂ CO ₂ ^t Bu	Cl	2.40	31.0	13.3	95
5	benzyl ^a	benzyl	PF_6	2.95	28.7	20.0	94
6	Cyclophane ^b		PF ₆	4.90	74.4	300	95

 $[^]a$ in single-pass mode; b in recirculation mode; c registered at steady-state; d analysed by $^1{\rm H}$ NMR spectroscopy.

To demonstrate the synthetic utility of our electrochemical flow-cell, the output stream containing complex 2 (i.e. formed in entry 1) in MeCN was introduced directly from the flow-cell into catalytic hydrosilylation reactions of functionalised ketones (Table 3). Near quantitative isolated yields, which were comparable to those reported by Nolan using CuCl/[IMesH]Cl as pre-catalyst, were achieved. 17 Identical reaction conditions using our 'dispensed' catalyst were reproduced using isolated and purified 2 as a catalyst, to provide very similar yields. The shorter reaction times observed by Nolan and co-workers when using in situ generated catalysts are likely to be a consequence of the formation of Cu¹-bis-NHC complexes. Such complexes were reported to be much more reactive, highlighting the importance of selective complex formation.¹⁷ Our results demonstrate the potential of the electrochemical flow-reactor as an 'on-demand dispenser' of high purity catalyst directly into a reaction without the need for isolation and work-up.

Table 3 Hydrosilylation reactions using catalyst 2 directly from the electrochemical flow-cell.

0	HSiEt ₃ (5 eq.), 2 (3 mol%)	O SiEt₃	
R R'	NaO ^f Bu, Toluene, 80 °C	R∕R'	

R	R'	Time	Yield	Time	Yield
		$(h)^a$	(%) ^{a,b}	(h) ^c	$(\%)^{b, c}$
Cyclohexyl	Cyclohexyl	2	97	2	98
2-Furyl	Methyl	6	95	6	94
2-Thiophenyl	Methyl	6	97	6	97
2-Pyridyl	Methyl	6	94	6.5	90
2-Chlorophenyl	Methyl	5	97	6	98

^a Using catalyst from electrochemical flow-cell in MeCN; ^b isolated yield; ^c using isolated and purified catalyst 2.

Conclusions

Two simple and effective electrochemical flow-reactors have been reported which perform highly selective and efficient syntheses of Cu^I-NHC complexes in excellent yields under neutral and ambient conditions. This was achieved through rational design and construction of a flow-cell to maximise interfacial area and mixing of species generated from the two electrodes, which resulted in much more controlled electrochemical conditions. The synthetic utility of the cell has been demonstrated through the preparation of a range of Cu^I-mono- and bis-NHCs comprising varying N-substituents. In addition, the flow-cell can be used to 'dispense' Cu(IMes)Cl 2 as catalyst directly into catalytic hydrosilylation reactions with virtually no difference in catalytic activity when compared to isolated catalyst.

Notes and references

- ^a School of Chemistry, University of Leeds, Woodhouse Lane, Leeds, LS2 9JT.
- ^b School of Mechanical Engineering, University of Leeds, LS2 9JT.

Acknowledgements: We would like to thank AstraZeneca for funding towards the first-generation flow-cell and the High Value Chemical Manufacturing Hub at Leeds for funding the second-generation flow-cell. Electronic Supplementary Information (ESI) available: Synthetic and catalytic procedures, CV data and cell design and optimisation. See DOI: 10.1039/c000000x/

- A. J. Arduengo, R. L. Harlow and M. Kline, J. Am. Chem. Soc., 1991, 113, 361-363.
- 2. W. A. Herrmann, Angew. Chem.-Int. Edit., 2002, 41, 1290-1309.
- M. N. Hopkinson, C. Richter, M. Schedler and F. Glorius, *Nature*, 2014, **510**, 485-496.
- E. A. B. Kantchev, C. J. O'Brien and M. G. Organ, *Angew. Chem.-Int. Edit.*, 2007, 46, 2768-2813.
- J. A. Mata, M. Poyatos and E. Peris, Coord. Chem. Rev., 2007, 251, 841-859
- K. M. Hindi, M. J. Panzner, C. A. Tessier, C. L. Cannon and W. J. Youngs, Chem. Rev., 2009, 109, 3859-3884.
- 7. L. Mercs and M. Albrecht, Chem. Soc. Rev., 2010, 39, 1903-1912.
- D. C. F. Monteiro, R. M. Phillips, B. D. Crossley, J. Fielden and C. E. Willans, *Dalton Trans.*, 2012, 41, 3720-3725.
- W. A. Herrmann and C. Kocher, Angew. Chem.-Int. Edit., 1997, 36, 2162-2187.
- D. Bourissou, O. Guerret, F. P. Gabbai and G. Bertrand, *Chem. Rev.*, 2000, **100**, 39-91.
- 11. I. J. B. Lin and C. S. Vasam, Coord. Chem. Rev., 2007, 251, 642-670.
- C. E. Willans, K. M. Anderson, M. J. Paterson, P. C. Junk, L. J. Barbour and J. W. Steed, Eur. J. Inorg. Chem., 2009, 2835-2843.
- B. Liu, Y. Zhang, D. C. Xu and W. Z. Chen, *Chem. Commun.*, 2011, 47, 2883-2885.
- B. R. M. Lake, E. K. Bullough, T. J. Williams, A. C. Whitwood, M. A. Little and C. E. Willans, *Chem. Commun.*, 2012, 48, 4887-4889.

Journal Name

- K. Watts, W. Gattrell and T. Wirth, *Beilstein J. Org. Chem.*, 2011, 7, 1108–1114.
- 16. A. Petronilho, H. Muller-Bunz and M. Albrecht, *Chem. Commun.*, 2012, **48**, 6499-6501.
- 17. S. Diez-Gonzalez, E. D. Stevens, N. M. Scott, J. L. Petersen and S. P. Nolan, *Chem.-Eur. J.*, 2008, **14**, 158-168.