
Journal of Materials Chemistry C

Accepted Manuscript



This is an *Accepted Manuscript*, which has been through the Royal Society of Chemistry peer review process and has been accepted for publication.

Accepted Manuscripts are published online shortly after acceptance, before technical editing, formatting and proof reading. Using this free service, authors can make their results available to the community, in citable form, before we publish the edited article. We will replace this Accepted Manuscript with the edited and formatted Advance Article as soon as it is available.

You can find more information about *Accepted Manuscripts* in the **Information for Authors**.

Please note that technical editing may introduce minor changes to the text and/or graphics, which may alter content. The journal's standard <u>Terms & Conditions</u> and the <u>Ethical guidelines</u> still apply. In no event shall the Royal Society of Chemistry be held responsible for any errors or omissions in this *Accepted Manuscript* or any consequences arising from the use of any information it contains.



Chemical and electrochemical routes to DNA-templated rhodium nanowires.

Hasan Daw A. Mohamed, a,b Scott M. D. Watson, Benjamin R. Horrocks, and Andrew Houlton, Horrocks, and Andrew Houlton, and Horrocks, and Ho

Received (in XXX, XXX) Xth XXXXXXXXX 20XX, Accepted Xth XXXXXXXX 20XX 5 DOI: 10.1039/b000000x

Two methods for the preparation of rhodium nanowires are described: (i) electroless metal deposition at duplex DNA 'template' molecules in bulk solution and (ii) electrochemical reduction in DNA-containing solution at a modified electrode. Both methods render essentially similar 1D nanostructures with a Rh/Rh-oxide core-shell structure. AFM studies revealed the resulting nanostructures are typically <10 nm in diameter with continuous and smooth metal coatings. However, the latter method was less effective with samples containing an ~3-fold increase in the bare template DNA remaining. A combination of SPM methods demonstrated the structures to be electrically conducting, hence confirming their nanowire nature. The conductivity was, however, several orders of magnitude lower than that of bulk Rh; a fact attributed to the presence of resistance-increasing mechanisms, such as grain boundaries present in the Rh coatings and electron surface scattering.

Introduction

The confinement of metals to the nanometre regime provides materials with a range of novel and useful properties not necessarily exhibited by their bulk counterparts. Examples include optical properties such as plasmon resonance bands, fluorescence and photothermal properties and new-found reactivity in noble and platinum group metals (PGM). Is also offers the means to further miniaturization of existing technologies, such as in electronics.

Of the PGM, nanoscale rhodium has been relatively little studied outside of nanoparticle-driven catalysis. ¹⁷ However, new routes to the fabrication of nanostructured rhodium architectures remain of value due to their interesting properties which offer potential in areas such as fuel cells, solar energy conversion, and NEMS systems. ¹⁸⁻²¹

It is established that duplex DNA is an effective template for the growth of a range of material types²²⁻³⁰ as one-dimensional (1D) nanostructures^{31, 32} and this can be compatible³³ with complex nanostructured architectures formed by, so-called, DNA-origami.³⁴ The capacity for DNA to function in this role lies in its ability to interact with precursor species and facilitate anisotropic growth. Importantly, this DNA-based method can allow access to structures at the lower end of the nanometre range. It also provides the benefit over templating approaches using porous membranes (*e.g.* anodic aluminium oxide, ³⁵⁻³⁷ polycarbonate membranes, ³⁸ porous silica^{39, 40}) of avoiding the need for additional post-synthetic steps in order to remove the template and liberate the nanostructured material.

The preparation of metal nanowires (*e.g.* Au, ⁴¹⁻⁴³ Ag, ⁴⁴ Pd, ^{45, 46} Cu, ^{47, 48}, Co, ⁴⁹ Fe⁵⁰) most commonly involves chemical reduction of cationic metal species either at bare DNA, ⁴⁴⁻⁴⁸ or at DNA seeded with particles of a hetero-metal. ^{33, 41-43, 49} The latter act to provide a catalytic surface upon which the reductive deposition of the metal takes place. A novel galvanic displacement method has been described by Harb and Woolley for materials, such as Te

and Bi₂Te₃, which cannot readily be prepared by simple precipitation.⁵¹ More recently, we have reported metal templating onto native DNA using an electrochemical approach as a further statement of alternative.⁵⁰

Here, we compare two DNA-templating approaches for the preparation of 1D Rh nanostructures using (i) chemical and (ii) electrochemical reduction of Rh³⁺ ions. The resulting nanostructured materials have been characterised to evaluate their chemical, structural and electrical properties.

Results and Discussion

Synthesis of DNA-templated Rh nanowires

The preparation of Rh nanowires by DNA-templating *via* both chemical and electrochemical reduction routes was carried out using RhCl₃·H₂O as a source of Rh³⁺ ions. Seeding of the DNA with Rh³⁺ ions was carried out by addition of the Rh salt to an aqueous solution containing duplex DNA. Metal ion interactions with DNA, which can take place through non-covalent interactions as metal complex species with the DNA phosphate backbone and/or coordination to sites on the DNA backbone/nucleobases^{52, 53} were monitored by FTIR spectroscopy. Changes in the spectrum as a result of the treatment with the metal salt suggest that the Rh³⁺ ions interact with both types of sites (see SI, Fig S1).

Chemical reduction method. Chemical reduction of the Rh³⁺ species in the presence of DNA was carried out by the addition of NaBH₄ to the reaction solution. In order to determine the chemical composition of the product material following reduction, Rh/DNA_{Chem}, powder X-ray diffraction (XRD) and X-ray photoelectron spectroscopy (XPS) studies were conducted. Figure 1 shows the XRD pattern acquired from a sample of the isolated product material. Three prominent peaks can be distinguished in the diffraction pattern at 2θ values of 41.1°, 85 45.1° and 69.2°, which are consistent with the (111), (200) and

(220) reflections of metallic Rh. 54-58 The broadened appearance of the peaks is a result of the nanocrystalline nature of the Rh material formed.⁵⁹ Using the line width of the diffraction peaks (β = 4.9°, as defined by the full-width-at-half-maximum of the (111) 5 reflection), the average crystallite size was estimated from Scherrer's equation $(D = k\lambda/[\beta\cos\theta])^{60}$ to be ~2 nm (SI, Fig S2). No additional peaks were observed in the diffraction pattern, indicating that metallic Rh is the sole crystalline phase formed under the conditions used here.




Fig. 1 XRD pattern obtained from a powder sample of DNA-templated Rh material prepared via the chemical reduction method.

The XP survey scan spectrum of the Rh/DNA_{Chem} nanostructures (SI, Fig. S3) indicates that both DNA and rhodium 15 are present in the product. There are peaks for O1s, N1s, C1s and P2p arising from DNA and Rh3d and Rh3p due to the presence of Rh. The presence of Na1s and Cl2p peaks, arising from the starting materials, is also evident.

While XP analysis confirmed the presence of metallic Rh in the 20 product material, an additional Rh species was also identified. This is evident in the high-resolution spectrum of the Rh3d region (see Fig. 2), in which curve-fitting required two separate doublets to be modelled in order to accurately reproduce the shape of the spectrum. The dominant doublet shown in the fitting has 25 associated binding energies of 305.9 eV (3d_{5/2}) and 310.6 eV (3d_{3/2}) and splitting of 4.7 eV, in agreement with literature values for metallic Rh. 61-64 The second doublet in the envelope occurs at higher binding energy $(3d_{5/2} = 308.1 \text{ eV}; 3d_{3/2} = 312.9 \text{ eV})$ and is consistent with the Rh present in the +3 oxidation state.




Fig. 2 High resolution XPS spectrum of Rh3d region of calf thymus DNAtemplated Rh nanowires form by chemical reduction. The experimental data is shown (black dots) along with a curve fitting of the envelope (dashed lines).

35 Given the surface sensitive nature of the XPS technique the distinction between the XPS data and the XRD data, in which only metallic Rh was identified, suggests that the surface constitutes only a small proportion of the product material and is not present in the crystalline form. Detection of a Rh^{III} state is 40 consistent with a hydrolysis product, ⁶⁴⁻⁶⁶ i.e. an oxyhydroxide, present as a surface layer of the product material.⁶⁵ As Rh⁰ and Rh^{III} can both be distinguished in the Rh3d XPS spectrum, this would suggest that the surface oxyhydroxide layer is either sufficiently thin that the underlying Rh(0) can still be detected 45 (i.e. <2–10nm, being is the typical sampling depth of the XPS technique), or that the oxidized coating is only partial, and does not encapsulate the whole of the Rh(0) metal.

Based on these findings, it is suggested that the chemical reduction method used to form the Rh nanowires initially yields 50 metallic Rh(0), and the surface of the metal subsequently reacts by hydrolysis to form the Rh(III) product at the metal surface. However, for convenience the product material will be referred to as "DNA-templated Rh" throughout, or Rh/DNA_{Chem}.

55 Electrochemical reduction method. Similar to the chemical reduction route described above, electrochemical fabrication of DNA-templated Rh nanostructures involved initial "doping" of the DNA template with Rh³⁺ ions by reaction in solution. However, in order to carry out the electrochemical reduction, the 60 DNA/Rh3+ reaction solution was deposited on an n-doped Si<100> wafer, which acts as the working electrode in a manner previously described.⁵⁰ Prior to use, the wafer was modified with a monolayer of trimethylsilane (TMS) in order to increase the hydrophobic character of the surface. When the DNA/Rh³⁺ 65 solution is applied to the Si substrate, it sits on the surface as a hemispherical droplet. This was necessary in order to ensure that the counter and reference electrodes could be readily inserted into the reaction solution in order for the electrochemical process to be carried out.




Fig. 3 Cyclic voltammogram for an aqueous solution of calf thymus DNA and RhCl₃.xH₂O, supported upon n-doped Si<100> wafer, used as the working electrode.

5 Cyclic voltammograms were performed with the n-Si as the electrode in the reaction solutions during electrochemical formation of the DNA-templated Rh structures to monitor the reaction. Figure 3 shows a typical voltammogram, which is characterised by a single broad peak in the cathodic 10 sweep located around E = -0.49V; this is assigned to the reduction of the Rh³⁺ species to metallic Rh(0).⁶⁸ The presence of only a single peak in the cathodic sweep indicates the absence of stable intermediate Rh oxidation states during the reduction of the Rh³⁺ to metallic Rh⁰. It should also be noted that the curve shows 15 no peak in the reverse (anodic) scan, confirming that the reduction process is totally irreversible as expected at a semiconductor electrode in the absence of bandgap illumination. The as-prepared material was transferred to clean substrates for further analysis. As with the chemical reduction route, the XP 20 survey scan spectrum of the nanostructures prepared by this electrochemical templating approach, Rh/DNA_{Echem}, (SI, Fig. S4) indicated the presence of both DNA and rhodium the product. Peaks corresponding to Na1s and Cl2p, arising from the starting materials, are again also evident.

²⁵ Confirmation that the metallic phase of Rh was deposited on the DNA templates was found in the Rh3d region of the spectrum. The corresponding Rh3d region of the XP data, again, indicated two different oxidation states (figure 4) assigned to zerovalent Rh⁰, formed upon electrochemical reduction and the presence of a ³⁰ Rh(III)-oxyhydroxide species, as for the Rh/DNA_{Chem} sample. ⁶⁵ The major component, with low-binding energies at 307.2 and 311.8 eV for 3d_{5/2} and 3d_{3/2} respectively, is in agreement with reported values of metallic Rh^{0.54,59,69-75} The higher BE doublet (3d_{5/2}, 309.1eV; 3d_{3/2}, 313.5 eV) is again attributed to an ³⁵ oxidized. ⁷³⁻⁷⁵

While both synthetic routes produce material with similar composition, *i.e.* metallic Rh⁰ core encapsulated by an oxidized sheath, comparison of the Rh3d region of the XPS spectra appears to reveal a ~2-fold increase in the oxidized species for the electrochemically-prepared material. However, these nanowires are smaller (see Figure 5) than those prepared by the chemical route and therefore in view of the surface-sensitivity of XPS the true extent of oxidation are not substantially different.




Fig. 4 High resolution XPS spectrum of Rh3d region of DNA-templated Rh nanowires, prepared via the electrochemical reduction approach. The experimental data is shown (black dots), along with a curve fitting of the envelope (dashed lines).

Structural characterisation of Rh-nanowires

AFM was used to establish structural details of the prepared materials and to judge the effectiveness of DNA as a template to direct the growth of the metal. Samples suitable for imaging individual Rh nanostructures from both methods were prepared using molecular combing^{76, 77} upon TMS-modified silicon/native oxide substrate. Figure 5(a) shows AFM height images of some typical examples of the DNA-templated Rh nanostructures prepared *via* the chemical reduction method while Fig 5(b) shows material from the electrochemical route.

Analysis of material prepared in either case shows the structures to exhibit the high aspect-ratio of the template DNA molecules, but with larger diameter (bare DNA <2nm by AFM, see S7 in SI).‡ A statistical analysis (≥100 nanowires) of the heights of the structures, acquired from the AFM data, is also shown in Figure 5. These data indicates a range of diameters from 3–31nm, with a modal value of 6 nm from chemical reduction. This is rather larger than the value derived from the XRD data and indicates that the nanowires are comprised of particles smaller than the measured AFM diameter in a manner similar to our previously prepared DNA-templated Pd nanowires (SI, Fig S5). A range of 3-23 nm with a modal value of 3-4 nm was found for the sample prepared by the electrochemical route.

Upon further inspection of the AFM data it can be seen that the Rh coatings along the length of the DNA appear to be continuous and rather regular. However, in some images a variety of morphologies is observed which include structures at an earlier stage of nanowire formation (e.g. see red and yellow boxes Fig 5(b) and SI, Fig S6). These structures are identified as having a particles-on-a-string appearance, or display visible "necking", features that are consistent with a growth of the nanowires taking place by a "nucleation and growth" mechanism. The uniform




Fig. 5 (a) AFM height images of DNA-templated Rh nanowires, prepared via the chemical reduction method, immobilised upon a Si/native SiO₂ wafer, and a histogram showing the size (diameter) distribution of a sample of 100 nanowires. (b) AFM height images of DNA-templated Rh nanowires, prepared via the electrochemical reduction method, immobilised upon a Si/native SiO₂ wafer, and a histogram showing the size (diameter) distribution of a sample of 100 nanowires. The nanowire diameters recorded in the histograms were determined from line profile measurements carried out using AFM data.

structure formation observed here has been attributed to a combination of instantaneous nucleation on the template (which 10 favours uniform particle growth), and confinement of the nuclei to a 1D templates which results in inhibition of the growth of larger particles because they experience overlap with their neighbours sooner.50 Based on this, and the low temperature nature of the synthesis, the nanowires are expected to comprise 15 closely packed particles. Comparison of the AFM and XRD data indicates that the morphology of these Rh nanowires has similarities to previously-published Pd nanowires;⁷⁸ the crystallite size from XRD (2 nm) is too small to observe by microscopy and much less than the diameter of the nanowires. Pd and Rh are both 20 noble metals and the reduction leads to the formation of many small nuclei in a highly irreversible process far from equilibrium. Lattice-gas simulations show that the external appearance of such nanowires may be rather smooth despite their complex internal structure.78


25 It is useful to make comparison of the two different approaches to preparing Rh-nanowires. While both produce examples of regular, smooth, continuous structures the effectiveness in terms of DNA metallisation of the electrochemical approach is comparatively low. Based on the statistical analysis, the fraction of bare DNA remaining with this method is considerably greater,

by a factor of ~3, than for the chemical reduction (Note: structures with diameters ≤2 nm are judged to be DNA molecules which remain bare in the reaction solution⁷⁹ (Figure S7), whereas thicker structures >2 nm are predominately DNA-templated Rh nanowires). This can be understood from the fact that the former method involves electron transfer at the electrode surface and thus a much smaller fraction of Rh(III) species are reduced than in the bulk solution chemical reduction method.

Electrical Characterization: Characterisation of the electrical properties of the prepared Rh/DNA materials was performed in an effort to confirm their nanowire credentials using a combination of scanning probe microscopy (SPM) methods; specifically scanning conductance microscopy (SCM) and
 conductive AFM (cAFM). Initial investigations were carried out using SCM, as this provides a relatively simple means of rapidly establishing if such 1D nanostructures display electrical conductivity. These data, provided in the Supporting Information, indicate that the samples are electrically conducting (Fig S8-9).
 Electrical characterisation was extended to conductive AFM (cAFM) which, though more technically challenging due to the need to make contact with the nanowires, provides more quantitative information. In addition, the ability to control the

placement of the cAFM probe at specific points along the nanowire under investigation allows for distance-dependent measurements to be made. From this data the contribution to the nanowires resistance from the probe-nanostructure contact resistance can be extracted.

For these experiments we used our previously reported experimental method to perform these analyses. 25 Briefly, this involves drop-casting nanowires from solution onto a $\rm Si/SiO_2$ substrate to form a large deposit of the nanostructured material.






Fig. 6 (a) Plot of the calculated resistance of a DNA-templated Rh nanowires prepared by chemical reduction as a function of relative distance. Each i–V measurement carried out to calculated the distance-dependent resistance, was performed at a deflection setpoint value of 0.5V. (b) Resistance of electrochemically prepared DNA/Rh nanowires as a function of relative distance at deflection setpoint of 0.5V.

At the periphery of the resulting deposit, it is possible (by AFM imaging) to identify individual, or small bundles of the, nanowires protruding from the larger network, (see SI Fig S10).

20 In this setup, the dense nanowire network can be exploited as a macroscopic electrode in contact with the end of the protruding nanowire to be studied. The conductive probe used in cAFM experiments is employed to act as the second electrode to make electrical contact with the nanowire.

²⁵ Following acquisition of height/current data, an additional function of the cAFM mode was used to carry out i-V measurements in order to extract quantitative information regarding the nanowire's conductance. Here, the AFM probe was brought into contact at specific points along the length of the nanowire and i-V measurements recorded over the range of -5V to +5V. The nanowire resistance was subsequently estimated from the slope of the i-V curve around zero bias. It has previously been demonstrated that the information gathered in this manner can be used not only to determine the resistance per

35 unit length of the nanowire, but also to extract the contribution to the measured resistance from the probe–nanowire contact resistance.²⁵

Samples from both chemical and electrochemical reduction methods were investigated by these cAFM techniques and the 40 results are shown in Figure 6. From these data it was possible to calculate the resistance per unit length from the slope of the of best fit lines as; $Rh_{-Chem} = 2x10^{11}\Omega \cdot cm^{-1}$. $Rh_{-Echem} = 1 \times 10^{11} \Omega$ cm⁻¹. In order to estimate the nanowire conductivity, their diameter and width were determined by AFM in order to 45 calculate the cross-section area (assumed elliptical). Based on these calculations, the conductivity of the DNA/Rh nanowires were Rh- $Chem} = 0.015 S \cdot cm^{-1}$; Rh- $Echem} = 0.024 S cm^{-1}$ and the resistivities Rh-_{Chem} = 65Ω ·cm; Rh-_{Echem} = 41 Ω cm. The small difference in conductivity may relate to the mechanism of the 50 reduction; electrochemically-prepared NWs consist of Rh particles formed by a faradaic process and therefore individual nuclei must be in some sort of electrical contact. In contrast, individual nuclei in the chemically-reduced NWs need not necessarily be in electrical contact with each other.

55 These resistivities are considerably greater than that reported for Rh in bulk form $(4.7 \text{ x} 10^{-6} \Omega \text{ cm})$. Such increases in the material resistivity upon a reduction to the nanometre size regime are not uncommon, with the preparation of other metals in 1D nanoscale form showing increases in resistivity by several orders 60 of magnitude. 82-84 In the case of the Rh structures reported here, this increase in resistivity is suggested to be most likely the result of the granular character of the Rh coatings on the DNA strands, as indicated by AFM and XRD, and leading to electron scattering at particle-particle interfaces and the nanowire surface (Note: 65 resistance caused by surface scattering is expected to become increasingly significant as the diameter of the nanowire approaches and decreases below the bulk mean free path). There may also be a contribution from the formation of the oxyhydroxide layer on the nanowires surfaces, as indicated by the 70 XPS data.

Conclusion. Rhodium nanowires have been successfully produced using DNA-templating in conjunction with either chemical or electrochemical reduction. The association of the 75 metal cations with DNA templates directs the subsequent growth of the metallic Rh formed during the reduction step to give 1-D nanostructures. Chemical characterization of nanowires prepared using either method indicates these to comprise a metallic Rh⁰ core coated with oxidised Rh species. AFM studies indicated that 80 both methods allow the fabrication of DNA/Rh nanowires with, essentially, complete coverage of the DNA templates by the Rh material. Closer inspection of the structures produced showed a degree of granular character associated with coatings, indicating that the metal growth upon the DNA template took place via a 85 nucleation and growth mechanism. 85 Despite the apparent granular nature of the nanowires investigation of electric conductivity indicates that the nanowires are conducting and hence the coating continuous. However their room temperature conductivity value, calculated from i-V curves recorded by c-90 AFM, was similar and low at 0.015 Scm⁻¹ and 0.024 Scm⁻¹, for chemical and electrochemical reduction, respectively. Based on

the statistical analysis, the electrochemical method of preparation

was less efficient, leaving a larger number of DNA molecules essentially bare. However, despite this, the simple demonstration of forming metal structures by an electrochemical method suggests the possibility for success of templating at more 5 complex pre-assembled DNA-structures using high-resolution electrochemical techniques such as scanning electrochemical microscopy.

Experimental

10 Materials Rhodium(III) chloride hydrate (RhCl₃.xH₂O) (Rh 38.40 %) and calf thymus DNA (CT-DNA) (highly polymerised, 6 % sodium), were purchased from Sigma-Aldrich Company Ltd. (Gillingham, Dorset, UK) and used as received. Lambda DNA (λ-DNA, Cat. No. N3011S) was purchased from New England 15 Biolabs UK Ltd. (Hitchin, Hertfordshire, UK). Sodium borohydride (NaBH₄, 98%) was purchased from Alfa Aesar. Si<n-100> wafers (phosphorous doped, 525±50 μm thickness, 1-10 Ω ·cm resistance, single side polished), were used as substrate supports for TappingModeTM AFM imaging. Si<n-100> wafers 20 with a 200nm thick, thermally grown SiO₂ layer on top (arsenic doped, $500\pm25 \mu m$, $<0.005 \Omega$ cm resistance, thermal oxide layer 200 nm±10% thickness, double side polished) were used in scanned conductance microscopy and magnetic force microscopy experiments. All Si wafers were purchased from Compart 25 Technology Ltd. (Peterborough, Cambridgeshire, NANOpure® deionised water (18 M Ω cm resistivity) was obtained from a NANOpure® DIamondTM Life Science ultrapure water system equipped with a DIamondTM RO Reverse Osmosis System (Barnstead International).

Large-scale preparation of DNA/Rh material using chemical reduction method

Samples for XRD and XPS studies were prepared through addition of 10 mL of an aqueous solution of RhCl₃.xH₂O (2.5 mM) to 5 mL of a solution of CT-DNA (500 μg mL⁻¹). The mixture was left to stand for 10 days at room temperature, before adding a freshly prepared NaBH₄ (10 mL; 25 mM) solution in water. The reaction solution turned brownish-black in colour and the resulting colloidal solution was then centrifuged and ⁴⁰ concentrated in order to extract the DNA/Rh final material. The collected black powder was allowed to dry at room temperature prior to analysis.

Preparation of λ-DNA/Rh samples using chemical reduction as method

5 μL of an aqueous solution of λ-DNA (500 μg mL⁻¹) was mixed with 10 μL of an aqueous solution of RhCl₃.xH₂O (2.5 mM), and incubated for 10 days at room temperature. Then, a freshly prepared NaBH₄ (10 μL; 25 mM) solution in water was added. The resulting DNA-templated rhodium nanostructures formed in the reaction solution was allowed to stand for further 10 min before being aligned on the TMS-modified Si<n-100> or Si<n-100>/200 nm SiO₂ wafers for AFM and EFM measurements, respectively. For nanowires alignment, 5 μL of the DNA/Rh solution was applied to a TMS-modified wafer as previously described, whilst being spun at 125 rpm. The wafer was then spun for a further 2 minutes at 250 rpm before the residual solution was withdrawn from the surface by a micropipette.

Finally, nanowires-modified wafer was left to dry at room 60 temperature before performing scanning probe microscopy measurements.

Large-scale preparation of DNA/Rh material using an electrochemical reduction method

 $_{65}$ 40 $\,\mu L$ of an aqueous solution of RhCl3.xH2O (2.5 mM) was mixed with 20 µL of an aqueous solution of CT-DNA (500 µg mL⁻¹) and incubated at room temperature. Then, 40 μL of the reaction solution was applied to a chemically oxidized Si<n-100> substrate modified with a TMS SAM. The modified Si substrate 70 was used as the working electrode during the electrochemical reduction process, while the counter and reference electrodes were a tungsten wire with diameter of 0.25 mm, and Ag/AgCl, respectively. The hydrophobic nature of the modified Si substrate results in 'beading' of the deposited DNA/Rh⁺³ solution enabling 75 the counter and reference electrodes to be easily inserted into the solution droplet without contacting the substrate surface. Cyclic voltammetry measurements were performed using a computer-interfaced SECM CHI 900 electrochemical microscope system (CH Instruments, Austin, Texas, USA), sweeping the ₈₀ potential between E = 0.3 V and E = -0.3 V, with a scan rate of v = 0.1 Vs^{-1} , quiet time, t = 2.0 seconds, and sweep segments = 2.0 secondsAfter completion of the electrochemical reduction, the reaction solution was removed from the Si working electrode by micropipette and transferred to a fresh TMS-modified Si<p-100> 85 substrate. The solvent was allowed to evaporating at room temperature in order to produce a thin film of the product

Preparation of λ-DNA/Rh samples using an electrochemical 90 reduction method

For the AFM, EFM and MFM measurements, DNA/Rh samples were prepared using λ -DNA. Here, samples were prepared by mixing 10 μ L of an aqueous solution of RhCl₃.xH₂O (2.5 mM) and 5 μ L of an aqueous solution λ -DNA (500 μ g mL⁻¹). The resulting DNA/Rh³⁺ solution system was allowed to stand for 10 days at room temperature before performing any electrochemical reduction process. Cyclic voltammetry measurements were subsequently carried out upon a 5 μ L of the DNA/Rh³⁺ solution system deposited on Si working electrode.

Following the CV measurements, the resulting DNA/Rh nanowires in the reaction solution were transferred by micropipette into a new TMS-modified n-Si<100> wafer, and then aligned as described earlier.

105 FTIR Studies

materials for XPS analysis.

For FTIR studies, samples were prepared as films of material upon silicon substrates. Samples for DNA/Rh³+ were prepared by mixing an aqueous solution of CT-DNA (30 μL; 500 μg mL⁻¹) with an aqueous solution of RhCl₃.xH₂O (30 μL; 2.5 mM). The resulting DNA/Rh³+ solution were allowed to stand at room temperature for 20 minutes. After 20 minutes reaction time had elapsed, 80 μL of the reaction solution was deposited upon a silicon substrate, and allowing the solvent to evaporate at room temperature. Samples of bare DNA were prepared by depositing 80 μL of a CT-DNA solution (500 μg mL⁻¹) upon Si substrates and the solvent allowed to evaporate at room temperature. FTIR

70

115 25.

28.

spectra were performed with a Bio-Rad Excalibur FTS-40 spectrometer (Varian Inc., Palo Alto, CA, USA), and spectra were recorded over the 400–4000 cm⁻¹ range, with 128 scans and at 4 cm⁻¹ resolution.

Powder X-ray diffraction

Samples of DNA/Rh material were prepared for powder X-ray diffraction (XRD) analysis by drop-casting the reaction solution onto piranha-cleaned Si<n-100> wafer and allowing to dry at room temperature. A PAN-alytical X'Pert Pro diffractometer equipped with a Cu K α radiation source (λ = 1.540 Å) was used for powder XRD data collection.

X-ray photoelectron spectroscopy (XPS)

- 15 XPS analysis was carried out using a Thermo K-Alpha XPS system with a monochromated Al Kα X-ray source. An electron/ion gun was used to compensate for charge build-up on the sample during analysis, and all binding energies were referenced to the C1s hydrocarbon peak at 284.6eV.
- 20 Scanning probe microscopy
 - TappingMode™ AFM imaging was performed in air, using Multimode Nanoscope IIIa and Dimension Nanoscope V instruments (Veeco Instruments Inc., Metrology Group, Santa Barbara, CA), with TESP (n-doped Si cantilevers, resonant
- ²⁵ frequency = 230-410kHz, spring force constant = 20-80N/m Veeco Instruments Inc.), and Tap300Al-G (Si cantilevers, resonant frequency = 200-400kHz, spring force constant = 20-75N/m, BudgetSensors) probes. Data acquisition was carried out using Nanoscope software version 5.12b36 (Multimode) and
- Nanoscope software version 7.00b19 (Dimension Nanoscope V) (Veeco Instruments Inc., Digital Instruments). For both AFM systems, vibrational noise was reduced with an isolation table (Veeco Inc., Metrology Group).
- Scanning conductance microscopy (SCM) was performed in air, on a Dimension Nanoscope V system, using MESP probes (n-doped Si cantilevers, metallic Co/Cr coating, resonant frequency = 50-100kHz, spring force constant = 1-5N/m, Veeco Instruments Inc.). Data acquisition was carried out using Nanoscope version 7.00b19 software.
- 40 Conductive AFM (cAFM) experiments were performed on a Dimension Nanoscope V AFM, using MESP probes. Both topographical data (obtained in contact mode) and current maps were acquired simultaneously during cAFM operation. Samples for analysis were prepared as previously described.²⁵

45 Acknowledgements

X-ray photoelectron spectra were obtained at the National EPSRC XPS User's Service (NEXUS) at Newcastle University, an EPSRC mid-range facility. This work was financially supported by One North East, EU-FP7 project LAMAND (Contract no. 245565), EU ITN NANOEMBRACE (Contract no.

316751), Newcastle University, Azzaytuna University, Tarhuna, Libya, and the Libyan Government.

Notes and references

- 55 ^a Chemical Nanoscience Laboratories, School of Chemistry, Bedson Building, Newcastle University, Newcastle upon Tyne, NE1 7RU (UK). Email: andrew.houlton@ncl.ac.uk
- ^b Current address: Chemistry Department, Faculty of Arts and Science, Azzaytuna University, P.O. Box 39011/39010, Tarhuna, Libya
- † Electronic Supplementary Information (ESI) available: FTIR data and assignments, P-XRD fit, XPS, scheme, AFM, SCM and cAFM data. See DOI: 10.1039/b000000x/
- ‡ The theoretical diameter of a molecule of duplex DNA is 2nm, though 65 AFM is well-known to underestimate this size (likely due to tip-induced compression of the molecule), with values as low as <1.0nm commonly measured.
 - R. J. Gehr and R. W. Boyd, Chem. Mater., 1996, 8, 1807-1819.
 - U. Heiz and W. D. Schneider, Crit. Rev. Solid State Mater. Sci., 2001, 26, 251-290.
 - 3. G. Li and R. Jin, Acc. Chem. Res., 2013 46, 1749-1758.
 - 4. B. Lim and Y. Xia, Angew. Chem. Int. Ed., 2011, 50, 76-85.
- 75 5. P. Moriarty, Rep. Prog. Phys., 2001, **64**, 297-381.
- T. Nagao, G. Han, C. Hoang, J. S. Wi, A. Pucci, D. Weber, F. Neubrech, V. M. Silkin, D. Enders, O. Saito and M. Rana, *Sci. Tech. Adv. Mater.*, 2010 11, 054506.
- 7. H. F. Qian, M. Z. Zhu, Z. K. Wu and R. C. Jin, *Acc. Chem. Res.*, 2012, **45**, 1470-1479.
- N. S. Ramgir, Y. Yang and M. Zacharias, Small, 2010, 6, 1705-1722.
- 9. J. Sharma and T. Imae, J. Nanosci. Nanotech., 2009, 9, 19-40.
- 10. I. Diez and R. H. A. Ras, *Nanoscale*, 2011, **3**, 1963–1970.
- P. K. Jain, X. Huang, I. H. El-Sayed and M. A. El-Sayed, Acc. Chem. Res., 2008, 41, 1578-1586.
- G. J. Hutchings and C. J. Kiely, Acc. Chem. Res., 2013, 46, 1759-1772
- 13. L. L. Chng, N. Erathodiyil and J. Y. Ying, *Acc. Chem. Res.*, 2013, **46**, 1825-1837.
- S. Schauermann, N. Nilius, S. Shaikhutdinov and H.-J. Freund, Acc. Chem. Res., 2012, 46, 1673–1681.
- H. Zhang, M. Jin, Y. Xiong, B. Lim and Y. Xia, Acc. Chem. Res., 2013, 46, 1783–1794.
- 95 16. C. M. Leiber, MRS Bulletin, 2003, **28**, 486-491.
- Y. Yuan, N. Yan and P. J. Dyson, ACS Catalysis, 2012, 2, 1057-1069.
- B. R. Sathe, B. K. Balan and V. K. Pillai, *Energy Environ. Sci.*, 2011, 4, 1029-1035.
- D. A. Boyd, Y. Hao, C. Li, D. G. Goodwin and S. M. Haile, ACS Nano, 2013, 7, 4919-4923.
- M. Li, T. S. Mayer, J. A. Sioss, C. D. Keating and R. B. Bhiladvala, *Nano Lett.*, 2007, 7, 3281-3284.
- M. Zahmakiran, Y. Román-Leshkov and Y. Zhang, *Langmuir*, 2012, 28, 60-64.
- L. Dong, T. Hollis, B. A. Connolly, N. G. Wright, B. R. Horrocks and A. Houlton, *Adv. Mater.*, 2007, 19, 1748-1751.
- L. Dong, T. Hollis, S. Fishwick, B. A. Connolly, N. G. Wright, B. R. Horrocks and A. Houlton, *Chem. Eur. J.*, 2007, 13, 822-
- J. Hannant, J. H. Hedley, J. Pate, A. Walli, S. A. Farha Al-Said, M. A. Galindo, B. A. Connolly, B. R. Horrocks, A. Houlton and A. R. Pike, *Chem. Commun.*, 2010, 46, 5870-
 - R. Hassanien, M. Al-Hinai, S. A. Farha Al-Said, R. Little, L. Šiller, N. G. Wright, A. Houlton and B. R. Horrocks, *ACS Nano*, 2010, **4**, 2149-2159.
- R. Hassanien, S. A. Farha Al-Said, L. Šiller, R. Little, N. G. Wright, A. Houlton and B. R. Horrocks, *Nanotechnology*, 2012, 23, 075601.
- Y. Ma, J. Zhang, G. Zhang and H. He, J. Am. Chem. Soc., 2004, 126, 7097-7101.
 - H. D. A. Mohamed, S. M. D. Watson, B. R. Horrocks and A. Houlton, *Nanoscale*, 2012, 4, 5936-5945.
- S. Pruneanu, S. A. Farha Al-Said, L. Dong, T. A. Hollis, M. A. Galindo, N. G. Wright, A. Houlton and B. R. Horrocks, *Adv. Funct. Mater.*, 2008, **18**, 2444-2454.

75 65.

66.

67.

69.

90 72.

74.

75.

76.

78.

80.

81.

82.

83.

84

85.

- S. M. D. Watson, J. H. Hedley, M. A. Galindo, S. A. Farha Al-Said, N. G. Wright, B. A. Connolly, B. R. Horrocks and A. Houlton, *Chem. Eur. J.*, 2012, 18, 12008-12019.
- 31. A. Houlton, A. R. Pike, M. A. Galindo and B. R. Horrocks, *Chem. Commun.*, 2009, 1797-1806.
- 32. A. Houlton and S. M. D. Watson, *Annu. Rep. Prog. Chem. Sect. A*, 2011, **107**, 21-42.
- Y. Geng, A. C. Pearson, E. P. Gates, B. Uprety, R. C. Davis, J.
 N. Harb and A. T. Woolley, *Langmuir*, 2013, 29, 3482-3490.
- 10 34. P. W. K. Rothemund, *Nature*, 2006, **440**, 297.
 - D. Borissov, S. Isik-Uppenkamp and M. Rohwerder, *J. Phys. Chem. C*, 2009, **113**, 3133-3138.
- M.-M. Song, W.-J. Song, H. Bi, J. Wang, W.-L. Wu, J. Sun and M. Yu, *Biomaterials*, 2010, 31, 1509-1517.
- 15 37. Q. Wang, G. Wang, B. Xu, J. Jie, X. Han, G. Li, Q. Li and J. G. Hou, *Mater. Lett.*, 2005, 59, 1378-1382.
- J. Verbeeck, O. I. Lebedev, G. Van Tendeloo, L. Cagnon, C. Bougerol and G. Tourillon, J. Electrochem. Soc., 2003, 150, E468-E471.
- D. Wang, H. P. Jakobson, R. Kou, J. Tang, R. Z. Fineman, D. Yu and Y. Lu, *Chem. Mater.*, 2006, 18, 4231-4237.
- D. Wang, H. Luo, R. Kou, M. P. Gil, S. Xiao, V. O. Golub, Z. Yang, C. J. Brinker and Y. Lu, *Angew. Chem. Int. Ed.*, 2004, 43, 6169-6173.
- W. E. Ford, O. Harnack, A. Yasuda and J. M. Wessels, *Adv. Mater.*, 2001, 13, 1793-1797.
 - 42. K. Keren, R. S. Berman and E. Braun, *Nano Lett.*, 2004, **4**, 323-326.
- 43. K. Keren, M. Krueger, R. Gilad, G. Ben-Yoseph, U. Sivan and E. Braun, *Science*, 2002, **297**, 72-75.
- E. Braun, Y. Eichen, U. Sivan and G. Ben-Yoseph, *Nature*, 1998, 391, 775-778.
- J. Richter, M. Mertig, W. Pompe, I. Mönch and H. K. 105 79.
 Schackert, Appl. Phys. Lett., 2001, 78, 536-538.
- J. Richter, R. Seidel, R. Kirsch, M. Mertig, W. Pompe, J. Plaschke and H. K. Schackert, Adv. Mater., 2000, 12, 507-510.
- C. F. Monson and A. T. Woolley, *Nano Lett.*, 2003, 3, 359-363.
- 48. S. M. D. Watson, N. G. Wright, B. R. Horrocks and A. Houlton, *Langmuir*, 2010, **26**, 2068-2075.
- Q. Gu, C. Cheng and D. T. Haynie, *Nanotechnology*, 2005, 16, 1358 - 1363
- 50. S. M. D. Watson, H. D. A. Mohamed, B. R. Horrocks and A. Houlton, *Nanoscale*, 2013, **5**, 5349-5359.
- J. Lui, B. Uprety, S. Gyawali, A. T. Woolley, N. V. Myung and J. N. Harb, *Langmuir*, 2013, 29, 11176-11184.
- 52. Nucleic Acid Metal Ion Interactions, John Wiley & Sons, New York, 1980.
- 53. G. L. Eichhorn and Y. A. Shin, *J. Am. Chem. Soc.*, 1968, **90**,
- 54. H.-B. Pan and C. M. Wai, *J. Phys. Chem. C*, 2010, **114**, 11364-11369.
- Y. T. Jeon and G. H. Lee, *Journal of Applied Physics*, 2008, 103, 094313/094311-094313/094315.
- 103, 094313/094311-094313/094315. K. S. Lokesh, Y. Shivaraj, B. P. Dayananda and S. Chandra,
- Bioelectrochemistry, 2009, 75, 104-109.
 J. D. Hoefelmeyer, K. Niesz, G. A. Somorjai and T. D. Tilley, Nano Letters, 2005, 5, 435-438.
- 58. T. D. Ewers, A. K. Sra, B. C. Norris, R. E. Cable, C.-H. Cheng, D. F. Shantz and R. E. Schaak, *Chemistry of Materials*, 2005, **17**, 514-520.
- Y. Zhang, M. E. Grass, S. E. Habas, F. Tao, T. Zhang, P. Yang and A. Somorjai, J. Phys. Chem. C, 2007, 111, 12243-12253.
- 60. E. W. Nuffield, X-Ray Diffraction Methods, Wiley, New york, 1966
- Y. Baer, P. F. Heden, J. Hedman, M. Klasson, C. Nordling and K. Siegbahn, *Phys. Scripta*, 1970, 1, 55.
- A. M. Dennis, R. A. Howard, K. M. Kadish, J. L. Bean, J. Brace and N. Winograd, *Inorg. Chim. Acta*, 1980, 44, L139
- 70 63. N. Claessens, F. Demoisson, T. Dufour, A. Mansour, A. Felten, J. Guillot, J.-J. Pireaux and F. Reniers, Nanotechnology, 2010, 21, 385603

- Y. Okamoto, N. Ishida, T. Imanaka and S. Teranishi, *J. Catal.*, 1979, 58, 82.
 - F. A. Cotton, G. Wilkinson, C. A. Murillo and M. Bochman, Advanced Inorganic Chemistry, Wiley Interscience, USA, 1999.
 - Y. Zhang, M. E. Grass, S. E. Habas, F. Tao, T. Zhang, P. Yang and G. A. Somorjai, *J. Phys. Chem. C* 2007, **111**, 12243-12253.
 - Y. Abe, K. Kato, M. Kawamura and K. Sasaki, Surf. Sci. Spectra, 2001, 8, 117.
- 68. J. Wang and Z. Taha, *Talanta*, 1991, **38**, 489-492
 - V. Cimpeanu, M. Kočevar, V. I. Parvulescu and W. Leitner, *Angew. Chem. Int. Ed.*, 2009, **48**, 1085-1088.
- J. P. Contour, G. Mouvier, M. Hoogewys and C. Leclere, J. Catal., 1977, 48, 217-228.
- R. Nyholm and N. Mårtensson, J. Phys. C Solid State, 1980, 13, L279-L284.
 - C. Force, E. Román, J. M. Guil and J. Sanz, *Langmuir*, 2007, 23, 4569-4574.
- G. Gallaher, J. G. Goodwin Jr, C.-S. Huang and M. Houalla, Journal of Catalysis, 1991, 127, 719-731.
 - C. Sleigh, A. P. Pijpers, A. Jaspers, B. Coussens and R. J. Meier, *Journal of Electron Spectroscopy and Related Phenomena*, 1996, 77, 41-57.
 - J. P. Contour, G. Mouvier, M. Hoogewys and C. Leclere, *Journal of Catalysis*, 1977, **48**, 217-228.
 - J. Li, C. Bai, C. Wang, C. Zhu, Z. Lin, Q. Li and E. Cao, *Nucleic Acids Res.*, 1998, **26**, 4785-4786.
- 77. Z. Deng and C. Mao, Nano Lett., 2003, 3, 1545-1548.
 - M. N. Al-Hinai, R. Hassanien, N. G. Wright, A. B. Horsfall, A. Houlton and B. R. Horrocks, *Faraday Discuss.*, 2013, **164**, 71-91.
 - S. M. D. Watson, J. H. Hedley, M. A. Galindo, S. A. F. Al-Said, N. G. Wright, B. A. Connolly, B. R. Horrocks and A. Houlton, *Chemistry A European Journal*, 2012, **18**, 12008-12019.
 - G. K. White and S. B. Woods, *Philosophical Transactions of the Royal Society of London. Series A, Mathematical and Physical Sciences*, 1959, **251**, 273-302.
 - E. Y. Garcia and D. G. Loffler, *Journal of Chemical & Engineering Data*, 1985, **30**, 304-305.
 - K. Critchley, B. P. Khanal, M. L. Gorzny, L. Vigderman, S. D. Evans, E. R. Zubarev and N. A. Kotov, *Adv. Mater.*, 2010, 22, 2338-2342.
 - A. Bid, A. Bora and A. K. Raychaudhuri, *Phys. Rev. B*, 2006, **74**, 035426.
 - J. Pate, F. Zamora, S. M. D. Watson, N. G. Wright, B. R. Horrocks and A. Houlton, *J. Mater. Chem. C*, 2014, 2, 9265-9273.
 - S. M. D. Watson, A. Houlton and B. R. Horrocks, *Nanotechnology* 2014, **23**, 505603.

Graphical Abstract

Both electroless and electrochemical routes to the deposition of rhodium at duplex DNA 'template' molecules provide <20 nm 1D electrically conductive metal wires

