



Energy transfer and unusual decay behaviour of BaCa2Si3O9:Eu2+,Mn2+ phosphor

Journal:	Dalton Transactions
Manuscript ID:	DT-ART-02-2015-000591.R1
Article Type:	Paper
Date Submitted by the Author:	16-Apr-2015
Complete List of Authors:	Müller, Matthias; Münster University of Applied Sciences, Department of Chemical Engineering Jüstel, Thomas; Münster University of Applied Sciences, Department of Chemical Engineering

SCHOLARONE™ Manuscripts Journal Name

RSCPublishing

ARTICLE

Energy transfer and unusual decay behaviour of BaCa₂Si₃O₉:Eu²⁺,Mn²⁺ phosphor †

Cite this: DOI: 10.1039/xoxxooooox

Matthias Müller and Thomas Jüstel*

Received ooth January 2012, Accepted ooth January 2012

DOI: 10.1039/x0xx00000x

www.rsc.org/

In this work the photoluminescence (PL) of BaCa₂Si₃O₉:Eu²⁺,Mn²⁺ and the energy transfer (ET) between Eu²⁺ and Mn²⁺ was examined. Therefore, a series of powder samples with various Mn²⁺ concentrations were prepared by high temperature solid state route. Phase purity was investigated using x-ray powder diffractometry. Emission and excitation spectra as well as diffuse reflectance spectra were recorded to elucidate the PL properties of co-doped BaCa₂Si₃O₉:Eu²⁺,Mn²⁺. Furthermore, fluorescence lifetime measurements were performed. PL and lifetime measurements were carried out from 100 to 800 K and 100 to 500 K, respectively. Moreover, external quantum efficiencies were determined and colour points were calculated. It turned that ET from Eu²⁺ to Mn²⁺ is of a resonant type and occurs *via* dipolequadrupole interaction. Temperature dependent PL measurements indicate high temperature stability of emission intensity in BaCa₂Si₃O₉:Eu²⁺,Mn²⁺. Finally, it was found that fluorescence lifetimes of Eu²⁺ BaCa₂Si₃O₉ show an unusual increase with increasing temperature.

1. Introduction

Even though the invention of bright blue light emitting diodes (LEDs) by Nakamura et al. nearly dates back a quarter of a century, LEDs still have a vast impact on advances in lighting technology. 1 Meanwhile, LEDs replace more and more conventional light sources such as incandescent and discharge lamps. This is because of the fact that LEDs provide many benefits compared to thermal and gas discharge light sources, such as longer lifetimes, higher wall plug efficiency and higher colour rendering.² Nowadays, most of the commercially available white light emitting LEDs comprise a blue emitting (In,Ga)N chip pumping a green-yellow emitting phosphor, e.g. (Y,Gd)₃Al₅O₁₂:Ce³⁺. This setup provides a high luminous efficacy due to emission in the green spectral range. Unfortunately, these lamps suffer from high colour temperature and low colour rendering index due to the lack of emission in the red spectral range.³ Therefore, these light sources are unpopular for domestic lighting. To overcome these drawbacks, one approach is to use a phosphor blend comprising a blue, green, and red phosphor, which is excited by an ultraviolet emitting LED. Using this concept, cold and warm white emitting LEDs with excellent colour points can be realized.⁴ However, these packages underlie a loss in blue emission due to re-absorption by the green and red phosphors. For this reason, many research groups are developing single phase white emitting phosphors to convert UV radiation into white light.5

One approach to realize a white emitting phosphor is to use the ion couple Eu²⁺ and Mn²⁺.6 The broad emission bands in the blue and red spectral range of Eu2+ and Mn2+ in many host structures complement each other to white light due to additive colour mixing. Furthermore, Eu2+ usually exhibits a broad excitation band in the UV range due to the spin and parity allowed $[Xe]4f^{7}$ - $[Xe]4f^{6}5d^{1}$ interconfigurational electric-dipole transition. Therefore, Eu²⁺ is well appropriated for pumping by UV LEDs. Additionally the blue emission band of Eu²⁺ is also suitable to sensitize the spin and parity forbidden [Ar] $3d^5$ -[Ar] $3d^5$ excitation transitions of Mn²⁺ via energy transfer (ET). To investigate the photoluminescence (PL) properties as well as the ET from Eu²⁺ to Mn²⁺, a series of co-doped $BaCa_2Si_3O_9{:}Eu^{2+},Mn^{2+}$ samples with various Mn^{2+} concentrations was synthesized. BaCa₂Si₃O₉ was firstly described by the work of Eskola in 1922.7 Later on, in 1965 Alfors et al. investigated the mineral walstromite.⁸ Based on their results on optical properties and x-ray powder diffraction data they stated that BaCa₂Si₃O₉ is identical to walstromite. Glasser et al. reported on the crystal structure of synthetic BaCa₂Si₃O₉ using photographic x-ray diffraction data in 1968.⁹ The crystal structure derived from a single crystal analysis of BaCa₂Si₃O₉ was firstly published by Barkley et al. in 2011.¹⁰ Shortly afterwards, Yao et al. presented the first report on the blue emission of Eu²⁺ doped BaCa₂Si₃O₉. 11 Moreover, Gaft et al. published an article concerning the luminescence of natural walstromite in 2013.¹²

ARTICLE Journal Name

BaCa₂Si₃O₉ crystalizes triclinic with the space group P1; ... The structure of triclinic BaCa₂Si₃O₉ is built up of layers consisting of alternating Si₃O₉ rings. Between these layers Ba and Ca atoms are incorporated. BaCa2Si3O9 comprises two nonequivalent Ca sites, namely Ca1 and Ca2. The Ca1 site is coordinated by 8 oxygen atoms with a mean distance of 2.545 Å. The Ca2 site is surrounded by 6 oxygen atoms with an average bond length of 2.370 Å. The Ba atoms are 8-fold coordinated with an average distance of 2.841 Å. The ionic radii of Ca for 8 and 6-fold coordination are 1.12 and 0.96 Å. Ba²⁺ in 8-fold coordination has an ionic radius of 1.42 Å. The ionic radii of Mn2+ and Eu2+ for 8 and 6-fold coordination are 0.96 and 0.83 as well as 1.25 and 1.17 Å, respectively. 13 Based on the ionic radii, it can be assumed that the Mn²⁺ ions tend to occupy the Ca sites whereas the Eu2+ ions tend to occupy the Ba²⁺ sites as well as the 8-fold coordinated Ca²⁺ sites.

2. Experimental

Preparation

 $Ba_{0.99}Eu_{0.01}(Ca_{1-x}Mn_x)_2Si_3O_9$ sample were synthesized *via* conventional high temperature solid state reaction. High purity starting materials BaCO₃ (Alfa Aesar, 99.8%), CaCO₃ (Merck KGaA, Reag. Ph. Eur.), SiO₂ (Merck KGaA, Ph. Eur.), Eu₂O₃ (Treibacher Industrie AG, 99.99%) and MnC₂O₄·2H₂O (Dr. Paul Lohmann, chem. pure) were weighted in stoichiometric amounts. 1 wt-% H₃BO₃ (Merck KGaA, Ph. Eur.) was added as a flux. Subsequently, the educts were ground in acetone in an agate mortar. After drying at ambient temperature, obtained powder blends were heated at 1000 °C for 2 h in air to decompose the carbonates. Afterwards the samples were ground and finally calcined in alumina boats at 1200 °C for 12 h in reducing forming gas flow (Westfalen, 5% H₂, 95% N₂). After calcination, hard sinter bodies with a slightly yellow body colour were obtained which were subsequently ground to a fine powder.

Characterization

Phase purity was investigated using x-ray powder diffractometry (XRD). XRD patterns were recorded on a Rigaku MiniFlex II diffractometer working in Bragg-Bretnano geometry using Cu K_{α} radiation. Step width and integration time were 0.02 and 1 s, respectively.

PL spectra and photoluminescence excitation (PLE) spectra were recorded on an Edinburgh Instruments

FSL900 spectrometer equipped with a Xe arc lamp (450 W) and a cooled (-20 °C) single-photon counting photomultiplier (Hamamatsu R2658P). PL spectra were corrected by using a correction file obtained from a tungsten incandescent lamp certified by the National Physics Laboratory U.K.

For photoluminescence decay (PLD) measurements on Eu²⁺, the spectrometer was equipped with a picosecond pulsed laser (5 mW, pulse width = 76.6 ps, λ_{em} = 375 nm). For PLD measurements on Mn²⁺ a microsecond pulsed Xe lamp (100 W, pulse width = 1 μ s) was attached to the spectrometer.

For temperature dependent measurements the spectrometer was equipped with a cryostat (Oxford Instruments). Liquid nitrogen was used as a cooling agent. Temperature stabilization time was 60 s and tolerance was set to $\pm 3 \text{ K}$.

Diffuse reflectance (DR) spectra were recorded on an Edinburgh Instruments FS900 spectrometer equipped with a Xe arc lamp (450 W), a cooled (-20 $^{\circ}$ C) single-photon counting photomultiplier (Hamamatsu R928) as well as a teflon-coated integration sphere. BaSO₄ (99.998%, Sigma-Aldrich) was used as a reflectance standard.

External quantum efficiencies $\eta_{\rm ext}$ were determined using the approach of Kawamura et al.¹⁴ To that end, PL spectra of the sample as well as of the excitation source were recorded in the integration sphere. From this, $\eta_{\rm ext}$ can be calculated by the following equation:

$$\eta_{\text{ext}} = \frac{\int I_{\text{em}}(\lambda) d\lambda}{\int I_{\text{ex}}(\lambda) d\lambda - \int I'_{\text{ex}}(\lambda) d\lambda}$$
 (1)

where $I_{\rm em}(\lambda)$ is the emission intensity of the sample. $I_{\rm ex}(\lambda)$ and $I'_{\rm ex}(\lambda)$ are the intensities of the excitation source in absence and presence of the sample.

3. Results and discussion

Collected XRD patterns of doped and also of undoped $BaCa_2Si_3O_9$ samples as well as the ICDD reference cards of $BaCa_2Si_3O_9$ and SiO_2 are presented in Fig. 1. The XRD patterns indicate the formation of the triclinic $BaCa_2Si_3O_9$ phase. Furthermore, with increasing doping concentrations of Eu^{2+} and Mn^{2+} , no change in the host structure can be observed. However, samples with x > 0.1 show an additional reflex at about 25.9° which can be assigned to SiO_2 . This proofs the successful synthesis of the investigated $BaCa_2Si_3O_9:Eu^{2+},Mn^{2+}$ phosphors with a Mn^{2+} concentration up to x = 0.1.

Fig. 2 shows DR spectra of undoped BaCa₂Si₃O₉ host material also of $Ba_{0.99}Eu_{0.01}Ca_2Si_3O_9$ $Ba(Ca_{0.95}Mn_{0.05})_2Si_3O_9$. Undoped $BaCa_2Si_3O_9$ exhibits high reflectance between 250 and 800 nm. Thus, undoped BaCa₂Si₃O₉ possess a white body colour. The DR spectrum of Ba_{0.99}Eu_{0.01}Ca₂Si₃O₉ shows a broad absorption band between 250 and 450 nm due to the allowed $[Xe]4f^3-[Xe]4f^65d^1$ transition of Eu²⁺. Because of the absorption band in the blue range of the electromagnetic spectrum, Ba_{0.99}Eu_{0.01}Si₃O₉ exhibits a slightly yellow body colour. The DR spectrum of Ba(Ca_{0.95}Mn_{0.05})₂Si₃O₉ shows absorption in the UV region between 250 and 350 nm which can be tentatively assigned to a Mn²⁺ charge transfer transition.¹⁵

The PLE spectrum as well as the PL spectrum of $Ba_{0.99}Eu_{0.01}Ca_2Si_3O_9$ are depicted in Fig 3a. The PLE spectrum was recorded monitoring the 460 nm emission of Eu^{2+} and exhibits a broad band consisting of various unresolved bands. This band is due to excitation from the $[Xe]4f^7$ ground state to the $[Xe]5d^1$ multiplet of Eu^{2+} . The PL spectrum of $Ba_{0.99}Eu_{0.01}Ca_2Si_3O_9$ ($\lambda_{ex}=320$ nm) shows an emission band peaking at about 444 nm with FWHM of 47 nm (2333 cm⁻¹). This emission originates from relaxation from the excited




Fig. 1 XRD patterns of pure $BaCa_2Si_3O_9$ as well as of $Ba_{0.99}Eu_{0.01}(Ca_{1.x}Mn_x)_2Si_3O_9$ and $Ba(Ca_{0.95}Mn_{0.05})_2Si_3O_9.$




Fig. 2 DR spectra of pure $BaCa_2Si_3O_9$ as well as of $Ba_{0.99}Eu_{0.01}Ca_2Si_3O_9$ and $Ba(Ca_{0.95}Mn_{0.05})_2Si_3O_9$.

[Xe] $5d^1$ state to the [Xe] $4f^2$ ground state. Further, Ba_{0.99}Eu_{0.01}Ca₂Si₃O₉ possesses an emission band in the red region of the spectrum. The PLE spectrum of this emission is shown as a dotted line. Fig 3b illustrates the PLE and PL




Fig. 3 Room temperature PLE and PL spectra of $Ba_{0.99}Eu_{0.01}Ca_2Si_3O_9$ a), $Ba(Ca_{0.95}Mn_{0.05})_2Si_3O_9$ b), and $Ba_{0.99}Eu_{0.01}Ca_2Si_3O_9$ c).

spectra of Ba(Ca_{0.95}Mn_{0.05})₂Si₃O₉. Monitoring the 590 nm emission of Mn²⁺, the PLE spectrum of Ba(Ca_{0.95}Mn_{0.05})₂Si₃O₉ shows various bands centred at 326, 348, 359, 405, 432, and 510 nm. These peaks can be assigned to transitions from the $^{6}A_{1}(^{6}S)$ ground state to $^{4}T_{1}(^{4}P)$, ⁴E(⁴D), $[{}^{4}E({}^{4}G){}^{4}A_{1}({}^{4}G)], {}^{4}T_{2}({}^{4}G), \text{ and } {}^{4}T_{1}({}^{4}G), \text{ respectively. The PL}$ spectrum of Ba(Ca_{0.95}Mn_{0.05})₂Si₃O₉ was recorded under an excitation wavelength of $\lambda_{ex} = 405$ nm and exhibits a broad band with a maximum at about 594 nm resulting from transition from the ${}^4T_1({}^4G)$ excited state to the ${}^6A_1({}^6S)$ ground state. This observation is in accordance to the results given by Gaft et al. regarding Mn²⁺ emission in natural walstromite. ¹² Additionally, the Mn²⁺ emission band comprises a tailing to the red range of the visible spectrum indicating emission from different crystallographic sites. PLE as well as PL spectra of co-doped $Ba_{0.99}Eu_{0.01}(Ca_{0.95}Mn_{0.05})_2Si_3O_9$ are depicted in Fig 3c. The PL spectrum of $Ba_{0.99}Eu_{0.01}(Ca_{0.95}Mn_{0.05})_2Si_3O_9$ shows two bands peaking at about 445 and 590 nm which can be assigned to electronic transitions of Eu²⁺ ([Xe]5d¹ to [Xe]4f⁷) and Mn²⁺ $({}^{4}T_{1}({}^{4}G)$ to ${}^{6}A_{1}({}^{6}S)$, respectively. PLE spectra of Ba_{0.99}Eu_{0.01}(Ca_{0.95}Mn_{0.05})₂Si₃O₉ were recorded, monitoring the 460 nm emission of Eu²⁺ as well as the 590 nm emission of Mn²⁺. These PLE spectra appear similar to the PLE of singly doped Ba_{0.99}Eu_{0.01}Ca₂Si₃O₉ monitoring the blue emission of Eu²⁺. This observation strongly implies the occurrence of ET from Eu²⁺ to Mn²⁺.

Fig 4 illustrates the PL spectra of the synthesized $Ba_{0.99}Eu_{0.01}(Ca_{1-x}Mn_x)_2Si_3O_9$ series with x=0, 0.005, 0.010, 0.015, 0.020, 0.050, 0.100, 0.150, and 0.200. As can be




Fig. 4 PL spectra of $Ba_{0.99}Eu_{0.01}(Ca_{1.x}Mn_x)_2Si_3O_9$ and integrated PL intensity in dependence of the Eu^{2+} and Mn^{2+} concentration (inset).

concluded from the spectra, with increasing Mn^{2+} concentration the PL intensity of Eu^{2+} decreases. This behaviour reflects the assumption provided above regarding ET from Eu^{2+} to Mn^{2+} . The inset in Fig 4 depicts the relative PL intensities of Eu^{2+} and Mn^{2+} . It was found that the PL intensity of Mn^{2+} increases continuously up to a Mn^{2+} concentration of x=0.15 where a saturation effect begins. Concentration quenching of the Mn^{2+} emission was not observed for the synthesized samples.

Furthermore, PLD measurements were performed monitoring Eu^{2+} emission to investigate the ET from Eu^{2+} to Mn^{2+} in more detail. Fluorescence lifetimes τ of $Ba_{0.99}Eu_{0.01}(Ca_{1-x}Mn_x)_2Si_3O_9$ samples with increasing Mn^{2+} content were determined, monitoring the 445 nm emission of Eu^{2+} under excitation wavelength of $\lambda_{ex}=375$ nm. Fig 5 illustrates the obtained PLD curves. The PLD curves can be best fitted with a bi-exponential function applying the following equation:

$$I = A_1 \cdot e^{\frac{-t}{\tau_1}} + A_2 \cdot e^{\frac{-t}{\tau_2}} \tag{2}$$

Here, I is the luminescence intensity, A_1 and A_2 are parameters and t is the time. The terms τ_1 and τ_2 are the partial lifetimes for the exponential components. The bi-exponential shape of the PLD curves originates from two different emitting centres and suggests Eu^{2+} emission from two distinct crystallographic sites. This is thoroughly possible since $BaCa_2Si_3O_9$ provides two different Ca sites and one Ba site, as mentioned above. This assumption is backed by PLD measurements monitoring the emission at 415 and 495 nm which yield different luminescence lifetimes (τ at 415 nm = 602 ns, τ at 415 nm = 702 ns) (Fig. S1 in ESI^{\dagger}). The average luminescence lifetimes τ of Eu^{2+} in $BaCa_2(Si_3O_9):Eu^{2+},Mn^{2+}$ can be derived using the above mentioned parameters and the following equation:

$$\tau = \frac{A_1 \tau_1^2 + A_2 \tau_2^2}{A_1 \tau_1 + A_2 \tau_2} \tag{3}$$

Table 1 Fluorescence lifetimes τ as well as partial lifetimes τ_1 and τ_2 and the emission fractions frac₁ and frac₂ of Eu²⁺ in Ba_{0.99}Eu_{0.01}(Ca_{1.x}Mn_x)₂Si₃O₉.

sample (x)	frac ₁ (%)	τ_1 (ns)	frac ₂ (%)	τ_2 (ns)	τ (ns)
0.000	13	212	87	698	634
0.005	14	208	86	697	629
0.010	13	206	87	690	625
0.015	13	206	87	693	630
0.020	12	204	88	687	628
0.050	13	201	87	680	617
0.100	13	193	87	673	609
0.150	15	175	85	636	569
0.200	16	176	84	629	555

Constants A_1 and A_2 , partial lifetimes τ_1 , and τ_2 and also the calculated average lifetimes are summarized in Table 1. The results show a decreasing lifetime τ of Eu²⁺ with increasing Mn²⁺ concentration. Since ET processes are usually faster than radiative transitions, this circumstance clearly indicates the occurrence of an ET from Eu²⁺ to Mn²⁺. The ET efficiency η_T be calculated using following equation: 16

$$\eta_{\rm T} = 1 - \frac{\tau_{\rm S}}{\tau_{\rm S0}} \tag{4}$$

In this equation $\tau_{\rm S}$ and $\tau_{\rm S0}$ are the average lifetimes of Eu²⁺ in presence and absence of Mn²⁺. The inset of Fig. 5 illustrates the calculated values for $\eta_{\rm T}$ for the investigated BaCa₂Si₃O₉:Eu²⁺,Mn²⁺ samples as a function of the Mn²⁺ content. This shows that the ET efficiency $\eta_{\rm T}$ continuously increases with increasing Mn²⁺ content. For the highest Mn²⁺ concentration with x=0.20, $\eta_{\rm T}$ amounts to 12 % whereas the PL intensity of Eu²⁺ decreases around 70%. Due to faster competitive ET processes, e.g. migration to defect sites, a significant amount of emission energy is lost before it can be transferred to the Mn²⁺ ions. These behaviour increases with increasing Mn²⁺ concentration.

The average distance between $\mathrm{Eu^{2+}}$ and $\mathrm{Mn^{2+}}$ ($R_{\mathrm{Eu-Mn}}$) in the host material at which ET occurs can be estimated by applying the following formula published by Blasse:¹⁷

$$R_{\text{Ce-Mn}} = 2 \left[\frac{3V}{4\pi x N} \right]^{\frac{1}{3}} \tag{5}$$

Here, V is the volume of the unit cell, x the concentration of $\mathrm{Eu^{2^+}}$ and $\mathrm{Mn^{2^+}}$ in the host, and N is the number of available sites for the dopants in the unit cell. For $\mathrm{BaCa_2Si_3O_9}$, V and N are 396.01 ų and 6, respectively. Using this equation for $x=0.005,\,0.010,\,0.015,\,0.020,\,0.050,\,0.100,\,0.150,\,\mathrm{and}\,0.200,\,(R_{\mathrm{Eu-Mn}})$ is calculated to be 20.3, 18.5, 17.1, 16.1, 12.8, 10.5, 9.2, and also 8.4 Å. The $\mathrm{Mn^{2^+}}$ concentration where the $\mathrm{Eu^{2^+}}$ PL intensity is one-half of that sample without $\mathrm{Mn^{2^+}}$ is called critical concentration x_{c} . Plugging in x_{c} into formula 5, the critical




Fig. 5 PLD curves of $Ba_{0.99}Eu_{0.01}(Ca_{1.x}Mn_x)_2Si_3O_9$ and ET efficiency η_T in dependence on the Mn²⁺ concentration (inset).

distance R_c can be derived. R_c is defined as the distance where the probability of ET from sensitizer to activator equals the probability of radiative transition in the sensitizer. For $Ba_{0.99}Eu_{0.01}(Ca_{1-x}Mn_x)_2Si_3O_9$, x_c was determined to be 0.134. From this, R_c is calculated to be 9.6 Å.

To elucidate the characteristics of the ET process in $Ba_{0.99}Eu_{0.01}(Ca_{1-x}Mn_x)_2Si_3O_9$, the obtained decay curves were analysed by applying the Inokuti-Hirayama model. Assuming a uniform distribution of Eu^{2+} and Mn^{2+} in the host structure, and neglecting further energy migration processes beside the ET from Eu^{2+} to Mn^{2+} , the time-dependent course of the PL intensity of Eu^{2+} can be described by following equation:¹⁸

$$I(t) = I_0 \times e^{-\frac{t}{\tau_0} - \alpha \left(\frac{t}{\tau_0}\right)^{\frac{3}{5}}}$$
 (6)

In this equation, t is the time, I(t) is the PL intensity after excitation, I_0 is the PL intensity at t = 0, τ_0 is the intrinsic luminescence lifetime of the sensitizer in absence of the activator, α is a parameter for the probability of ET. S is related to the electronic multipole character of the ET. S = 6, 8, and 10 corresponds to dipole-dipole, dipole-quadrupole, and quadrupole-quadrupole interactions, respectively. Modifying equation 6 leads to following relation:

$$\ln\left[-\ln\left(\frac{I(t)}{I_0}\right) - \left(\frac{t}{\tau_0}\right)\right] \sim \ln\left(\frac{t}{\tau_0}\right)^3 \tag{7}$$

Plotting the PLD curves using this relation yields a straight line with a slope equal to 1/S. The obtained curves for the measured $Ba_{0.99}Eu_{0.01}(Ca_{1-x}Mn_x)_2Si_3O_9$ samples with $x=0.005,\ 0.010,\ 0.015,\ 0.020,\ 0.050,\ 0.100,\ 0.150,\ and\ 0.200$ are depicted in Fig. 6. The calculated S values are roughly coincident with the theoretical value of S=8. This result suggests dipole-quadrupole interactions as the dominant mechanism of ET from Eu^{2+} to Mn^{2+} in co-doped $BaCa_2Si_3O_6$: Eu^{2+} . Mn^{2+} .




Fig. 6 Plots of $\ln[-\ln(I(t)/I_0)-(t/\tau_0)]$ versus $\ln(t/\tau_0)^3$. Experimental data is represented by the dots. Grey lines represent the fitting functions.

This finding is well reasonable since the electronic [Xe] $4f^65d^1$ -transition in Eu²⁺ is allowed whereas the electronic [Ar] $3d^5$ -[Ar] $3d^5$ -transition in Mn²⁺ is forbidden. Therefore, the critical distance R_c for ET from Eu²⁺ to Mn²⁺ can be calculated using the spectral overlap method: 17,19

$$R_{\rm c}^8 = 0.63 \times 10^{28} \frac{f_q \lambda_{\rm S}^2 Q_{\rm A}}{f_d E^4} \int F_{\rm S}(E) F_{\rm A}(E) dE$$
 (8)

In this formula $f_{\rm q}=10^{-10}$ and $f_{\rm d}=10^{-7}$ are the oscillator strengths of dipole and quadrupole electronic absorption transitions, respectively, for Mn²⁺. The absorption cross section $Q_{\rm A}$ of Mn²⁺ can be expressed using the relationship $Q_{\rm A}=4.8\times10^{-16}$ $f_{\rm d}$ derived by Blasse. $\lambda_{\rm S}$ is the emission wavelength of Eu²⁺. E is the energy of maximal spectral overlap. From this, the critical distance $R_{\rm c}$ is calculated to be 8.9 Å. This value is in accordance with the one calculated using Blasse's approach (9.6 Å).

To investigate the temperature dependence of the PL of codoped $Ba_{0.99}Eu_{0.01}(Ca_{0.90}Mn_{0.10})_2Si_3O_9$, PL spectra were recorded from 100 to 800 K. The obtained PL spectra are depicted in Fig. 7. The spectra demonstrates that with increasing temperature PL intensity of Eu^{2+} and Mn^{2+} decreases due to thermal quenching. Furthermore, with increasing temperature the PL maximum of Mn^{2+} emission is shifted




Fig. 7 PL spectra of $Ba_{0.99}Eu_{0.01}(Ca_{0.90}Mn_{0.10})_2Si_3O_9$ from 100 to 800 K and PL integral in dependence of the temperature (inset).

towards shorter wavelengths. This shift originates from expansion of the equilibrium distance between $\mathrm{Mn^{2^+}}$ ions and its ligands. Therefore, crystal field splitting decreases whereby the energy of the ${}^4\mathrm{T_1}({}^4\mathrm{G}) {\rightarrow} {}^6\mathrm{A_1}({}^6\mathrm{S})$ -transition increases. The inset of Fig. 7 illustrates the normalized PL integrals versus its temperature. From this, activation energy E_A for thermal quenching can generally be estimated by fitting the data points by a Fermi-Dirac distribution:

$$I(T) = \frac{I_0}{1 + B \times e^{\frac{-E_A}{kT}}} \tag{9}$$

In this equation, I(T) is the luminescence intensity at a certain temperature and I_0 is the luminescence intensity at zero Kelvin. B is the quenching frequency factor, T is the temperature and k is the Boltzmann constant. However, due to an additional turning point, the present data points cannot be fitted by ordinary Fermi-Dirac distribution. Therefore, equation 9 is expanded to a sum of two weighed Fermi-Dirac distributions:

$$I(T) = A \frac{I_{0,a}}{1 + B \times e^{\frac{-E_{A,a}}{kT}}} + (1 - A) \frac{I_{0,b}}{1 + B \times e^{\frac{-E_{A,b}}{kT}}}$$
(10)

Here, $I_{0,a}$ and $I_{0,b}$ are the PL intensities at zero Kelvin. A describes the fraction of the first term. From this, $E_{A,a}$ and $E_{A,b}$ were determined to be about 0.07 and 0.84 eV, respectively. Plugging in the values for $E_{A,a}$ and $E_{A,b}$ in equation 11 yields $T_{1/2,a}$ and $T_{1/2,b}$:

$$T_{1/2} = \frac{-E_{\rm A}}{k \times \ln\left(\frac{1}{R}\right)} \tag{11}$$

 $T_{1/2}$ is the temperature at which PL intensity of a luminescent centre is decreased to one-half of its maximum. For $Ba_{0.99}Eu_{0.01}(Ca_{0.90}Mn_{0.10})_2Si_3O_9$, $T_{1/2,a}$ and $T_{1/2,b}$ were calculated to be 242 and 666 K, respectively. The PL intensities originating from Eu^{2+} and Mn^{2+} were plotted separately (Fig. S2 and Fig. S3 in ESI†). From that it can be seen that the bi-




Fig. 8 PLD curves of $Ba_{0.99}Eu_{0.01}(Ca_{0.90}Mn_{0.10})_2Si_3O_9$ at 100, 300 and 500 K monitoring the emission of Eu^{2+} . Fluorescence lifetimes in dependency of temperature (inset).

sigmoidal temperature behaviour strongly decreases if investigating the PL intensities of Eu2+ solely. Due to overlapping the red emission band the bi-sigmoidal shape doesn't vanish completely. To examine the origin of this double sigmoidal quenching behaviour, PL of singly doped Ba_{0.99}Eu_{0.01}Si₃O₉ was measured in the temperature range from 100 to 800 K as well (Fig. S4 in ESI†). At low temperatures an additional emission band extending from about 600 to 750 nm arises. PLD measurements of this emission band revealed a fluorescence lifetime of about 945 ns (Fig. S5 in ESI†). This value matches well with the decay time of Eu²⁺. Furthermore, the obtained PLD curve shows mono-exponential decay indicating emission from one crystallographic site. These Eu²⁺ ions presumably occupy the 6fold coordinated Ca2 sites in BaCa2Si3O9. On this small site, crystal field splitting of the d-orbitals of Eu²⁺ is rather high by what the lower edge of the [Xe]5d multiplet is moved towards the ground state. Due to relatively low emission energies in the red spectral range and consequently strong multi-phonon relaxation as well as large Stokes shift, this emission exhibits lower quenching temperature. Furthermore, with increasing temperature a blue shift of Mn²⁺ emission can be observed. This behaviour is due to increasing average distance between the Mn²⁺ ions and its oxygen ligands with increasing temperatures. As a consequence, the crystal field splitting of the 3d orbitals of Mn^{2+} decreases resulting in a shift of the ${}^{4}T_{1}({}^{4}G) \rightarrow {}^{6}A_{1}({}^{6}S)$ transition to higher energies.²⁰

To obtain more detailed information regarding the temperature depended behaviour of $Ba_{0.99}Eu_{0.01}(Ca_{0.90}Mn_{0.10})_2Si_3O_9$, PLD measurements were performed from 100 to 500 K. Fig. 8 depicts the PLD curves of $Ba_{0.99}Eu_{0.01}(Ca_{0.90}Mn_{0.10})_2Si_3O_9$ monitoring the 445 nm emission of Eu^{2+} . The curves can be best fitted with a biexponential function, suggesting Eu^{2+} emission from two distinct crystallographic sites as previously mentioned. The derived fluorescence lifetimes are presented in Tab. 2 and show

an unusual increase with increasing temperature. This phenomenon was only reported by a few authors and is still uncommon.^{21,22} According to Meijerink and Blasse, this behaviour is presumably caused by thermal population of higher energetic 4f 65d states. Excited states in Eu2+ can either be (spin) octets or sextets. The sextet states are at higher energies than the octet states according to Hund's rule. With increasing temperature the higher energetic sextet states will be populated. For these states, transition to the ⁸S_{7/2} ground state is spin-forbidden resulting in lower decay rates and thus longer fluorescence lifetimes.²² Fluorescence lifetimes of Mn²⁺ emission in dependency of temperature were measured, too. The obtained PLD curves are depicted in Fig. 9 and can be well fitted with a bi-exponential function. This result is in coincidence with the assumption made above that Mn²⁺ is located on two different crystallographic sites. The calculated average lifetimes of Mn2+ are summarized in Tab. 2. With increasing temperature, Mn²⁺ fluorescence lifetimes decrease continuously due to an increase in non-radiative relaxation to the ground state. Therefore, it can be concluded that thermal quenching of emission in BaCa₂Si₃O₉:Eu²⁺,Mn²⁺ is primarily caused by Mn²⁺ ions. As deduced from PLD curves of Mn²⁺ emission as well as from ionic radii of Ba²⁺, Ca²⁺ and Mn²⁺, it can be concluded that Mn²⁺ ions preferably occupy the two Ca sites in BaCa₂Si₃O₉. Since the ionic radii of 6- and 8-fold coordinated Mn²⁺ are smaller compared to those of Ca²⁺, the excited states of Mn²⁺ can strongly be polarized. This leads to an increase in the equilibrium distance between Mn2+ and its oxygen ligands and therefore to a shift of the ground and excited state parabolas in the configurational coordinate

diagram. Further, the crossing point of the parabolas is shifted to lower energies, thus to lower activation energy for thermal quenching.

To investigate the PL efficiency of the Ba_{0.99}Eu_{0.01}(Ca_{1-x}Mn_x)₂Si₃O₉ samples, external quantum efficiencies $\eta_{\rm ext}$ were measured as mentioned above. To our understanding, external quantum efficiency $\eta_{\rm ext}$ is defined as:




Fig. 9 PLD curves of $Ba_{0.99}Eu_{0.01}(Ca_{0.90}Mn_{0.10})_2Si_3O_9$ at 100, 300 and 500 K monitoring the emission of Mn^{2+} . Fluorescence lifetimes in dependency of temperature (inset).

Table 2 Fluorescence lifetimes τ as well as partial lifetimes τ_1 and τ_2 , and the emission fractions frac₁ and frac₂ of Eu²⁺ and Mn²⁺ in Ba_{0.99}Eu_{0.01}(Ca_{1-x}Mn_x)₂Si₃O₉ from 100 to 500 K.

	Eu ²⁺	Mn^{2+}								
T(K)	frac ₁ (%)	τ_1 (ns)	frac ₂ (%)	τ ₂ (ns)	τ (ns)	frac ₁ (%)	τ_1 (ms)	frac ₂ (%)	τ_2 (ms)	τ (ms)
100	16	214	84	637	570	9	19	91	47	44
125	15	205	85	637	571					
150	14	190	86	635	574	9	17	91	45	42
175	13	191	87	638	578					
200	12	184	88	644	587	6	13	94	41	39
225	12	190	88	645	591					
250	13	205	87	656	597	8	15	92	38	36
275	13	199	87	656	597					
300	12	199	88	659	602	10	16	90	35	33
325	13	187	87	663	600					
350	15	215	85	681	612	5	10	96	31	30
375	15	216	85	684	615					
400	14	216	86	687	621	8	12	92	29	28
425	14	195	86	689	619					
450	13	199	87	688	622	4	7	96	26	26
475	15	211	85	701	628					
500	13	201	87	687	622	4	7	96	24	24

ARTICLE Journal Name

$$\eta_{\rm ext} = \frac{N_{\rm emission}}{N_{\rm absorption}} \tag{12}$$

Where, $N_{emission}$ is the number of photons emitted by the phosphor and $N_{absorption}$ is the number of photons absorbed by the phosphor. The resulting quantum efficiencies η_{ext} are summarized in Table 3. For the investigated samples η_{ext} is around 30%. The low quantum efficiency of $BaCa_2Si_3O_9:Eu^{2+},Mn^{2+}$ can be ascribed to the overlap of the blue emission band and the excitation band of the red emission of Eu^{2+} . Due to ET from the blue Eu^{2+} site to the red Eu^{2+} site which is thermally quenched, η_{ext} decreases.

According to the relevant PL spectra, Commission International de l'Eclairage 1931 (CIE) chromaticity coordinates were calculated. Fig. 10 depicts the CIE chromaticity diagram for $Ba_{0.99}Eu_{0.01}(Ca_{1-x}Mn_x)_2Si_3O_9$ with x =0, 0.005, 0.010, 0.015, 0.020, 0.050, 0.100, 0.150, and 0.200. By increasing the Mn²⁺ concentration, the chromaticity coordinates can be shifted from blue to magenta colour tones. Due to the lack of emission in the green spectral range, BaCa₂Si₃O₉:Eu²⁺,Mn²⁺ has to be combined with an additional green emitting phosphor to generate white light, such as $(Ba,Sr)_2SiO_4:Eu^{2+}, Sr_{12}Al_{14}O_{32}Cl_2:Eu^{2+} or KBaBP_2O_8:Tb^{3+}.^{23}$ Figure S6 shows a simulated white emission spectrum $Ba_{0.99}Eu_{0.01}Ca(_{0.80}Mn_{0.20})_{2}Si_{3}O_{9}$ consisting (Ba_{0.49}Sr_{0.49}Eu_{0.02})₂SiO₄. The CIE 1931 colour coordinates of the spectrum are x = 0.327 and y = 0.333 which result in a colour temperature of 5745 K. The colour rendering index (CRI) R_a of the simulated spectrum is equal to 82. This CCT is similar to that of a phosphor-converted white LED consisting of a blue LED chip and YAG: Ce^{3+} (CCT = 5600 K) whereas the CRI is higher compared to that of this phosphor-converted LED $(R_a = 71)^{24}$

Table 3 External quantum efficiencies η_{ext} and CIE colour coordinates of $Ba_{0.99}Eu_{0.01}(Ca_{1.x}Mn_x)_2Si_3O_9$.

sample	$\eta_{ m ext}$	$\mathrm{CIE}(x y)$
x = 0.000	0.31	(0.151 0.043)
x = 0.005	0.31	(0.163 0.053)
x = 0.010	0.30	$(0.170 \mid 0.060)$
x = 0.015	0.31	$(0.182 \mid 0.073)$
x = 0.020	0.32	$(0.190 \mid 0.080)$
x = 0.050	0.34	(0.224 0.112)
x = 0.100	0.36	(0.260 0.146)
x = 0.150	0.26	(0.323 0.210)
x = 0.200	0.30	(0.354 0.240)




Fig. 10 CIE chromaticity diagram of $Ba_{0.99}Eu_{0.01}(Ca_{1.x}Mn_x)_2Si_3O_9$ with different Mn^{2+} concentrations.

4. Conclusions

A series of BaCa₂Si₃O₉:Eu²⁺,Mn²⁺ powder samples with various Mn²⁺ concentrations was prepared *via* high temperature state synthesis. Excited by UV BaCa₂Si₃O₉:Eu²⁺,Mn²⁺ shows two emission bands located at about 444 and 594 nm originating from Eu²⁺ and Mn²⁺, Eu^{2+} It turned out that respectively. BaCa₂Si₃O₉:Eu²⁺,Mn²⁺ occupy the 8-fold coordinated Ba and Cal sites as well as the 6-fold coordinated Ca2 sites. Mn²⁺ ions tend to occupy both Ca sites. These results are confirmed by PLD measurements. The highest PL intensity of Mn²⁺ was found at a Mn^{2+} concentration of x = 0.15. It was further demonstrated that ET from Eu^{2+} to Mn^{2+} in $BaCa_2Si_3O_9:Eu^{2+},Mn^{2+}$ is of resonant type and occurs \emph{via} dipole-quadrupole interaction. The critical distance R_c between Eu²⁺ and Mn²⁺ was derived by using Blasse's concentration quenching method as well as spectral overlap method and was calculated to be 9.6 and 8.9 Å, respectively. Temperature depended PL measurements proof a "double" sigmoidal decrease of the PL intensity of $\mathrm{Eu^{2+}}$. Therefore, $\mathrm{BaCa_2Si_3O_9}:\mathrm{Eu^{2+}},\mathrm{Mn^{2+}}$ has two $T_{1/2}$ values, $T_{1/2,a}$ and $T_{1/2,b}$; which were calculated to be 242 and 666 K, respectively. In addition to that, PLD measurements revealed an unusual increase of Eu²⁺ fluorescence lifetime, which presumably originates from thermal population of higher excited energy levels. Temperature depended PLD measurements on the Mn² suggest that thermal quenching BaCa₂Si₃O₉:Eu²⁺,Mn²⁺ is primarily caused by Mn²⁺ ions. CIE 1931 colour points can be tuned from the blue to the magenta colour range.

Acknowledgement

The authors are grateful to Merck KGaA Darmstadt, Germany for generous financial support.

Notes and references

Department of Chemical Engineering, Münster University of Applied Sciences, Stegerwaldstrasse 39, 48565 Steinfurt, Germany

*Corresponding Author: E-mail address: tj@fh-muenster.de (Thomas Jüstel)

†Electronic Supplementary Information (ESI) available: PLD curves of $Ba_{0.99}Eu_{0.01}Ca_2Si_3O_9$ monitored at 415 and 495 nm, PL integrals of Eu^{2+} and Mn^{2+} in dependence of temperature, PL spectra of $Ba_{0.99}Eu_{0.01}Ca_2Si_3O_9$ from 100 to 800 K and PL integral in dependence of temperature, PLD curve of $Ba_{0.99}Eu_{0.01}Ca_2Si_3O_9$ monitored at $\lambda_{em}=700$ nm and T=77 K, simulated white emission spectrum. See DOI: 10.1039/b0000000x/

- S. Nakamura, P. Stephen and F. Gerhard, *The Blue Laser Diode: The Complete Story*, Springer-Verlag, Berlin/Heidelberg, 1997.
- 2 a) C. Feldmann, T. Jüstel, C. R. Ronda and P. J. Schmidt, *Adv. Funct. Mater.*, 2003, 13, 511–516.
 - b) E. F. Schubert and J. K. Kim, Science, 2005, 308, 1274-1278.
- 3 H. S. Jang, W. B. Im, D. C. Lee, D. Y. Jeon and S. S. Kim, *J. Lumin.*, 2007, 126, 371–377.
- 4 Y. Uchida and T. Taguchi, Opt. Eng., 2005, 44, 124003.
- 5 M. Shang, C. Li and J. Lin, Chem. Soc. Rev., 2014, 43, 1372.
- 6 a) W. Lv, M. Jiao, Q. Zhao, B. Shao, W. Lü and H. You, *Inorg. Chem.*, 2014, 53, 11007–11014.
 - b) W.-J. Yang and T.-M. Chen, Appl. Phys. Lett., 2006, 88, 101903.
- 7 P. Eskola, Am. J. Sci., 1922, 4, 331–375.
- J. T. Alfors, M. C. Stinson and R. A. Matthews, *Am. Mineral.*, 1965, 50, 314–340.
- 9 L. S. Dent Glasser and F. P. Glasser, Am. Mineral., 1968, 53, 9-13.
- 10 M. C. Barkley, R. T. Downs and H. Yang, Am. Mineral., 2011, 96, 797–801.
- 11 S. Yao, L. Xue and Y. Yan, Optics & Laser Technology, 2011, 43, 1282–1285.
- 12 M. Gaft, H. Yeates and L. Nagli, Eur. J. Mineral., 2013, 25, 71-77.
- 13 R. D. Shannon, Acta Crystall. A-Crys., 1976, A32, 751-767.
- 14 Y. Kawamura, H. Sasabe and C. Adachi, Jpn. J. Appl. Phys., 2004, 43, 7729–7730.
- 15 a) A. Mehra, *Jpn. J. Appl. Phys.*, 1968, **7**, 963–964.
 - b) E. van der Kolk, P. Dorenbos, C. W. van Eijk, A. P. Vink, M. Weil and J. P. Chaminade, *J. Appl. Phys.*, 2004, **95**, 7867.
- 16 a) H. C. Kandpal and H. B. Tripathi, *Indian J. Pure Appl. Phys.*, 1979, 17, 587–589.
 - b) P. Paulose, G. Jose, V. Thomas, N. Unnikrishnan and M. Warrier, *J. Phys. Chem. Solids*, 2003, **64**, 841–846.
- 17 G. Blasse, Philips Res. Rep., 1969, 24, 131-144.
- 18 M. Inokuti and F. Hirayama, J. Chem. Phys., 1965, 43, 1978.
- 19 D. L. Dexter, J. Chem. Phys., 1953, 21, 836.
- 20 Y. Tanabe and S. Sugano, J. Phys. Soc. Jpn., 1954, 9, 766-779.
- 21 a) J. P. Spoonhower and M. S. Burberry, J. Lumin., 1989, 43, 221–226.
 - b) T. Tsuboi and P. Silfsten, *J. Phys.:Condens. Matter*, 1991, **3**, 9163–9167.
 - c) C. K. Duan, A. Meijerink, R. J. Reeves and M. F. Reid, J. Alloy. Compd., 2006, 408-412, 784–787.
- 22 A. Meijerink and G. Blasse, J. Lumin., 1990, 47, 1-5.

- 23 a) B. Han, J. Zhang, P. Li and H. Shi, *Phys. Stat. Sol. A*, 2014, 211, 2483–2487.
 - b) Z. Jiang, Z. Sun, X. Su, L. Duan and X. Yu, J. Alloy. Compd., 2013, 577, 683–686.
 - c) T. L. Barry, J. Electrochem. Soc., 1968, 115, 1181-1184.
- 24 M. R. Krames, O. B. Shchekin, R. Mueller-Mach, G. O. Mueller, L. Zhou, G. Harbers and M. G. Craford, *J. Display Technol.*, 2007, 3, 160–175.