
Journal of Materials Chemistry A

Accepted Manuscript



This is an *Accepted Manuscript*, which has been through the Royal Society of Chemistry peer review process and has been accepted for publication.

Accepted Manuscripts are published online shortly after acceptance, before technical editing, formatting and proof reading. Using this free service, authors can make their results available to the community, in citable form, before we publish the edited article. We will replace this Accepted Manuscript with the edited and formatted Advance Article as soon as it is available.

You can find more information about *Accepted Manuscripts* in the **Information for Authors**.

Please note that technical editing may introduce minor changes to the text and/or graphics, which may alter content. The journal's standard <u>Terms & Conditions</u> and the <u>Ethical guidelines</u> still apply. In no event shall the Royal Society of Chemistry be held responsible for any errors or omissions in this *Accepted Manuscript* or any consequences arising from the use of any information it contains.



www.rsc.org/materialsA

ARTICLE



Ammonia-storage in lithium intercalated fullerides

Accepted 00th January 20xx DOI: 10.1039/x0xx00000x

Received 00th January 20xx,

www.rsc.org/

D. Pontiroli,^a D. D'Alessio,^a M. Gaboardi,^a G. Magnani,^a C. Milanese,^b S. Duyker,^{c,d} V. K. Peterson,^c N. Sharma^e and M. Riccò*^a

Ammonia has been proposed as an indirect hydrogen carrier, as solid-state ammonia-storage could reveal easier than directly absorbing hydrogen in materials. Here we investigate the structural evolution of hyper-ammoniated lithium fulleride (ND₃)_vLi₆C₆₀ during ammonia desorption, using *in-situ* high intensity neutron powder diffraction. In (ND₃)_vLi₆C₆₀, ammonia molecules are stored in their neutral state inside the inter-fullerene interstices and are coordinated to the intercalated Li ions, forming Li-ND_3 clusters. Li_6C_{60} is found to absorb up to 36.8 wt% ND_3, which corresponds to approximately 14 ammonia molecules per C60. The ammonia release, studied either in-situ or ex-situ by means of manometric analyses and differential scanning calorimetry, takes place in two main steps, at 350-410 K and 500-540 K respectively. This corresponds to two clear 1st order structural phase transitions and the absorption process is partially reversible. These findings suggest that the system could be a good candidate for ammonia-storage applications.

Introduction

The depletion of oil reserves and the environmental damage caused by burning fossil fuels represent major global issues, which could be overcome by switching to a so-called "Hydrogen economy".¹ Hydrogen is a very efficient energy vector, able to deliver three times the energy of other chemical fuels and burns without emitting greenhouse gases.² However, one of the main problems with hydrogen is the development of an efficient hydrogen-storage system, especially for automotive applications. Among the solutions proposed, the best performance is reached by loading hydrogen in solid-state materials, but so far none of these are able to meet the technical targets imposed by industry and the Department of Energy (US DoE).³

In this context, the feasibility to use ammonia as a hydrogen carrier represents an interesting alternative, since ammonia is easy to synthesize and allows high H₂ storage capacity (up to 18 wt% in liquid NH_3 ⁴. Currently, ammonia is mainly produced by reacting atmospheric nitrogen with the hydrogen contained in natural gas, through the Haber process⁵; but other sources, such as coal or coke gasification, are available, which, in combination with CO₂ sequestration, could in principle offer a

Università degli Studi di Pavia, V.le Taramelli 16, 27100 Pavia, Italy ^{c.} The Bragg Institute, Australian Nuclear Science and Technology Organisation,

Locked Bag 2001, Kirrawee DC, NSW 2232, Australia

long-term ammonia production at zero emission.⁴ In contrast to hydrogen, even though liquid NH₃ is more toxic than common hydrocarbons, infrastructure for handling and transporting bulk ammonia are already well-established and developed. Nevertheless, especially for mobile applications, hazards associated with ammonia use should be further reduced ideally being a safer solution than gasoline. These hazards can in principle be lowered by storing ammonia in solid systems, such as metal ammines, which are able to reversibly absorb/desorb ammonia gas, provided at elevated temperatures.⁶ Use of NH₃ as a fuel can be direct, for instance by feeding ammonia straight into solid oxide fuel cells (SOFC),⁷ or indirect, through the catalytic decomposition of ammonia⁸ at high temperatures (300-500°C) and using hydrogen as energy source.

Notably, some common solid ammonia containing systems find direct use as hydrogen-storage materials, for example, ammonia borane (NH₃BH₃ with 19.6 wt% H₂),⁹ or the ammonia complexes of borohydrides (LiBH₄·nNH₃ with 18 wt% H₂, $Mg(BH_4)_2 \cdot nNH_3$ with 16 wt% H_2).^{10,11} This is because in these compounds the thermal decomposition usually causes the recombination of the N-H and B-H groups (followed by H₂ emission), rather than the release of pure ammonia. It is worth noting that this recombination makes the H₂-storage irreversible in these systems. The situation is different in the case of metal ammine complexes M(NH₃)_nX_m, where M is a metal cation (e.g. Mg, Ca, Ni) and X is an anion (e.g. Cl, SO₄). Metal ammine complexes^{6,12} were reported to reversibly store up to 10 wt% NH₃, although the complete ammonia release occurs at temperatures too high for practical applications, i.e. up to 650 K. More recently, the ammine complex Li₂B₁₂H₁₂ was found to catch seven NH₃ molecules and to completely release them below 473 K, corresponding to 43.4 wt% NH₃ stored at

^{a.} Dipartimento di Fisica e Scienze della Terra, Università di Parma, Viale delle Scienze 7/a, 43124 Parma, Italy. E-mail: mauro.ricco@fis.unipr.it

^{b.} Pavia H2 Lab, C.S.G.I & Dipartimento di Chimica, Sezione di Chimica Fisica,

^{d.}School of Chemistry, The University of Sydney, Sydney, Australia

e. School of Chemistry, University of New South Wales (UNSW), Sydney, Australia

Supplementary Information Electronic (ESI) available. DOI: See 10.1039/x0xx00000x

ARTICLE

mild conditions.¹³ Another noteworthy compound is LiBH₄, forming four stable ammoniated species.¹⁴ In particular, the mono-ammoniated phase of lithium borohydride contains 44 wt% ammonia and was reported to release ammonia at the accessible thermal decomposition temperature of just 313 K, although it presents a minor equilibrium NH₃ vapour pressure (8.4 mbar) at room temperature.¹⁵ Different approaches, based on the NH₃ physisorption in highly porous materials, like covalent organic frameworks (COFs), led to lower storage performance, up to 25.5 wt % ammonia stored at 1 bar.¹⁶

Recently, alkali intercalated fullerides (AIFs) have attracted some interest in the field of solid energy storage, for their ability to reversibly absorb hydrogen with favourable binding energies.¹⁷⁻¹⁹ In case of hydrogen, the storage mechanism occurs through the chemical bond of H atoms on the C₆₀ molecule (formation of the hydrofullerene C₆₀H_x), which is mediated²⁰ by the catalytic activity of the intercalated alkali (lithium, sodium) clusters²¹⁻²⁴ and can be optimized by the presence of catalysers.^{25,26}

The ability of AIFs to react with ammonia is another wellknown phenomenon.^{27,28} Typically, NH₃ molecules can be cointercalated in the AIF lattice interstices directly during the synthesis stage, from the reaction of C_{60} with the alkali metal (e.g. Li, Na, K) in ammonia solution,²⁹ or by exposing the prepared AIF to ammonia vapours.³⁰ Ammonia acts as a neutral spacer for the fulleride lattice and coordinates with the alkali ions.^{31,32} The induced lattice expansion dramatically affects the electronic and magnetic properties of the metallic highly-correlated AIF phases, which generally lie on the verge of a metal-to-insulator transition.³³ However, despite the intense research activity on these compounds, so far there have been no investigations on these systems for ammoniastorage purposes.

In this work, the ND₃ desorption as a function of the temperature of the ammoniated phases of lithium fulleride $(ND_3)_y Li_6 C_{60}$ is investigated using neutron powder diffraction (NPD). The structural evolution of the compound was, in addition to the NPD data, followed by the *in-situ* monitoring of ammonia release via a Sievert apparatus directly connected to the sample-holder. *Ex-situ* manometric measurements and differential scanning calorimetry (DSC) analyses were also performed, in order to precisely determine the thermodynamic properties of this system.

Experimental

Synthesis

The hyper-ammoniated lithium fullerides $(ND_3)_V Li_x C_{60}$, with x = 3, 6, 12, were prepared as follows. First, approximately half-gram of $Li_x C_{60}$ was synthesized by mixing stoichiometric amounts of finely cut metallic Li (Aldrich, 99.9% purity) and C_{60} powder (MER corp., 99.9% purity) via high-energy ball-milling. Specifically, the reagents were put in a 10 ml agate bowl of a mini-mill Fritsch Pulverisette 23 with three agate grinding-balls and were milled for 30 min at 30 Hz in Ar atmosphere (<0.1 ppm H₂O, O₂). After this step, an

homogeneous black powder was obtained, which was placed in a Pyrex Schlenk vial under vacuum in thermal contact with a methanol bath at 213 K and anhydrous deuterated ammonia (ISOTEC_{INC}-, min. 99 atom % D) was slowly condensed on the sample. The temperature was then increased to 243 K and the mixture was kept overnight under continuous magnetic stirring. Following this reaction, excess ammonia in the reactor was slowly condensed back in a bottle dipped in liquid N₂, finely regulating the evaporation with a needle valve and progressively increasing the temperature from 243 to 273 K. After the complete evaporation of ND₃ gas, the reactor containing the ammoniated sample was sealed and quickly put in Ar glove box and the product was recovered from the vial.

Methods

Preliminary X-ray powder diffraction (XPD) measurements were performed with a Bruker D8 Discover diffractometer, operating in Debye-Scherrer geometry, equipped with a CuK_{α} sealed tube generator and a 2D area (GADDS) detector.

NPD experiments were performed on the three obtained hyper-ammoniated lithium fullerides $(ND_3)_yLi_xC_{60}$ at the highflux powder diffractometer WOMBAT,³⁴ at the Bragg Institute of the Australian Nuclear Science and Technology Organisation (ANSTO, Sydney, Australia), using an incident wavelength of λ =2.9654(2) Å, determined using the La¹¹B₆ NIST standard reference material 660b. The high neutron flux intensity on this instrument meant that the typical accumulation time of each pattern was on the order of 1 min. Samples were loaded in vanadium cells equipped with a gas delivery tube and isolation valve. Sample loading was performed in a He glovebox with < 0.1 ppm H_2O and O_2 . The gas delivery tube was then connected with a Hiden Isochema IMI gas-delivery system, able to perform in-situ Sievert analysis of the ND₃ desorption process. During the experiment, ND₃ desorption was induced by gradually increasing the temperature of samples, which were varied in the range of 15-500 K using a cryofurnace on the sample position. The temperature was controlled via a k-type thermocouple at the base of the sample cell, with a second thermocouple attached to the cell above the sample level for monitoring purposes.

Samples synthesized at the same conditions starting from natural ammonia (Aldrich, 99.99+ % purity) were investigated in parallel with *ex-situ* manometric/DSC analysis at the Pavia H₂ lab, by heating the sample from room temperature up to 653 K under 0.3 bar of He at 5 K/min in a high pressure cell of a Sensys DSC (Setaram) connected with a PCTPro-2000 manometric instrument (Hy Energy - Setaram). This was undertaken in order to better determine the thermodynamic parameters of the NH₃ release process.

Results and discussion

Preliminary XPD data collected either on the Li-only intercalated fulleride precursors, or on the hyper-ammoniated $(ND_3)_yLi_xC_{60}$ samples, revealed strong differences among them

(see Supporting Information, Figure 1S). The former shows the expected *fcc* pattern profile,²⁵ with no presence of unreacted C_{60} or Li. On the other hand, in the latter the shift of the reflection to lower 2 θ values is indicative of the effective co-intercalation of the ammonia molecules in the host fulleride lattice. In order to quantify the ND₃ concentration in the samples, the weights were compared before and after the ammoniation process. In the case of x = 6 the nominal stoichiometry was found to be $(ND_3)_{13,99(15)}Li_6C_{60}$, corresponding to 36.8(3) wt% ND₃ absorbed by the sample.

Structural thermal evolution

In Figure 1 right, a colour map showing the evolution of the neutron powder diffraction patterns for the $(ND_3)_V Li_6 C_{60}$ sample is displayed as a function of temperature. It is possible to identify at least four distinctive regions, corresponding to the three different structural phase transitions, that the Li intercalated fulleride experiences when different amounts of ND₃ are co-intercalated in the sample. In Figure 1 left, the thermal evolution of the normalized total counts (*i.e.* the

neutron total counts measured by the detectors, normalized to the incident neutron flux) is shown (red curve), which is approximately proportional to the mass of the sample and follows well the structural evolution. Concomitant with the phase transitions, a decrease of the mass of the sample is noted and this is ascribed to the ammonia release. The normalized total counts are plotted together with the effective ND₃ stoichiometry of the sample (black curve), monitored by in-situ manometric measurements, performed by continuously monitoring the pressure of a reference vessel. This forms a closed system with the sample vessel and was monitored during the whole desorption process. In order to keep the ammonia pressure on the sample roughly constant and to avoid perturbations of the desorption process itself, the manifold was manually evacuated when the pressure overcame the value of 1 bar (after isolating the sample vessel). Hence, the black curve shown in Figure 1 was obtained by measuring the cumulative pressure during the desorption process, discarding the evacuation stages. This value is approximately proportional to the amount of ammonia




Figure 1: Left: Time evolution of the normalized total counts (red) of $(ND_3)_{\gamma}Li_6C_{60}$, plotted together with the estimated ND_3 stoichiometry of the sample (black), as evaluated by *in-situ* Sievert analysis. Right: Colour map showing the thermal evolution of the neutron diffraction profile in the range 300-500 K. The presence of three structural phase transitions at 350 K, 410 K and 500 K is evident. These are promoted by the progressive desorption of ND_3 molecules, co-intercalated in the host fullerene lattice. Discrete temperature points are reported in the middle, referring both to the left and right plots.

ournal of Materials Chemistry A Accepted

ARTICLE

ARTICLE

released and resulted in a value of around 14 ammonia molecules per formula unit absorbed in the hyperammoniated phase, which is in good agreement with the weighted value.

For the sake of clarity, selected diffraction patterns of the four regions are plotted in separate panels in Figure 2. Below room temperature, the diffraction pattern consists of a set of broad peaks, superimposed to few narrower ones. Although not indexed, the broad peaks were ascribed to the hyper-expanded ammoniated fulleride phase containing up to 14 ammonia molecules per C₆₀ (phase 0), while the latter were indexed with the tetragonal phase of LiND₂ (S.G. I4, a = b = 5.03(1) Å, c = 10.26(3) Å)³⁵ which is present as minority phase in the sample (< 2 wt%).

At around 350 K, the first phase transition occurs, indicated by a slight rearrangement of the fulleride cell parameters, which is probably associated to a small amount of ammonia released by the sample. The reflections were successfully indexed with a hexagonal cell, containing about 12 ND₃ molecules per C₆₀ (phase 1 - *hcp*, *a* = 10.86(1) Å, *c* = 18.57(1) Å, γ = 120°, V_{cell} = 1794(5) Å³ - V_{C60} = 948(2) Å³).

A more dramatic structural transition is found at 410 K, when the powder pattern starts to change, with new peaks arising in the region at $30 < 2\theta < 50^{\circ}$. At the same time, the total counts rapidly decrease, indicating a significant loss of sample mass. At 470 K this second phase transition is complete and all the observed reflections are indexed with a *bcc* phase, isostructural to the already known Mott-Hubbard insulating phase of $(NH_3)_6Li_3C_{60}$ (phase 2 – *bcc*, S.G. Im-3, *a* = 11.92(1) Å, $V_{cell} = 1742(6)$ Å³ - $V_{C60} = 871(3)$ Å³.^{29,32}

It is worth noting that at this stage (above 470 K) the peaks referred to $LiND_2$ are no longer present, even if the melting point and the decomposition temperature of the $LiND_2$ phase are expected at a much higher temperatures (648 and 973 K respectively). This fact, which was not observed in the other investigated samples (see Supplementary Information, Figure 2S), could be due to a chemical reaction occurring between the segregated Li amide and the fulleride, similarly to that observed with hydrides.¹⁸

The *bcc* phase appears stable for a wide range of temperatures, against a continuous loss of mass probed by the neutron total counts; during this stage the estimated amount of ammonia ranges between 7 and 5 ND₃ molecules per C_{60} .

Finally, at 500 K a third structural phase transition is observed, which suddenly brings to a *fcc* rearrangement of the fullerene packing, similarly to what is observed in pristine Li_6C_{60} (phase 3 – *fcc*, S.G. Fm-3m, *a* = 14.02(1) Å, V_{cell} = 2758(5) Å³ - V_{C60} = 689(3) Å³).^{17,25} This phase is compatible with an ammonia-free




Figure 2: Left: structural representation for the three indexed phases of Li_6C_{60} at different degrees of ammoniation. Right: selected powder neutron diffraction patterns of the $(ND_3)_yLi_6C_{60}$ sample during the ND_3 desorption process, referring to the four identified phases discussed in the text. Some sharp peaks (indicated by asterisks) were ascribed to the spurious $LiND_2$ phase, which in this sample is present in a very low amount (<2 wt%), thus not significantly affecting the sample properties.

structure. The comparison between the mass before and after the experiment, in fact, reveals a loss of about 26.7 wt%, which corresponds to the complete desorption of ammonia from the sample. A more precise determination of the parameters describing the ammonia release process is discussed below, through the analysis of manometric/DSC data collected *ex-situ* (see also Table 1).

Table 1: Crystal symmetry, ND₃ content and transition temperature, detected either with *in-situ* or *ex-situ* manometric measurements, for the four phases assumed by $(ND_3)_{v}Li_6C_{60}$ on heating.

Phase	Symmetry	ND ₃ cont. (wt%)	<i>In-situ</i> tr. T (K)	<i>Ex-situ</i> tr. T (K)
Phase 0	not indexed	36.8(3)	-	-
Phase 1	hcp	~32	~350 K	-
Phase 2	bcc	13 – 18	~410 K	350(5) K
Phase 3	fcc	-	~500 K	535(5) K

Similar neutron powder diffraction measurements were performed on $(ND_3)_y Li_x C_{60}$ samples with x = 3 and 12 and data were shown in Figure 2S of the Supplementary Information. However, in these cases the ammonia-storage performance was revealed to be worse if compared with Li_6C_{60} . In particular, for $(ND_3)_y Li_3C_{60}$, the amount of co-intercalated ammonia turned out to be significantly lower, on the order of 10 wt%. This is most likely due to the lack of formation of a hyperexpanded ammoniated phase in this case. Moreover, the complete desorption of ammonia was not reached during the *in-situ* thermal treatment - even at 500 K the sample still shows the *bcc* arrangement.

On the other hand, in the case of $(ND_3)_{y}Li_{12}C_{60}$ the behaviour is similar to $(ND_3)_{y}Li_{6}C_{60}$, even if a rather large amount of LiND₂ is present. The increase in LiND₂ content at this composition is due to the partial reaction of Li with ND₃ during the ammoniation process. The peaks ascribed to LiND₂ remain during the whole thermal treatment (see Figure 2S) and allowed us to estimate the amide amount in the sample at about 12 wt%. Such an amount clearly affects the effective stoichiometry of the Li fulleride, which after corrections, turns out to be $Li_{6.7(5)}C_{60}$, where part of the Li is involved in the formation of the amide phase. Notably, this fact also suggests an upper limit for the Li stoichiometry of the ammoniated $(ND_3)_yLi_xC_{60}$ phases, with x around 6.

Ex-situ NH₃ desorption

Desorption of ammonia in $(NH_3)_y Li_6 C_{60}$ was also monitored with ex-situ manometric/DSC coupled measurements, in order to further understand the discharge process. In Figure 3 a), the evolution of the amount of ammonia desorbed from the sample is shown as a function of temperature, in the range 300-650 K. Temperature was increased at rate of 5 K/min and the pressure in the sample chamber was kept constant at 0.3 bar, by means of a gas-flow controller. Two steps of mass loss, at around 350 K and 535 K respectively, are visible and correspond to the two structural *hcp-bcc* and *bcc-fcc* phase transitions discussed above.

The observed transition temperatures are slightly different with respect to those observed in the *in-situ* NPD experiment, but such discrepancy can be easily rationalized by taking into account the different sample environment, which in this case allowed a more precise control of the thermodynamic parameters. The amount of ammonia released in the two processes is roughly the same and corresponds to about six NH₃ molecules per C₆₀. Therefore, these findings confirm the results of the *in-situ* manometric analysis. DCS data indicate that the two desorption processes are endothermic, as expected.

The peak at 350 K appears broader than the one at 535 K, probably due to the more complex release mechanism of the first process, which actually involves two structural phase transitions (from phase 0 to phase 1 and from phase 1 to phase 2). From the peak area an estimate of the binding-energy of the released ammonia molecules was calculated. This ranges between 24 and 28 kJ/mol NH₃, a value significantly lower than the binding energy of Li-NH₃ clusters reported in literature (see also discussion below).³⁶

Discussion

It is well known that the ammonia molecule has the ability to co-intercalate into AIFs and to act as a neutral spacer for the host fullerene lattice. This phenomenon was exploited in the past in order to tune the electronic properties of fullerides. In fact, cubic A_3C_{60} compounds are highly correlated metals, which are found close to a Mott-insulating transition (MIT); a slight increase of the lattice parameter, obtained by inserting ammonia molecules in such compounds, can hence profoundly affect their electronic behaviour, for example pushing-up the superconducting transition temperature of the metallic phase, or even driving the system towards a MIT.³⁷⁻³⁹ However, to our knowledge, no research has so far explored systematically the ammonia-storage properties of these systems.




Figure 3: a) Manometric data of the NH₃ desorption process in $(NH_3)_y Li_6 C_{60}$ upon heating in the range 300-650 K (rate of 5 K/min). b) DSC data of the NH₃ desorption process. c) Refined volume per C₆₀ as a function of the number of ammonia molecules intercalated for the ammonia free-, super-expanded *bcc*- and hyper-expanded *hcp* phases of $(NH_3)_y Li_6 C_{60}$. The observed trend is roughly linear (dotted line).

In particular, the lithium intercalated fulleride $(NH_3)_6Li_3C_{60}$ is known to be stable at ambient conditions and possesses a super-expanded insulating *bcc* lattice, which leads to the onball localization of the three electrons donated by Li to C_{60} .³² In such system, two ammonia molecules are coordinated to each Li (see Figure 2 left) and occupy the 24g Wyckoff positions with half fractional occupancy. On the other hand, Li ions are in quasi-linear coordination with these sites, occupying at 25% occupancy the 24g position (0.38, 0.41, 0), with the Li-N

distance of ~2.15 Å, falling in the typical range observed in Li-NH₃ clusters.^{29,39,40} Such an arrangement indicates a relatively high degree of disorder, suggesting that more Li could in principle be accommodated in the lattice. In fact, in this work we observe a similar bcc structure in the (ND₃)_vLi₆C₆₀ phase, with y = 5-7 (phase 2), as shown in Figure 2. This system revealed to be stable in the temperature range 400-500 K during the desorption experiment and retains about half of the total amount of ammonia that can be stored in this system. The hyper-expanded $(ND_3)_y Li_6 C_{60}$ (see Figure 3 c)), with y = 12, 14 (phases 0 and 1), shows a different structure, that to our knowledge has been never observed so far, and it is stable up to 350-400 K. Although a detailed structural analysis was not possible, due to the low crystallinity of this phase, for y = 12we managed to index all the observed reflections with a hcp cell (see Figure 2 left and Figure 1S). The hcp-bcc transformation observed during the desorption process, when about half of the ammonia is released through an endothermic process, is not easily explained in terms of group-subgroup relations, while it can be rationalized in the framework of the Burgers model.⁴¹ Moreover, the *hcp-bcc* phase coexistence observed around 410 K suggests that this is a 1st order phase transition.

Above 500 K, the *bcc* structure undergoes a further phase transition to cubic *fcc* (phase 3), which results as an ammonia-free phase (see Figure 2 and Figure 1S). During the NPD experiment, this transition was reached by evacuating the sample space; for this reason, the manometric/DSC measurements provided a slightly higher *bcc-fcc* transition temperature, of about 535 K.

It is worth noting here that this value is still far lower than the decomposition temperature reported by Durand and coworkers for $(NH_3)_6Li_3C_{60}$,²⁹ which appeared stable up to 673 K. A higher thermal stability for (ND₃)_yLi₃C₆₀ was also evidenced by our NPD data, as for this phase the complete ammonia release was not reached at the accessible thermodynamic conditions (see in Figure 2S). This suggests that the Li-NH₃ binding energy in these systems should be somewhat driven by the Li stoichiometry, as it is known that, on increasing the Li content, its ionization progressively decreases and, as an example, in $Li_{12}C_{60}$ the charge transferred to C_{60} is of only 6 electrons.²² Specifically, during the past years, the stability of the Li(NH₃)_n (n = 1-5) complexes was thoroughly investigated⁴²⁻ ⁴⁴ in order to understand the unusual optical properties of alkali metals solvated in liquid ammonia;⁴⁵ in particular, the Li-N dissociation energies seem to strongly depend either on the number of ammonia molecules coordinated to the alkali atom, or to the charge state of the $Li(NH_3)_n$ cluster.³⁶ In our systems, depending on the amount of co-intercalated ammonia molecules, we expect the formation of Li(NH₃)_n clusters with n = 1-2, for which the calculated dissociation enthalpy range between 61.4 kJ/mol (n = 1) and 46.1 kJ/mol (n = 2) for the cluster in the neutral state, and between 169 kJ/mol (n = 1) and 125.8 kJ/mol (n = 2) for the cations $Li(NH3)_n^{+.36}$ Although a

1.

2.

5.

6.

8.

Journal Name

direct comparison with these data is not trivial, the DSC data collected on $(NH_3)_y Li_6 C_{60}$ (see Figure 3 b)) suggest that the cointercalation of the Li-ammonia clusters in the fullerene matrix is effective in bringing the Li-NH₃ binding energies towards lower values, probably due to the partial negative charge redistribution on the C₆₀ LUMO.

In order to check the reversibility of the ammoniation process, the completely discharged Li_6C_{60} sample underwent a second treatment in liquid NH₃, at the same conditions employed for the first process. By comparing the weight of the sample before and after the process, an increase of 14.8 wt% was again found and this corresponds to the nominal stoichiometry $(NH_3)_{6.64}Li_6C_{60}$. Therefore, the ammonia-storage appears partially reversible in this system. Laboratory XPD data indicated an improvement of the crystallinity in the ammoniated phase after the second treatment, although a fraction of Li amide (peak at $2\theta = 43^{\circ}$ in Figure 1S)⁴⁶ also appears. This fact may be due to a partial Li segregation, as a metal, upon the NH₃ discharge, followed by the reaction of the bare alkali with ammonia during the second uptake. This process is expected to limit the reversibility of the ammonia absorption of this system. Further investigations are however required in order to better evaluate the robustness of this system upon cycling.

Conclusions

The known ability of Li fullerides to co-intercalate ammonia was investigated thoroughly, with the aim to evaluate their possible applications in the field of energy-storage. Li₆C₆₀ is found to absorb up to 14 ammonia molecules per C_{60} , corresponding to the notable value of 36.8 wt% ND₃ (equivalent to 31.2 wt% NH₃) stored. This value slightly exceeds the hydrogen equivalent of 5.5 wt% which corresponds to the DoE goal for 2015.³ The hyper-ammoniated phase is stable at room temperature and the complete ammonia release was reached in two main steps, respectively at 350-410 K and 500-540 K, thus falling in a convenient temperature window, if compared with other known ammonia-storage systems. The comparison between the experimental desorption enthalpies for the two processes and those calculated for the dissociation of the Li(NH₃)_n clusters (n = 1-2) suggests that the co-intercalation of the Li-ammonia clusters in the fullerene matrix is effective to bring the Li-NH₃ binding energies towards values more suitable for applications in the field of ammonia-storage.

Acknowledgements

The authors would like to acknowledge the financial support from the Cariplo foundation (Project number 2013-0592, "Carbon based nanostructures for innovative hydrogen storage systems") and IRSES-EU Project MagNonMag nr. 295180.


References

- L. W. Jones, Science, 1971, 174, 367-370.
- L. Schlapbach and A. Zuttel, Nature, 2001, 414, 353-358.
- U.S DOE Annual energy outlook. Available online at http://www.eia.doe.gov/oiaf/aeo/.).
- A. Klerke, C. H. Christensen, J. K. Norskov and T. Vegge, Journal of Materials Chemistry, 2008, 18, 2304-2310.
 - V. Smil, Nature, 1999, 400, 415-415.
 - C. H. Christensen, R. Z. Sorensen, T. Johannessen, U. J. Quaade, K. Honkala, T. D. Elmoe, R. Kohler and J. K. Norskov, Journal of Materials Chemistry, 2005, 15, 4106-4108.
- 7. G. G. M. Fournier, I. W. Cumming and K. Hellgardt, Journal of Power Sources, 2006, 162, 198-206.
 - J. C. Ganley, F. S. Thomas, E. G. Seebauer and R. I. Masel, Catalysis Letters, 2004, 96, 117-122.
- 9. B. Peng and J. Chen, Energy & Environmental Science, 2008, 1, 479-483.
- 10. Y. Guo, G. Xia, Y. Zhu, L. Gao and X. Yu, Chemical Communications, 2010, 46, 2599-2601.
- G. Soloveichik, J.-H. Her, P. W. Stephens, Y. Gao, J. Rijssenbeek, M. Andrus and J. C. Zhao, Inorganic Chemistry, 2008, 47, 4290-4298.
- R. Z. Sørensen, J. S. Hummelshøj, A. Klerke, J. B. Reves, T. Vegge, J. K. Nørskov and C. H. Christensen, Journal of the American Chemical Society, 2008, 130, 8660-8668.
- Z. Huang, J. Gallucci, X. Chen, T. Yisgedu, H. K. Lingam,
 S. G. Shore and J.-C. Zhao, Journal of Materials Chemistry, 2010, 20, 2743-2745.
- 14. E. A. Sullivan and S. Johnson, The Journal of Physical Chemistry, 1959, 63, 233-238.
- S. R. Johnson, W. I. F. David, D. M. Royse, M. Sommariva, C. Y. Tang, F. P. A. Fabbiani, M. O. Jones and P. P. Edwards, Chemistry – An Asian Journal, 2009, 4, 849-854.
- C. J. Doonan, D. J. Tranchemontagne, T. G. Glover, J. R. Hunt and O. M. Yaghi, Nature Chemistry, 2010, 2, 235-238.
- J. A. Teprovich, M. S. Wellons, R. Lascola, S.-J. Hwang, P. A. Ward, R. N. Compton and R. Zidan, Nano Letters, 2011, 12, 582-589.
- P. Mauron, A. Remhof, A. Bliersbach, A. Borgschulte, A. Züttel, D. Sheptyakov, M. Gaboardi, M. Choucair, D. Pontiroli, M. Aramini, A. Gorreri and M. Riccò, International Journal of Hydrogen Energy, 2012, 37, 14307-14314.
- P. Mauron, M. Gaboardi, A. Remhof, A. Bliersbach, D. Sheptyakov, M. Aramini, G. Vlahopoulou, F. Giglio, D. Pontiroli, M. Riccò and A. Züttel, The Journal of Physical Chemistry C, 2013, 117, 22598-22602.
- M. Aramini, M. Gaboardi, G. Vlahopoulou, D. Pontiroli, C. Cavallari, C. Milanese and M. Riccò, Carbon, 2014, 67, 92-97.
- T. Yildirim, O. Zhou, J. E. Fischer, N. Bykovetz, R. A. Strongin, M. A. Cichy, A. B. Smith Iii, C. L. Lin and R. Jelinek, Nature, 1992, 360, 568-571.

- F. Giglio, D. Pontiroli, M. Gaboardi, M. Aramini, C. Cavallari, M. Brunelli, P. Galinetto, C. Milanese and M. Riccò, Chemical Physics Letters, 2014, 609, 155-160.
- 23. M. Gaboardi, C. Cavallari, G. Magnani, D. Pontiroli, S. Rols and M. Riccò, Carbon, 2015, 90, 130-137.
- M. Gaboardi, S. Duyker, C. Milanese, G. Magnani, V. K. Peterson, D. Pontiroli, N. Sharma and M. Riccò, The Journal of Physical Chemistry C, 2015, DOI: 10.1021/acs.jpcc.5b06711.
- M. Aramini, C. Milanese, D. Pontiroli, M. Gaboardi, A. Girella, G. Bertoni and M. Riccò, International Journal of Hydrogen Energy, 2014, 39, 2124-2131.
- A. K. Douglas, A. T. Joseph, Jr., S. Andrew, P. Brent, A. W. Patrick, N. C. Robert and Z. Ragaiy, Nanotechnology, 2013, 24, 455601.
- 27. M. J. Rosseinsky, D. W. Murphy, R. M. Fleming and O. Zhou, Nature, 1993, 364, 425-427.
- Zhou, R. M. Fleming, D. W. Murphy, M. J. Rosseinsky, A. P. Ramirez, R. B. van Dover and R. C. Haddon, Nature, 1993, 362, 433-435.
- 29. P. Durand, Y. Dubitsky, M. J. Rosseinsky and A. Zaopo, Dalton Transactions, 2004, 3137-3143.
- M. Riccò, M. Belli, T. Shiroka, D. Pontiroli, M. Pagliari,
 F. Gianferrari and A. Gorreri, Physica B: Condensed Matter, 2006, 374–375, 255-258.
- 31. S. Margadonna, E. Aslanis and K. Prassides, Journal of the American Chemical Society, 2002, 124, 10146-10156.
- 32. P. Durand, G. R. Darling, Y. Dubitsky, A. Zaopo and M. J. Rosseinsky, Nature Materials, 2003, 2, 605-610.
- P. Wzietek, T. Mito, H. Alloul, D. Pontiroli, M. Aramini and M. Riccò, Physical Review Letters, 2014, 112, 066401.
- A. J. Studer, M. E. Hagen and T. J. Noakes, Physica B: Condensed Matter, 2006, 385–386, Part 2, 1013-1015.
- M. H. Sørby, Y. Nakamura, H. W. Brinks, T. Ichikawa,
 S. Hino, H. Fujii and B. C. Hauback, Journal of Alloys and Compounds, 2007, 428, 297-301.
- 36. T. E. Salter and A. M. Ellis, Chemical Physics, 2007, 332, 132-138.
- M. Riccò, T. Shiroka, A. Sartori, F. Bolzoni and M. Tomaselli, EPL (Europhysics Letters), 2001, 53, 762.
- M. Riccò, G. Fumera, T. Shiroka, O. Ligabue, C. Bucci and F. Bolzoni, Physical Review B, 2003, 68, 035102.
- T. Shiroka, G. Fumera, O. Ligabue, M. Riccò and G. C. Antonioli, The Journal of Chemical Physics, 2006, 124, 204717.
- 40. T. E. Salter and A. M. Ellis, The Journal of Physical Chemistry A, 2007, 111, 4922-4926.
- 41. W. G. Burgers, Physica, 1934, 1, 561-586.
- 42. V. A. Nicely and J. L. Dye, The Journal of Chemical Physics, 1970, 52, 4795-4803.
- 43. M. Trenary, H. F. Schaefer and P. Kollman, Journal of the American Chemical Society, 1977, 99, 3885-3886.
- 44. R. L. Woodin and J. L. Beauchamp, Journal of the American Chemical Society, 1978, 100, 501-508.
- 45. J. C. Thompson, Electrons in liquid ammonia, Oxford University Press, 1976.
- 46. W. I. F. David, M. O. Jones, D. H. Gregory, C. M. Jewell, S. R. Johnson, A. Walton and P. P. Edwards,

Journal of the American Chemical Society, 2007, 129, 1594-1601.

8 | J. Name., 2012, 00, 1-3



 $\label{eq:Li_6C_60} \mbox{ can absorb up to 14 NH_3 per C_{60}, its structural evolution upon desorption is studied with neutron powder diffraction. $$1270x635mm (96 x 96 DPI)$ }$