

Water Diffusion Measurements of Single Charged Aerosol Using H2O/D2O Isotope Exchange and Raman Spectroscopy in an Electrodynamic Balance

Page 1 of 10 Physical Chemistry Chemical Physics

Received 00th January 20xx, Accepted 00th January 20xx

DOI: 10.1039/x0xx00000x

www.rsc.org/

Water Diffusion Measurements of Single Charged Aerosol Using H2O/D2O Isotope Exchange and Raman Spectroscopy in an Electrodynamic Balance

Katherine A. Nadler,^a Pyeongeun Kim,^a Dao-Ling Huang,^a Wei Xiong,^a and Robert E. Continetti^a

Sea spray aerosols contain a large array of organic compounds that contribute to high viscosities at low relative humidity and temperature thereby slowing translational diffusion of water. The Stokes-Einstein equation describes how viscosity is inversely correlated with the translational diffusion coefficient of the diffusing species. However, recent studies indicate the Stokes-Einstein equation breaks down at high viscosities achieved in the particle phase (>10¹² Pa·s), underestimating the predicted water diffusion coefficient by orders of magnitude and revealing the need for directly studying the diffusion of water in single aerosol. A new method is reported for measuring the water diffusion coefficient in single suspended charged sucrose-water and citric acid (CA)-water microdroplets in the 30-60 micron diameter range. The translational water diffusion coefficient is quantified using H₂O/D₂O isotope exchange technique between 26-54% relative humidity (RH) for sucrose and 7-25% RH for CA with a recently developed mobile electrodynamic balance apparatus. The results are in good agreement with literature, particularly the Vignes-type parameterization from experiments using isotope exchange and optical tweezers. Below 15% RH CA droplets show incomplete H₂O/D₂O exchange. This mobile electrodynamic balance will allow future studies of atmospherically relevant chemical systems, including field studies.

1 Introduction

Atmospheric aerosols are capable of scattering and absorbing solar radiation directly as well as interacting indirectly through cloud formation, and thus have great impact on climate and the hydrological cycle. Recently, the discovery of highly viscous and amorphous biogenic aerosol^{1,2} has attracted attention due to the prospect for very slow kinetics governing chemical change in these systems.³⁻⁵ While aqueous droplets with low viscosities establish equilibrium with the surrounding environment rapidly, the reduced translational mobility of molecules in high viscosity droplets reduces the rate of equilibration. This inevitably leads to reductions in heterogeneous reaction rates,^{6,7} impedes hygroscopic growth, $8-10$ and enhances ice nucleation.^{11,12} In order to quantify and model these phenomena, an understanding of water diffusion within such aerosol particles is essential as water is often the most mobile component in a viscous aqueous solution. This work presents a method for spectroscopically measuring water diffusion using isotope exchange in single model aerosol using an electrodynamic balance.

The Stokes-Einstein relation describes the diffusivity of solutes as a function of viscosity. A number of experimental techniques have been developed4,13–15 to measure the viscosity of individual aerosol particles both in the field and in the laboratory. In particular, recent studies have examined the impact of chemical composition and oxidation state of a variety of organic compounds on viscosity spanning a dynamic range from 10^{-3} Pa·s to values above the glass transition of 10^{12} Pa·s.¹⁶ Experimental techniques for measuring viscosity are important for improving our understanding of how chemical and environmental factors impact the phase state and heterogeneous reaction rates of ambient aerosol. Saccharides, in particular sucrose, have been used as model systems for validating new techniques to measure single aerosol viscosity $9,15$ because they can undergo a change in viscosity of greater than 10 orders of magnitude between $0 - 100$ % RH, allowing for the comparison of methods over a wide dynamic range. Sea spray has been shown to contain a significant fraction of organic material, particularly in the smaller size range $(d < 1 \mu m)^{17}$ Sucrose-water and CA-water can serve as benchmark systems to study the impacts of oxidized organic solutes sea spray aerosol at varying RH. However, application of the Stokes-Einstein relationship to aerosols using viscosity measurements alone has been shown to provide only a lower bound to the estimation of the diffusion coefficient because of the ability of water molecules to percolate through channels in viscous matrices.16,18,19 Therefore, techniques which measure water diffusion independent from viscosity are necessary to accurately predict evaporation, condensation, and cloud activation processes.

The development of methods to measure slow water diffusion directly has been a challenge, and only in recent years several complementary methods have been reported. Zhu *et al.* quantified maltose diffusion using Raman microscopy and isotopic labeling by compressing a non-deuterated and deuterated drop of maltose between two glass slides, creating an interface between the droplets.²⁰ The Raman C-D and C-H stretches were used to monitor the diffusion of the molecules across the interface as a function of temperature and humidity. Price *et al.* extended the method of Zhu to measure the diffusion coefficient for water in a sucrose-water disk by isotopically labeling the gas phase molecules and monitoring the substitution of D_2O for H_2O in the solution with Raman microscopy.²¹

However, compared to studying water diffusion of atmospheric aerosols on a substrate, contactless single particle techniques are preferred, because the aerosol is free from impacts of surface perturbations at concentrations above the solubility limit. In addition, single particle measurements are preferred over ensemble-averaged experiments, because composition and local chemical environments vary from particle to particle. Optical tweezers are one technique for spectroscopic studies of single, spherical particles from 1-10 μ m in diameter trapped at the center of a tightly focused laser beam by a balance of photon gradient forces that are insensitive to charge state.²² Scattering from the focusing laser is collected to provide high resolution size measurements using cavity enhanced features of the light

a.Department of Chemistry and Biochemistry, University of California San Diego, 9500 Gilman Drive, La Jolla, California 92093-0340, USA. E-mail:

rcontinetti@ucsd.edu; Tel: +1-858-534-6402

[†] Electronic Supplementary Information (ESI) available: [submitted with manuscript]. See DOI: 10.1039/x0xx00000x

ARTICLE Journal Name

scattering such as morphology dependent resonances,^{23,24} as well as chemical identity from the Raman scattering or fluorescence. The response of a single particle to changes in humidity or ambient gaseous composition provides measurements of chemical kinetics,25,26 and hygroscopicity.²⁷ For example, Davies *et al.* combined the isotopic exchange technique with an aerosol optical tweezer for single-particle confinement²⁸ allowing for a reduction in the sample size to less than 6 µm radius, speeding up the experimental timescales from weeks to hours. Isotopic tracer experiments have been carried out at a constant relative humidity (RH) leading to a constant size and solute concentration. Using Fick's second law of diffusion, Davies *et al.* modeled the time-dependent intensities of the ν(O-D) and ν(O-H) Raman peaks to quantify the diffusion coefficient as a function of concentration or water activity.²⁸

The electrodynamic balance (EDB) is a single particle technique that offers similar advantages including contactless levitation. However, it is not limited by size or morphology, as the trapping potential depends solely on mass-to-charge ratio. EDBs have been used extensively to measure physicochemical properties of single aerosol particles such as evaporation rates $29-32$ and nucleation, $33-37$ and provide complementary results to optical tweezers. For example, Zobrist *et al* used an EDB to conduct water diffusion measurements by creating a step change in the RH and observing the change in particle size using Mie resonance spectroscopy.³⁸ The result was interpreted using a theoretical framework based on principles of masstransport by dividing the particle into a discrete number of shells, within which water molecules translationally move to establish equilibrium. The flux of water molecules between shells, along with dynamic adjustment to the timesteps and shell thickness, was calculated to extract a concentrationdependent diffusion coefficient. Under high viscosity conditions the particle was assumed as a core-shell phase state as the surface established equilibrium rapidly while the core remained viscous, creating a non-linear radial concentration gradient. This led to the refractive index becoming a fit parameter along with the radius, decreasing the accuracy of the model at low RH. Despite differences in experimental setups, the isotope tracing model and mass transport model produce similar water diffusion coefficients in sucrose over a wide range of RH.21,28,38

The present work reports a technique that combines the Raman spectroscopic isotope tracing method previously applied on single aerosol in optical tweezers by Davies *et al.*²⁸ with an RH-controlled EDB to trap single charged aerosol droplets for measuring water diffusion. Sucrose-H₂O and CA-H₂O microdroplets are serially trapped and equilibrated at a specific RH, and then exposed to D_2O at the same RH. Raman spectra of the droplet are acquired as a function of time, in order to assess the progression of D_2O diffusing into the droplet. In the analysis of these measurements, it is assumed that the entire droplet is irradiated with the laser and the total content of water remains constant throughout an experiment so that a volume-averaged Fickian diffusion model can be used to describe the exponential growth of the ν(O-D) Raman peak. In the case of sucrose, D2O was observed to eventually replace all H_2O , as indicated by complete disappearance of the ν(O-H) asymmetric stretch peak in the Raman spectrum. At RH below 10% CA was not observed to completely exchange, indicating a kinetic limitation. In the following section, the experimental approach is described followed by presentation of the data for sucrose-water and CA-water.

2 Experimental

Water diffusion in single, charged aqueous microdroplets was studied using a D₂O/H₂O isotope exchange method in a new electrodynamic balance (EDB). Schematics of the experimental setup and optical layout are shown in Fig. 1. The electrodynamic balance electrode geometry is based on the design of Schlemmer *et al.*³⁹ later characterized in detail by Trevitt *et al.*⁴⁰ The balance is composed of two conical endcap electrodes separated by 5.3 mm with a 2.5 mm axial channel for laser optical access. Eight concentric rod electrodes replace the ring electrode in a traditional Paul trap, allowing for optical access over a wide range of angles. Each rod is electrically isolated, however an external DC levitation voltage is applied to the two rods directly below the trap center to counterbalance the gravitational force of the trapped microdroplet. The AC voltage is applied to the endcap electrodes only, at typical values V_p = 1500 V and f = 150 Hz. During an experiment the levitation voltage is adjusted using an automated LabView feedback control loop for maintaining the droplet in the trap center, while the AC frequency is maintained approximately constant.

The balance is mounted on a DN63CF Conflat flange equipped with electrical feedthroughs as well as a 1/8" OD copper gas-line feedthrough for introducing humidified or dried nitrogen gas directly into the trap. The balance is constructed on two octagonal plates, and is isolated from the air in the chamber by a set of stainless steel plates outfitted with windows, serving to electrically shield the high voltage electrodes which may otherwise interfere with the trajectory of incoming charged droplets. The plates also isolate the air in the center of the balance from the surrounding chamber, reducing the surface area and thus the time for equilibration of the RH. The isolation of the balance is augmented by a secondary Teflon housing that provides a direct channel from the opening of the chamber. The droplet generator is located above the balance, allowing droplets to be injected directly into the trapping volume. An electronic shutter is located at the opening of the chamber that opens for the introduction of a new droplet. A piezoelectric droplet generator (Engineering Arts DE03) is connected to an electronic syringe pump for precise control of the production of the aqueous droplets. Filtered aqueous sucrose or CA solutions are aspirated into the capillary of the droplet generator from which single droplets approximately 40 µm diameter are generated on demand using computer-controlled pulse generation to drive the piezoelectric element. A charging ring located above the shutter and electrically connected to the grounded piezoelectric tip inductively charges the droplets using an electrostatic potential. Occasionally multiple droplets are trapped simultaneously and the frequency of the AC is adjusted until all but one droplet are ejected.

The relative humidity in the balance is controlled with digital mass flow controllers (Alicat MC-500SCCM) by mixing N_2 with the humidified vapor headspace of a bubbler containing water. The humidified nitrogen is subsequently directed through copper tubing wrapped around and welded to a copper standoff in thermal contact with a Stirling free-piston coldhead cooler (Sunpower Cryotel CT) and resistive heaters, which serve to maintain a constant temperature and thermalize the air before entering the trap. However, the temperature control was not used in these experiments and the trap was maintained at the laboratory temperature, approximately 20-23° C. The temperature is recorded using a temperature probe (Vaisala HMP60) with $\pm 1^{\circ}$ C accuracy. Two bubblers, one containing distilled H₂O and the other

Fig 1. A) Experimental setup of the electrodynamic balance (EDB) apparatus contained in a secondary Teflon housing inside an environmental chamber and equipped with a droplet generator and dual bubbler RH control. **B)** Optical layout for a trapped droplet irradiated with a pulsed 532 nm laser. The forward Mie elastic scattering is collected on a CCD camera and the back-scattered Raman signal is passed through a beamsplitter and focused into a monochromator.

containing high purity D_2O (>99.8% D atom, Acros Organics), are arranged using 3-way valves as shown in Fig 1A so that air from one bubbler is selected to flow into the chamber while the other bubbler is exhausted. Experiments are carried out at constant RH by first trapping a single sucrose or CA droplet in H₂O RH and allowing sufficient time for equilibration. Then D_2O vapor at the same RH is introduced to the chamber, replacing the gas-phase H_2O in the balance and eventually diffusing into the H_2O droplet. During each experimental run, the H_2O humidified air is initially directed into the chamber for droplet equilibration while the D_2O bubbler is exhausted to fill intermediate tubing lines, minimizing changes in RH during the gas transition in the trap. The relative humidity and temperature are monitored using a humidity probe (Vaisala HMP60) with ±3% RH accuracy located approximately 25 mm downstream of the RH flow. For each water diffusion measurement the relative humidity is maintained constant to ±1%, or within the error of the probe. When the chamber atmosphere is switched to D_2O , the humidity probe measurement must be corrected for the difference in equilibrium vapor pressure of D_2O versus H_2O^{41} as shown in Eqn (1) where A = -0.30661, B = 9.14056, and C = 75.753 and T is in Celsius.

$$
ln\left(\frac{p_{H_2O}^0}{p_{B_2O}^0}\right) = A + \frac{B}{C+T}
$$
\n(1)

Two spectroscopic methods are used to characterize a trapped particle: Mie scattering for determining the particle size and Raman spectroscopy for chemical analysis. Shown in Fig. 1B the trapped droplet is irradiated with a focused 80 kHz, 532 nm Nd:YAG laser beam (RPMC Wedge XF). The elastic Mie scattering is collimated using an *f/2* lens with a solid angle of 24.5° centered at 45° in the forward-scattering direction and imaged onto a monochromatic CCD camera. The morphology of the trapped droplet is determined by the Mie scattering pattern. Spherical droplets exhibit evenly spaced bands and crystalline or amorphous solid particles exhibit an irregular pattern.³³ Fig. 2 shows an example Mie image of a single droplet and the resulting angular intensity spectrum, previously demonstrated in the literature to follow closely with Mie theory.²⁴ The diameter of droplets in these experiments is significantly larger than the wavelength of light, allowing a geometric optics approximation to be applied. The intensity spectrum is processed using a fast Fourier Transform (FFT) to compute an average band

spacing, Δθ, (rad-1). The band spacing is used in conjunction with the index of refraction, *n*, to calculate the particle radius*, r*, using Eqn (2):⁴²

$$
r = \frac{\lambda}{\Delta\theta} \left(\cos\left(\frac{\theta}{2}\right) + \frac{n\sin\left(\frac{\theta}{2}\right)}{\sqrt{1 + n^2 - 2n\cos\left(\frac{\theta}{2}\right)}} \right)^{-1}
$$
(2)

where λ is the laser wavelength (μ m) and θ is the median scattering angle (rad). The parameterization of the index of refraction with concentration of sucrose is described further in the Results section.

The evolving chemical composition of the trapped droplet from H_2O to D₂O is analyzed using the intensity of the stretches $v(O-D) \approx 2500 \text{ cm}^{-1}$ and ν(O-H) ~ 3400 cm-1 in the Raman spectrum. A representative Raman spectrum for a sucrose droplet is shown in Figure 2, and a representative spectrum for a CA droplet is showing in the Electronic Supplimentary Information (ESI) in Figure S3. The integrated intensity of the O-H and O-D stretches features allows calculation of the fractional concentration of D_2O in the droplet over time. The back-scattered Raman signal is collected using *f/2* optics, transmitted through the 532 nm laser edge beam splitter, and focused into a fiber optic cable coupled into a monochromator (Acton SpectraPro 275) with an open-electrode TE-cooled CCD detector (Horiba Syncerity). The spectrometer is equipped with a 600 g/mm grating with a 750 nm blaze for optimized quantum efficiency between 620-660 nm. The integration time for each spectrum is 30-120 s to achieve adequate signal-to-noise ratio. The LabView control and data acquisition program records the Mie and Raman spectra at a designated interval along with trap settings and conditions.

3 Results and Discussion

In this work, the time-dependent intensity of the *v*(O-D) Raman peak is modeled using Fick's second law of diffusion to calculate the water diffusion coefficient in sucrose and CA microdroplets for a range of RH. The timescale for diffusion is highly dependent on the droplet radius and therefore an accurate size measurement is necessary for incorporation into the diffusion model. In order to calculate the droplet size from the angular intensity spectrum produced by the Mie scattering, the index of refraction was calculated as a function of sucrose or CA concentration, which varies with

ARTICLE Journal Name

Fig. 2. A) Mie scattering image collected on a CCD camera for a 54 µm sucrose droplet and the associated angular intensity spectrum used to calculate the droplet size. **B)** Representative Raman spectrum for a sucrose droplet undergoing isotope exchange contains overlapping vibrational peaks which are simulated with a series of Gaussian peaks shown as the sum (red) and individual peak contributions (grey dashed).

water activity or RH. The method of parameterization of the index of refraction will be presented, followed by a discussion of how the Raman spectra were analyzed to determine the rate of isotopic substitution as D₂O diffused into the suspended droplet. With these results, the soluteconcentration-dependent water diffusion coefficients were calculated and modeled using a Vignes-type fit for comparison with the literature and validation of this method.

Parameterizations of the index of refraction

Calculation of the index of refraction for the droplet as a function of varying RH requires parameterization of the mass fraction solute (MFS) and density (*ρ*). The dependence of MFS on water activity, *aw*, has been well studied for sucrose solutions and the treatment by Norrish⁴³ has been shown to correlate with experimental measurements over the entire RH range:

$$
a_w = x_w exp\left(kx_s^2\right) \tag{3}
$$

where x_w and x_s are the mole fractions of water and solute, respectively, and k is an empirical constant equal to -6.47 for sucrose.⁴⁴ While other parameterizations have been proposed,^{38,45} the Norrish parametrization was

shown to be most appropriate for sucrose solutions over a wide range of RH.^{16,28} The density of a sucrose-water mixture can be taken as the volume additivity of pure component densities (VAD), with the pure component density of water, ρ_w = 1000 kg·m⁻³, and sucrose,⁴⁴ ρ_s = 1580.5 kg·m⁻³ giving:

$$
\frac{1}{\rho} = \frac{1 - MFS}{\rho_w} + \frac{MFS}{\rho_s} \tag{4}
$$

The refractive index of a sucrose solution varies with MFS and is parameterized using a linear fit with the refractive index for water, $n = 1.33$. at MFS(0) and *n* = 1.558 at MFS(1).⁴⁶ The calculated index of refraction of the sucrose droplet at a given RH is then used in Eqn (2) to calculate the droplet diameter. The uncertainty in droplet size (±10 nm) due to wavelengthdependent dispersion is negligible compared the experimental error (±500 nm) from the RH probe,⁸ making it unnecessary to implement the highly accurate parameterization for sucrose solutions reported by Rosenbruch et al.⁴⁷ For CA, comprehensive parametrization of MFS with *aw* and the refractive index of CA solution by Lienhard et al. was adopted.⁴⁸

Diffusion of D2O using Raman spectroscopy

The coefficient for translational diffusion of water, *Dw*, as a function of water activity, or RH, is extracted using a solution to Fick's second law of diffusion as applied to a sphere.⁴⁹ Considering sucrose, since the total amount of sucrose is constant throughout each experiment all spectra are normalized to the sucrose $v(C-H)$ peak at 2930 cm⁻¹, allowing for correction for fluctuations in spectral intensity due to low amplitude motions of the droplet in the laser beam. A seven-Gaussian fit is applied to the spectrum between 2000 – 3800 cm-1 to determine individual peak contributions and therefore calculations of relative abundances of chemical species present. One Gaussian contributes to the O-D band, two Gaussians to the C-H stretch, one Gaussian to the weak C-H overtone peak (α) , two Gaussians to the O-H band, and a weak, broad Gaussian accounts for background signal. Fig. 2B shows the contributions of the seven Gaussians for an example Raman spectra of a sucrose droplet approximately halfway through an isotope exchange experiment when distinct peaks from both H_2O and D_2O are present.

In the case of CA droplets, 8 Gaussians are used to fit the spectra. The values of fit parameters are adjusted relative to sucrose due to the distinct Raman spectra. Typical fit parameters are given in the ESI. Three Gaussians

Fig. 3. **A)** An example set of Raman spectra for a 54 µm sucrose droplet undergoing isotope exchange at 44% RH shows the decrease in peak intensity of the ν(O-H) at ~3400 cm⁻¹ and the growth of the ν(O-D) at ~ 2500 cm⁻¹. **B)** The fraction of the water concentration of D₂O and H₂O in the droplet over time is modeled with Fickian diffusion to determine the concentration-dependent water diffusion coefficient.

are assigned to O-D and O-H band each and two Gaussians represent C-H stretch peak. For spectra of CA droplets overall broadening of O-D and O-H stretch band was observed and the α peak was found to be negligible compared to sucrose droplets. We note multiple Gaussians for fitting the O-H/O-D bands are necessary, because of the multiple configurations of the hydrogen bond network in liquid water.⁵⁰ Typical CA spectra and examples for the Gaussian fitting parameters for CA droplets are presented in the ESI.

At a constant relative humidity, the total amount of water in the droplet is assumed to be constant and equal to the sum of the contributions from H_2O and D_2O . Fig. 3A shows the progression of Raman spectra collected during an experiment, starting from the top where only the ν(O-H) is observed and over time the intensity of the ν(O-H) decays and the ν(O-D) grows in. The spectrum is decomposed using multiple Gaussian peaks fitting as discussed earlier, from which the peak areas for O-D and O-H are used to calculate the fractional concentration of D_2O in the droplet:

$$
\phi_{OD} = \frac{A_{OD}}{A_{OD} + \frac{1}{\sqrt{2}} A_{OH}}
$$
\n(5)

where the O-D stretch located at 2500 $cm⁻¹$ has a lower integrated intensity by a factor of 1/√2 based on the difference in reduced mass.²¹ When the gas manifold valves are rotated to switch from H_2O to D_2O , there is a time delay until the chamber is sufficiently filled with D_2O and the isotope exchange begins. Fig. 3B shows the concentration fractions of D_2O and H_2O at 44% RH that are initially constant as the droplet equilibrates and then abruptly change from baseline values. It can be assumed that for a period of time, approximately 30 – 480 s over the RH range from 54% to 7%, respectively, the droplet is undergoing isotope exchange while the chamber atmosphere is a mixture of H₂O, HOD, and D₂O. Formation of HOD in an H₂O/D₂O mixture does not cause any detectable peak shift and intensity change from spectral features for the pure D_2O/H_2O mixture, e.g., the spectral peak intensity of a 50/50 H₂O/D₂O (that is composed of 25% H₂O, 25% D₂O and 50% HOD), agree with theoretical spectral features composed with 50% H₂O and 50% D₂O, so it makes using a method based Eq. (5) still valid for determine the original fractional concentration of D_2O^{50} During this time the vapor-liquid interface does not meet the condition that the gas-phase concentration of D_2O is constant, assumed by the diffusion model derived from Fick's second law. In addition, we have neglected the difference in diffusion coefficient as H_2O and D₂O are assumed to have identical physical properties, within the reported error.⁴⁹ We therefore introduce a systematic approach for determining when constant D_2O RH is reached by fitting the time-dependent fractional concentration of OD with a three-parameter S-shaped curve where A, B, and C are empirically determined:

$$
\phi_{OD} = \frac{1}{1 + A \exp\left(-B + Ct\right)}\tag{6}
$$

The time at the inflection point of the S-shaped fit is selected as $t = 0$ for D_2O diffusion and indicates the time at which D_2O vapor has sufficiently replaced the $H₂O$ in the trapping volume, and only the successive O-D fractional concentration data (e.g., the regionn where the green line spans in Fig. 4b) are used in the calculations. The solution to Fick's second law of diffusion applied to a sphere is used to model the time-dependent dimensionless fractional concentration of the diffusing D_2O :^{28,49}

$$
\phi_{D_2O} = 1 - \left(\frac{6}{\pi^2}\right) \sum_{n=1}^{\infty} \frac{1}{n^2} exp\left(-\frac{n^2 \pi^2 D_w t}{a^2}\right) \tag{7}
$$

where *a* is the particle radius and D_w is the translational diffusion constant. A three-term expansion of equation (7) with a single adjustable parameter is used to calculate *Dw* for each of the experimental runs at a different RH. The upper limit for diffusion coefficients measured using this technique is calculated as \approx 5 x 10⁻¹³ m²s⁻¹. The sources of the upper limit include the rapid diffusion in the droplet sizes at high RH, the acquisition time required for adequate spectral signal-to-noise, and the time delay associated with fully replacing the composition of the atmosphere in the trapping volume.²⁸

Water diffusion in aqueous sucrose droplets

The water diffusion coefficients measured for sucrose-water droplets at RH between 26-54% at room temperature are shown in Fig. 4. The RH is reported with absolute error of the probe, ±3 %, and the error in the *Dw* measurement is estimated as 50%, calculated from an uncertainty of ±20% in the model fit, ±1 µm uncertainty in the size calculation, differences in self-diffusion between H₂O and D₂O (10-24%)²¹, the RH fluctuation (\pm 1%) and temperature stabilization (\pm 1 °C) over the course of an experiment. The results are compared with parameterizations from literature reported by Zobrist et al.,³⁸ Price *et al.*,²¹ and Davies *et al.*²⁸ Over the range where data was obtained, the results agree well with the Vignes-type parameterization that describes the variation of the water diffusion coefficient, D_w , with composition in a binary mixture:⁵¹

$$
D_w = (D_{w,w}^0)^{x_w} (D_{w,s}^0)^{(1-x_w)}
$$
(8)

, where x_w is the mole fraction of water, $D^0_{w,w}$ is the translational diffusion coefficient in pure water (2 x 10^{-9} m²s⁻¹), and $D^0_{w,s}$ is the self-diffusion coefficient of water in pure solute $(1.9 \times 10^{-27} \text{ m}^2\text{s}^{-1})$, reported by Davies *et al.*²⁸). Excellent agreement was found between the present results using the EDB and previous reports with various techniques^{28,52,53} showing the viability of this method for quantifying the translational diffusion coefficient over a range of water activities. However, the agreement deviates when approaching at the high RH limit. At 54% the timescale for diffusion is comparable to the turnover time for replacing the air in the chamber, allowing for isotopic exchange to occur rapidly in the droplet while exposed to an effectively lower D_2O concentration because the air is still a mixture of H₂O and D₂O. The resulting D_w at high RH, approximately 1 x 10⁻¹³ m²s⁻¹, is lower than the Vignes-type trend followed by other published results and serves as an upper bound to the dynamic range of the diffusion coefficients that can be quantified using this experimental setup.

The results in Fig. 4. are consistent with measurements carried out using isotope exchange over $6 - 300$ μ m diameter samples which suggests there is

Fig. 4. Calculated water diffusion coefficients in sucrose droplets at varying RH studied in this work compared with parameterizations provided by Zobrist *et al.*, ³⁸ Price *et al.*²¹ and Davies *et al.*²⁸

not a significant impact of droplet size on the water diffusion coefficient in the 35 – 60 µm size range studied. The droplet diameters studied in this work were significantly larger than the <10 µm diameter droplets used by Zobrist *et al.*³⁸ and Davies *et al.*²⁸ and significantly smaller than the 200 – 300 µm diameter substrate-supported disks used by Price *et al.*²¹ This suggests that the droplet size does not have a significant effect on the diffusion coefficient as a correlation between *Dw* and diameter across these different size ranges is not observed. *Dw* of sucrose solution below 25% RH is of great interest because prediction from two methods (isotope exchange and mass transport) diverges orders of magnitude. The large discrepancy is due to different assumptions used in two models. In the mass transport model, the radius of the droplet changes as it experiences sorption and desorption of water with the RH change. On the other hand, the isotope exchange model assumes a constant radius of the droplet held at fixed RH. Thus, the mass transport model involves a moving and nonlinear boundary condition while the isotope exchange model assumes a fixed linear boundary condition.49,52 Measuring *D^w* at RH below 25% in the case of sucrose was beyond the scope of the current measurements due to the diffusion timescales.54,55

The present results can be compared with both charge-neutral particles in the case of the isotope-exchange measurements of Price *et al.*²¹ and Davies *et al.*²⁸ and charged particles in the mass-transport measurements of Zobrist *et al.*³⁸ The comparison suggests that the surface charge density on the droplets in this work $\left($ <40 elementary charges/ μ m²) do not significantly influence D_2O diffusion into droplets. If the charge state significantly impacted the diffusion of D_2O into the droplet the best agreement would be expected between the results conducted in EDBs, which is not the case. Instead, the best agreement was found with the optical tweezer measurements on neutral microdroplets using the isotope labeling technique. These results can be understood in the context of studies on the influence of charge on both ice nucleation and efflorescence. Homogeneous ice nucleation rates of pure water droplets were measured in a temperaturecontrolled EDB as a function of temperature and absolute charge and it was concluded that while temperature strongly influenced the nucleation rate, no correlation with the surface charge was observed over a range of ± 200 charges/μm².^{34,56} Charged droplets with 10x greater surface charge density compared to the droplets in the current work were examined and no effect of the charge on nucleation was found, supporting the conclusion that excess charges are not interfering with bulk processes such as diffusion within a droplet. Another recent study measured the dependence of the efflorescence relative humidity on the magnitude of the surface charge in sodium chloride microdroplets and found no correlation below 500 elementary charges/ μ m².³⁷ Molecular dynamics simulations showed that above this charge density threshold, the charges interact with dissolved ionic species to form stable critical cluster sizes necessary for overcoming the energetic nucleation barrier at higher RH compared to neutral droplets. In the present work, the sucrose droplets contain surface charge density significantly below the threshold suggested by Hermann *et al.*³⁷ to impact efflorescence behavior. Thus, the present work demonstrates an alternative way that can be used to study particles imcompatible with optical trapping techniques, e.g., amorphous (or glassy) aerosols or solid particles which have nonspherical morphology.

Water diffusion in aqueous citric acid droplet

Water diffusion in citric acid solution droplets was measured over a lower RH range (7-25 %) compared to sucrose. The RH-dependent refractive index of a CA solution was parameterized using the MFS of CA and water to deduce

ARTICLE Journal Name

droplet size.⁴⁸ The RH dependent D_w values of CA droplet are shown in Fig. 5, revealing good agreement with the other isotope exchange measurements using optical tweezers²⁸ and a significant deviation from from D_W values measured by mass-transfer⁵⁷ as well as the predictions of the the S-E equation.⁵⁸ Isotope-exchange derived *DW* values of CA below 10% RH at room temperature are reported here for the first time, and it is found that in this regime, the intensity of Raman O-H band at 3400 cm-1 does not diminish to zero in the exchange process. This may arise from inhibited diffusion of water in CA droplet under very dry conditions. In addition, the results at RH lower than 15% reveal that the aqueous CA droplets do not undergo full isotope exchange, with all labile hydrogens replaced by deuterium, over a period up to 65 hours. This observation may be a result of the much larger size of the droplet compared to the study of Davies and Wilson.²⁸ Because equation (7) assumes complete H_2O/D_2O exchange, it is no longer valid for describing water diffusion at RH < 15%. To analyze incomplete H_2O/D_2O exchange for CA at lower RH's we introduce a modified solution to Fick's 2nd law, equation (9). The equation contains an additional parameter χ that represents the fractional exchange as a function of RH, and reveals the kinetic limitation of water diffusion. For instance, $χ = 1$ means complete exchange of H₂O to D₂O and equation (9) is analogous to equation (7) while χ = 0.7 indicates 70% of total H_2O in the droplet is exchanged to D_2O .

$$
\phi_{D_2O} = \chi(1 - \left(\frac{6}{\pi^2}\right) \sum_{n=1}^{\infty} \frac{1}{n^2} exp\left(-\frac{n^2 \pi^2 D_w t}{a^2}\right))
$$
(9)

Application of the two equations (7) and (9) to the isotope exchange data at low RH is illustrated in ESI figure S5, showing that equation (9) represents the physical phenomena significantly better than equation (7). Figure 6. shows the strong observed dependence of χ on RH illustrating the incomplete H₂O/D₂O exchange at lower RH (χ < 1) and full exchange of H₂O to D₂O at RH higher than 15% ($\chi \sim 1$). It is not surprising for CA droplets of this size to develop a radial concentration gradient under dry conditions. Consequently, the true values of D_w are expected to be smaller than the values calculated using equation (9) because the diffusion of D_2O into the droplet core is not complete. The Fickian diffusion model assumes a homogeneous mixture after sufficient equilibration time, which is not truly achieved here owing to the kinetic limitation, but it was chosen for analysis of D_w in the CA droplets as well owing to its simplicity and applicability to both sucrose and CA data. A kinetic multi-layer model⁵⁹ or Maxwell-Stefan diffusion model⁶⁰ may be used in future studies to describe the formation of concentration gradient within

Fig. 5. RH dependent D_w for CA droplets compared to other experiments. Isotopic exchange using optical tweezer (Davies et al.)²⁸, mass transfer (Lienhard *et al.*) ⁵², and S-E prediction from viscosity data (Marshall *et al.*) 53

the droplet as these models explicitly consider the droplet as a series of spherical shells.

Similar kinetic limitations of diffusion have previously been observed for ambient organic aerosol, particularly in highly viscous or glassy state aerosol where formation of a significant radial concentration gradient in the droplet, inhibits reaching thermodynamic equilibrium.^{1,61} The inhibited diffusion of water in CA droplets may be attributed to formation of molecular clusters in the supersaturated solution. It is worth comparing the results of H_2O/D_2O exchange at the lower RH bound for sucrose (26%) and CA (7%). The exchange was incomplete for CA over several days while sucrose showed full exchange $(X = 1)$ even though the D_w value of CA (9.19 x 10⁻¹⁶ m² s⁻¹) is notably higher than that of sucrose $(4.52 \times 10^{-16} \text{ m}^2 \text{ s}^{-1})$ at the stated conditions. In addition, the viscosities of the droplets show orders of magnitude difference (~10¹⁰) Pa · s for sucrose vs ~10⁴ Pa · s for CA). Taking these observations into account, one can suppose that CA has a much higher propensity to form organized molecular structures with water than sucrose does within the highlysaturated solution (MFS > 0.9). This is supported by studies that observed solute clustering in supersaturated CA solutions.⁶²⁻⁶⁵ From a chemical perspective, citric acid is a tricarboxylic acid that will have much stronger interactions with water through the acidic hydrogens and the polar –COOH groups compared to sucrose. Similar kinetic inhibition for diffusion of reactive condensed-phase species have been reported for glassy aerosol at low RH8,9,57 but our result explicitly shows the strong dependence of this phenomenon on RH. Aggregation of solute-water clusters in supersaturated droplets may lead to radial concentration gradients that promote formation of a core-shell morphology, preserving the unreacted core species with potential implications for surface-sensitive phenomena such as cloud condensation nucleation (CCN) and ice nucleation (IN) activities.⁶⁶ Mie scattering measurements remained consistent with liquid droplets even at these low RH, so the question that arises is how 'liquid' or 'solid' a particle needs to be to distinguish the particle phase by Mie scattering.67,68

4 Conclusions

The translational water diffusion coefficient was measured in single charged sucrose and CA droplets as a model system for sea spray aerosol at humidities ranging from 26-54% RH for sucrose and 7-25% RH for CA at room temperature. Water diffusion has been quantified using H_2O/D_2O isotope tracing measured with Raman spectroscopy of a single charged droplet trapped in a humidity-controlled EDB. The measured water diffusion coefficients-molar concentration relationship follows an exponential dependence, described as a Vignes-type parameterization. The data were

shown as nonunity ϕ_{D_2O} values given by equation (9). Error bars represent the 95% confidence interval of the fitting parameter χ.

compared with previous studies of the sucrose-water and CA-water system using the isotope exchange technique on neutral samples and a mass transport method on charged droplets. The comparison between our results and other Raman spectroscopy based methods shows good agreement of water diffusion coefficients across a wide range of sample sizes and volumes, suggesting the *Dw* values are not size-dependent. The agreement of this work using charged droplets in an EDB with neutral particles in an optical trap suggests that charge does not play a significant role under the conditions studies.

The Raman spectroscopic technique for isotope exchange analysis is limited to particle sizes greater than 1µm because of the low signal to noise ratio. Improvement of the sensitivity of the optical setup would be of great value in extending the present measurements to smaller aerosols with diameters of 50-200 nm, which are the size population most efficient for cloud activation^{69,70} and therefore of large climate relevance. Experimental modifications to control temperature and particle charge will reduce uncertainties in the diffusion measurements and allow a more detailed examination of charge effects. Temperature control will also serve for further comparisons of the method over a range of atmospherically relevant temperatures with the temperature-dependent *Dw* measurements made using the mass transport method,³⁸ as well as extending these measurements to examine the effect of viscosity and chemical composition on ice nucleation.

The present measurements further demonstrate the ability to measure water diffusion independently from viscosity under atmospherically relevant conditions. The isotope exchange method for measuring water diffusion rates can be applied to a variety of chemical systems and complexity including ternary mixtures of atmospheric relevance, the influence of hygroscopic inorganic salts, and concentration-dependent effects of monovalent and divalent cations found in sea spray aerosols. One of the first systems to investigate at reduced temperatures will be the citric acid system to examine further the origin of the strong kinetic limitation to isotope exchange.

Conflicts of interest

There are no conflicts to declare.

Acknowledgements

This work was supported by NSF through the NSF Center for Aerosol Impacts on Chemistry of the Environment (CAICE), CHE-1801971. We thank J. Mayer for his contributionsto apparatus design and fabrication. We also thank the reviewers for insightful comments. All relevant data will be made available online at the CAICE digital collection at the UC San Diego library.

(https://library.ucsd.edu/dc/collection/bb96275693).

References

- 1 B. Zobrist, C. Marcolli, D. A. Pedernera and T. Koop, *Atmos. Chem. Phys.*, 2008, **8**, 5221–5244.
- 2 M. V Orellana, P. A. Matrai, C. Leck, C. D. Rauschenberg, A. M. Lee and E. Coz, *Proc. Natl. Acad. Sci. U. S. A.*, 2011, **108**, 13612–13617.
- 3 A. Virtanen, J. Joutsensaari, T. Koop, J. Kannosto, P. Yli-Pirila, J. Leskinen, J. M. Makela, J. K. Holopainen, U. Poschl, M. Kulmala, D. R. Worsnop and A. Laaksonen, *Nature*, 2010, **467**, 824–827.
- 4 E. Jarvinen, K. Ignatius, L. Nichman, T. B. Kristensen, C. Fuchs, C. R. Hoyle, N. Hoppel, J. C. Corbin, J. Craven, J. Duplissy, S. Ehrhart, I. El Haddad, C. Frege, H. Gordon, T. Jokinen, P. Kallinger, J. Kirkby, A. Fig. 6. Kinetic limitations of water diffusion are evident at RH below 15%

Kiselev, K. H. Naumann, T. Petaja, T. Pinterich, A. S. H. Prevot, H.

ARTICLE Journal Name

30, 2113–2122.

- 56 D. Rzesanke, J. Nadolny, D. Duft, R. Muller, A. Kiselev and T. Leisner, *Phys. Chem. Chem. Phys.*, 2012, **14**, 9359–9363.
- 57 D. M. Lienhard, A. J. Huisman, D. L. Bones, Y. F. Te, B. P. Luo, U. K. Krieger and J. P. Reid, *Phys. Chem. Chem. Phys.*, 2014, **16**, 16677– 16683.
- 58 F. H. Marshall, R. E. H. Miles, Y. C. Song, P. B. Ohm, R. M. Power, J. P. Reid and C. S. Dutcher, *Chem. Sci.*, 2016, **7**, 1298–1308.
- 59 M. Shiraiwa, C. Pfrang and U. Pöschl, *Atmos. Chem. Phys.*, 2010, **10**, 3673–3691.
- 60 K. Fowler, P. J. Connolly, D. O. Topping and S. O'Meara, *Atmos. Chem. Phys.*, 2018, **18**, 1629–1642.
- 61 A. Virtanen, J. Joutsensaari, T. Koop, J. Kannosto, P. Yli-Pirilä, J. Leskinen, J. M. Mäkelä, J. K. Holopainen, U. Pöschl, M. Kulmala, D. R. Worsnop and A. Laaksonen, *Nature*, 2010, **467**, 824–827.
- 62 J. W. Mullin and C. L. Leci, *Philos. Mag.*, 1969, **19**, 1075–1077.
- 63 K. Ohgaki, Y. Makihara, M. Morishita, M. Ueda and N. Hirokawa, *Chem. Eng. Sci.*, 1991, **46**, 3283–3287.
- 64 K. Ohgaki, N. Hirokawa and M. Ueda, *Chem. Eng. Sci.*, 1992, **47**, 1819–1823.
- 65 M. A. Larson and J. Garside, *Chem. Eng. Sci.*, 1986, **41**, 1285–1289.
- 66 M. Shiraiwa, Y. Li, A. P. Tsimpidi, V. A. Karydis, T. Berkemeier, S. N. Pandis, J. Lelieveld, T. Koop and U. Pöschl, *Nat. Commun.*, 2017, **8**, $1 - 7$.
- 67 C. F. Bohren and D. R. Huffman, *Absorption and Scattering of Light by Small Particles*, 1998, vol. 31.
- 68 C. Mätzler, *IAP Res Rep*, 2002, **2002**–**08**, opening-18.
- 69 M. Komppula, H. Lihavainen, V. M. Kerminen, M. Kulmala and Y. Viisanen, *J. Geophys. Res.*, 2005, **110**, D06204.
- 70 H. C. Che, X. Y. Zhang, L. Zhang, Y. Q. Wang, Y. M. Zhang, X. J. Shen, Q. L. Ma, J. Y. Sun and J. T. Zhong, *Sci. Rep.*, 2017, **7**, 5819.

Water Diffusion Measurements of Single Charged Aerosol Using H2O/D2O Isotope Exchange and Raman Spectroscopy in an Electrodynamic Balance

Katherine A. Nadler,^a Pyeongeun Kim,^a Dao-Ling Huang,^a Wei Xiong,^a and Robert E. Continetti^a

Table of Contents Entry:

We report water diffusion measurements on single charged aerosol using isotope exchange in an electrodynamic balance.

Table of Contents Graphic:

