

# Soft Matter

Accepted Manuscript



This is an *Accepted Manuscript*, which has been through the Royal Society of Chemistry peer review process and has been accepted for publication.

*Accepted Manuscripts* are published online shortly after acceptance, before technical editing, formatting and proof reading. Using this free service, authors can make their results available to the community, in citable form, before we publish the edited article. We will replace this *Accepted Manuscript* with the edited and formatted *Advance Article* as soon as it is available.

You can find more information about *Accepted Manuscripts* in the [Information for Authors](#).

Please note that technical editing may introduce minor changes to the text and/or graphics, which may alter content. The journal's standard [Terms & Conditions](#) and the [Ethical guidelines](#) still apply. In no event shall the Royal Society of Chemistry be held responsible for any errors or omissions in this *Accepted Manuscript* or any consequences arising from the use of any information it contains.

**Role of the hydrophobic phase  
for the unique rheological properties  
of saponin adsorption layers**

Konstantin Golemanov,<sup>1</sup> Slavka Tcholakova,<sup>2</sup>  
Nikolai Denkov,<sup>2</sup> Eddie Pelan,<sup>1</sup> Simeon D. Stoyanov<sup>1,3,4\*</sup>

<sup>1</sup> *Unilever R&D, Vlaardingen, The Netherlands*

<sup>2</sup> *Department of Chemical Engineering  
Faculty of Chemistry and Pharmacy, Sofia University  
1 J. Bourchier Ave., 1164 Sofia, Bulgaria*

<sup>3</sup> *Laboratory of Physical Chemistry and Colloid Science, Wageningen  
University, 6703 HB Wageningen, The Netherlands*

<sup>4</sup> *Department of Mechanical Engineering, University College London, Torrington Place,  
London WC1E 7JE, UK*

\*Corresponding author:

Prof. Simeon Stoyanov  
Unilever R&D  
Vlaardingen  
The Netherlands

Phone: (+31) 10 460 6221

Fax: (+31) 10 460 6384

E-mail: Simeon.Stoyanov@unilever.com

**Keywords:** surface rheology, shear, saponins, oil-water interface, surface elasticity, surface viscosity.

### Abstract

Saponins are diverse class of natural, plant derived surfactants, with peculiar molecular structure consisting of a hydrophobic scaffold and one or several hydrophilic oligosaccharide chains. Saponins have strong surface activity and are used as natural emulsifiers and foaming agents in food and beverage, pharmaceutical, ore processing, and other industries. Many saponins form adsorption layers on air-water interface with extremely high surface elasticity and viscosity. The molecular origin of the observed unique interfacial visco-elasticity of saponin adsorption layers is of great interest from both scientific and application viewpoints. In the current study we demonstrate that the hydrophobic phase in contact with water has very strong effect on the interfacial properties of saponins and that the interfacial elasticity and viscosity of the saponin adsorption layers decrease in the order: air > hexadecane >> tricaprylin. The molecular mechanisms behind these trends are analyzed and discussed in the context of the general structure of the surfactant adsorption layers at various nonpolar phase-water interfaces.

## 1. Introduction.

The term “saponin” includes a great variety of natural surfactants, found in more than 500 plant species.<sup>1-3</sup> The saponins are inverted to common surfactants (having hydrophilic head group and hydrophobic tail), since they consist of hydrophobic headgroup, called aglycone, and one or several hydrophilic oligosaccharide (sugar) chains, connected via glycoside bonds to the aglycone. The saponins are classified on the basis of: (i) The type of aglycone (triterpenoid or steroid), and (ii) The number of attached sugar chains. The most common saponins are those with two sugar chains (bidesmosidic saponins) and one sugar chain (monodesmosidic saponins).

Due to their amphiphilic molecular structure, many saponins have strong surface activity. Several authors<sup>4-11</sup> reported high surface elasticity of saponin adsorption layers at air-water interface, both in dilatation<sup>4-6</sup> and shear deformations.<sup>7-11</sup> These properties are important in the context of saponin applications as foam and emulsion stabilizers, because the interfacial properties were shown to control many of the dynamic properties of foams and emulsions, such as water drainage, rheological properties, Ostwald ripening, etc.<sup>12-21</sup> In addition, the high shear elasticity of thin layers became of particular interest recently,<sup>4-8,22-26</sup> because it was associated with the formation of drops and bubbles with non-Laplacian shapes, periodic wrinkles at interfaces, and other complex phenomena in soft matter systems, which still lack a complete understanding and quantitative description.

In our previous study<sup>8</sup> we investigated the surface rheological properties of a series of eight triterpenoid and three steroid saponins, with different numbers of oligosaccharide chains. Adsorption layers on air-water interface, under shear deformations, were studied. All steroid saponins showed no surface shear elasticity and viscosity. In contrast, most of the triterpenoid saponins showed complex visco-elastic behavior with extremely high elastic modulus (up to 1100 mN/m) and viscosity (130 N.s/m). These values were explained by the formation of densely packed adsorption layers with strong hydrogen bonds between the sugar residues in the neighbouring adsorbed molecules.

In an independent study, Wojciechowski<sup>6</sup> examined the effect of the hydrophobic phase on the properties of adsorption layers of the saponin extract from one plant (*Quillaja saponaria*). He showed that the surface dilatational elasticity of this triterpenoid saponin decreases in the order air-water > tetradecane-water > olive oil-water interface. No explanation for the observed dependence was proposed and the question whether the same trend holds for other saponins and for shear deformation remained open.

Similar effects of the non-polar phase on the rheological properties of adsorption layers of other types of surfactants were reported by several groups.<sup>27-31</sup> For example, Benjamins et al.<sup>30</sup> found that the surface dilatational elasticity of adsorption layers of globular proteins decreases in the order air > tetradecane > triglyceride. The same trend was reported for other proteins by several groups.<sup>27,30-31</sup> Similar effect was reported by Garofalakis and

Murrey<sup>28</sup> for monolayers of nonionic low-molecular-mass surfactants, when comparing air-water and tetradecane-water interfaces. These results are usually explained in the literature by reduced attraction between the adsorbed surfactant molecules, due to their solvation by the oil molecules at the oil-water interface.

Interestingly, for polymer adsorption layers an opposite effect was reported by Camino et al.<sup>29</sup> higher surface elasticity was measured at triglyceride-water interface, compared to air-water interface. This result was also explained with the formation of mixed oil-polymer adsorption layer, which is more visco-elastic, due to (assumed) strong attraction between the oil molecules and the hydrophobic segments of the polymer molecules.

For all types of surfactant systems (including the mixed surfactant+cosurfactant systems, often used in various applications) one could envisage two possible, conceptually different explanations for the effect of the non-polar phase on the adsorption layer properties. The first mechanism implies a direct intercalation of the oil molecules in between the adsorbed surfactant molecules, thus modifying the molecular interactions within the adsorption layer (Figure 1A-B). The second mechanism assumes a partial dissolution of surfactant molecules into the oily phase (Figure 1C-D). In both cases, the result is a decreased density of the surfactant adsorption layers and reduced cohesion between the adsorbed molecules (unless a strong specific attraction with the oil molecules is assumed, as in Ref. 29). The first mechanism is expected to be relevant for the globular proteins, due to their low solubility in oil. The second mechanism is expected to be relevant to systems containing low-molecular-mass nonionic surfactants, because of their non-negligible solubility in the oily phase.

For the saponins, which are the main subject of the current study, it is entirely unclear in advance which of these mechanisms could occur, due to the lack of essential information about their interfacial rheological properties and their solubility in oil. Furthermore, a given saponin extract usually contains molecules with different numbers of attached saccharide residues, viz. these extracts are surfactant mixtures containing molecules with different hydrophilic/lipophilic balance. The oily phase could dissolve the most lipophilic components in the saponin extracts, thus effectuating the mechanism illustrated in Figure 1D. The latter effect could be particularly important also for another very important class of surfactant systems, namely the mixtures of ionic+nonionic surfactants (e.g. mixture of ionic surfactant + fatty alcohol or fatty acid) which are widely used in the scientific studies<sup>32-37</sup> and in various applications to control the surface mobility and dynamic properties of foams.

The main purpose of the current study is to investigate systematically the effect of the hydrophobic phase on the interfacial rheological properties of saponin adsorption layers and to explain the observed trends. We studied a series of eleven saponin extracts,<sup>8</sup> which differ significantly in their molecular structure - in the type of aglycone and in the number of oligosaccharide chains. Adsorption layers at the air-water, hexadecane-water and tricapylin-

water interfaces are compared. Hexadecane is chosen as a representative of the typical non-polar oils, whereas tricaprilin is chosen as a representative of the moderately “polar” triglyceride oils, relevant to food and pharmaceutical applications.

We have chosen to compare the shear (not dilatational) rheological properties of the adsorption layers, because the shear deformation does not change the area per molecule. Therefore, this type of measurement emphasizes the role of intermolecular interactions, by excluding their interference with the changes in the area per molecule and the related adsorption-desorption processes, which occur in dilatational surface deformation.

The current study reveals a strong effect of the hydrophobic phase on the interfacial rheological properties of saponin layers. The molecular mechanisms behind the observed trends are explained, and the relevance of the two possible explanations (Figure 1) to other surfactant systems of general interest is discussed. Besides, the obtained results demonstrate that the saponins can be used as a coherent series of surfactant systems which covers a very wide range of interfacial rheological properties. Therefore, they are particularly suitable for systematic investigation of the (still elusive) relation between the interfacial rheological properties and the foaming and emulsifying properties of surfactants.

The article is organized as follows. Section 2 gives brief information on the materials and methods used. Section 3 presents the main results and their discussion. Section 4 summarizes the main conclusions.

## 2. Materials and methods.

**2.1. Materials.** We studied 11 saponin extracts, obtained from 10 different plants – see the Supplementary information for the molecular structure and the basic physico-chemical properties of the saponins studied. Most of the saponins (8 out of 11) have a triterpenoid hydrophobic backbone – Escin (ES), Horse chestnut extract (HC), Tea Saponin (TS), Berry Saponin Concentrate (BSC), Sapindin (Sap), Quillaja Dry (QD), Gisenosides (GS) and Ayurvedic Saponin Concentrate (ASC). The other saponins - Tribulus terrestris (TT), Fenusterols (FS) and Foamation dry (FD) have a steroid hydrophobic backbone. A single extract may contain different saponin molecules which share the same aglycone while having different oligosaccharide chains. These chains may differ in number, length or composition (type of sugar residues). Most extracts contained between 25 and 50 wt % saponins. Exceptions were Tea saponin, Escin, and Ginsenosides, which were of higher purity (> 80 %). Only one of the studied saponins (Escin) was a single pure chemical, product of Sigma: escin (type II): cat. num. E1378, CAS Number 6805-41-0, molecular formula  $C_{54}H_{84}O_{23}$ . All experiments were performed with solutions containing 0.5 wt % saponin and 10 mM NaCl. Note that all saponin extracts used in this study are highly soluble in water and that the used concentration is well below their solubility limit.

n-Hexadecane with purity 99 % was obtained from Alfa Aesar (cat. No. A10322; CAS 544-76-3). Tricaprylin (glyceryl trioctanoate) with purity  $\geq 99\%$  was obtained from Sigma (cat. No.T9126; CAS 538-23-8). Both oils were used as received. Hexadecane and tricapyrin are abbreviated in the text as “C16” and “3C8” respectively. The terms “hexadecane-water” and “tricapyrin-water” are abbreviated as “C16-W” and “3C8-W”, respectively.

According to literature data,<sup>38</sup> the viscosity of n-hexadecane at 20 °C is 3.45 mPa.s. The viscosity of tricapyrin at 20 °C was 20.2 mPa.s, as measured with a rotational rheometer AR2000ex (TA Instruments), equipped with a cone and plate geometry with cone radius of 6 cm and cone angle of 0.3 °.

**2.2. Methods.** The surface rheological properties were characterized with a double-wall ring (DWR),<sup>39</sup> attached to ARG2 rotational rheometer (TA instruments). The rheometer provides information for the angle of rotation of the ring,  $\Omega$ , and the torque,  $M$ , exerted on the ring. From these data and from the geometrical parameters of the setup, one can determine the surface stress and the deformation of the adsorption layer.

In the general case, one has to account for the coupling between the flows in the surface and the sub-surface layers, and the raw data for the torque should be corrected using a numerical procedure.<sup>39</sup> However, if the adsorption layer has high surface viscosity,  $\eta_s$ , and the Boussinesq number,  $Bo \gg 1$ , the analysis is greatly simplified, because the torque originates almost exclusively from the contribution of the surface stress. By definition, the Boussinesq number represents the ratio between the surface and sub-surface drags:<sup>40</sup>

$$Bo = \frac{\eta_s(V/L_S)P_S}{(\eta + \eta_o)(V/L_B)A_S} = \frac{\eta_s}{(\eta + \eta_o)Q} \quad (1)$$

where  $\eta$  is bulk viscosity of aqueous solution,  $\eta_o$  is the bulk oil viscosity,  $V$  is the characteristic flow velocity, and  $L_S$  and  $L_B$  are characteristic length-scales, over which the surface and sub-surface flows decay.  $P_S$  is the perimeter of the geometry in contact with the interface,  $A_S$  is the area of the geometry in contact with the bulk phase (solution and oil), and  $Q$  is a geometrical parameter. The value of  $Q$  for the DWR is  $\approx 0.7$  mm.<sup>39</sup> In most of the experiments presented in the current paper, the Boussinesq number was  $Bo \gg 1000$  (viscoelastic layers) or  $Bo > 100$  (viscous layers with relatively high  $\eta_s$ ) – for these systems the torque on the tool is dominated by the surface stress. In such a case, taking into account that DWR configuration is a 2D-analog of the double-wall rheometer, one can calculate the surface strain,  $\gamma$ , and surface stress,  $\tau$ , via the relations:<sup>41</sup>



$$\gamma = \frac{\Omega}{\left(\frac{R_2}{R_1}\right)^2 - 1} + \frac{\Omega}{1 - \left(\frac{R_3}{R_4}\right)^2} \quad (2)$$

$$\tau = \frac{M}{2\pi(R_2^2 + R_3^2)} \quad (3)$$

Here  $R_2$  and  $R_3$  are the inner and outer radii of the ring, while  $R_1$  and  $R_4$  are the inner and outer radii of the circular channel, respectively.

We subjected the saponin layers to rheological tests in oscillatory (amplitude sweep) and in creep-recovery shear deformation. All experiments were performed at 20 °C. Before each experiment, the studied adsorption layer was pre-sheared for 3 min at shear rate of  $103 \text{ s}^{-1}$  (11 rad/s). Next, the layer was left to age for certain period (30 min) and the actual rheological measurements were performed.

In the amplitude sweep test we varied the strain amplitude,  $\gamma_A$ , from 0.01 to 20 %, at constant frequency  $\nu = 1 \text{ Hz}$ . In the creep-recovery experiments we applied constant stress for a given creep time,  $t_{CR} = 100 \text{ s}$ , and afterwards we monitored the relaxation of the deformation for 30 min. Experiments at different torque values were performed.

The experiments showed that the modulus of the visco-elastic saponin layers increased significantly with the time elapsed after the pre-shear of the layer,  $t_A$  (for brevity, we call this period “time of layer aging”). To characterize the process of layer aging, we applied continuous oscillations of the adsorption layers for 12 h, at very small strain amplitude (0.1 %) and constant frequency (1 Hz). These measurements allowed us to monitor the evolution of the viscous and elastic moduli of the layers, as functions of their aging time,  $t_A$ .

### 3. Results and discussion.

**3.1. Comparison of the rheological response of the adsorption layers, formed at various hydrophobic phase-water interfaces.** In our previous study<sup>8</sup> we showed that the saponin extracts with the highest surface elastic moduli at air/water interface, were those of Escin, Tea saponins and Berry saponins, all containing predominantly monodesmosidic triterpenoid saponins. Similarly high surface modulus was measured with Ginsenosides extract, containing bidesmosidic triterpenoid saponins with short sugar chains. Intermediate elastic modulus ( $\approx 100 \text{ mN/m}$ ) and viscosities ( $\approx 10 \text{ Pa.s.m}$ ) were measured with saponin extracted from *Quillaja saponaria*, containing bidesmosidic triterpenoid saponins with long sugar chains. The other saponin extracts (incl. all steroid saponins) showed much lower or negligible surface elasticity on air-water interface.



In the current study we first compare all these extracts in creep-recovery experiments, with adsorption layers formed on hexadecane-water and tricaprylin-water interfaces, see Figure 2. The same experimental conditions are used, as in our previous study<sup>8</sup> – a torque of 1  $\mu\text{N.m}$  was applied for 100 s, after 30 min of layer aging. For better structuring the presentation, it is convenient to use the classification from our previous study, where the saponins were divided into several groups, depending on the type of rheological response of the adsorption layers, formed on air-water interface:

(1) Group EV includes QD, BSC, TS, Escin and GS saponins which form layers on air-water interface with very high surface shear Elasticity and Viscosity.

From these extracts only QD showed such high elasticity and viscosity on all three interfaces studied – see Figure 2A where the strain amplitude of the QD elastic adsorption layers is compared for the various interfaces.

The adsorption layers of Escin and Tea saponin extracts exhibit similar visco-elastic response at air-water and hexadecane-water interfaces, whereas no elasticity and very low viscosity on tricaprylin-water interface were observed, cf. Figures 2B and 2D.

The adsorption layer of GS showed no elasticity and very low viscosity on both oil-water interfaces studied, see Figure 2D.

(2) Group V includes HC and SAP which showed purely Viscous response at air-water interface, with very high shear viscosity (could be measured directly, because  $Bo \gg 1$ ).

In this group, only Sapindin showed high viscosity,  $\approx 1.6 \text{ mPa.m.s}$ , on C16-water interface (Figure 2C), whereas the layer formed on tricaprylin-water interface had much lower viscosity (Figure 2D). HC showed no measurable elasticity or viscosity for any of the oil-water interfaces studied.

(3) Group LV (Low surface Viscosity) includes FD, FS, TT and ASC. These extracts show detectable viscous response on the air-water interface, but the surface viscosity is rather low ( $Bo < 30$ ). All these saponins showed no measurable elasticity or viscosity on any of the oil-water interfaces studied.

From these results we see that the hydrophobic phase has a remarkably high impact on the shear rheological properties of the saponin adsorption layers. The shear visco-elasticity decreases in the order air-water > hexadecane-water  $\gg$  tricaprylin-water interface, which agrees with the trend reported by Wojciechowski<sup>6</sup> for the dilatational properties of QD adsorption layer. Therefore, the hydrophobic phase affects significantly both the shear and dilatational surface properties for all saponins studied.

As we are interested mostly in the systems with visco-elastic behaviour, below we focus the study on the saponins from Group EV.

### 3.2. Characterization of saponin group EV in creep-recovery experiments.

In our previous creep-recovery experiments<sup>7,8</sup> we showed that the layer compliance is described by a single master curve, viz. the rheological parameters are stress-independent, if the applied stress is below a certain critical value,  $\tau < \tau_C$ . The stress  $\tau_C$  was similar in value to the critical stress,  $\tau_0$ , determined from oscillatory experiments (see section 3.3). Therefore, both  $\tau_C$  and  $\tau_0$  characterise the stress which leads to disruption of the layer structure.

Previous experiments showed also that the visco-elastic response of the adsorption layers of QD, Escin, TS and GS, formed on air-water interface, could be described very well by compound Voigt (CV) model.<sup>42</sup> The mechanical analogue of this model is a combination of one Maxwell and two parallel Kelvin elements, connected sequentially, see Figure 4C in Ref. [8]. No simpler rheological model could describe the observed visco-elastic response of these layers, due to the complex shape of the creep-recovery curves.<sup>7</sup>

According to the CV model, the compliance during creep,  $J_{CR}$ , is described by the equation:

$$J(t) = \frac{1}{G_0} + \frac{1}{G_1} \left[ 1 - \exp\left(-\frac{t}{\lambda_1}\right) \right] + \frac{1}{G_2} \left[ 1 - \exp\left(-\frac{t}{\lambda_2}\right) \right] + \frac{t}{\eta_0} \quad (4)$$

and the compliance during recovery is governed by the expression:

$$J_R(t) = \frac{t_{CR}}{\eta_0} + \frac{1}{G_1} \left[ 1 - \exp\left(-\frac{t_{CR}}{\lambda_1}\right) \right] \exp\left(-\frac{t}{\lambda_1}\right) + \frac{1}{G_2} \left[ 1 - \exp\left(-\frac{t_{CR}}{\lambda_2}\right) \right] \exp\left(-\frac{t}{\lambda_2}\right) \quad (5)$$

Here  $G_0$ ,  $\eta_0$  and  $\lambda_0 = \eta_0 / G_0$  are the elastic modulus, viscosity, and relaxation time of the Maxwell element, while  $G_i$ ,  $\eta_i$  and  $\lambda_i = \eta_i / G_i$  are the respective characteristics of  $i$ -th Kelvin element ( $i = 1, 2$ ).

As explained above, the adsorption layers from QD extract behave as elasto-viscous body on all three interfaces studied (Figure 2A) and the experimental curves are described very well by the CV model. The adsorption layers of TS on air-water and hexadecane-water interfaces are also described well by CV model, see Figure 2B. Interestingly, the Escin adsorption layer on hexadecane-water interface could be described by the simpler Burgers model (BM) which is represented as one Maxwell and one Kelvin elements, connected sequentially.<sup>43</sup>

The rheological response of the BSC adsorption layer on air-water interface was described as well by the BM and has surface elasticity. On the air-hexadecane interface, the same layer was better described with the Maxwell model (BM without a Kelvin element) with parameters:  $G_0 = 27 \pm 5$  mN/m and  $\eta_0 = 10 \pm 1$  mPa.m.s.

Thus we see that lower elasticity and simpler rheological response are observed in the transition from air-water to hexadecane-water and tricaprylin-water interfaces.

The rheological parameters, determined at the different interfaces, are compared in Figure 3 and Table S2 in Supplementary information. For QD layers, one sees that the shear elasticities and viscosities decrease by  $\approx 2$  times when replacing A-W with C16-W interface, and further strong reduction is observed for 3C8-W interface. Even larger effects are observed for the other saponins in this group.

### 3.3. Characterization of EV adsorption layers in oscillatory experiments.

Figure 4 presents the dependence of the elastic and viscous moduli of different saponins on C16-W interface, as a function of the strain amplitude,  $\gamma_A$ , at constant frequency (1 Hz). In Figure 5 we compare these dependences for QD adsorption layers, formed on A-W, C16-W and 3C8-W interfaces.

In all these systems (except for BSC layer on C16-W interface) the elastic modulus at low strain amplitude is much higher than the viscous modulus, i.e. these layers are predominantly elastic. In all systems,  $G'$  and  $G''$  remain almost constant at low strain amplitudes, up to 1-2 %. At a certain strain, the elastic modulus starts to decrease, while the viscous modulus passes through a maximum. These maxima in  $G''$  dependence are explained as arising from the perpetual formation and destruction of the contacts between the structural entities in the slowly deforming layer.<sup>44,45</sup> In our layers, we expect that  $G''$  increases initially, due to the friction between the sliding domains in the slowly sheared adsorption layers, while the layer structure is disrupted significantly after the maximum in  $G''$ , as evidenced by the rapidly decreasing layer elasticity at higher deformation.<sup>8</sup>

One can define several characteristics of the saponin adsorption layers which can be compared and interpreted from physico-chemical and structural viewpoints:

Strain,  $\gamma_0$ , at which the elastic modulus decreases down to 95 % of the initial value in the plateau region at  $\gamma \rightarrow 0$ . We found in ref. 8 that the rheological properties of the adsorption layers are practically the same for all stresses  $\tau \leq \tau_0$ , where  $\tau_0$  is the stress corresponding to  $\gamma_0$ .

Strain,  $\gamma_{CR}$ , at which  $G' = G''$  and significant structural changes of the adsorption layers occur. Above the stress  $\tau_{CR}$ , which corresponds to  $\gamma_{CR}$ , the adsorption layers become fluid and the elastic structure of the layer is lost. At intermediate stresses  $\tau_0 < \tau < \tau_{CR}$ , the structural changes in the adsorption layers reduce its stiffness, but the main structure of the layer is preserved and one can describe the rheological response by the same rheological model as for the elastic layer, though with reduced values of the rheological parameters;

Figure 6 presents a comparison of some of these characteristics for the adsorption layers on air-water, hexadecane-water and tricaprylin-water interfaces, for the different saponins studied. One sees that, for a given saponin, the critical strain  $\gamma_{CR}$  is not affected by

the nature of the hydrophobic phase, see Figure 6A. In contrast, the values of  $\gamma_0$  are strongly affected by the hydrophobic phase. The values of  $\gamma_0$  are much lower for C16-W interface, compared to A-W interface for Escin and TS, whereas there are similar for QD. Significant decrease of  $\gamma_0$  for QD adsorption layers is observed only for the layers formed on tricaprilyn-water interface.

The critical stress  $\tau_{CR}$ , above which the internal structure of the adsorption layers is completely disrupted, is lower for C16-W interface, compared to A-W interface for all these saponins, see Figure 6B. The effect of the hydrophobic phase is even larger for  $\tau_0$  (except for QD on C16-W interface), see the full symbols in Figure 6B.

In Figure 7 we summarize the surface elastic and viscous moduli for all saponins, for the three interfaces studied. One sees that the various systems demonstrate a wide variety of behaviours, including highly elastic layers (with much lower viscosity), highly viscous layers (with low elasticity), and layers with negligible visco-elasticity. This variety of surface properties provides a unique toolbox for studying the complex relation between the interfacial rheological properties of the saponin solutions, the peculiar properties of saponin-stabilized drops and bubbles, and the bulk properties of the respective foams and emulsions.

In ref. 4 we have demonstrated already that the Quillaja saponin layers make a “skin” on the surface of water droplets with a subsequent wrinkling upon large surface contraction (see Figure 9 in Ref. 4). Here, as an additional illustration of the peculiar properties of these systems, we show in Figure 8 the oil droplets of sunflower-in-water emulsion, stabilised with QD and BSC extracts, which have stable non-spherical shape with wrinkled surface that does not relax for many days. This is a manifestation of the formation of highly elastic and potentially non-homogenous surface layer that do not obey the Laplace law of capillarity. The relation between the interfacial rheological properties and the conditions for formation of such droplets of peculiar shape is not clear at the moment and we are performing a systematic series of experiments to elucidate this relation. The analysis of this relation is complex and goes beyond the scope of the current paper. We could mention now only that the emulsions prepared with the saponin solutions, studied in the current paper, were stable, with a lifetime of days and weeks.

Before entering the discussion section, we briefly describe the effect of aging (time after pre-shear) of the adsorption layers on their rheological properties. In our previous study<sup>8</sup> we showed that the properties of the saponin adsorption layers formed on air-water interface change significantly with aging time for the saponins with EV behaviour, see Figure 8 in Ref. [8]. These changes reflect a slow rearrangement of the saponin molecules in the adsorption layer, at almost fixed saponin adsorption. For the current study we performed similar series of oscillatory experiments in which the surface modulus of the adsorption layers on C16-W and 3C8-W interfaces were measured, as a function of time, at constant frequency (1 Hz) and deformation (0.1%). For all systems with EV behaviour we observed steady increase of  $G'$

over time which was described well by bi-exponential function (see Figure S3 in Supplementary information):

$$G' = G_0' + G_1' (1 - \exp(-t/t_{R1})) + G_2' (1 - \exp(-t/t_{R2})) \quad (6)$$

where  $G_0'$ ,  $G_1'$ ,  $G_2'$  are the surface elastic moduli, while  $t_{R1}$  and  $t_{R2}$  are the two characteristic times for rearrangement of the saponin molecules in the adsorption layers. From the best fits to the experimental data we determined the values of the parameters which are summarized in Table S3 in Supplementary information.

These results show that  $t_{R1}$  and  $t_{R2}$  are much longer (scale of hours) than the characteristic relaxation times,  $\lambda_i$ , determined in the creep-relaxation experiments (seconds to several minutes). Therefore, the aging includes very slow processes of building and compaction of the domain structure of the adsorption layers. The characteristic times for QD molecules in the adsorption layers at A-W, C16-W and 3C8-W interfaces are all very similar. On the other hand  $t_{R1}$  is about 2 times longer for Escin adsorption layer and by more than 4 times longer for TS layers formed on C16-W interface, compared to A-W interface. For TS layers the hydrophobic phase affects also the second characteristic time,  $t_{R2}$ . The observed difference between the various saponin extracts are discussed in the following section 3.4.

### 3.4. Molecular interpretation of the observed effects.

Two aspects are considered in the current section from the viewpoint of molecular structure and interactions in the adsorption layer: (1) how the oil phase affects the properties of the adsorption layers of a given saponin and (2) how the saponin molecular structure affects the layer properties.

Aspect (1) can be considered on the basis of the two possible mechanisms, illustrated in Figure 1. The possible dissolution of saponin components in the oily phase (Figure 1C-D) was directly checked by placing 0.5 wt % of each saponin extract (as solid powder) in contact with hexadecane or tricaprilin oil, under stirring with magnetic stirrer for 1 h. Afterwards, these oily phases were stored overnight for sedimentation of the non-dissolved solid particles and a drop of these oily phases was placed in contact with pure water to measure the oil-water interfacial tension. Any reduction of the interfacial tension below that of the pure oil-water interface would indicate dissolution of some saponin components in the oily phase.

These measurements showed that only TS had noticeable dissolution in hexadecane and BSC - in tricaprilin. For all other saponin extracts, the oil-water interfacial tension was not affected by the oil-saponin contact which is a clear indication for the lack of saponin solubility in the oily phase. Thus we can conclude that, for almost all saponin systems studied,

the observed lower surface elasticity and viscosity could be explained only by intercalation of oil molecules between the adsorbed saponin molecules, Figure 1A-B.

The experimental results indicate that the intercalation of hexadecane molecules weakens the interactions between the saponin molecules in the adsorption layers (Figure 9A-B), but without destroying the layer structure and the layers preserve their visco-elastic nature. The observed effect of tricaprilyn is more dramatic, probably because the polar heads of the triglyceride molecules tend to be in contact with the water molecules at the interface, as shown in Figure 9C. Such deep penetration of the bulky tricaprilyn molecules inside the adsorption layer should lead to much larger spacing between the adsorbed saponin molecules and strongly reduced interactions, just as observed experimentally. Indeed, the comparison of the surface tension isotherms of Tea Saponin on air-water and tricaprilyn-water interfaces showed that the slope of the dependence interfacial tension vs. logarithm of surfactant concentration is by about 50 % larger for the air-water interface. According to Gibbs adsorption equation, this larger slope corresponds to larger area per molecule in the adsorption layer at oil-water interface.

Only for TS at the hexadecane-water interface and for BSC on tricaprilyn-water interface we could not determine unambiguously which of the two mechanisms is dominant – the observed solubility of these saponins in the oil phase keeps open the possibility that the mechanism of partial dissolution, shown in Figure 1D could be also important, beside the intercalation mechanism shown in Figure 1B.

Aspect (2) concerns the effect of saponin molecular structure on the layer rheological properties. As explained in our previous study,<sup>8</sup> the layers of Escin, TS and QD exhibit high visco-elasticity, most probably due to formation of strong intermolecular hydrogen bonds between the sugar chains of the nicely packed neighbouring molecules in the adsorption layers. The latter explanation is supported by the fact that the elastic properties of these layers are lost when a chaotropic agent urea (known to disrupt the hydrogen bonds) is placed in the aqueous phase, see Figure 10.

As discussed in Refs. 7-8, the monodesmosidic Escin and Tea saponins (with one oligosaccharide chain) are packed at air-water interface in side-on configuration (Figure 9A) with area per molecule around  $0.5 \text{ nm}^2$ , whereas the bidesmosidic QD is in a lay-on configuration (Figure 9D) with area per molecule  $\approx 1 \text{ nm}^2$ . The current study shows that the monodesmosidic saponins had much lower visco-elastic modulus on oil-water interface, as compared to air-water interface. In contrast, the modulus of the bidesmosidic QD layer was only moderately lower for hexadecane-water interface and still significant for tricaprilyn-water interface. All relaxation times for QD are weakly affected by the hydrophobic phase which was not the case for the other saponins. Thus we see that the lay-on configuration of QD saponins is significantly less affected by the nature of the hydrophobic phase. Apparently, the

two sugar chains attached to the aglycone of the QD molecules act as “anchors” and fix better the QD molecules to the interface, thus reducing the effect of the oil molecules.

At the end, let us discuss briefly the relevance of the mechanisms shown in Figure 1 to the other main systems, mentioned in the introduction. The proteins are typically insoluble in the oil phases. Therefore, the intercalation of oil molecules between the adsorbed protein molecules is the only possible mechanism for these systems (Figure 1B).

For the mixtures of ionic surfactant + fatty acids, very high surface dilatational moduli were reported for air-water interface, of the order of 100-300 mN/m. For the current study we measured the surface modulus for the same systems (by oscillating drop method) on hexadecane-water and tricapriline-water interfaces and found that the surface moduli were strongly reduced to  $< 5$  mN/m. The fatty acids used as cosurfactants in these systems, are known to have rather high solubility in the oily phases. Therefore, for these systems we see that both mechanisms are operative, as shown in Figure 1, because the extraction of the cosurfactant molecules is accompanied also with intercalation of oil molecules between the chains of the main surfactant. The latter assumption is supported by measurements of other authors<sup>28</sup> which showed that the area per molecule of the surfactants is usually larger at oil-water interfaces, as compared to air-water interface. Similar is the mechanistic explanation for the other type of nonionic cosurfactant (dodecanol, tetradecanol) widely used in foam studies and applications.

#### 4. Main results and conclusions.

In this article we compare the shear rheological properties of saponin adsorption layers on air-water, hexadecane-water and tricapriline-water interfaces. Eight triterpenoid and three steroid saponins are compared. The main conclusions could be summarized as follows:

In all experiments, the steroid saponins (TT, FS and FD) had very low shear interfacial viscosity and no measurable elasticity.

Three of the triterpenoid saponins showed visco-elastic behaviour on the hexadecane-water interface. These were two monodesmosidic saponins (TS and ESC) and one bidesmosidic saponin (QD), which all share the same aglycone (triterpenoid, oleanane type). The obtained results show that the layers of the monodesmosidic saponins are affected to a much higher degree by their contact with hexadecane and tricapriline, as compared to the bidesmosidic saponin with the same aglycone. The oil molecules get intercalated in the adsorption layer and perturb strongly the packing of the monodesmosidic molecules on the interface, thus weakening the interactions between them (Figure 9A-C). In contrast, the orientation of the bidesmosidic molecules on the interface is better fixed by the two



oligosaccharide chains in their molecules – as a result, the layer structure and rheological behaviour are less dependent on the nature of the non-aqueous phase (Figure 9D).

The possible mechanisms behind the observed trends are discussed, Figures 1 and 9, and a comparison with other systems forming visco-elastic adsorption layers (proteins, mixtures of ionic+nonionic surfactants) is performed in section 3.4.

The observed variety of interfacial rheological properties (see Figure 7) shows that the saponins present a unique series of structurally similar molecular systems which cover all major types of surface visco-elastic behaviour. This variety of properties makes the saponins particularly suitable for studying the intriguing and still poorly understood relation between the interfacial rheological properties and the properties of drops and bubbles, emulsions and foams (e.g. Figure 8).

### **Acknowledgments**


The authors are grateful to Unilever R&D Vlaardingen, FP7 Project Beyond Everest, COST Actions FA1001 and MP1106 for the support. K.G. is grateful to the Marie Curie Intra-European fellowship program. The measurements of the dilatational modulus of SLES+CAPB+myristic acid by the oscillating drop method and of the saponin solubility characterization were performed by Ms. Nevena Borisova. The authors are particularly grateful to the referees who made several useful suggestions for improving the manuscript.

**References:**


1. Hostettmann, K.; Marston, A. *Saponins*; Cambridge University Press: New York, **1995**.
2. Vincken, J.-P.; Heng, L.; De Groot, A.; Gruppen, H. Saponins, classification and occurrence in the plant kingdom. *Phytochemistry* **2007**, *68*, 275.
3. Guglu-Ustundag, Q.; Mazza, G. Saponins: Properties, applications and processing. *Critical Rev. Food Sci. Nutrition* **2007**, *47*, 231-258.
4. Stanimirova, R.; Marinova, K.; Tcholakova, S.; Denkov, N. D.; Stoyanov, S.; Pelan, E. Surface Rheology of Saponin Adsorption Layers. *Langmuir* **2011**, *27*, 12486-12498.
5. Wojciechowski, K.; Orczyk, M.; Marcinkowski, K.; Kobiela, T.; Trapp, M.; Gutberlet, T.; Geue, T. Effect of hydration of sugar groups on adsorption of *Quillaja* Bark saponin at air/water and Si/water interfaces. *Colloid Surface B* **2014**, *117*, 60.
6. Wojciechowski, K. Surface Activity Of Saponin From Quillaja Bark At The Air/Water And Oil/Water Interfaces. *Colloid Surface B* **2013**, *108*, 95.
7. Golemanov, K.; Tcholakova, S.; Denkov, N. D.; Pelan, E.; Stoyanov, S. Surface shear rheology of saponins. *Langmuir* **2012**, *28*, 12071.
8. Golemanov, K.; Tcholakova, S.; Denkov, N. D.; Pelan, E.; Stoyanov, S. D. Remarkably high surface visco-elasticity of adsorption layers of triterpenoid saponins. *Soft Matter* **2013**, *9*, 5738-5752.
9. Shorter, S. A. On Surface Separation from solutions of Saponin Peptone, and Albumin. *Phil. Mag.* **1909**, *17*, 560-563.
10. Joos, P.; Vochten, R.; Ruysen, R. The Surface Shear Viscosity of Mixed Monolayers Interaction Between Cholesterol and Digitonin. *Bull. Soc. Chim. Belges* **1967**, *76*, 601.
11. Blijdenstein, T. B. J.; de Groot, P. W. N.; Stoyanov, S. D. On the link between foam coarsening and surface rheology: Why hydrophobins are so different. *Soft matter* **2010**, *6*, 1799-1808.
12. Dickinson, E.; Murray, B. S.; Stainsby, G. Coalescence Stability of Emulsion-sized Droplets at Planar Oil-Water Interface and the Relationship to Protein Film Surface Rheology. *J. Chem. Soc. Faraday Trans.* **1998**, *84*, 871.
13. Mun, S.; McClements, J. Influence of Interfacial Characteristics on Ostwald Ripening in Hydrocarbon Oil-in-Water Emulsions. *Langmuir* **2006**, *22*, 1551.
14. Meinders, M. B. J.; Kloek, W.; van Vliet, T. Effect of Surface Elasticity on Ostwald Ripening in Emulsions. *Langmuir* **2001**, *17*, 3923.
15. Tcholakova, S.; Mitrinova, Z.; Golemanov, K.; Denkov, N. D.; Vethamuthu, M.; Ananthpadmanabhan, K. P. Control of bubble Ostwald ripening in foams by using surfactant mixtures. *Langmuir* **2011**, *27*, 14807-14819.
16. Langevin, D. Influence of interfacial rheology on foam and emulsion properties. *Adv. Colloid Interface Sci.* **2000**, *88*, 209-222.
17. Langevin, D. Aqueous foams: A field of investigation at the Frontier between chemistry and physics. *ChemPhysChem* **2008**, *9*, 510-522.

18. Marze, S.P.L., Saint-Jalmes, A., Langevin, D. Protein and surfactant foams: Linear rheology and dilatancy effect. *Colloids Surf. A* **2005**, *263*, 121-128.
19. Saint-Jalmes, A., Zhang, Y., Langevin, D. Quantitative description of foam drainage: Transitions with surface mobility. *European Phys. J. E* **2004**, *15*, 53-60.
20. Saint-Jalmes, A., Langevin, D. Time evolution of aqueous foams: Drainage and coarsening. *J. Physics Condensed Matter* **2002**, *14*, 9397-9412.
21. Zang, D.Y., Rio, E., Delon, G., Langevin, D., Wei, B., Binks, B.P. Influence of the contact angle of silica nanoparticles at the air-water interface on the mechanical properties of the layers composed of these particles. *Molecular Physics* **2011**, *109*, 1057-1066.
22. Alexandrov, N.A., Marinova, K.G., Gurkov, T.D., Danov, K.D., Kralchevsky, P.A., Stoyanov, S.D., Blijdenstein, T.B.J., Pelan, E., Lips, A. Interfacial layers from the protein HFBII hydrophobin: Dynamic surface tension, dilatational elasticity and relaxation times. *J. Colloid Interface Sci.*, **2013**, *376*, 296-306.
23. Knoche, S., Vella, D., Aumaitre, E., Degen, P., Rehage, H., Cicuta, P., Kierfeld, J. Elastometry of deflated capsules: Elastic moduli from shape and wrinkle analysis. *Langmuir* **2013**, *29*, 12463-12471.
24. Erni, P., Jerri, H.A., Wong, K., Parker, A. Interfacial viscoelasticity controls buckling, wrinkling and arrest in emulsion drops undergoing mass transfer. *Soft Matter* **2012**, *8*, 6958-6967.
25. Aumaitre, E., Knoche, S., Cicuta, P., Vella, D. Wrinkling in the deflation of elastic bubbles. *European Phys. J. E* **2013**, *36*, art. no. 22.
26. Subramaniam, A.B., Abkarian, M., Mahadevan, L., Stone, H.A. Colloid science: Non-spherical bubbles. *Nature* **2005**, *438*, 930.
27. Seta, L.; Baldino, N.; Gabriele, D.; Lupi, F.R.; de Cindio, B. The effect of surfactant type on the rheology of ovalbumin layers at the air/water and oil/water interfaces. *Food Hydrocolloids* **2012**, *29*, 247-257.
28. Garofalakis, G.; Murray, B.S. Surface pressure isotherms, dilatational rheology, and Brewster angle microscopy of insoluble monolayers of sugar monoesters. *Langmuir* **2002**, *18*, 4765-4774.
29. Camino, N.A.; Perez, O.E.; Sanchez C.C.; Patino, J.M.R.; Pilosof, A.M.R. Hydroxypropylmethylcellulose surface activity at equilibrium and adsorption dynamics at the air-water and oil-water interfaces. *Food Hydrocolloids* **2009**, *23*, 2359-2368.
30. Benjamins, J.; Lyklema, J.; Lucassen-Reynders, E.H. Compression/expansion rheology of oil/water interfaces with adsorbed proteins. Comparison with the air/water surface. *Langmuir* **2006**, *22*, 6181-6188.
31. Wustneck, R.; Moser, B.; Muschiolik, G. Interfacial dilatational behavior of adsorbed  $\beta$ -lactoglobulin layers at the different fluid interfaces. *Colloids Surf. B* **1999**, *15*, 263-273.
32. Koehler, S. A.; Hilgenfeldt, S; Stone, H. A. Liquid Flow through Aqueous Foams: The Node-Dominated Foam Drainage Equation. *Phys. Rev. Lett.* **1999**, *82*, 4232.


33. Golemanov, K.; Denkov, N.D.; Tcholakova, S.; Vethamuthu, M.; Lips, A. Surfactant mixtures for control of bubble surface mobility in foam studies. *Langmuir* **2008**, *24*, 9956.
34. Adami, N.; Dorbolo, S.; Caps, H. Single thermal plume in locally heated vertical soap films. *Phys. Rev. E* **2011**, *84*, 046316.
35. Biance, A.L.; Delbos, A.; Pitois, O. How topological rearrangements and liquid fraction control liquid foam stability. *Phys. Rev. Letter* **2011**, *106*, 068301.
36. Dollet, B. Local description of the two-dimensional flow of foam through a contraction. *J. Rheology* **2010**, *54*, 741.
37. Mitrinova, Z.; Tcholakova, S.; Golemanov, K.; Denkov, N.D.; Vethamuthu, M.; Ananthapadmanabhan, K.P. Surface and foam properties of SLES + CAPB + fatty acid mixtures: Effect of pH for C12-C16 acids. *Colloid Surf. A* **2013**, *438*, 186-198.
38. Cooper, E. F.; Astour, A. A-F. Densities and Kinematic Viscosities of some C<sub>6</sub>-C<sub>16</sub> n-Alkane Binary Liquid Systems at 293.15 K. *J. Chem. Eng. Data* **1991**, *36*, 285.
39. Vandebril S.; Franc, A.; Fuller, G. G.; Moldenaers, P.; Vermant, J. A double wall-ring geometry for interfacial shear rheometry. *Rheol. Acta.* **2010**, *49*, 131.
40. Edwards, D. A.; Brenner, H.; Wasan, D. T. *Interfacial Transport Processes and Rheology*, Butterworth-Heinemann, Boston, 1991.
41. Franck, A.; Vandebril, S.; Vermant, J.; Fuller, G. Double wall ring geometry to measure interfacial rheological properties. 5<sup>th</sup> International Symposium on Food Rheology and Structure. Zurich, Switzerland, 2008.
42. Mainardi, F.; *Fractional Calculus and Waves in Linear Viscoelasticity: An Introduction to Mathematical Models*, Imperial College Press: London, 2010.
43. Mezger, T. G.; *The Rheology Handbook*, 2<sup>nd</sup> ed, Vincentz Network, Hannover, 2006.
44. Hyun, K., Wilhelm, M., Klein, C.O., Cho, K.S., Nam, J.G., Ahn, K.H., Lee, S.J., Ewoldt, R.H.; McKinley, G.H. A review of nonlinear oscillatory shear tests: Analysis and application of large amplitude oscillatory shear (LAOS). *Progress in Polymer Sci.* 2011, **36**, 1697-1753.
45. Parthasarathy, M., Klingenberg, D.J. J. Large amplitude oscillatory shear of ER suspensions. *Non-Newtonian Fluid Mechanics* 1999, **81**, 83-104.



**Figure 1.** Schematic presentation of the two main mechanisms of reducing the density and the visco-elasticity of adsorption layers upon their contact with non-polar liquid (oily) phase. (A)→(B) The oil molecules penetrate between the hydrophobic parts of the adsorbed molecules. (C)→(D) Some fraction of the adsorbed molecules is extracted into the oily phase. In both cases the result is an increased area per molecule and decreased attraction (cohesion) between the molecules in the adsorption layer. Note that the two mechanisms are not alternative, because the extraction of lipophilic surfactants in (D) could be combined with intercalation of oil molecules, as shown in (B).




**Figure 2.** Creep and relaxation of different saponin adsorption layers: (A,B,C) Group EV of saponins with Elasto-Viscous properties of the adsorption layers; (C) Group V with measurable surface shear Viscosity (Sap); (D) Group LV with Very Low shear surface viscosity. The data for other saponins from this group are given in Supplementary information. The experimental conditions are:  $t_A = 30$  min;  $t_{CR} = 100$  s; torque  $M = 1$   $\mu$ N.m.




**Figure 3.** (A) Surface shear elasticities, (B) Surface shear viscosities, and (C) Relaxation times for Maxwell (index 0) and two Kelvin elements (indexes 1 and 2) of adsorption layers, formed from Quillaja solution on air-water (A-W), hexadecane-water (C16-W) and tricapyrylin-water (3C8-W) interfaces. These values are determined from the best fits to the experimental data with compound Voigt model. The data are averaged from at least four experiments, performed at least at two different stresses below the critical stress leading to layer fluidization.







**Figure 4.** (A) Elastic modulus and (B) Viscous modulus vs. the strain amplitude at constant frequency (1Hz) for saponin adsorption layers, formed on hexadecane-water interface. The strain amplitude is varied logarithmically from 0.01 to 20 %. Layer aging time after pre-shear  $t_A = 30$  min.




**Figure 5.** (A) Elastic modulus and (B) Viscous modulus vs. the strain amplitude at constant frequency (1Hz) for adsorption layers of QD on different interfaces (air-water, hexadecane-water, tricaprylin-water). The strain amplitude is varied logarithmically from 0.01 to 20 %.  $t_A = 30$  min.




**Figure 6.** (A) Strain amplitude at which  $G' = 0.95G''$  ( $\gamma \rightarrow 0$ ) denoted as  $\gamma_0$  (full symbols), and strain amplitude at which  $G' = G''$  denoted as  $\gamma_{CR}$  (empty points), for saponin adsorption layers formed on air-water (red circles); hexadecane-water (blue squares) and tricaprylin-water (green triangles) interfaces and the respective stresses (B).




**Figure 7.** (A) Elastic modulus upon shear deformation and (B) Viscous modulus upon shear deformation of various saponins at various interfaces. Values taken for 0.1 % shear deformation (in the linear regime) and 1 s period of oscillations.



**Figure 8.** Micrographs of sunflower oil-in-water emulsion droplets, stabilized by (A) BSC and (B) QD saponin. The droplets have wrinkled surfaces and many are with non-spherical, elongated shape that does not relax for many days, which is indicative for the formation of peculiar adsorption layer with unusual rheological properties at the oil-water interface. The scale bar in the image is 20  $\mu\text{m}$ .



**Figure 9.** Schematic presentation of the structure of the saponin adsorption layers for (A-C) monodesmosidic saponins Escin and TS, and (D) bidesmosidic saponin QD at various interfaces.



**Figure 10.** Creep and relaxation curves for adsorption layers of tea saponin (TS) on air-water interface, with 4 M urea and without urea in the aqueous phase. The chaotropic agent urea breaks the hydrogen bonds and the layer is fluidized, as evidenced by the large creep in presence of urea (red curve). The conditions of the experiment are  $t_A = 30$  min;  $t_{CR} = 100$  s; torque  $M = 1 \mu\text{N.m}$ .


TOC

**Non-spherical emulsion droplets (centre) may appear at high interfacial elasticity which, however, depends on the type of oil used**



## Role of the hydrophobic phase for the unique rheological properties of saponin adsorption layers

Konstantin Golemanov, Slavka Tcholakova, Nikolai Denkov, Eddie Pelan, Simeon D. Stoyanov



We compared surface rheological properties various type of Saponins, at air/water, hexadecane/water and Tricaprylin/water interface and demonstrated that hydrophobic phase has very strong effect on the interfacial rheological properties of the same saponins.