



Cite this: *Green Chem.*, 2025, **27**, 12107

Received 27th September 2024,
Accepted 29th August 2025

DOI: 10.1039/d4gc04844j

rsc.li/greenchem

A proposal of twelve principles for LCA of chemicals

Daniele Cespi  *^{a,b}

Green chemistry gained prominence after the publication of its 12 fundamental principles. Life Cycle Assessment (LCA) complements green chemistry by evaluating environmental impacts during the entire life cycle of products or part of it (cradle to gate). This perspective proposes 12 principles for the LCA of chemicals, a list of issues that should be addressed by LCA practitioners, in a procedural way, in order to apply correctly the life cycle perspective within the green chemistry discipline.

Green foundation

1. The development of twelve fundamental principles of Life Cycle Assessment (LCA) applied to chemicals can support practitioners in the field of green chemistry in adopting the LCA methodology to guide and enhance their research.
2. LCA is a versatile tool; therefore, all branches of chemistry and chemical engineering may benefit from understanding the procedural approach needed to correctly apply the life cycle perspective within the discipline of green chemistry.
3. Innovation from a life cycle perspective is aimed at embracing all dimensions of sustainability—environmental, social, and economic. I hope that proposing 12 fundamental principles of LCA applied to chemicals may help in assessing the potential of new reactions from the outset, in line with one of the core pillars of green chemistry: benign by design.

Green chemistry is right now a well-established concept, spread around the World and consolidated among a variety of chemical disciplines. The term was first coined by Paul T. Anastas in 1991. However, it gains more relevance after the publication of the 12 fundamental principles in 1998.¹

These principles represent a recommendation for synthetic and industrial chemists, guiding them in performing more sustainable research activities in the field of chemistry.

Similarly, the life cycle thinking approach is gaining increasing attention within the chemical community due to its ability to be applied to syntheses, processes, and their components in order to identify inefficiencies and explore alternative solutions. The life cycle perspective represents a complex set of different tools which can be used individually or in combination (in a life cycle sustainability perspective). Among these, Life Cycle Assessment (LCA) represents a more consolidated tool, being the oldest and thanks to its standardization.^{2,3} It addresses the potential environmental impacts of products and systems in a cradle-to-grave approach, from raw material extraction up to the end-of-life (EoL) stage, by considering several impact categories oriented towards environmental problems (e.g., climate change potential, acidification potential, etc) or the damage to the final

receptors (*i.e.*, human health, ecosystem quality and resource consumption).

As highlighted by Gilbertson *et al.*,⁴ “green chemistry looks at the entire life cycle through the application of a set of principles to optimize the design”. Therefore, a strong connection between green chemistry and LCA exists.

However, while green chemistry promotes the adoption of key principles to guide research towards more sustainable practices, it does not provide a standardized framework for classifying chemicals based on their environmental impact.

Although Kreuder *et al.*⁵ have proposed an approach for assessing chemicals and chemical processes in alignment with the 12 principles of green chemistry, they utilized information compiled for compliance with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS). The green chemistry metrics (GCM) proposed by the authors enable the ranking of chemicals or processes using a hierarchical system: (1) scores corresponding to each of the 12 principles, (2) rankings across three categories for new and improved chemicals/processes (enhanced resource efficiency, improved energy efficiency, and reduced human and environmental hazards), and (3) an overall summary ranking for comparison.

Conversely, LCA is a versatile and powerful tool able to provide a standardized framework to assess the environmental sustainability of green chemistry choices (e.g., less hazardous or material intensive reagents, reduction in steps, waste prevention, etc), even though it relies on specific case studies for its application.

^aDepartment of Industrial Chemistry “Toso Montanari”, University of Bologna, Via Piero Gobetti 85, 40136 Bologna (BO), Italy. E-mail: daniele.cespi2@unibo.it

^bCenter for Chemical Catalysis - C3, University of Bologna, Via Piero Gobetti 85, 40136 Bologna (BO), Italy



Thus, green chemistry offers a set of guiding principles for designing safer and more sustainable chemical processes, whereas LCA provides quantitative and standardized metrics to evaluate their environmental impacts. Despite these differences, there are points of intersection between them. In fact, several approaches were already proposed (i) to support the application of LCA to the chemical sector, in order to structure a procedure to fill data gaps in the inventory,^{6–9} (ii) to assist researchers in the field of green chemistry to become familiar with the methodology,¹⁰ by highlighting the benefits ascribable to the usage of LCA within green chemistry,¹¹ and (iii) to highlight the numerous methodological challenges in LCA studies of the chemical sector.¹²

However, to the best of my knowledge, no one has proposed a list of issues that should be addressed by an LCA practitioner, in a procedural way, in order to apply correctly the life cycle perspective within the green chemistry discipline. Therefore, similar to green chemistry, in the following communication, the 12 fundamental principles for LCA of chemicals are proposed as follows:

- 1 Cradle to gate
- 2 Consequential if under control
- 3 Avoid to neglect
- 4 Data collection from the beginning
- 5 Different scales
- 6 Data quality analysis
- 7 Multi-impact
- 8 Hotspot

9 Sensitivity

10 Results transparency, reproducibility and benchmarking

11 Combination with other tools

12 Beyond environment

The principles are ordered based on the logical sequence a practitioner should follow. Principles 1 and 2 pertain to system boundary definition (within the Goal and Scope definition, the first stage). Principles 3–6 address the life cycle inventory (the second and most time-consuming phase of the LCA). Principles 7–8 relate to the life cycle impact assessment (the third stage). Principles 9 and 10 are categorized as miscellaneous, as they include aspects of LCI, LCIA, and interpretation. Finally, Principles 11 and 12 focus on integrating the LCA with other tools and methodologies.

(1) *Cradle to gate*: the system boundaries of a study may vary, but at a minimum the cradle-to-gate boundary should always be ensured. The cradle-to-grave approach is a more established approach and consistently enables the comparison of two or more alternatives based on their function. However, very often chemicals represent intermediate products with several applications in downstream and, thus, different EoL also depending on the market. Therefore, other perspectives may be acceptable, depending on the study's goal and scope. One such approach is the cradle-to-gate approach, which enables analysis from the "roots" (raw material extraction) up to the production of the chemical in its finished form. In the case of some types of chemicals, like pharmaceuticals, the cradle-to-synthesis¹³ approach is sometimes used including all steps up to the point where the purified active pharmaceutical ingredient (API) is obtained, while excluding tableting and packaging. This approach is particularly common in supporting R&D activities focused on optimizing API synthesis. The cradle-to-gate approach allows for a comprehensive analysis of alternatives, particularly when the main chemical or technical differences lie in the upstream and/or core stages. This could be the case of alternative pathways for producing the same molecule with equal usage and EoL. An example is represented by the comparison between the bottle-grade polyethylene terephthalate (PET) derived from fossil and its bio-based counterpart. The molecule obtained is the same, as well as all the downstream stages (*i.e.*, distribution, usage and EoL)†. Therefore, downstream stages can be excluded from the analysis if they are not relevant to the intended audience. However, if the comparison extends to a different class of polymers, such as polylactic acid (PLA), which varies in reference service life and disposal method (*e.g.*, PLA is compostable, while PET is not), the study must encompass all stages up to the grave. For chemical products, gate-to-gate boundaries (which generally focus only on Scope 1 flows) should be discouraged. In fact, to promote a 'benign by design' society, the harmful effects associated with material and energy extraction, purification, and the final fate of molecules and materials should always be taken into account—as also suggested by the principles of green chemistry—moving beyond what happens solely in the



Daniele Cespi

Daniele Cespi is an Associate Professor at the University of Bologna (Department of Industrial Chemistry "Toso Montanari") and works in the field of green chemistry, environmental chemistry and life cycle thinking, adopting Life Cycle Assessment (LCA), Social-LCA and Safe and Sustainable by Design framework (SSbD) to chemical processes and reactions. In 2014, he was a Visiting Assistant in Research at Yale University under the supervision of Prof. Paul

Anastas. In 2015, he completed his PhD in Chemistry at the University of Bologna and received the Empowering Research Award from Philip Morris International. In 2022 he received the "Mario Molina" Medal from the Italian Chemical Society for his innovative contribution to the evaluation of the environmental impacts of the industrial processes. He serves as a reviewer for the Italian Ministry, UN Environment, and for many international peer-reviewed journals. Since 2025, he has been an Advisory Board Member of the journal Green Chemistry – RSC Publishing – and an invited member of the Royal Society of Chemistry. Since 2025 he is Board Member of the Environmental and Cultural Heritage Division, Italian Chemical Society

† If the same market scenario is assumed: the same distribution, the same usage and equal EoL.




beaker.¹⁴ For example, different catalyst substrates should be selected not only based on their efficiency within the reaction, but also by considering their criticality,¹⁵ the resource intensity of their extraction,¹⁶ and their recyclability potential.¹⁷

(2) *Consequential if under control*: according to the literature,¹⁸ an attributional LCA focuses on describing the environmental characteristics of a life cycle and its subsystems. In contrast, a consequential LCA aims to capture the effects of changes within the life cycle. In other words, an attributional LCI modelling framework inventories the input and output flows of all processes within a system as they naturally occur. Conversely, consequential LCI modelling identifies and evaluates all processes in the background system that arise as a result of decisions made in the foreground system.¹⁹ The primary LCI methodological approaches associated with these frameworks are allocation for attributional modelling and system expansion or substitution for consequential modelling.¹⁹ In simple terms, a consequential approach is more action-oriented than an attributional one, although capturing changes in physical, technical, and socio-economic variables. Thus, while the attributional approach quantifies the potential environmental impacts of the system as it is, the consequential approach aims to assess the potential environmental impacts resulting from changes within the system under study. Therefore, a consequential approach is more complex, as it extends the analysis beyond the plant facility to include a broader portion of the industrial ecosystem. Considering multiple variables can affect the final results and provide the user with a more powerful tool to support decision-making by incorporating various scenarios. However, this approach in the chemical sector is far from easy. A typical example of a consequential approach is when LCA boundaries are expanded to account for credits from material extraction or energy production, such as using bio-based waste to generate energy in a cogeneration plant as a substitute for fossil fuels. For greater consistency, the application of a consequential model to part of the life cycle should ideally extend to the entire system boundaries. In cases of avoided impacts from material or energy recovery, this approach should ideally encompass the whole supply chain, where appropriate (*i.e.*, when co-products

generated by process units within the supply chain could potentially be used as substitutes for virgin materials). However, while this approach might offer consistency, it can also lead to an underestimation or overestimation of the overall environmental impacts. This is because the consequential model may not be consistently applied across all upstream and downstream processes, over which the LCA practitioner typically has no direct control. When direct control is not guaranteed, the data used to build the models are classified as background data. These data generally fall under the category of secondary data, although primary data may also be provided by suppliers in the form of self-declared information or, preferably, certified or verified by a third party. Databases are examples of tools that help fill data gaps. On the other hand, foreground data should represent all core activities under the control of the practitioner, where primary information (both qualitative and quantitative) should ideally always be collected (Fig. 1).

As a general rule, consequential approaches—such as accounting for avoided products—should be limited to parts of the life cycle where direct control over substitution is ensured. Otherwise, they should be used only for sensitivity analysis (see Principle 9).

(3) *Avoid to neglect*: when evaluating a reaction, there may be instances where certain data are unavailable to the LCA practitioner. This often occurs when the reaction is outside direct or indirect control,⁹ leading to gaps in data availability. One of the most common examples is the energy consumption of a reaction at the laboratory or pilot scale. Another case is the inclusion of the full mass balance in the LCA model. Since the life cycle results reflect the amount and quality of data used in the inventory (Life Cycle Inventory, LCI), the greater the percentage of omitted information, the lower the reliability of the study. Therefore, as a general rule of thumb, all the input and output flows within the system boundaries should be incorporated into the model. A complete mass balance must always be achieved, accounting for all input and output flows within the system under study, including reagents and auxiliaries (*e.g.*, solvents), products and co-products, as well as waste and emission flows. Cut-off criteria may be applied to



A, B and C represent three alternative scenarios for co-product management

Fig. 1 Simplified system boundaries.



flows contributing $\leq 1\%$ of the overall mass (or volume) only if the material does not have a significant environmental footprint (*e.g.*, substances of very high concern or noble metals). Catalysts may sometimes be excluded from the mass balance if they are recovered and reused in subsequent cycles (*e.g.*, heterogeneous catalysts).⁹

Energy consumption is also critically important, as it often represents a major contributor to the overall environmental impact of a reaction. However, its estimation can be challenging. In such cases, an enthalpy balance is recommended to ensure that the model accounts for the minimum energy required by the process. A recent publication⁹ presents a step-by-step procedure for completing the LCI of chemicals, discussing both limitations and advantages, and providing guidance and strategies to address data gaps.

(4) *Data collection from the beginning*: LCA studies are often conducted after the experimental phase is completed, a practice commonly referred to in the literature as *ex-post* or *retrospective* LCA.²⁰ However, when life cycle thinking is integrated during the research process to support innovation, it is more valuable and appreciated. During lab-scale activities, scientists typically focus on optimizing system efficiency (*e.g.*, product yield) or improving characterization (*e.g.*, active surface area on catalysts), often overlooking variables that can significantly impact the final environmental footprint of the chemical process. These overlooked factors may include energy consumption, time requirements per stage, and the exact volumes of solvent used for sample storage. Unfortunately, recovering such information after the experiment is challenging, requiring multiple assumptions to fill in the gaps. To avoid this, data collection should begin from the outset, using dedicated checklists to gather both quantitative and qualitative data for each stage of the process. An exhaustive example of a checklist was recently published in the literature.²¹ The spreadsheet file reported in the SI can be used by practitioners as a starting point to build their own checklist.

(5) *Different scales*: a life cycle approach can be valuable in supporting the scaling up of reactions by conducting an initial LCA at an early design phase, when the technology is at a low readiness level (TRL). This helps to identify potential challenges or advantages, particularly important for lab-scale reactions where the degree of freedom is significantly higher. However, to fully grasp the potential of the innovation being studied, the analysis should also be extended to higher TRL levels, by setting the basis for a future-oriented LCA and investigating the environmental impacts of currently immature pathways. Recently, Arvidsson *et al.* suggested using the term *prospective* LCA to refer to studies with a future temporal positionality.²² In the case of chemical reactions, the assessment should also investigate the effects of changes in background systems, *e.g.*, new materials for vessels and reactors to reduce heat dissipation, alternative energetic mixes to meet future climate targets, innovative catalytic systems to mitigate metal criticalities, *etc.*

The most challenging activity is LCI upscaling. The first and more consolidated option is using software engineering

simulation, considered, so far, the top level when primary data are not available.²³ Various commercial and open-source software programs are available (*e.g.*, Aspen Plus®,²⁴ CHEMCAD™,²⁵ DWSIM,²⁶ Aspen HYSYS®,²⁷ ProSim,²⁸ *etc.*) for estimating heat duty in reactions and unit operations, as well as electricity consumption for pumps, compressors, and other electric drives. However, these tools require a minimum set of input data—such as reactor type, kinetic equations, and reaction conditions—to function effectively. Without access to this information, conducting simulations becomes virtually impossible. Moreover, the process demands specialized expertise and a dedicated budget, which are not always readily available.⁹ Therefore, if not feasible, a simplified approach can be implemented by practitioners based on constitutive equations for individual equipment units. Piccinno *et al.*²⁹ developed a framework to support the scale-up of chemical production processes for LCA studies when only laboratory-scale data are available. It is intended for LCA practitioners with limited expertise in chemical engineering and provides a logical, systematic approach to guide the scale-up process.

(6) *Data quality analysis*: due to the varying availability of necessary information for compiling the synthesis inventory (*e.g.*, thermodynamic values for energy balance, reaction stoichiometry to identify by-products, *etc.*), a data quality analysis should be incorporated into the study.

This analysis should begin during data acquisition to prevent the loss of information—an issue that often arises when a chemical process involves multiple unit operations carried out by different research groups. To streamline the procedure, the checklist file (SI) can include an additional column to classify data based on their source and to rank them as primary or secondary. Qualitative information (*e.g.*, direct measurements) can also be collected, and a scoring system (*e.g.*, from 1 to 5) may be applied.

A valuable method to estimate data uncertainties and screen the entire dataset is the quality pedigree matrix.³⁰ This approach often needs to be adjusted to better align with the specific case study. Once the analysis is complete, the scores are used to assign standard deviation values to each input/output flow, which are then applied in an uncertainty analysis using Monte Carlo simulation. The formula for standard deviation calculation is commonly reported in the literature.³¹ There is no fixed number of iterations recommended to accurately capture data variability in the final results; software can perform the analysis with a very high number of iterations (*e.g.*, over 10 000).

(7) *Multi-impact*: ISO 14 044 clearly defines the need for a multi-impact approach in life cycle assessment studies. However, LCA models in green chemistry innovation studies often focus on a single indicator at a time (*e.g.*, carbon footprint),³² rather than considering multiple impacts simultaneously. Although a single-indicator approach may be easier and more cost-effective, a comprehensive and holistic assessment can be achieved using methods that encompass a wider range of impact categories.^{33,34} Among the more consolidated examples, several methods exist: ReCiPe 2016 (18 midpoint cat-



egories and 3 endpoint receptors),³⁵ IMPACT World+ (18 midpoint categories and 3 endpoint receptors)³⁶ and EF 3.0 (28 midpoint categories and no endpoint)³⁷ are some of them. Except for the Environmental Footprint methodology,³⁸ there is no fixed rule for the inclusion or exclusion of specific impact categories in traditional LCA. As a general rule of thumb, when a method is selected, the full set of impact categories should be included in the evaluation. For example, when using ReCiPe 2016,³⁵ all 18 midpoint categories should be considered at the characterization level and reported in the manuscript or in the electronic supporting information. The discussion, however, can focus on a subset of these categories by highlighting those that are most relevant.

This selection should follow a rational approach: depending on the type of process or material being assessed, certain categories cannot be omitted. For instance, in the case of bio-based products, the use of dedicated biomass necessitates the inclusion of impact categories such as land use, eutrophication, and ecotoxicity. Similarly, for battery production, the consideration of mineral resource consumption is essential.

Another option—often used in combination with the above—is to identify the impact categories that contribute most to the cumulative single score after applying a weighting step. However, weighting is not mandatory in all multi-impact assessment methods. It is considered an optional element, as it introduces a degree of subjectivity that can influence the final results, even though most methods include predefined weighting schemes.

(8) *Hotspot*: green chemistry innovation should prioritize reagents, solvents, auxiliaries, or process steps that have the greatest impact across the entire life cycle. To effectively target efforts—often constrained by limited budgets—a hotspot analysis³⁹ should always be conducted to identify where improvements are most needed. Results of this evaluation, also called contribution analysis, allow the identification of dominant hotspots. In this context, a preliminary LCA can be valuable in pinpointing inefficiencies and assessing how alternative approaches might reduce the overall environmental footprint. When a database is presented in the form of unit processes (a list of elementary flows entering and leaving each unit), hotspot analysis reveals the step(s) with the greatest contribution. A further network analysis can then be conducted to identify the flow(s) with the highest contribution, which can serve as a basis for exploring potential alternatives. Replacement is sometimes challenging, as the availability of practical chemical alternatives on the market is limited. However, this limitation drives continuous innovation and improvement in the development of greener and more sustainable solutions.

(9) *Sensitivity*: the traditional LCA approach typically represents a stable scenario with fixed geographical, technical, and temporal boundaries, producing a snapshot of the system under study during the impact assessment stage. However, how do changes in variables affect the results? To assess the robustness of the LCA model, sensitivity analysis is highly recommended, especially in the chemical sector. Factors such as

process efficiencies (yield, conversion, and selectivity), chemical and physical conditions, catalyst quantities, raw material sources, energy mixes, transportation, and other variables can be adjusted to reflect a wider range of scenarios. Often, sensitivity analysis by evaluating the variations of parameters is impractical and not feasible due to the high number of variables. Therefore, the practitioner can limit the sensitivity analysis to only dominant hotspots and substances. The simplest example is represented by the energy vector(s) used to run the reaction. The practitioner can evaluate how the results are affected by switching from a traditional energy carrier (*e.g.*, natural gas)⁴⁰ to electricity,⁴¹ and then perform a further sensitivity analysis to identify the optimum carrier under different energy mix scenarios.

(10) *Results transparency, reproducibility and benchmarking*: the chemical sector is characterized by highly specialized corporate knowledge, making it difficult to fully reconstruct systems. Key information such as energy consumption, catalyst quantities, and regeneration flow requirements is often confidential.

Confidentiality is also a common characteristic of commercial databases (*e.g.*, ecoinvent).⁴² However, two essential pillars of the life cycle thinking approach are transparency and the reproducibility of data and outcomes. In line with the European Open Science policy,⁴³ researchers and practitioners in the field of LCA should provide at least the system boundary flowsheet (Principle 1), the complete LCI with assumptions and exclusions (in line with Principle 3), and the characterization factors used during impact assessment (Principle 7). This information constitutes the minimum knowledge required for reproducibility, even though data sharing is also desirable (as encouraged by the Environmental Footprint methodology).³⁷ In this sense, sharing data in the form of elementary flows without further details about the unit processes involved may help protect confidential information. While this approach may have some benefits, it reduces the amount of information that can be extracted from the results to support eco-design.⁴⁴ Furthermore, an independent third-party critical review of the study should be ensured when the results are intended for external communication, particularly at the company level.

In fact, the results of an LCA study are intended for both internal and external stakeholders, depending on the target audience. In the latter case, the study has to undergo a critical third-party review, as required by the reference standards. In accordance with the ISO 14044, the critical review process is necessary to decrease the likelihood of misunderstanding, by ensuring that:

- the methods used are consistent with the ISO standard;
- the methods used are scientifically and technically valid;
- the data used are appropriate and reasonable, in relation to the goal of the study;
- the interpretation reflects the limitations;
- the study report is transparent.

As reported above, the principles of green chemistry and LCA are considered key approaches for supporting innovation.



LCA is comparative in nature, and its results should be interpreted by comparing them with one or more benchmarks. Many standards^{45–47} support claims by evaluating a product's performance relative to an average product (with the same function) available on the market. Another common approach is to compare a greener chemical or pathway with a traditional one (e.g., patented route vs. commercial route;¹³ fossil vs. bio-based⁴⁸). However, benchmarking can be challenging during the early design stage of a new chemical, especially when no comparable products are yet available on the market. In such cases, applying a streamlined LCA^{49,50} from the outset can support decision-making throughout the optimization process. In these cases, the benchmark is the chemical product/process synthesized or developed in the stage prior to optimization.

(11) *Combination with other tools*: the structure and nature of LCA allow for seamless integration with other approaches, enhancing insights into reactions and effectively supporting R&D efforts. Combining LCA with green metrics is recommended, since they can act as complementary sets of indicators.⁵¹ Chemists often use tools like the E-factor,^{52,53} atom economy,⁵⁴ or process mass intensity (PMI)⁵⁵ to evaluate their syntheses at the laboratory scale. While these tools are simple to apply and can help identify key performance indicators for tracking over time and during scale-up, combining them with LCA ensures a more comprehensive assessment by quantifying potential environmental impacts from significant waste generation (high E-factor) and/or excessive resource consumption (high PMI). A recent quantitative study by Lucas *et al.*⁵¹ found weak correlations between mass- and energy-based metrics and life cycle impacts across environmental and human protection categories (*i.e.*, climate change, pollution, toxicity, and resource depletion). Their findings suggest that metrics like PMI and E-factor alone are not reliable indicators of the overall environmental impact of chemical production processes. From a practical standpoint, researchers may adopt standardized process metrics (e.g., PMI, E-factor, and energy intensity) in combination with LCA-based indicators. As a general rule of thumb, the combination of multiple indicators into a single score (*i.e.*, green metrics + LCA indicators) should generally be discouraged. However, if it is applied, it should always be accompanied by an analysis of each investigated impact factor separately.

Another recommended approach for chemical reactions is risk assessment (RA). While LCA typically offers an overview of potential environmental impacts from actual releases, RA provides valuable insights into the potential risks faced by workers handling hazardous substances during synthesis, as well as the possible environmental and human health risks during the molecule's use and end-of-life stages. The combined use of both approaches was first proposed in the late 1990s,⁵⁶ and has since been reiterated by several researchers as a key strategy to support green chemistry innovation and policy development.^{57–59}

In general, RA can support LCI by predicting the likelihood of exposure to specific substances during handling or reaction

steps (e.g., emissions). This is achieved by identifying or assuming potential exposure routes (inhalation, dermal, and ingestion), assessing release potential (e.g., volatility, dustiness, fugacity, temperature, and pressure), and considering the risk management measures in place. This integration helps practitioners achieve more reliable results regarding toxicological impacts.

Recently Cefic (The European Chemical Industry Council) and JRC (Joint Research Center) have worked on the standardization of an innovative assessment scheme, the so-called Safe and Sustainable by Design chemicals and materials (SSbD).^{60,61} SSbD integrates safety considerations, environmental sustainability, and social and economic sustainability (the latter two are discussed later in Principle 12) into the design of new chemicals and materials by incorporating safety analysis (including intrinsic risk and risk during production, usage, and EoL stages) before the environmental and socio-economic dimensions.

(12) *Beyond environment*: to fully advance the development of green chemistry, the life cycle approach should extend beyond environmental sustainability. Ideally, the economic and social dimensions of sustainability should also be considered in evaluations where feasible. Life Cycle Costing (LCC)⁶² and Social-LCA (S-LCA)⁶³ are the primary globally recognized methods for assessing these potential impacts. Among them, only S-LCA is currently progressing toward standardization. The European ORIENTING (Operational Life Cycle Sustainability Assessment Methodology Supporting Decisions Towards a Circular Economy)⁶⁴ project has developed a unified approach for Life Cycle Sustainability Assessment (LCSA), a comprehensive methodology that integrates the results of LCA, LCC, and S-LCA into a single score.

In summary, twelve fundamental principles of LCA applied to chemicals are suggested here. These principles serve as general guidelines to support a more standardized and consolidated use of LCA within the field of green chemistry. While most principles should always be adhered to, any deviations should be clearly justified. Some aspects, such as integrating other methodologies like LCC and S-LCA or applying more complex frameworks (e.g., LCSA and SSbD), may be more challenging to implement. Although expanding the assessment beyond environmental factors requires specialized expertise, the scientific community strongly encourages the use of additional methodologies or comprehensive approaches to do that.

These principles are not intended to be definitive; rather, the author's aim is to share them with the LCA practitioner community working in the field of green chemistry, inviting interested parties to engage in a discussion regarding their potential expansion and/or refinement.

Conflicts of interest

There are no conflicts to declare.



Data availability

No primary research results, software or code have been included, and no new data were generated or analysed as part of this review.

Supplementary information is available. Example checklist for completing the Life Cycle Inventory (LCI) stage. See DOI: <https://doi.org/10.1039/d4gc04844j>.

References

- P. T. Anastas and J. C. Warner, *Green Chemistry: Theory and Practice*, Oxford University Press, Oxford, 1998.
- International Organization for Standardization (ISO), 14040:2006, Environmental Management—Life Cycle Assessment—Principles and Framework, 2006, ISO, Geneva, Switzerland.
- International Organization for Standardization (ISO), 14044:2006, Environmental Management—Life Cycle Assessment—Requirements and Guidelines, 2006, ISO, Geneva, Switzerland.
- L. M. Gilbertson, J. B. Zimmerman, D. L. Plata, J. E. Hutchison and P. T. Anastas, *Chem. Soc. Rev.*, 2015, **44**, 5758–5777.
- A. DeVierno Kreuder, T. House-Knight, J. Whitford, E. Ponnusamy, P. Miller, N. Jesse, R. Rodenborn, S. Sayag, M. Gebel, I. Aped, I. Sharfstein, E. Manaster, I. Ergaz, A. Harris and L. Nelowet Grice, *ACS Sustainable Chem. Eng.*, 2017, **5**, 2927–2935.
- C. Jiménez-González, S. Kim and M. R. Overcash, *Int. J. Life Cycle Assess.*, 2000, **5**, 153–159.
- S. Kim and M. Overcash, *J. Chem. Technol. Biotechnol.*, 2003, **78**, 995–1005.
- R. Hirschier, S. Hellweg, C. Capello and A. Primas, *Int. J. Life Cycle Assess.*, 2005, **10**, 59–67.
- D. Cespi, *Green Chem.*, 2024, **26**, 9554–9568.
- D. Kralisch, D. Ott and D. Gericke, *Green Chem.*, 2015, **17**, 123–145.
- R. L. Lankey and P. T. Anastas, *Ind. Eng. Chem. Res.*, 2002, **41**, 4498–4502.
- L. M. Tufvesson, P. Tufvesson, J. Woodley and P. Börjesson, *Int. J. Life Cycle Assess.*, 2013, **18**, 431–444.
- D. Cespi, E. S. Beach, T. E. Swarr, F. Passarini, I. Vassura, P. J. Dunn and P. T. Anastas, *Green Chem.*, 2015, **17**, 3390–3400.
- D. Cespi, I. Esposito, R. Cucciniello and P. T. Anastas, *Curr. Res. Green Sustainable Chem.*, 2020, **3**, 100028.
- European Commission, *Study on the EU's list of Critical Raw Materials – Final Report*, 2020.
- P. Nuss and M. J. Eckelman, *PLoS One*, 2014, **9**, e101298.
- B. K. Reck and T. E. Graedel, *Science*, 2012, **337**, 690–695.
- T. Ekvall, *J. Cleaner Prod.*, 2002, **10**, 403–406.
- European Commission - Joint Research Centre - Institute for Environment and Sustainability: International Reference Life Cycle Data System (ILCD) Handbook - General guide for Life Cycle Assessment - Detailed guidance. First edition March 2010. EUR 24708 EN. Luxembourg. Publications Office of the European Union; 2010.
- B. A. Sandén and M. Karlström, *J. Cleaner Prod.*, 2007, **15**, 1469–1481.
- European Commission, Joint Research Centre V. Santucci U. Eynard A. Arrigoni E. Weidner and F. Mathieux, *LCA Checklist: a tool to improve the communication of the environmental sustainability of the Clean Hydrogen Joint Undertaking projects*, Publications Office of the European Union, Luxembourg, 2024, vol. 1, JRC136429, <https://data.europa.eu/doi/10.2760/529754>.
- R. Arvidsson, M. Svanström, B. A. Sandén, N. Thonemann, B. Steubing and S. Cucurachi, *Int. J. Life Cycle Assess.*, 2023, **29**, 607–613.
- A. G. Parvatker and M. J. Eckelman, *ACS Sustainable Chem. Eng.*, 2019, **7**, 350–367.
- Aspen Technology, *Aspen Plus®*. Available online: <https://www.aspentech.com/en/products/engineering/aspentech-plus> (accessed on 04 September 2025).
- Chemstations, *CHEMCAD™*. Available online: <https://chemstations.com/chemcad> (accessed on 04 September 2025).
- DWSIM. Available online: <https://dwsim.org/> (accessed on 04 September 2025).
- Aspen Technology, *Aspen HYSYS®*. Available online: <https://www.aspentech.com/en/products/engineering/aspentech-hysys> (accessed on 04 September 2025).
- Fives ProSim. Available online: <https://www.prosim.net/en/> (accessed on 04 September 2025).
- F. Piccinno, R. Hirschier, S. Seeger and C. Som, *J. Cleaner Prod.*, 2016, **135**, 1085–1097.
- B. P. Weidema and M. Wesnaes, *J. Cleaner Prod.*, 1996, **4**, 167–174.
- M. Goedkoop, A. De Schryver and M. Oele, *Introduction to LCA with SimaPro 7*, PRé Consultants, 2006.
- International Organization for Standardization (ISO), 14067:2018, Greenhousegases—Carbon footprint of products—Requirements and guidelines for quantification, 2018, ISO, Geneva, Switzerland.
- Ó. Ögmundarson, M. J. Herrgård, J. Förster, M. Z. Hauschild and P. Fantke, *Nat. Sustain.*, 2020, **3**, 167–174.
- D. Cespi, *Sustainable Chem.*, 2023, **4**, 184–196.
- M. A. J. Huijbregts, Z. J. N. Steinmann, P. M. F. Elshout, G. Stam, F. Verones, M. D. M. Vieira, A. Hollander, M. Zijp and R. van Zelm, *ReCiPe 2016 – A harmonized life cycle impact assessment method at midpoint and endpoint level*, National Institute for Public Health and the Environment (RIVM), Netherlands, 2017.
- C. Bulle, M. Margni, L. Patouillard, A. M. Boulay, G. Bourgault, V. De Bruille, V. Cao, M. Hauschild, A. Henderson, S. Humbert, S. Kashef-Haghighi, A. Kounina, A. Laurent, A. Levasseur, G. Liard, R. K. Rosenbaum, P.-O. Roy, S. Shaked, P. Fantke and O. Jolliet, *Int. J. Life Cycle Assess.*, 2019, **24**, 1653–1674.
- European Platform on Life Cycle Assessment. Available online: <https://eplca.jrc.ec.europa.eu/LCDN/developerEF.xhtml> (accessed on 04 September 2025).



- 38 European Commission, Commission Recommendation (EU) 2021/2279 of 15 December 2021 on the Use of the Environmental Footprint Methods to Measure and Communicate the Life Cycle Environmental Performance of Products and Organisations. Available online: https://environment.ec.europa.eu/system/files/2021-12/Commission%20Recommendation%20on%20the%20use%20of%20the%20Environmental%20Footprint%20methods_0.pdf (accessed on 04 September 2025).
- 39 P. G. Jessop and A. R. MacDonald, *Green Chem.*, 2023, **25**, 9457–9463.
- 40 Eurostat, *Final energy consumption in industry - detailed statistics*. Available at: https://ec.europa.eu/eurostat/statistics-explained/index.php?title=Final_energy_consumption_in_industry_-_detailed_statistics#Chemical_and_petrochemical_industry (accessed on 04 September 2025).
- 41 Bogaerts, *Nat. Chem. Eng.*, 2025, **2**, 336–340.
- 42 Ecoinvent Centre (formerly Swiss Centre for Life Cycle Inventories), Ecoinvent v.3.10 Database, 2025.
- 43 European Commission, Open Science. Available online: https://research-and-innovation.ec.europa.eu/strategy/strategy-2020-2024/our-digital-future/open-science_en (accessed on 04 September 2025).
- 44 International Organization for Standardization (ISO), ISO 14006:2020 Environmental management systems—Guidelines for incorporating ecodesign, 2020, ISO, Geneva, Switzerland.
- 45 Made Green in Italy. Available at: <https://www.mase.gov.it/portale/lo-schema-nazionale-made-green-in-italy-> (accessed on 04 September 2025).
- 46 Carbon Footprint Italy. Available at: <https://www.carbon-footprintitaly.it/en/il-programma> (accessed on 04 September 2025).
- 47 The Carbon Trust label. Available at: <https://www.carbon-trust.com/en-eu/what-we-do/carbon-footprint-labelling> (accessed on 04 September 2025).
- 48 D. Cespi, F. Passarini, G. Mastragostino, I. Vassura, S. Larocca, A. Iaconi, A. Chierigato, J.-L. Dubois and F. Cavani, *Green Chem.*, 2015, **17**, 343–355.
- 49 J. A. Todd and M. A. Curran, Streamlined life cycle assessment: a final report from the SETAC-north America streamlined LCA workgroup, in *1999 Society of Environmental Toxicology and Chemistry, SETAC Press, Pensacola, FL, 6/99*, 31 p.
- 50 J. B. Guinée, *Handbook on Life Cycle Assessment: Operational Guide to the ISO Standards*, Kluwer Academic Publishers, 2002.
- 51 E. Lucas, A. J. Martín, S. Mitchell, A. Nabera, L. F. Santos, J. Pérez-Ramírez and G. Guillén-Gosálbez, *Green Chem.*, 2024, **26**, 9300–9309.
- 52 R. A. Sheldon, *Chem. Ind.*, 1992, **23**, 903–906.
- 53 R. A. Sheldon, *Chem. Ind.*, 1997, **1**, 12–15.
- 54 B. M. Trost, *Science*, 1991, **254**, 1471–1477.
- 55 A. D. Curzons, *Green Chem.*, 2001, **3**, 1–6.
- 56 J. W. Owens, *Risk Anal.*, 1997, **17**, 273–399.
- 57 M. Herrchen and W. Klein, *Pure Appl. Chem.*, 2000, **72**, 1247–1252.
- 58 H. S. Matthews, L. Lave and H. MacLean, *Risk Anal.*, 2002, **22**, 819–1033.
- 59 S. J. Cowell, R. Fairman and R. E. Lofstedt, *Risk Anal.*, 2002, **22**, 819–1033.
- 60 C. Caldeira, R. Farcas, I. Garmendia Aguirre, L. Mancini, D. Tosches, A. Amelio, K. Rasmussen, H. Rauscher, J. Riego Sintes and S. Sala, *Safe and Sustainable by Design chemicals and materials-Framework for the definition of criteria and evaluation procedure for chemicals and materials*. EUR31100 EN, Publications Office of the European Union, Luxembourg, 2022, ISBN978-92-76-53264-4, p.JRC128591, DOI: [10.2760/487955](https://doi.org/10.2760/487955).
- 61 The European Chemical Industry Council (Cefic), *Safe and Sustainable by Design: A transformative Power*, 2022. Available online: <https://cefic.org/app/uploads/2022/04/Safe-and-Sustainable-by-Design-Guidance-A-transformative-power.pdf> (accessed on 04 September 2025).
- 62 D. G. Woodward, *Int. J. Prog. Manag.*, 1997, **6**, 335–344.
- 63 International Organization for Standardization (ISO), *ISO 14075:2024 Environmental management — Principles and framework for social life cycle assessment*, Geneva, Switzerland, ISO, 2024.
- 64 Operational Life Cycle Sustainability Assessment Methodology Supporting Decisions Towards a Circular Economy – ORIENTING. Available online: <https://orienting.eu/> (accessed on 04 September 2025).

