Dalton Transactions

PERSPECTIVE

Cite this: Dalton Trans., 2016, 45 18803

Synthetic routes to iron chalcogenide nanoparticles and thin films

Peter D. Matthews, t^a Masood Akhtar, t^a M. Azad Malik, ^b Neerish Revaprasadu^c and Paul O'Brien*a,b

Received 7th September 2016, Accepted 12th November 2016 DOI: 10.1039/c6dt03486a

<www.rsc.org/dalton>

Iron chalcogenides are earth abundant, cheap and environmentally benign materials that have seen extensive research directed toward a range of applications, most notably for photovoltaics. The most common forms of materials for these applications are either nanoparticles or thin films. This perspective seeks to summarise the key synthetic routes to these materials by highlighting the key aspects that lead to control over phase and morphology. **PERSPECTIVE**

Synthetic routes to iron chalcogenide

Synthetic routes to iron chalcogenide

Synthetic routes and thin films

Signals and the state control of the state of the state of the state of the state of the state

1. Introduction

Iron chalcogenides are earth abundant, cheap and environmentally benign materials that have seen extensive research across a range of applications. These include hydrogen evolution, photovoltaics, Li-ion batteries, high temperature superconductors, supercapacitors and memory devices.¹⁻⁷ For these applications nanoparticles and thin films offer a large degree

^bSchool of Materials, University of Manchester, Oxford Road, Manchester, M13 9Pl, UK. E-mail: paul.o'brien@manchester.ac.uk

 c Department of Chemistry, University of Zululand, Private Bag X1001, Kwadlangezwa, 3886 South Africa

†These authors contributed equally.

of flexibility as the size/thickness and morphology can be tuned during their formation. Unlike iron oxide nanoparticles and thin films, which have long been studied, the chalcogenide counterparts have historically received less attention, though this has changed in recent years.

The most studied applications for iron chalcogenides are as photovoltaics or supercapacitors, with considerable research directed towards the magnetic properties of these materials. Iron chalcogenides have the potential to act as a photoabsorber layer within a photovoltaic device; this requires a very precisely defined morphology in order to maximise current flow whilst minimising hole-electron recombination at defect sites. Only pyrite (Fes_2) demonstrates photoactivity, and contamination with secondary phases is prone to reduce the efficiency of devices.

Peter D. Matthews

Peter D. Matthews studied for his MSci at the University of Cambridge (2008–2012) and completed his PhD (2012–2016) there with Prof. Dominic S. Wright and Prof. Ali Alavi FRS, working on polyoxotitanate cages and heteroatom doped graphites. He has moved to the University of Manchester to take up an EPSRC Doctoral Prize with Prof. Paul O'Brien FRS.

Masood Akhtar

Masood Akhtar completed his PhD at the University of Manchester in 2013 with Prof. Paul O'Brien FRS. He is a postdoctoral fellow at the University of Zululand and Visiting Researcher at the University of Manchester (2014–). He obtained his M.Sc. degree from the University of Azad Jammu and Kashmir and served as a lecturer in chemistry in the education department of Azad Kashmir. His research interest is the deposition of thin films and synthesis of nanoparticles for various applications.

^aSchool of Chemistry, University of Manchester, Oxford Road, Manchester, M13 9PL, UK

Magnetic nanocrystals have a broad remit of applications, ranging from use as contrast agents in magnetic resonance imaging $(MRI)^{8,9}$ to magnetic data storage¹⁰ and even paleomagnetism.¹¹ Thus the variation of magnetic behaviour with particle morphology and size is an important area of study.

Iron sulfide has seven phases, whilst iron selenide and iron telluride both have three, which makes these systems quite complex. Most applications require a high degree of phase purity – secondary phases can hinder or reduce the efficiency of a device. Thus it is important that synthetic routes demonstrate the ability to control the phase of the obtained material, as well as the morphology.

The purpose of this perspective is not to summarise every single reaction in the literature, but to highlight the important aspects of those that lead to phase and/or shape/size control. It is through careful control of these variables that iron chalcogenides will be able to fulfil their exciting potential for applications.

2. Iron sulfide

There are seven major phases of iron sulfide, which indicates the complexity of the system. The phases are: iron sulfide (FeS), greigite (Fe3S4), pyrrhotite (Fe1−xS), troilite (FeS) mackinawite (Fe_{1+x}S), marcasite (orthorhombic FeS₂) and pyrite (cubic $FeS₂$) and these are shown in Fig. 1.

Pyrite is the key phase for photovoltaic applications, with an appropriate band gap (0.95 eV), high absorption coefficient (>105 cm−¹) a good carrier diffusion length (100–1000 nm) and an extremely high natural abundance.¹²⁻¹⁴ On the other hand, FeS and pyrrhotite (Fe_{1-x}S) have been proposed as the preferred phases for Li-ion batteries,¹⁵ and troilite and greigite are the premier candidates for use in supercapacitors.¹⁶ It is apparent that the performance of each device here is phase dependent, and so it is clear that phase control is a clear requirement during the synthesis of iron sulfides.

Fig. 1 The different phases of iron sulfide. (a) FeS, (b) greigite, (c) pyrrhotite, (d) troilite, (e) mackinawite, (f) marcasite and (g) pyrite. Brown = Fe, yellow = S .

2.1 Synthesis of nanoparticles

Iron sulfide nanoparticles, like most others have been synthesised via a number of different routes, the two most common of which are the hot-injection method or a solvothermal route.

2.1.1 Hot injection. The hot injection method involves the injection of the precursors in a high boiling point solvent at temperatures greater than the breakdown temperature of the precursor. There are two major types of syntheses: those that use elemental sulfur or those that make use of a single source precursor featuring Fe–S bonds.

The former use a variety of iron sources in differing oxidation states, including FeCl_2 ,¹⁷ [Fe(CO)_5] ,¹⁸ [Fe(acac)_2] ¹⁹ or

M. Azad Malik

Mohammad Azad Malik completed his PhD at the University of London in 1990 and since then has been working with Prof. Paul O'Brien initially at Queen Mary University of London (1990–1995), then Imperial College (1995–2000), and currently the University of Manchester (2000–). He has been involved in various projects and has a wide range of experience in single-source molecular precursors for II/VI, III/V, III/VI, and IV/VI semiconductors, and the colloidal synthesis of nanoparticles.

Neerish Revaprasadu

Neerish Revaprasadu is a professor of Chemistry and SARChI Chair holder in Nanotechnology at the University of Zululand, South Africa. He obtained his BSc(Hons.) from the University of Natal in 1993 and PhD from Imperial College in 2000. He started as a Senior Lecturer at the University of Zululand in 2000, was promoted to associate professor in 2004 and full professor in 2008. His research interest is the synthesis and pro-

cessing of semiconductor nanomaterials. He was elected Member of South African Academy of Science (ASSAF) in 2014.

[Fe(acac)₃]²⁰ (acac = acectylacetonate). It appears that a degree of shape control, as well as the phase of the nanoparticles can be achieved by the choice of iron source.

 FeCl_2 favours the formation of pyrite (FeS₂), with the iron oxidation state increasing from $Fe(II)$ to $Fe(IV)$, owing to the oxidizing environment created by the sulfur. It should be noted that Kirkeminde et al. successfully made FeS nanowires using FeCl_2 ²¹ though the majority of syntheses resulted in pyrite. Li et al., found that they could control both the size and shape of their products by varying the concentration of FeCl_2 in their reaction. Low concentrations of $FeCl₂$ in oleylamine (OA) resulted in the formation of ∼250 nm nanocubes, whilst higher concentrations resulted in the formation of \sim 10 nm nanodendrites.²²

FeCl₂ has also been utilized by Steinhagen¹⁷ and Shukla²³ in OA to generate cube-shaped nanoparticles, whilst Puthussery et al. found that they were able to make more stable colloidal suspensions by exchanging the OA ligands for octadexylxanthate.²⁴ Macpherson et al. have produced a highly interesting study in which they were able to exert a high degree of shape control with FeCl_2 (at the expense of monodispersity) through tuning the chemical potential of sulfur. 2 They made use of a three step process: initial nucleation in a sulfur rich environment followed by 2 growth periods in near stoichiometric conditions for FeS₂ (Fig. 2). This level of control was driven by theoretical predictions that the {100} face is the lowest energy face in S poor conditions, whilst the $\{210\}$ and ${111}$ faces are favoured with increasing S concentration.^{25,26} **Outon Transactions**

Uncertainty control as well as the plane of the inneptiate is uncertainty control as the set of the interval control as the control as the creative commons the common access are control as the common

 $[Fe(CO)₅]$ has been used in conjunction with elemental sulfur in OA to generate hexagonally shaped nanoplates of pyrite,¹⁸ though its high toxicity makes it an undesirable reagent for large scale use.

Beal *et al.* used $[Fe(acac)_2]$ to synthesize both greigite $[Fe_3S_4]$ and pyrrhotite (Fe_{1-x}S) nanoparticles, though these were poly-

Paul O'Brien

Paul O'Brien FRS FREng CBE is Chair of Inorganic Materials Chemistry in the Schools of Chemistry and Materials at the University of Manchester; he was Research Dean 2000–03, Head of the School of Chemistry 2002–09 and Head of the School of Materials 2011–15. He has held academic positions at Chelsea, Queen Mary and Imperial Colleges in the University of London. He was awarded the Kroll, Sir Colin Humphreys and

Platinum Medals of the IoM3 and the 1^{st} Peter Day Award and the Longstaff prize from the RSC. His research centres on developing new chemical processes for thin films and nanoparticles; especially of chalcogenides. In May 2013 he was elected a Fellow of the Royal Society London. In 2016 he was awarded a CBE and elected as a Fellow of the Royal Academy of Engineering.

Fig. 2 TEM images and conditions employed by Macpherson et al .² during their synthesis of pyrite nanocubes. Reprinted with permission from ref. 2, ©2012 American Chemical Society.

Fig. 3 Two of the major classes of single source precursors that have been explored for the synthesis of iron sulfide nanoparticles and thin films. (an) Iron(III) diethyldithiocarbamate $[Fe(S_2CNEt_2)_3]$ and (b) iron(III) O-ethylxanthate $[Fe(S₂COEt₂)₃]$. In both cases the ethyl group might be exchanged for other alkyl groups. Brown = Fe, yellow = S, grey = C, blue = N and red = O. Hydrogens omitted for clarity.

disperse and offered limited shape control.^{19,27} Other groups have used $[Fe(ace)]$ which resulted in carbon coated nanosheets of troilite (FeS). They found that the use of 1-dodecanethiol (1-DDT) gave more regular shapes than the usual OA/S mixture.²⁰

The second major hot-injection technique is to use a single-source precursor that features preformed Fe–S bonds. The first examples of this in the iron sulfide field featured the decomposition in OA of $[N^nBu_4]_2[Fe_4S_4(SPh)_4]^{28}$ and $[\text{Fe}(N\text{-MeIm})_6]$ S₈] (N-MeIm = N-methylimidazole).²⁹ The former resulted in the formation of pyrrhotite at 180 °C and greigite at 200 °C, demonstrating a good degree of phase control.²⁸ The latter gave a multi-faceted morphology with greigite formed in a burst-nucleation when $[Fe(N-MeIm)_6]S_8$ was injected at 300 °C, followed by rapid cooling. The greigite was converted to pyrrhotite if the reaction was not immediately cooled to room temperature.²⁹

Giovanni et al. investigated the use of $[Fe₂S₂(CO)₆]$ as a single source precursor (SSP), the thermolysis of which in OA led to the formation of pyrrhotite nanohexagons.³⁰

A major class of SSPs that have been investigated are iron dialkyldithiocarbamates $[Fe(S_2CNR_2)_x]$ (x = 2 or 3, Fig. 3a) and iron O-alkyxanthates $[Fe(S_2COR)_x]$ (x = 2 or 3, Fig. 3b). Hexagonal two-dimensional pyrrhotite (Fe_{1-x}S) and greigite $(Fe₃S₄)$ nanosheets were synthesized by thermolysing $[Fe(S_2CNEt_2)_2(phen)]$ (phen = 1,10-phenanthroline) and $[Fe(S_2CNEt_2)_3]$ respectively, both in OA.³¹ The influence of the OA as a capping ligand was investigated by the introduction of non-coordinating octadecene (ODE). For $[Fe(S_2CNEt_2)_2(phen)]$ this resulted in less defined, quasi-hexagonal shapes of $Fe_{1-x}S$, which indicates that the oleylamine ligand controls the growth of the nanosheets along the {100} and {110} faces. Therefore, it is important to note that the choice of solvent system plays a key role in the shape of the obtained nanoparticles.

A range of symmetrical and asymmetrical $Fe(III)$ dithiocarbamates ([Fe(S₂CNRR')₃] where R = Et, R' = ⁱPr; R,R' = Hex; R = Me, R' = Et; and R,R' = Et) were used by Akhtar *et al.*³² They found that the precursors with symmetrical long chain alkyl groups gave pure greigite phase at lower thermolysis temperature but a mixture of greigite and pyrrhotite at higher temperatures. Symmetrical short chain alkyl groups give the pure greigite (Fe₃S₄) phase at both 230 and 300 °C. The unsymmetrical alkyl groups gave mixed phase (greigite and pyrrhotite) iron sulfide nanocrystals at all temperatures.

In a similar manner, O'Brien and co-workers made use of a series of tris(O-alkylxanthato)iron(m) complexes $[(Fe(S_2COR)_3)$, $R = Me$, Et, and ⁱBu, Fig. 3b] in oleylamine.³³ These systems proved to be complex, with the O-methylxanthate giving a mixture of greigite and pyrrhotite. The O-ethylxanthate complexes gave pure greigite at low temperature, but a mixture of greigite, pyrrhotite and pyrite at high temperatures. This behaviour is also exhibited by the O-iso-butylxanthates. These nanocrystals showed random shapes with a wide polydispersity. The size range could be controlled somewhat by choice of solvent: 14–139 nm in length and 12–65 nm in width nanocrystals were synthesized in oleylamine whereas smaller nanocrystals 12–31 nm length 7–26 nm width were obtained from hexadecylamine.

The same group used an $Fe(m)$ complex of 1,1,5,5-tetraiso-propyl-2-thiobiuret $[Fe(SON(CN^\mathrm{i}Pr_2)_2)_3]$ as a single source precursor for the synthesis of iron sulfide nanoparticles, by thermolysis in hot oleylamine (OA), octadecene (ODE), or 1-dodecanethiol (1-DDT).³⁴ Several combinations of different injection solvents and capping agents were used in the reaction mixture to control the shape and the phase of the material. The thermolysis of the iron complex in OA or OA/ 1-DDT produced crystalline $Fe₇S₈$ nanoparticles with different morphologies (spherical, hexagonal plates and nanowires) depending on the growth temperature and precursor concentration. This system is more susceptible to solvent change than others, with the introduction of ODE resulting in an amorphous material.³⁴

2.1.2 Solvothermal. A second major technique that has been used to generate nanoparticles is solvothermal synthesis. In this technique a Teflon-lined autoclave is loaded with the precursor(s) and chosen solvent and then the sealed vessel is placed in an oven at temperatures greater than the boiling point of the solvent. This combination of pressure and temperature leads to the supersaturation of the solvent by a product which will then crystallize out upon slow cooling. In the generation of iron sulfide nanoparticles this is a technique which has received substantial attention.

Kar, $35,36$ Nath³⁷ and Xuefeng³⁸ all reported the synthesis of nanowires from various iron salts and sulfur sources, with the

Fig. 4 The solvothermal reaction of $FeSO_4·7H_2O$ and Na_2S_3 gives nanorods in ethylenediamine and nanoparticles in benzene, demonstrating the solvent dependency of the morphology. Reprinted with permission from ref. 38, ©2001 Elsevier.

constant being ethylenediamine as the solvent. Kar et al. found that the solvothermal reaction of $[Fe(NO₃)₃·9H₂O]$, [FeSO₄·7H₂O] or FeCl₃ with thiourea or Na₂S resulted in the formation of pyrite nanowires, though the $Na₂S$ reactions gave substoichiometric FeS_{2-x}.^{35,36} Xuefeng et al. carried out a similar process with $[FeSO_4·7H_2O]$ and Na_2S_3 as the precursors. They found a solvent-based morphology dependency that resulted in pyrite nanowires in ethylenediamine but pyrite nanoparticles in benzene (Fig. 4). 38 This indicates that the solvent can be chosen to target the desired the morphology.

Nath et al. reacted $[FeCl₂·4H₂O]$ with thioacetamide in ethylenediamine to generate a slurry that was annealed in an argon atmosphere to give Fe₇S₈ nanowires at 200 °C and Fe_{1−x}S at 300 °C.

Cao³⁹ and Zhang⁴⁰ both successfully synthesized Fe₃S₄ nanoparticles, the former using $FeSO₄$ and L-cysteine in water,³⁹ whilst the latter used [FeCl₃·6H₂O] with thiourea in an ethyleneglycol-water mixture.⁴⁰

Finally, Chen⁴¹ and Wadia⁴² both used a SSP in the form of iron tris-diethyldithiocarbamate $[Fe(S_2CNEt_2)_3]$ in water for Chen, resulting in pyrite nanocubes.⁴¹ Wadia on the other hand used iron tris-diethyldithiophosphate $[Fe(S_2P(OEt)_3)]$ in hexadecyltrimethylammonium bromide to generate pyrite nanocubes.⁴²

2.1.3 Other. Other routes to iron sulfide nanowires involve the sulfurization of either steel foil or hematite nanowires. Cabán-Acevedo et al. formed pyrite nanowires by heating steel foil at 350 °C in a sulfur atmosphere.⁴³ In a similar manner, Cummins synthesized the pure phase iron sulfide nanowires by sulfurization of hematite nanowire arrays. The hematite was reacted in a 15 Torr H_2S atmosphere at 300 °C for 2 hours and was completely converted to FeS nanostructures. A hollow iron sulfide nanotube was observed under TEM analysis with diameters in the range of 100–300 nm, wall thicknesses ∼60 nm, and an average length of 3 μ m.⁴⁴

Morrish and co-workers also made use of $Fe₂O₃$ nanorods which they converted to FES_2 through plasma assisted sulfurization. For this preparation, nanorods of Fe₂O₃ (~150 nm sized) were prepared by chemical bath deposition method using FeCl₃ and NaNO₃ on FTO glass plates. The Fe₂O₃ nanorods were converted to FES_2 by sulfurization using a mixture of 10% $H₂S$: 90% Ar gas. Iron sulfide prepared by this method contained both marcasite and pyrite phases, which was confirmed by Raman spectroscopy measurement. The prolonged sulfurization of $Fe₂O₃$ nanorods increased the percentage of pyrite without completely eradicating the marcasite phase.⁴⁵

Bauer et al. produce greigite nanorods through the vapoursolid interaction of Fe vapour and ZnS solid in an ultra-high vacuum environment.⁴⁶

2.2 Synthesis of thin films

Iron sulfide thin films have been deposited by a number of methods, which includes the sintering of iron sulfide nanoparticle inks, 24 sulfurization of iron oxides to FeS₂, 47 ion beam and reactive sputtering (Fes_2) ,⁴⁸ sulfurization of iron $(Fes₂)$,^{49,50} flash evaporation $(Fes₂)$,⁵¹ vacuum thermal evaporation (Fes_2) ,⁵² vapour transport (Fes_2) ,⁵³ chemical spray pyrolysis (FeS_2) ,¹⁴ high-energy mechanical milling combined with mechanochemical processing for FeS and FeS₂,⁵⁴ sulfurreducing bacteria for Fe_{1−x}S and Fe₃S₄,^{55,56} the decomposition of single-source precursors for FeS₂,⁵⁷ and other atmosphericor low-pressure metal–organic chemical vapour deposition (AP- or LP-MOCVD) methods.⁵⁸⁻⁶⁰ **Outon Tanactions**
 Open Equidation (1400) and Tanachila chemical control can be equided the control in the case of the set of the set of the case of the case of the set of th

2.2.1 Inks. Mitzi 61 pioneered the solution processing of metal chalcogenide inks for thin film production – a tactic that has gone on to be applied to iron sulfides. Solutions of iron sulfide nanoparticles are often prepared for the purpose of generating inks, which can then be deposited onto a surface and sintered to generate the desired thin film. Deposition techniques include dip-coating, $24,62$ spin-coating, $63,64$ dropcasting²¹ or the use of the doctor's blade method.⁶⁵ These processing methods allow for a high degree of control over the thickness of the produced film, which is desirable for the optimization of devices.

2.2.2 Chemical vapour deposition. Chemical vapour deposition (CVD) is a broad term that encompasses a number of different processing methods. However, they all share some basic principles: namely that precursor chemicals are vaporised and transported into the hot-zone of a furnace, where they decompose/react and form the desired product. The thickness and quality of the resulting film can be tuned by controlling the vapour concentration/flow rate and the reaction time/temperature.

The two most commonly used types of CVD in this area are low-pressure (LP-) and aerosol assisted (AA-). Low pressure can improve film uniformity, whilst AA-CVD involves the formation of aerosols, allowing the use of less-volatile precursors. These two methods can be further broken down into multicomponent precursor solutions and single-source precursors.

LP-CVD is more amenable to multi-component systems than single-source precursors, with Schleich⁶⁰ and Thomas⁵⁸ reporting the use of $[Fe(CO)_5]$ and *tert*-butyl disulfide to generate pyrite thin films. Schleich et al. also noted that it as

possible to kinetically trap marcasite at lower temperatures (200 °C) in their system. 60 Chi and co-workers used a related precursor $[Fe_2(CO)_6S_2]$ to make a mixture of $Fe_{1-x}S$ and Fe_7S_8 at 300 °C and FeS at 600 °C.⁶⁶

In 2000 O'Brien et al. discovered that their iron(III) dithiocarbamates would not produce films under LP-conditions. However, they generated pyrite thin films via aerosol assisted- (AA-) CVD using $[Fe(S_2CNRR')_3]$ $(R = Me, R' = {}^{i}Pr; R, R' = {}^{n}Bu)$.⁵⁷ Takahashi used $[FeCl₃]$ and thioacetamide in an atmospheric pressure CVD apparatus to make pyrite at 500 $\mathrm{^{\circ}C},^{67}$ though this route has not been widely adopted.

Ramasamy used the iron thioburets $[Fe{SON(CNR₂)}₂$ ₃] $(R = {}^{i}Pr, Et, Me)$ that were successful in the synthesis of nanoparticles³⁴ in an AA-CVD reaction to give an interesting mixture of films. The ⁱPr complex gave hexagonal troilite FeS films with a small amount of tetragonal pyrrhotites at 300 °C, whereas only troilite was deposited above 350 °C. The ethyl compounds deposited a mixture of hexagonal troilite and cubic pyrite films at all temperatures (Fig. 5), whereas the methyl complexes produced very thin films of troilite at all temperatures.⁶⁸

The idea of using $Fe(m)$ dithiocarbamates has been further expanded upon by Akhtar,⁶⁹ Khalid⁷⁰ and Mlowe⁷¹ to encompass short- and long-chain, asymmetrical and cyclic amine groups with mixed success. The asymmetrical groups gave mixed phase pyrite/marcasite films, whilst the use of dihexyldithiocarbamates led to a mixture of pyrite and pyrrhotite. Shorter chain, diethyldithiocarbamates on the other hand gave mixed pyrite/marcasite films, but at temperatures above 400 °C this turned into pure pyrrhotite.⁶⁹ Khalid *et al.* used the same diethyldithiocarbamate complex as Akhtar, but exchanged the solvent for THF instead of toluene, resulting in the formation of clean pyrite films and thus indicating the importance of

Fig. 5 SEM images of troilite thin films produced from the aerosol assisted chemical vapour deposition of $[Fe(SON(CNEt₂)₂)]$ at (a) 300 °C, (b) 350 °C, (c) 400 °C (inset 45° tilt image of film) and (d) 450 °C. Reprinted with permission from ref. 68, ©2010 American Chemical Society.

Fig. 6 The three major phases of iron selenide: (a) α -FeSe, (b) achavalite and (c) ferroselite (FeSe₂). Brown = Fe, green = Se.

solvent choice during AA-CVD reactions.⁷⁰ The use of heterocyclic amines in the form of tris-(piperidinedithiocarbamato) $iron(m)$ and tris-(tetrahydroquinolinedithiocarbamato)iron(m) was trialled by Mlowe *et al.*, but this appears to offer no significant advantage over the simpler systems, only resulting in the formation of a complex, mixed phase film. 71

3. Iron selenide

Fewer phases of iron selenide are known than its sulfide counterpart, with three different phases: a tetragonal phase α-FeSe with PbO-structure (Fig. 6a), a NiAs-type β-phase (achavalite, hexagonal Fe_7Se_8 and monoclinic Fe_3Se_4 , Fig. 6b) and a $FeSe₂$ phase that has the orthorhombic marcasite structure (ferroselite, Fig. 6c). The hexagonal $Fe₇Se₈$ and monoclinic $Fe₃Se₄ phases have attracted the most interest owing to their$ favourable magnetic properties. Perspective Details are the common access Article. Published on 14 novembre 2016. The Common access Article is licensed under the common access Article is licensed under a creative Common and Creative Common and Creative

Iron selenide has garnered a lot of attention, due to its semiconductor, photoabsorption, and magnetic properties. It is a prime candidate for photovoltaics with a band gap of ~1 eV and an absorption coefficient >10⁵ cm⁻¹.⁷²⁻⁷⁴ Iron selenide has also been shown to demonstrate high temperature superconductivity, which is a very exciting result.^{75,76}

3.1 Synthesis of nanoparticles

Iron selenide nanoparticles have been synthesised by a number of different routes. Amongst these, the ubiquitous hot-injection method takes precedence. Chen et al. made PbOtype nanoflakes from the simple reaction of FeCl_2 in a mixture of oleylamine (OA), oleic acid and trioctylphosphine selenide (TOPSe).⁷⁷ TOPSe (and the corresponding telluride, TOPTe) are often described as a mixture of the elemental chalcogen in TOP (or other phosphine), though there is no 'free' chalcogen in the final solution. Instead, the phosphine is oxidised to the corresponding chalcogenide, though for tellurium there is an equilibrium between tellurium and the phosphine telluride.⁷⁸ Zhang et al. also made use of a mixed precursor system, reacting $[Fe(acac)_3]$ and Se powder in OA generating 'nanocacti'. Interestingly, they found that they could change the particles morphology to nanosheets by adding oleic acid into the reaction mixture (Fig. 7). 79

Akhtar et al. decomposed the $Fe(m)$ single source precursors tris(N,N-diethyl-N'-naphthoylselenoureato)iron(III) [Fe(napC-(O)

Fig. 7 SEM images of $Fe₃Se₄$ (a) 'nanocacti', (b) nanosheets, and (c) nanoplatelets synthesized by Zhang et al.,⁷⁹ with the morphology dictated by the amount of oleic acid present in the reaction. Reprinted with permission from ref. 79, ©2011 American Chemical Society.

Fig. 8 The crystal structures of (a) tris(N,N-diethyl-N'-naphthoylselenoureato)iron(III) [Fe(napC-(O)NC(Se)NEt₂)₃] (nap = napthyl) and (b) bis (tetraphenyldiselenoimidodiphosphinato)iron(II) [Fe{(SePPh₂)₂N}₂], which have been used by Akhtar et al. to generate iron selenide nanoparticles and thin films.^{80,81}

 $NC(Se)NEt₂)₃$ (nap = napthyl, Fig. 8a) in oleylamine (OA) at 190, 240 and 290 °C to make mixed phase iron selenide nanoparticles.⁸⁰ The same authors found that they could make pure phase FeSe₂ by switching to the Fe(II) complexes bis(tetraalklyldiselenoimidodiphosphinato)iron (n) where the alkyl is either an iso-propyl or a phenyl $([Fe{(SePR₂)₂N}₂] R = {^{i}Pr}, Ph, Fig. 8b).$ Decomposition of these SSPs in OA resulted in plate-like crystallites of ferroselite (FeSe₂).⁸¹

Iron selenide nanoparticles have also been synthesised by a variety of other routes. These include mechanochemical ball milling of Fe and Se powders, and though this method might be beautifully simple, it resulted in a mixture of Fes e 2 , Fes e 5 e, Fe₇Se₈ and Fe₃O₄.⁸²

Liu et al. synthesised Fes_{2} nanorods by the hydrothermal co-reduction method using hydrazine as the reductant. An aqueous solution of [FeCl₃·6H₂O], [Na₂SeO₃], in distilled water was heated in Teflon-lined stainless steel autoclave to 140 °C for 12 hours. After cooling to room temperature the black product was filtered off, dried and revealed to be the orthorhombic phase of $FeSe₂$. The reaction was found to be dependent on the concentration of hydrazine, with the reaction only producing pure phase FeSe_2 in 1.5 M aqueous hydrazine.⁸³

Dalton Transactions Perspective

3.2 Synthesis of thin films

There are very few examples of iron selenide thin films, with the majority of synthetic routes focussing on CVD^{74,80,81,84,85} though more novel routes such as electrolytic bath deposition 86 and pulsed laser deposition 87 have also been explored.

Wu et al. generated clean FeSe films from the toxic lowpressure- (LP-) CVD reaction of [Fe(CO)₅] and H_2 Se.^{74,84} This process generated clean FeSe films that demonstrated good electrical properties, but both precursors are not the safest to use, and so interest in other routes to FeSe films remains.

Akhtar and co-workers used the Fe (m) selenoureato and the Fe (n) selenoimidophosphines (Fig. 8) that they used for iron selenide nanoparticle synthesis to deposit thin films through an AA-CVD process. The selenoimidophosphine precursors decomposed to form a mixture of Fe_7Se_8 and $FeSe_2$, 81 whilst the selenoureato gave FeSe thin films, but only at the relatively high temperature of 625 $°C.^{80}$.

A more complex precursor was chosen by Hussain et al.: 1-acetyl-3-(4-ferrocenylphenyl) selenourea, a substituted ferrocene derivative. This compound was dissolved in toluene and used in an AA-CVD process, but resulted in a very complicated mixture of different phases, indicating that simpler compounds with an easier decomposition route might be more appropriate.⁸⁵

Chemical bath deposition is a process that has received considerable attention for materials such as zinc oxide, zinc sulfide and cadmium sulfide, $88-91$ but little research has focused on its suitability for iron sulfide deposition. Thanikaikarasan et al. have carried out aqueous electrolytic bath depositions using $FeSO₄$ and $SeO₂$, which resulted in the formation of FeSe films.⁸⁶ One major advantage of this technique is that the average thickness of the deposited layers can be controlled through the applied plating current and the deposition time.

4. Iron telluride

Iron telluride is the least studied of the iron chalcogenides. There are three iron telluride structures: NiAs-type hexagonal FeTe (Fig. 9a), tetragonal Fe_{1.125}Te (Fig. 9b) and orthorhombic frohbergite (FeTe $_2$, Fig. 9c).

Research in iron telluride has focussed on its potential to be a high temperature superconductor and its magnetic properties.⁹² There are therefore comparatively few examples of the synthesis of nanoparticles or thin films of this material.

Fig. 9 The three major phases of iron telluride. (a) NiAs-type hexagonal FeTe, (b) tetragonal Fe $_{1.125}$ Te and (c) orthorhombic frohbergite (FeTe₂). $Brown = Fe$, beige = Te.

Iron telluride has most often been prepared directly by mixing the elements in sealed tubes at high temperatures and high pressures.⁹³⁻⁹⁵ More recently, new synthetic methods and metalorganic chemical vapour deposition (MOCVD) and pulsed laser deposition routes have been used for the synthesis of iron telluride. $96,97$

4.1 Synthesis of nanoparticles

Zhang and co-workers reported an aqueous route to prepare nanocrystalline orthorhombic $Fer F_{2}$ through a reaction between an aqueous alkaline of Te powder and KOH, and [Na2{Fe(EDTA)}]. An aqueous solution of tellurium was used to avoid handling H_2 Te and K_2Te_2 .⁹⁸

Liu et al. extended their hydrothermal reduction synthesis of FeSe₂ nanocrystals to include FeTe₂, through the reaction of $[FeCl₃·6H₂O]$ and $[Na₂TeO₃]$ using hydrazine as the reducing agent.⁸³

Another aqueous route by Roy et al. soaked Te nanorods, synthesized from the reduction of TeO₂ by hydrazine,⁹⁹ with FeCl₃, to result in FeTe nanorods through a galvanic reaction. They discovered an interesting application in the FeTe rod's ability to detect glucose.¹⁰⁰

Oyler and others used the traditional hot-injection route to make iron telluride nanoparticles from hexadecylamine (HDA), trioctylphosphine oxide (TOPO), trioctylphosphine telluride (TOPTe) and $[Fe(CO)_5]$. The Fe and Te ratio should be 20:1 to form pure FeTe and for $FeTe₂$ a larger amount of Te is required. FeTe products are two-dimensional single crystals nanosheets with thickness of 2–3 nm and edge length ranging from 200 nm to several micrometres. FeTe₂ formed as a mixture of nanosheets and one-dimensional sheet-derived nanostructures.⁷³ This method reveals a strong ability to control the obtained phase of iron telluride, and so represents a good step forward in this field.

4.2 Synthesis of thin films

There are not many examples of iron telluride thin film synthesis, but Bochmann reported the synthesis of the iron– tellurium complex $[Fe({}^tBu_2P(Te)NR)_2]$ $(R = {}^iPr$, cyclohexyl) which they used for the gas-phase deposition of $Fer F_{2}$ films.^{96,101} Additionally, Steigerwald has demonstrated a LP-CVD route to iron telluride thin films via the decomposition of $[\{Cp(Et_3P)(CO)Fe\}_2Te]$ and $[\{Cp(Et_3P)(CO)FeTe\}_2]$. The former gave films of pure FeTe, whilst the latter gave pure films of FeTe₂, demonstrating another great degree of $control¹⁰²$

There are a couple of examples of iron telluride cages that, like the iron sulfide cubane clusters, 28 might make good options for the formation of iron telluride nanocrystals/thin films. For example, Steigerwald has reported the synthesis of $[(Et_{3}P)4Fe_{4}Te_{4}]$ ¹⁰³ and Roof has also synthesised both $[(Ph_4P)_2\{Fe_5Te_4(CO)_{14}\}]$ and $[(Ph_4P)_2\{Fe_8Te_{10}(CO)_{20}\}]$.¹⁰⁴ All three of these compounds have an Fe–Te core and so resembles an interesting target for future research. Perspective Maccess Articles. Published on 14 novembre 2016. Downloaded on 14 novembre 2016. Downloaded on 2016. This article is likensed under the same complete complete is likensed under a creative Commons are complete

5. Conclusions

This short perspective has sought to summarise the key synthetic routes to a relatively unexplored class of compounds. Iron sulfide represents a good candidate for thin film photovoltaics, and the synthetic routes to such a promising material must be improved if it is to be commercialised. The other iron chalcogenides, the selenides and particularly the tellurides, have received very little attention and the door remains wide open for interesting and novel research in this area.

Acknowledgements

The authors thank the EPSRC (Doctoral Prize for P. D. M.) and the Royal Society DFID Africa Capacity Building Initiative for financial support.

Notes and references

- 1 D. Jasion, J. M. Barforoush, Q. Qiao, Y. Zhu, S. Ren and K. C. Leonard, ACS Catal., 2015, 5, 6653–6657.
- 2 H. A. Macpherson and C. R. Stoldt, ACS Nano, 2012, 6, 8940–8949.
- 3 J. W. Choi, G. Cheruvally, H. J. Ahn, K. W. Kim and J. H. Ahn, J. Power Sources, 2006, 163, 158–165.
- 4 Z. P. Yin, K. Haule and G. Kotliar, Nat. Mater., 2011, 10, 932–935.
- 5 M.-R. Gao, Y.-F. Xu, J. Jiang and S.-H. Yu, Chem. Soc. Rev., 2013, 42, 2986–3017.
- 6 Y.-X. Wang, J. Yang, S.-L. Chou, H. K. Liu, W. Zhang, D. Zhao and S. X. Dou, Nat. Commun., 2015, 6, 8689.
- 7 M. Barawi, I. J. Ferrer, E. Flores, S. Yoda, J. R. Ares and C. Sánchez, J. Phys. Chem. C, 2016, 120, 9547–9552.
- 8 D. A. J. Herman, P. Ferguson, S. Cheong, I. F. Hermans, B. J. Ruck, K. M. Allan, S. Prabakar, J. L. Spencer, C. D. Lendrum and R. D. Tilley, Chem. Commun., 2011, 47, 9221–9223.
- 9 S. Cheong, P. Ferguson, K. W. Feindel, I. F. Hermans, P. T. Callaghan, C. Meyer, A. Slocombe, C. H. Su, F. Y. Cheng, C. S. Yeh, B. Ingham, M. F. Toney and R. D. Tilley, Angew. Chem., Int. Ed., 2011, 50, 4206–4209.
- 10 S. Sun, C. B. Murray, D. Weller, L. Folks and A. Moser, Science, 2000, 287, 1989–1992.
- 11 M. J. Dekkers, H. F. Passier and M. A. A. Schoonen, Geophys. J. Int., 2000, 141, 809–819.
- 12 P. P. Altermatt, T. Kiesewetter, K. Ellmer and H. Tributsch, Sol. Energy Mater. Sol. Cells, 2002, 71, 181–195.
- 13 A. Ennaoui and H. Tributsch, Sol. Energy Mater., 1986, 14, 461–474.
- 14 G. Smestad, A. Da Silva, H. Tributsch, S. Fiechter, M. Kunst, N. Meziani and M. Birkholz, Sol. Energy Mater., 1989, 18, 299–313.
- 15 B. Wu, H. Song, J. Zhou and X. Chen, Chem. Commun., 2011, 47, 8653–8655.
- 16 X. Rui, H. Tan and Q. Yan, Nanoscale, 2014, 6, 9889–9924.
- 17 C. Steinhagen, T. B. Harvey, C. J. Stolle, J. Harris and B. A. Korgel, J. Phys. Chem. Lett., 2012, 3, 2352–2356.
- 18 A. Kirkeminde, B. A. Ruzicka, R. Wang, S. Puna, H. Zhao and S. Ren, ACS Appl. Mater. Interfaces, 2012, 4, 1174– 1177.
- 19 J. H. L. Beal, S. Prabakar, N. Gaston, G. B. Teh, P. G. Etchegoin, G. Williams and R. D. Tilley, Chem. Mater., 2011, 23, 2514–2517.
- 20 C. Xu, Y. Zeng, X. Rui, N. Xiao, J. Zhu, W. Zhang, J. Chen, W. Liu, H. Tan, H. H. Hng and Q. Yan, ACS Nano, 2012, 6, 4713–4721.
- 21 A. Kirkeminde, P. Gingrich, M. Gong, H. Cui and S. Ren, Nanotechnology, 2014, 25, 205603.
- 22 W. Li, M. Doblinger, A. Vaneski, A. L. Rogach, F. Jackel, J. Feldmann, M. Döblinger, A. Vaneski, A. L. Rogach, F. Jäckel and J. Feldmann, J. Mater. Chem., 2011, 21, 17946–17952.
- 23 S. Shukla, G. Xing, H. Ge, R. R. Prabhakar, S. Mathew, Z. Su, V. Nalla, T. Venkatesan, N. Mathews, T. Sritharan, T. C. Sum and Q. Xiong, ACS Nano, 2016, 10, 4431– 4440.
- 24 J. Puthussery, S. Seefeld, N. Berry, M. Gibbs and M. Law, J. Am. Chem. Soc., 2011, 133, 716–719.
- 25 A. S. Barnard and S. P. Russo, J. Mater. Chem., 2009, 19, 3389–3394.
- 26 D. R. Alfonso, J. Phys. Chem. C, 2010, 114, 8971–8980.
- 27 J. H. L. Beal, P. G. Etchegoin and R. D. Tilley, J. Solid State Chem., 2012, 189, 57–62.
- 28 P. V. Vanitha and P. O'Brien, J. Am. Chem. Soc., 2008, 130, 17256–17257.
- 29 J. H. L. Beal, P. G. Etchegoin and R. D. Tilley, J. Phys. Chem. C, 2010, 114, 3817–3821.
- 30 C. Di Giovanni, W.-A. Wang, S. Nowak, J.-M. Grenèche, H. Lecoq, L. Mouton, M. Giraud and C. Tard, ACS Catal., 2014, 4, 681–687.
- 31 W. Han and M. Gao, Cryst. Growth Des., 2008, 8, 1023– 1030.
- 32 M. Akhtar, J. Akhter, M. A. Malik, P. O'Brien, F. Tuna, J. Raftery and M. Helliwell, J. Mater. Chem., 2011, 21, 9737–9745.
- 33 M. Akhtar, M. A. Malik, F. Tuna and P. O'Brien, J. Mater. Chem. A, 2013, 1, 8766–8774.
- 34 A. L. Abdelhady, M. A. Malik, P. O'Brien and F. Tuna, J. Phys. Chem. C, 2012, 116, 2253–2259.
- 35 S. Kar and S. Chaudhuri, Mater. Lett., 2005, 59, 289–292.
- 36 S. Kar and S. Chaudhuri, Chem. Phys. Lett., 2004, 398, 22– 26.
- 37 M. Nath, A. Choudhury, A. Kundu and C. N. R. Rao, Adv. Mater., 2003, 15, 2098–2101.
- 38 Q. Xuefeng, X. Yi and Q. Yitai, Mater. Lett., 2001, 48, 109– 111.
- 39 F. Cao, W. Hu, L. Zhou, W. Shi, S. Song, Y. Lei, S. Wang and H. Zhang, Dalton Trans., 2009, 9246–9252.
- 40 Z. J. Zhang and X. Y. Chen, J. Alloys Compd., 2009, 488, 339–345.
- 41 X. Chen, Z. Wang, X. Wang, J. Wan, J. Liu and Y. Qian, Inorg. Chem., 2005, 44, 951–954.
- 42 C. Wadia, Y. Wu, S. Gul, S. K. Volkman, J. Guo and A. P. Alivisatos, Chem. Mater., 2009, 21, 2568–2570.
- 43 M. Cabán-Acevedo, M. S. Faber, Y. Tan, R. J. Hamers and S. Jin, Nano Lett., 2012, 12, 1977–1982.
- 44 D. R. Cummins, H. B. Russell, J. B. Jasinski, M. Menon and M. K. Sunkara, Nano Lett., 2013, 13, 2423–2430.
- 45 R. Morrish, R. Silverstein and C. A. Wolden, J. Am. Chem. Soc., 2012, 134, 17854–17857.
- 46 E. Bauer, K. L. Man, A. Pavlovska, A. Locatelli, T. O. Mentes, M. A. Nino and M. S. Altman, J. Mater. Chem. A, 2014, 2, 1903–1913.
- 47 B. Ouertani, J. Ouerfelli, M. Saadoun, B. Bessaïs, H. Ezzaouia and J. C. Bernède, Mater. Charact., 2005, 54, 431–437.
- 48 M. Birkholz, D. Lichtenberger, C. Höpfner and S. Fiechter, Sol. Energy Mater. Sol. Cells, 1992, 27, 243–251.
- 49 S. Bausch, B. Sailer, H. Keppner, G. Willeke, E. Bucher and G. Frommeyer, Appl. Phys. Lett., 1990, 57, 25–27.
- 50 Y. Hu, Z. Zheng, H. Jia, Y. Tang and L. Zhang, J. Phys. Chem. C, 2008, 112, 13037–13042.
- 51 I. J. Ferrer and C. Sánchez, J. Appl. Phys., 1991, 70, 2641– 2647.
- 52 B. Rezig, H. Dahman and M. Kenzari, Renewable Energy, 1992, 2, 125–128.
- 53 A. Ennaoui, S. Fiechter, C. Pettenkofer, N. Alonso-Vante, K. Buker, M. Bronold, C. Hopfner and H. Tributsh, Sol. Energy Mater. Sol. Cells, 1993, 29, 289–370.
- 54 P. P. Chin, J. Ding, J. B. Yi and B. H. Liu, J. Alloys Compd., 2005, 390, 255–260.
- 55 J. H. P. Watson, D. C. Ellwood, A. K. Soper and J. Charnock, J. Magn. Magn. Mater., 1999, 203, 69–72.
- 56 J. H. P. Watson, B. A. Cressey, A. P. Roberts, D. C. Ellwood, J. M. Charnock and A. K. Soper, J. Magn. Magn. Mater., 2000, 214, 13–30.
- 57 P. O'Brien, D. J. Otway and J. H. Park, Mater. Res. Soc. Symp. Proc., 2000, 606, 133–138.
- 58 B. Thomas, C. Höpfner, K. Ellmer, S. Fiechter and H. Tributsch, J. Cryst. Growth, 1995, 146, 630–635.
- 59 B. Thomas and K. Ellmer, J. Mater. Sci.: Mater. Electron., 1998, 9, 61–64.
- 60 D. M. Schleich and H. S. W. Chang, J. Cryst. Growth, 1991, 112, 737–744.
- 61 D. B. Mitzi, Adv. Mater., 2009, 21, 3141–3158.
- 62 Y. Bi, Y. Yuan, C. L. Exstrom, S. A. Darveau and J. Huang, Nano Lett., 2011, 11, 4953–4957.
- 63 S. Seefeld, M. Limpinsel, Y. Liu, N. Farhi, A. Weber, Y. Zhang, N. Berry, Y. J. Kwon, C. L. Perkins, J. C. Hemminger, R. Wu and M. Law, J. Am. Chem. Soc., 2013, 135, 4412–4424. **Outon Transctons**

24 A. Abdelhady, M. A. Malik, P. O'ziein and F. Tuna, 61 D.B. Mini, Ca. E. Assum, C. A. Darbourn, A. Characters A. Darbourn, A. Characters A. Darbourn, A. Characters A. Darbourn, A. Characters A. Assoc
	- 64 W. Li, T. Dittrich, F. Jäckel and J. Feldmann, Small, 2014, 10, 1194–1201.
	- 65 E. Strauss, D. Golodnitsky, K. Freedman, A. Milner and E. Peled, J. Power Sources, 2003, 115, 323–331.
	- 66 K. Chi, S. Shyu, J. Wu, C. Wu and S. Chuang, Inorg. Chim. Acta, 2001, 334, 276–282.
	- 67 N. Takahashi, T. Sawada, T. Nakamura, T. Nakamura and Y. Momose, J. Mater. Sci. Lett., 2000, 19, 2223–2224.
	- 68 K. Ramasamy, M. A. Malik, M. Helliwell, F. Tuna and P. O'Brien, Inorg. Chem., 2010, 49, 8495–8503.
	- 69 M. Akhtar, A. L. Abdelhady, M. Azad Malik and P. O'Brien, J. Cryst. Growth, 2012, 346, 106–112.
	- 70 S. Khalid, E. Ahmed, M. Azad Malik, D. J. Lewis, S. Abu Bakar, Y. Khan and P. O'Brien, New J. Chem., 2015, 39, 1013–1021.
	- 71 S. Mlowe, D. J. Lewis, M. A. Malik, J. Raftery, E. B. Mubofu, P. O'Brien and N. Revaprasadu, Dalton Trans., 2016, 45, 2647–2655.
	- 72 G. Li, B. Zhang, J. Rao, D. Herranz Gonzalez, G. R. Blake, R. A. De Groot and T. T. M. Palstra, Chem. Mater., 2015, 27, 8220–8229.
	- 73 K. D. Oyler, X. Ke, I. T. Sines, P. Schiffer and R. E. Schaak, Chem. Mater., 2009, 21, 3655–3661.
	- 74 X. J. Wu, Z. Z. Zhang, J. Y. Zhang, B. H. Li, Z. G. Ju, Y. M. Lu, B. S. Li and D. Z. Shen, J. Appl. Phys., 2008, 103, $1 - 6$.
	- 75 L. Sun, X.-J. Chen, J. Guo, P. Gao, Q.-Z. Huang, H. Wang, M. Fang, X. Chen, G. Chen, Q. Wu, C. Zhang, D. Gu, X. Dong, L. Wang, K. Yang, A. Li, X. Dai, H. Mao and Z. Zhao, Nature, 2012, 483, 67–69.
	- 76 F.-C. Hsu, J. Luo, K.-W. Yeh, T.-K. Chen, T.-W. Huang, P. M. Wu, Y.-C. Lee, Y.-L. Huang, Y.-Y. Chu, D.-C. Yan and M. Wu, Proc. Natl. Acad. Sci. U. S. A., 2008, 105, 14262– 14264.
	- 77 L. Chen, H. Zhan, X. Yang, Z. Sun, J. Zhang, D. Xu, C. Liang, M. Wu and J. Fang, CrystEngComm, 2010, 12, 4386–4391.
	- 78 R. García-Rodríguez, M. P. Hendricks, B. M. Cossairt, H. Liu and J. S. Owen, Chem. Mater., 2013, 25, 1233–1249.
	- 79 H. Zhang, G. Long, D. Li, R. Sabirianov and H. Zeng, Chem. Mater., 2011, 23, 3769–3774.
	- 80 M. Akhtar, J. Akhtar, M. A. Malik, F. Tuna, M. Helliwell and P. O'Brien, J. Mater. Chem., 2012, 22, 14970– 14975.
	- 81 M. Akhtar, M. A. Malik, J. Raftery and P. O'Brien, J. Mater. Chem. A, 2014, 2, 20612–20620.
	- 82 C. E. M. Campos, J. C. De Lima, T. A. Grandi, K. D. Machado, V. Drago and P. S. Pizani, J. Magn. Magn. Mater., 2004, 270, 89–98.
- 83 A. Liu, X. Chen, Z. Zhang, Y. Jiang and C. Shi, Solid State Commun., 2006, 138, 538–541.
- 84 X. J. Wu, D. Z. Shen, Z. Z. Zhang, J. Y. Zhang, K. W. Liu, B. H. Li, Y. M. Lu, B. Yao, D. X. Zhao, B. S. Li, C. X. Shan, X. W. Fan, H. J. Liu and C. L. Yang, Appl. Phys. Lett., 2007, 90, 88–91. **Perpective**

USI A Licence Access Articles. Common Access Articles. Common Access Common Access 206, 138, 5314-541.

Someon, 2006, 138, 5314-541. Common Access Articles. Denote 2016. The Figure and H. S. Novembre 2016, 2
	- 85 R. A. Hussain, A. Badshah, A. Younis, M. D. Khan and J. Akhtar, Thin Solid Films, 2014, 567, 58–63.
	- 86 S. Thanikaikarasan, T. Mahalingam, K. Sundaram, A. Kathalingam, Y. Deak Kim and T. Kim, Vacuum, 2009, 83, 1066–1072.
	- 87 Y. Han, W. Y. Li, L. X. Cao, S. Zhang, B. Xu and B. R. Zhao, J. Phys.: Condens. Matter., 2009, 21, 235702.
	- 88 B. Cao and W. Cai, J. Phys. Chem. C, 2008, 112, 680– 685.
	- 89 P. O'Brien and J. McAleese, J. Mater. Chem., 1998, 8, 2309– 2314.
	- 90 P. O'Brien, T. Saeed and J. Knowles, J. Mater. Chem., 1996, 6, 1135–1139.
	- 91 A. Bayer, D. S. Boyle, M. R. Heinrich, D. J. Otway, O. Robbe and P. O'Brien, Green Chem., 2000, 2, 79–86.
	- 92 Y. Mizuguchi, F. Tomioka, S. Tsuda, T. Yamaguchi and Y. Takano, Physica C, 2009, 469, 1027–1029.
- 93 T. Bither, C. T. Prewitt, J. L. Gillson, P. E. Bierstedt, R. B. Flippen and H. S. Young, Solid State Commun., 1966, 4, 533–535.
- 94 T. Bither, R. J. Bouchard, W. H. Cloud, P. C. Dokohue and W. J. Siemons, Inorg. Chem., 1968, 7, 2208–2220.
- 95 Y. Mizuguchi, F. Tomioka, S. Tsuda, T. Yamaguchi and Y. Takano, Appl. Phys. Lett., 2009, 94, 7–10.
- 96 M. Bochmann, Chem. Vap. Deposition, 1996, 8, 85–96.
- 97 Y. Han, W. Y. Li, L. X. Cao, X. Y. Wang, B. Xu, B. R. Zhao, Y. Q. Guo and J. L. Yang, Phys. Rev. Lett., 2010, 104, 17003.
- 98 W. Zhang, Y. Cheng, J. Zhan, W. Yu, L. Yang, L. Chen and Y. Qian, Mater. Sci. Eng., B, 2001, 79, 244–246.
- 99 Z. H. Lin, Z. Yang and H. T. Chang, Cryst. Growth Des., 2008, 8, 351–357.
- 100 P. Roy, Z.-H. Lin, C.-T. Liang and H.-T. Chang, Chem. Commun., 2012, 48, 4079–4081.
- 101 X. Song and M. Bochmann, J. Chem. Soc., Dalton Trans., 1997, 2689–2692.
- 102 M. L. Steigerwald, Chem. Mater., 1989, 1, 52–57.
- 103 M. L. Steigerwald, T. Siegrist, S. M. Stuczynski and Y. U. Kwon, J. Am. Chem. Soc., 1992, 114, 3155–3156.
- 104 L. C. Roof, W. T. Pennington and J. W. Kolis, Angew. Chem., Int. Ed. Engl., 1992, 31, 913–915.