Green Chemistry



View Article Online **PAPER**



Cite this: Green Chem., 2016, 18

CHEM21 selection guide of classical- and less classical-solvents†

Denis Prat,*a Andy Wells,b John Hayler, Helen Sneddon, C. Robert McElroy,d Sarah Abou-Shehada^d and Peter J. Dunn^e

A selection guide of common solvents has been elaborated, based on a survey of publically available solvent selection guides. In order to rank less classical solvents, a set of Safety, Health and Environment criteria is proposed, aligned with the Global Harmonized System (GHS) and European regulations. A methodology based on a simple combination of these criteria gives an overall preliminary ranking of any solvent. This enables in particular a simplified greenness evaluation of bio-derived solvents.

Received 12th May 2015, Accepted 13th August 2015 DOI: 10.1039/c5gc01008j

www.rsc.org/greenchem

Introduction

The Innovative Medicines Initiative (IMI)-CHEM21 publicprivate partnership is a European consortium which promotes sustainable biological and chemical methodologies. It comprises six pharmaceutical companies from the European Federation of Pharmaceutical Industries and Associations (EFPIA),² ten universities and five small to medium enterprises. CHEM21 financially supports research projects and will provide a training package to ensure that the principles of sustainable manufacturing are embedded in the education of future scientists. This education task is the main mission of CHEM21 work package 5 (WP5). For example, the training package will include a set of metrics permitting to compare the "greenness" of processes or syntheses.³

In a drug substance synthesis, solvents represent at least half of the material used in a chemical process.⁴ Therefore, limiting their amount and selecting the "greenest" solvents⁵ are the most efficient levers to reduce the environmental impact of an active pharmaceutical ingredient. A preceding paper⁶ describes a survey of publically available solvent selection guides, ⁷ often from pharmaceutical companies. The data given in these guides were compiled, and where possible combined, in order to allow a ranking comparison. Of the 51 clasThese rankings are defined as below:

- Recommended (or preferred): solvents to be tested first in a screening exercise, if of course there is no chemical incompatibility in the process conditions.
- Problematic: these solvents can be used in the lab or in the Kilolab, but their implementation in the pilot plant or at the production scale will require specific measures, or significant energy consumption.
- Hazardous: the constraints on scale-up are very strong. The substitution of these solvents during process development is a priority.
- Highly hazardous: solvents to be avoided, even in the laboratory.

The boundary between hazardous and highly hazardous cannot be clearly established, given that not all pharmaceutical companies and institutions have identical lists of prohibited solvents.7c,8

This survey may be very useful for the quick selection of a solvent, in particular in academic institutions or companies which do not have their own solvent selection guides. Nonetheless, the ambition of CHEM21 is to develop a solvent guide which is not limited to a final ranking, but also presents explicit Safety, Health and Environment (SH&E) criteria, and encompasses newer solvents, such as bio-derived solvents.9 This new guide would aid in the ranking of the seventeen

sical solvents considered, an acceptable alignment could be met, permitting a ranking into four categories: recommended, problematic, hazardous and highly hazardous. 17 solvents could not be ranked by this simplified methodology, thus reflecting differences in the weighing of criteria between the institutions (Table 1). Carbon disulfide (CS2; CAS 75-15-0; volatile and highly flammable) and hexamethyl phosphoramide (HMPA; CAS 680-31-9; carcinogen), which are highly hazardous and are rarely used nowadays, were added to the list in order to prevent their use in the laboratories.

^aSanofi-Aventis Research & Development, BP 14, 94403 Vitry sur Seine, France. E-mail: denis.prat@sanofi.com; Fax: +(33) 155713835; Tel: +(33) 155718014 ^bCharnwood Technical Consulting, Parklands, Northage Close, Quorn, Leicestershire, LE12 8AT, UK

^cGlaxoSmithKline Medicines Research Centre, Gunnels Wood Road, Stevenage, Hertfordshire SG1 2NY, UK

^dGreen Chemistry Centre of Excellence, University of York, Heslington, York, YO10

^ePfizer Global Supply, Discovery Park, Ramsgate Road, Kent, CT139NJ, UK †Electronic supplementary information (ESI) available. See DOI: 10.1039/ c5gc01008j

Green Chemistry Paper

Table 1 Results from initial survey of publically available solvent guides

Recommended Recommended or problematic? Problematic Problematic or hazardous? Hazardous Highly hazardous

Water, EtOH, i-PrOH, *n*-BuOH, EtOAc, i-PrOAc, *n*-BuOAc, anisole, sulfolane.

MeOH, *t*-BuOH, benzyl alcohol, ethylene glycol, acetone, MEK, MIBK, cyclohexanone, MeOAc, AcOH, Ac₂O. Me-THF, heptane, Me-cyclohexane, toluene, xylenes, chlorobenzene, acetonitrile, DMPU, DMSO. MTBE, THF, cyclohexane, DCM, formic acid, pyridine.

Diisopropyl ether, 1,4-dioxane, DME, pentane, hexane, DMF, DMAc, NMP, methoxy-ethanol, TEA. Diethyl ether, benzene, chloroform, CCl₄, DCE, nitromethane, CS₂, HMPA.

"intermediate" solvents using these criteria. This task was given to a sub-team of WP5, and the outcomes are reported in this paper.

Elaboration of safety, health & environmental criteria

This ranking of the most common solvents is based on a benchmark of existing guides. Before integrating neoteric and bio-derived solvents into the CHEM21 guide, a set of criteria is needed to assess the desirability of any solvent, and this assessment must be consistent with the ranking of the commonly used solvents at the industrial level, which are fully registered in REACh.¹⁰ Classically, solvent selection guides are mainly based on a set of SH&E criteria, to which Industrial or Regulatory constraints can be added. In this work, for simplicity, the criteria were combined in order to limit their number to three, resulting in one Safety, one Health and one Environment criterion, each scored from 1 to 10, 10 representing the highest hazard in each category. A colour code was associated with this scoring: green for 1-3, yellow for 4-6, and red for 7-10. A final combination of these three SH&E scores should also allow a direct preliminary ranking in the three categories: recommended, problematic and hazardous. At this level, one cannot make the distinction between hazardous and highly hazardous solvents, even if a solvent with any score of 10 is a good candidate for the latter category.

The safety scoring system was the easiest to establish. As process chemists are expected to know or check the compatibility of the solvent with the reagents, the reactivity was not taken into account. Thus, the main hazard is its flammability. In the European Community, the Global Harmonized System (GHS)¹¹ has been integrated into the Classification, Labelling & Packaging (CLP) regulation. 12 In this system, the fire hazard is mainly based on the flash point (FP), combined to the boiling point (BP) when FP < 24 °C. The safety score presented in this guide is aligned with GHS/CLP, but instead of considering the boiling point for solvents with FP < 24 °C, it makes a finer distinction, by introducing three subcategories (Table 2). In order to take into account other hazards, the safety score is incremented by one if the solvent has a low auto-ignition temperature (AIT < 200 °C), if it accumulates electrostatic charges (resistivity > $10^8 \Omega$ m) or if it easily forms explosive peroxides (hazard statement EUH019 in CLP). For example, diethyl ether, with a flash point of -45 °C, an AIT of 160 °C, a resistivity of $3 \times 10^{11} \Omega$ m and a EUH019 hazard statement, has a combined safety score of 10.

Table 2 Safety criteria

Basic safety score	1	3	4	5	7
Flash point (°C) GHS	>60 —	24 to 60 H226	23 to 0	−1 to −20 H225 or H224	<-20

- 1 is added to the safety score for each of the following properties:
- AIT < 200 °C
- Resistivity > $10^8 \Omega$ m
- Ability to form peroxides (EUH019)

Any solvent with a high energy of decomposition (>500 J g⁻¹), like nitromethane, ¹³ would be scored 10.

The health scoring system reflects the occupational hazard. The ideal would be to link it with the occupational exposure limits imposed by authorities or agencies. However these limits are only established for the most widely used solvents or reagents, the use of which would narrow the applicability and scope of the guide. Moreover, threshold limit values are not unified, even in Europe (Table 3). For a simplified analysis, a health scoring based on the hazard statements in the GHS/CLP system is sufficient. Even if the nature of the hazards are not directly comparable, at least the hazard level is clearly integrated in the system, as illustrated by the acute toxicity by inhalation: H330 (lethal) is worse than H331 (toxic), which is worse than H332 (harmful). Also, H314 (causes severe skin

Table 3 Some occupational exposure limit values (ppm)

Solvent	VLEP (France)	AGW (Germany)	TLV (USA)	TWA (USA)	
Methanol	200	200	200	200	
Acetone	500	500	500	1000	
THF	50	150	200	200	
Benzene	1	_	10	1	
DCM	50	75	50	25	
Chloroform	2	0.5	10	na	
Acetonitrile	40	20	20	40	
Pyridine	5	_	1	2	
TEA	1	1	1	25	

VLEP (8 h): Valeur Limite d'Exposition Professionnelle. ¹⁴ AGW (8 h): Arbeitsplatzgrenzwerte. ¹⁵ TLV (8 h): Threshold Limit Values (American Conference of Governmental Industrial Hygienists). ¹⁶ TWA: Permissive Exposure Limit/Threshold Limit Value (Occupational Safety & Heath Administration). ¹⁷

Paper

burns and eye damage) reflects a higher hazard level than H318 (causes serious eye damage), which in turn is higher than H315 (causes skin irritation). As such, a simple health scoring system based by default on the CLP statements and the GHS pictograms has been constructed. The health score of any solvent is equal to the figure corresponding to the highest hazard according to Table 4, to which one is added if the solvent's boiling point is lower than 85 °C. This adjustment allows a scoring of 10 for the carcinogens benzene and 1,2-dichloroethane, 18 reflecting the higher occupational risk linked with the use of volatile solvents. In this system, water's health score is one, a value which can also be assigned to any other solvent with a BP ≥ 85 °C that does not have any H3xx statements after full REACh registration.¹⁹ It is important to bear in mind that H3xx statements are not assigned to chemicals unless toxicological data are available. In order to exclude bias toward solvents with incomplete toxicological data, a score of 5 is attributed by default.

The proposed scoring system for the environmental impact of a solvent is still incomplete. Such an assessment should include acute toxicity towards aquatic life, bioaccumulation, the ability to generate harmful Volatile Organic Compounds (VOC), and a metric to evaluate the CO₂ impact of its synthesis, recycling and disposal. Such data are often not available, as shown by the debate on the energy balance of the so-called "bio-fuels". 20 Life cycle analysis systems have been proposed, based on multiple effects (eutrophication, global warming potential, cumulated energy demand, acute toxicity, etc.), which are sometimes combined.21 As some of the life cycle

Table 4	Health criteria				
Health score	2	4	6	7	9
CMR			H341 H351 H361		H340 H350 H360
STOT	H304 H371 H373	H334	H370 H372		
Acute toxicity	H302 H312 H332 H336 EUH070		H301 H311 H331		H300 H310 H330
Irritation	H315 H317 H319 H335 EUH066	H318 (eyes)		H314 (skin/ eyes)	

CMR: carcinogen, mutagen or reprotoxic.²² STOT: single target organ toxicity. 1 is added to the health score if BP < 85 °C.

impacts are linked to human health, and thus already integrated into the health score, we preferred to focus on criteria which are solely linked to environment issues (ozone layer depletion, acute ecotoxicity, bio-accumulation, volatility, recyclability). As a basis of environment ranking, a set of criteria is proposed, each scored between 1 and 10, with the highest scoring criterion dictating the final score (Table 5). The lowest score, one, is assigned to water. Decontamination of water following contact with reagents and solvents can be tedious and energy-demanding²³ but at least, when properly treated, the effluents are safe. On the other limit of the scale, solvents which are hazardous to the atmospheric ozone layer²⁴ (H420 in GHS: carbon tetrachloride, trichloroethylene) are scored 10. In order to illustrate the qualitative nature of the system, only three intermediate figures are used: 3, 5 and 7. The boiling point plays an important role in the environment impact. A low boiling solvent will generate VOCs, but on the other hand, a high boiling solvent cannot easily be recycled, and complicates the work-up and downstream unit operations such as product drying. The ideal temperature range has been set between 70 and 139 °C.

The acute environmental toxicity and the bio-accumulation potential are highlighted by H4xx statements in the GHS. If such labels are present, they give a score of 5 or 7. In the absence of data, Quantitative Structure-Activity Relationship (QSAR) modelling can give an estimate of eco-toxicity, 25 such as the ECOSAR tool which is freely available to use.26 We did not make this choice, as the accuracy of the toxicity values generated strongly depends on how the molecule matches the training set used. Without full environment toxicity data, a score of 5 is set by default. If the solvent, after full REACh registration, does not have any H4xx statement, the corresponding score will be 3. Other criteria linked to environment have not yet been included in the scoring, for the sake of simplification. For example, water solubility has not been taken into account, considering that a high solubility in water is not per se an environmental issue. The most eco-toxic solvents (heptane, cyclohexane) are scarcely soluble in water. The recycling of a water miscible solvent may require a high energy

Table 5 Environment criteria									
Environment score	3	5	7						
BP (°C)	70-139	50-69 140-200	<50 >200						
GHS	No H4xx after full REACh registration	H412 H413	H400 H410 H411						
Other		No, or partial REACh registration							

Water: score = 1.H420 (ozone layer hazard): score = 10.

Green Chemistry

demand, whereas a benign solvent-water solution can often be treated in water treatment plant (e.g. alcohols, acetone), even if it can be problematic. Volatile solvents can partition into air, and high concentrations of readily biodegradable solvents can lead to a high chemical oxygen demand which can be deleterious to degrading organisms.

The renewable origin of the solvent also deserves to be considered, but an in-depth analysis is needed, as often, solvents which can be bio-derived are currently mostly synthetized by the petrochemical industry (e.g. methanol, n-butanol). It would also be ideal to have a simple metric to evaluate the environmental impact involved in manufacturing solvents, such as the CO₂ footprint (in kg kg⁻¹) or the Cumulative Energy Demand (CED, in MJ kg⁻¹). Both can be calculated by software such as Ecosolvent® for some solvents.22 However a benchmark analysis of our companies' data gave very divergent figures in some cases, and an in depth comparison of existing computation systems is needed before integration into the scoring. The only unambiguous result is that in all simulations the synthesis of THF is the most energy demanding.

Criteria concerning industrial issues which are not directly linked with SH&E, have not been included, such as the cost, the security of commercial supply if the solvent has a single source, and the freezing point (some solvents are solid at 20 °C and have to be melted before charging). These safety, health and environment scores can be combined in order to give a ranking by default of any solvent. As a combination based on the sum of the scores could under-estimate a major issue, a ranking based on the most stringent criteria is proposed (Table 6).

This simplified analysis does not make a distinction between "hazardous" and "highly hazardous" solvents. The decision to blacklist a solvent can only be made by a company or institution after appraisal of all the available data and internal policy. It is important to note that CMR solvents of category 1 (H340, H350 or H360) have a health score of 9 or 10, which ranks them directly as "hazardous" by default. This is consistent with the CMR regulation which imposes the substitution of such solvents, or the justification for their use if substitution is not possible.

This methodology has been applied to the 53 common solvents (Table 7). Of the 36 solvents which have a clear ranking in the survey, the ranking by default coincides with 29 of them (81%). For 2 solvents (anisole and sulfolane²⁷), the ranking by default gives a more severe ranking, and for 5 solvents (1,4-

Table 6 Ranking by default

Score combination Ranking One score ≥8 Two "red" scores Hazardous One score = 7 Problematic Two "yellow" scores **Problematic** Other Recommended

The final ranking is given by the most stringent combination.

dioxane, chloroform, acetonitrile, DMSO and TEA), a less severe ranking. Moreover, for the 17 solvents which did not have a clear ranking in the survey, the ranking by default is always close, except in one case (pyridine). Thus, the ranking methodology described here gives a very satisfactory alignment with the former results.

However, this simplified system sometimes underestimates the health hazard, as illustrated by the cases of acetonitrile, nitromethane and pyridine: the health score of these solvents, based on the H3xx statements, do not reflect their low occupational threshold values (Table 3) or ICH limits.²⁸ In-depth discussions within the CHEM21 solvent sub-team were sometimes needed to assess the ranking of the 53 solvents (Table 7). As a general rule, we decided not to modify the clear rankings given by the survey (Table 1), except in the case of sulfolane which was "recommended". Its ranking was changed to "hazardous", as a reproductive study on rat suggests that this solvent could affect the development of the unborn child.²⁹ As a result, sulfolane has recently been labelled H360.30 Interestingly, though THF and Me-THF were both ranked as "problematic", the scoring methodology indicates that Me-THF offers advantages in terms of health and environment.

For the "intermediate" solvents tert-butanol, benzyl alcohol, ethylene glycol, MEK, MIBK, methyl acetate, MTBE, cyclohexane, DCM, formic acid, acetic acid and acetic anhydride, we confirmed the ranking by default. Methanol was finally ranked as "recommended", though it is ranked as "problematic" by default. As a matter of fact, despite alarming H3xx statements, the current occupational exposure limits for methanol are relatively high, and consistent between authorities (Table 3), as well as its ICH limit (3000 ppm). Besides, its synthesis is very short and has a low energy-demand.31 In the ketone family, acetone was ranked as "recommended" in contrast with its ranking by default. Acetone generates VOCs, but is not toxic and readily biodegradable. Cyclohexanone was ranked as "problematic", given that its synthesis via benzene and cyclohexane is not sustainable, and in order to favour the other ketones. Pyridine and TEA were ranked as "hazardous", on the basis of their low occupational limit values.

The CHEM21 solvent guide developed is relatively well equilibrated, with 14 recommended, 17 problematic, and 22 hazardous or highly hazardous solvents. Furthermore, these rankings are generally (81%) in agreement with the SH&E scorings given by the simple methodology proposed.

In this methodology, the safety score may appear as under-estimated, some highly flammable solvents such as acetone having a moderate safety score of 5. This does not mean that the fire hazard is neglected. The manufacture of active pharmaceutical ingredients requires very high levels of containment, controlled nitrogen blanketing of reactors, careful aspiration of solvent vapours, grounding of all pieces of equipment and high levels of process safety evaluation before any scale-up. Increasing the safety score would have given a less satisfactory alignment with the existing solvent guides.

Table 7 CHEM21 solvent guide of "classical" solvents

Family	Solvent	BP (°C)	FP (°C)	Worst H3xx ^a	H4xx	Safety score	Health score	Env. score	Ranking by default	Ranking after discussion ^b
Water	Water	100	na	None	None	1	1	1	Recommended	Recommende
Alcohols	MeOH	65	11	H301	None	4	7	5	Problematic	Recommende
	EtOH	78	13	H319	None	4	3	3	Recommended	Recommende
	i-PrOH	82	12	H319	None	4	3	3	Recommended	Recommende
	n-BuOH	118	29	H318	None	3	4	3	Recommended	Recommende
	t -BuOH c	82	11	H319	None	4	3	3	Recommended	Recommende
	Benzyl alcohol	206	101	H302	None	1	2	7	Problematic	Problematic
	Ethylene glycol	198	116	H302	None	1	2	5	Recommended	Recommende
Ketones	Acetone	56	-18	H319	None	5	3	5	Problematic	Recommende
	MEK	80	-6	H319	None	5	3	3	Recommended	Recommende
	MIBK	117	13	H319	None	4	2	3	Recommended	Recommende
	Cyclohexanone	156	43	H332	None	3	2	5	Recommended	Problematic
Esters	Methyl acetate	57	-10	H302	None	5	3	5	Problematic	Problematic
	Ethyl acetate	77	-4	H319	None	5	3	3	Recommended	Recommende
	i-PrOAc	89	2	H319	None	4	2	3	Recommended	Recommende
	n-BuOAc	126	22	H336	None	4	2	3	Recommended	Recommende
Ethers	Diethyl ether	34	-45	H302	None	10	3	7	Hazardous	HH
	Diisopropyl ether	69	-28	H336	None	9	3	5	Hazardous	Hazardous
	MTBE	55	-28	H315	None	8	3	5	Hazardous	Hazardous
	THF	66	-14	H351	None	6	7	5	Problematic	Problematic
	Me-THF	80	-11	H318	None	6	5	3	Problematic	Problematic
	1,4-Dioxane	101	12	H351	None	7	6	3	Problematic	Hazardous
	Anisole	154	52	None	None	4	1	5	Problematic	Recommende
	DME	85	-6	H360	None	7	10	3	Hazardous	Hazardous
Hydrocarbons	Pentane	36	-40	H304	H411	8	3	7	Hazardous	Hazardous
,	Hexane	69	-22	H361	H411	8	7	7	Hazardous	Hazardous
	Heptane	98	-4	H304	H410	6	2	7	Problematic	Problematic
	Cyclohexane	81	-17	H304	H410	6	3	7	Problematic	Problematic
	Me-cyclohexane	101	-4	H304	H411	6	2	7	Problematic	Problematic
	Benzene	80	-11	H350	None	6	10	3	Hazardous	THIE
	Toluene	111	4	H351	None	5	6	3	Problematic	Problematic
	Xylenes	140	27	H312	None	4	2	5	Problematic	Problematic
Halogenated	DCM	40	na	H351	None	1	7	7	Hazardous	Hazardous
rarogenatea	Chloroform	61	na	H351	None	2	7	5	Problematic	HH
	CCl ₄	77	na	H351	H420	2	7	10	Hazardous	HH
	DCE	84	13	H350	None	4	10	3	Hazardous	HH
	Chlorobenzene	132	29	H332	H411	3	2	7	Problematic	Problematic
Aprotic polar	Acetonitrile	82	2	H319	None	4	3	3	Recommended	Problematic
iprotic polar	DMF	153	58	H360	None	3	9	5	Hazardous	Hazardous
	DMAc	166	70	H360	None	1	9	5	Hazardous	Hazardous
	NMP	202	96	H360	None	1	9	7	Hazardous	Hazardous
	DMPU	246	121	H361	None	1	6	7	Problematic	Problematic
	$DMSO^c$	189	95	None	None	1	1	5	Recommended	Problematic
	Sulfolane ^c	287	177	H360	None	1	9	7	Hazardous	Hazardous
	HMPA	>200	144	H350	None	1	9		Hazardous	HH
	Nitromethane	101	35	H302	None	10	2	3	Hazardous	HH
Miscellaneous	Methoxy-ethanol	125	42	H360	None	3	9	3	Hazardous	Hazardous
viiscellalicous	Carbon disulfide	46	-30	H361	H412	9	7	<u> </u>	Hazardous	HH
Acids	Formic acid	101	-30 49	H314	None	3	7	3	Problematic	Problematic
ACIUS			39				4	3		
	Acetic acid	118		H314	None	3	7		Problematic	Problematic
	Ac ₂ O Pyridine	139 115	49 23	H314 H302	None	3 4	2	3	Problematic Recommended	Problematic Hazardous
Amines				H302	None	/1	-,	4	Recommended	

^a Only the highest scoring statements (cf. Table 4) are shown. The lowest figure is given when there are more than one statement in the highest scoring category, for the sake of simplicity. ^b HH: highly hazardous. ^c Solid at 20 °C.

Extension to less common solvents

As this methodology allows a satisfactory preliminary greenness assessment of classical solvents in the context of the pharmaceutical industry, it can also be used to evaluate other solvents, even those not yet described in any guide. An Excel® table, available in the ESI,† automatically gives the SH&E scorings and the

ranking by default, using the physical data and hazard statements extracted from Safety Data Sheets. The "neoteric" or less common solvents have been listed by CHEM21 to be of potential interest in the synthesis of pharmaceutical intermediates, and some of them are being actively employed in CHEM21 projects³³ (Table 8). In this round, supercritical fluids and gas expanded liquids³⁴ have not been included, although CHEM21

Table 8 Ranking of less common solvents

Family	Solvent	CAS	BP (°C)	FP (°C)	Worst H3xx ^a	H4xx ^a	Safety score ^b	Health score	Env. score	Ranking by default
Alcohols	i-Butanol	78-83-1	107	28	H318	None	3	4	3	Recommended
	i-Amyl alcohol	123-51-3	131	43	H315	None	3	2	3	Recommended
	1,3-Propane diol	504-63-2	214	>100	None	None	1	1	7	Problematic
	Glycerol	56-81-5	290	177	None	None	1	1	7	Problematic
Esters	i-Butyl acetate	110-19-0	115	22	H336	None	4	2	3	Recommended
	i-Amyl acetate	123-92-2	142	25	None	None	3	1	5	Recommended
	Glycol diacetate	111-55-7	186	82	None	None	1	1	5	Recommended
	γ-Valerolactone	108-29-2	207	100	n.a.	n.a.	1	5	7	Problematic
	Diethyl succinate	123-25-1	218	91	n.a.	n.a.	1	5	7	Problematic
Ethers	TAME	994-05-8	86	-7	H302	None	6	2	3	Recommended
	CPME	5614-37-9	106	-1	H302	H412	7	2	5	Problematic
	ETBE	637-92-3	72	-19	H336	None	7	3	3	Problematic
Hydro-carbons	D-Limonene	5989-27-5	175	49	H304	H400	4	2	7	Problematic
•	Turpentine	8006-64-2	166	38	H302	H411	4	2	7	Problematic
	<i>p</i> -Cymene	99-87-6	177	27	n.a.	n.a.	4	5	5	Problematic
Aprotic polar	Dimethyl carbonate ^c	616-38-6	90	16	None	None	4	1	3	Recommended
	Ethylene carbonate ^d	96-49-1	248	143	H302	None	1	2	7	Problematic
	Propylene carbonate	108-32-7	242	132	H319	None	1	2	7	Problematic
	Cyrene	53716-82-8	203	61	H319	None	1	2	7	Problematic
Miscella-neous	Ethyl lactate	687-47-8	155	47	H318	None	3	4	5	Problematic
	Lactic acid	50-21-5	230	113	H318	None	1	4	7	Problematic
	TH-furfuryl alcohol	97-99-4	178	75	H360	None	1	9	5	Hazardous

Only the hazard statements given in the REACh dossiers¹⁵ are included, except in the case of TH-furfuryl alcohol, for which the ECHA harmonized classification³² is more recent. ^a n.a.: not available: no full REACh registration; only the highest scoring H3xx statements (cf. Table 4) are shown. The lowest figure is given when there are more than one H3xx statement in the highest scoring category. ^b TAME, CPME and ETBE are estimated as resistive as MTBE ($\rho = 5 \times 10^9 \ \Omega$ m); the hydrocarbons even more ($\rho > 10^{11} \ \Omega$ m). ^c Water sensitive. ^d Solid at 20 °C.

involves some projects using supercritical carbon dioxide. A number of other emerging solvent classes proposed as greener solutions such as ionic liquids, ³⁵ high molecular weight glymes, ³⁶ or Poly-Ethylene Glycols (PEGs), ³⁷ fluorinated solvents, ³⁸ switchable solvents³⁹ and deep eutectic solvents have also been omitted. Ionic liquids and switchable solvents have so far made little penetration in pharmaceutical synthesis, although they are being used as process liquids in other sectors. The same can be said of PEGs, which are more widely used in the formulation sectors. Likewise, trifluorotoluene and fluorous phase solvents have made no impact in pharmaceutical synthesis, and their synthesis is far from being green. While we have not included these materials in the current analysis, there is no reason why the methodology described here could not be used to rank them.

New ethers have been developed and proposed to circumvent the issues of the classical ethers (low flash point, volatility, solubility in water and persistence in the environment). Ethyl-tert-butyl ether (ETBE) is produced using bio-ethanol, and substitutes MTBE as gasoline additive. ⁴¹ Cyclopentylmethyl ether (CPME) is obtained from dicyclopentadiene, via cyclopentene. ⁴² In a similar way, tert-amyl-methyl ether (TAME, or methoxypentane®) derives from C5 distillation fractions of naphta. ⁴³ The syntheses of ETBE, CPME and TAME are short, atom efficient (addition of an alcohol to an alkene) and thus moderately energy consuming. To this list can be added 2-methyl-tetrahydrofuran (Me-THF), a bio-derived ether, ⁴⁴ which has now entered the club of classical solvents. Their solubility in water is comparable (ca. 1%), as well as

their boiling point and their toxicity. The ranking by default (Table 8) clearly indicate that these solvents offer advantages compared to MTBE (Table 7, hazardous). The ranking of CPME and ETBE as "problematic" mainly reflects their resistivity associated with the low auto-ignition point (180 °C) of the former, and the ability to form peroxides of the latter. Nevertheless, these hazards are manageable in most industrial facilities. This illustrates the importance of not limiting a solvent guide to a simple ranking, and of analyzing the criteria supporting such conclusions.

There is an increasing interest in bio-derived solvents in the Green Chemistry community, which aims to benefit from a sustainable source of solvents to help circumvent potential fossil fuel shortages in the future.

In line with recent European standards⁴⁵ applied to lubricants which can be marketed as bio-derived if more than 25% of the carbon is from a renewable resource (assessed by ¹⁴C content),⁴⁶ a similar bio-derivability criterion is to be applied to solvents.⁴⁷ A three band system is proposed, band A if more than 95% of carbon is bio-based, band B between 50 and 95% and band C between 25 and 50% (*e.g.* ETBE: 33%). Below 25%, solvents are considered as petrochemically derived (*e.g.* CPME: 17%). The other neoteric solvents here discussed can theoretically be obtained at scale as band A. Such a standard will permit to establish if they are fully, or only partly, bio-derived, which is not always obvious.

Nowadays, most of ethanol is prepared by fermentation (bio-ethanol).⁴⁸ Other commonly used solvents could be

Paper

carbonate.

produced from the biomass: n-butanol, isobutanol, isoamyl alcohol⁴⁹ as well as their related acetates, acetone, diethyl succinate,⁵⁰ etc. when it becomes economic to do so. Other solvents are solely obtained from natural sources: glycerol (from oils and fats), turpentine (from pine resin), and limonene⁵¹ (from citrus waste). γ -Valerolactone,⁵² Me-THF, tetrahydrofurfuryl alcohol and dihydrolevoglucosenone⁵³ (cyrene) are produced from ligno-cellulosic biomass. Lactic acid is obtained by fermentation of starch,⁵⁴ and gives access to ethyl lactate.⁵⁵ Isomerization and dehydrogenation of limonene

offers a bio-derived route to p-cymene, 56 although it is cur-

rently only commercially available from petrochemical feed-

stocks. Some solvents derive from carbon dioxide, such as

dimethyl carbonate, ethylene carbonate and propylene

Tetrahydrofurfuryl alcohol is ranked "hazardous" because it has recently been classified as toxic to the unborn child. Many bio-derived solvents are ranked "problematic" by default, as a result of their high boiling point, thus reflecting the difficult separation of the product and recycling of the solvent. Additionally a number of new solvents are only produced on a relative small scale, or only as intermediates (γ -valerolactone), and have not yet come under consideration by REACh, resulting in a default scoring of at least 5 in Health and Environment criteria.

D-Limonene, turpentine and *p*-cymene are also ranked as problematic, with relatively high boiling points and aquatic toxicity for D-limonene and turpentine. Besides, the first two are also prone to oxidation.

The carbonate solvents show a remarkable range of polarity, dimethyl carbonate being a potential replacement for MEK, ethyl acetate, MIBK, butyl acetate and most other ketones and glycol ethers. Cyclic carbonates such as ethylene and propylene carbonate are much more polar and could replace undesirable aprotic polar solvents such as DMF.⁵⁷ According to this assessment, dimethyl carbonate seems to be the greenest carbonate. As it is also considered as a mild methylating/carboxymethylating agent,⁵⁸ careful check of the reaction compatibility is necessary before any scale-up.

The solvent sub-team decided to confirm the ranking by default as final ranking in CHEM21 solvent guide for all these less common solvents. This ranking may evolve on the basis of new toxicology or ecotoxicity studies, especially for solvents which are not yet registered in REACh.

Conclusion

The solvent sub-group of CHEM21 has elaborated a selection guide based on a survey of publically available solvent guides for pharmaceutical industry. As this survey was based on the most classical solvents, there was a need to expand this guide to neoteric solvents, and particularly bio-derived solvents. A model was elaborated, allowing a hazard-driven scoring of Safety, Health and Environment of any solvent, and an overall ranking by default into three categories (recommended,

problematic or hazardous). As this model gave a satisfactory alignment with the classical solvents, it can be used to make a preliminary greenness assessment of newer solvents. This ranking methodology is consistent with the CMR and atmospheric ozone regulations, and aligned with the Global Harmonized System. It is based on easily available physical properties and toxicological/eco-toxicological data given in the solvent's REACh dossier. When these data are not published, the solvent is ranked as at least "problematic" by default, which reflects well the difficulties to implement such solvent on industrial scale. Lack of available data can indeed be a key detractor from the uptake of new solvents in the pharmaceutical industry. We would urge solvent suppliers to publish data on toxicity to allow a ranking in the ICH Guidelines. Some good examples include the data published for Me-THF and CPME.59

The methodology described here cannot be presented as an expert system. In the timeframe of CHEM21, we could not elaborate a health scoring based on occupational threshold limit values. This choice was made because the latter are not available for newer solvents, and often not unified for classical solvents. Also, the environmental scoring should include a life-cycle impact analysis of the solvents manufacture, or at least their carbon footprint or total energy demand. Such a simplified system only gives a preliminary ranking which needs to be challenged case by case by solvents experts of each institution, as we did to assign the final rankings of CHEM21 solvent guide. This is also why existing solvent guides will continue to be used in the corresponding pharmaceutical companies.

However the strength of our methodology is that it can easily be maintained by chemists using data and hazard statements available in Safety Data Sheets. The highest hazards are highlighted by the system, which gives a satisfactory alignment with the existing solvent guides. Besides, the methodology is versatile enough to accept further improvement.

This solvent guide will be the cornerstone of the CHEM21 training package on solvents dedicated to students and chemists in the pharmaceutical or fine chemical industry.

It cannot be presented as a universal solvent guide, because it was developed to give solvent rankings adapted to the pharmaceutical industry. But the field of green chemistry is wider, and the same methodology can be applied to design solvent guides for other applications such as coating, formulation, consumer products, agrochemicals *etc.*, by changing the selection and combination of criteria. For example, for some of these applications in which the solvent is not recovered, the boiling point impact can be revised. In the same way, the flash point impact needs to be scored more severely for applications using solvents in open air such as paint stripping, coating, *etc.*

This will reflect the high interest of some bio-derived solvents for such applications, whereas these solvents often appear as "problematic" for pharmaceutical chemistry, as a result of their high boiling points which complicate the recov-

ery and downstream processing on scale, or require the use of new process technologies.

Remark

The conclusions reached in this paper are the collective opinion of the authors who contribute to the CHEM21 consortium and do not reflect, at time of publishing, official policy of any individual company or institution.

Acknowledgements

We would like to thank Oskari Karjalainen (Orion) and Wim Aelterman (Johnson & Johnson) for fruitful discussion. In addition we would like to thank Kevin Bartnik (Pfizer), Christopher Seaman (GSK) and Pascal Isnard (Sanofi) for their expertise in evaluating toxicity data when this was required.

This paper is presented as part of CHEM21 under the Innovative Medicines Initiative Joint Undertaking^{1a} under grant agreement n°115360, resources of which are composed of financial contribution from the European Union's Seventh Framework Program (FP7/2007-2013) and EFPIA companies' in-kind contributions.

Notes and references

- 1 (a) http://www.imi.europa.eu; (b) http://www.chem21.eu.
- 2 http://www.efpia.eu.
- 3 C. R. McElroy, A. Constantinou, L. C. Jones, L. Summerton and J. H. Clark, *Green Chem.*, 2015, 17, 3111–3121.
- 4 C. Jimenez-Gonzalez, C. S. Ponder, Q. B. Broxterman and J. B. Manley, *Org. Process Res. Dev.*, 2011, 15, 912–917.
- 5 (a) C. Capello, U. Fischer and K. Hungerbühler, Green Chem., 2007, 9, 927–934; (b) J. H. Clark and S. T. Tavener, Org. Process Res. Dev., 2007, 11, 149; (c) P. G. Jessop, Green Chem., 2011, 13, 1391–1398; (d) C. P. Ashcroft, P. J. Dunn, J. D. Hayler and A. S. Wells, Org. Process Res. Dev., 2015, 19, 740–747.
- 6 D. Prat, J. Hayler and A. Wells, Green Chem., 2014, 16, 4546–4551.
- 7 (a) K. Alfonsi, J. Colberg, P. J. Dunn, T. Fevig, S. Jennings, T. A. Johnson, H. P. Kleine, C. Knight, M. A. Nagy, D. A. Perry and M. Stefaniak, *Green Chem.*, 2008, 10, 31–36; (b) R. K. Henderson, C. Jimenez-Gonzalez, D. J. C. Constable, S. R. Alston, G. G. A. Inglis, G. Fisher, J. Sherwood, S. P. Binks and A. D. Curzons, *Green Chem.*, 2011, 13, 854–862; (c) D. Prat, O. Pardigon, H. W. Flemming, S. Letestu, V. Ducandas, P. Isnard, E. Guntrum, T. Senac, S. Ruisseau, P. Cruciani and P. Hosek, *Org. Process Res. Dev.*, 2013, 17, 1517–1525; (d) Document entitled *Solvent Selection Guide*, on GCI-PR website: http://www.acs.org/content/acs/en/greenchemistry/industry-business/pharmaceutical.html.
- 8 T. Laird, Org. Process Res. Dev., 2012, 16, 1-2.
- 9 Y. Gu and F. Jerome, Chem. Soc. Rev., 2013, 42, 9550-9570.

- 10 Regulation (EC) n° 1907/2006 of the European Parliament and of the Council of 18 December 2006.
- 11 United Nations Economic Commission for Europe, Globally Harmonized System of Classification and Labelling of Chemicals (GHS): http://www.unece.org/trans/danger/publi/ghs/ghs welcome e.html.
- 12 European Regulation (EC) n°1272/2008.
- 13 P. J. Urben and M. J. Pitt, *Bretherick's Handbook of Reactive Chemical Hazards*, Academic Press, Elsevier, 7th edn, 2007, ISBN-13: 978-0-12-373945-2; ISBN-10: 0-12-373945-4.
- 14 French Decree nº 2012-746.
- 15 Technische Regel Gefahrstoffe TRGS 900 (Germany).
- 16 http://www.acgih.org.
- 17 https://www.osha.gov/dts/chemicalsampling/toc/toc_chemsamp. html.
- 18 DCE is on the REACh authorization list and should not be used anymore at the industrial scale in Europe in 2017, without authorization.
- 19 http://echa.europa.eu/information-on-chemicals/registeredsubstances.
- 20 (a) P. P. Peralta-Yahya, F. Zhang, S. B. del Cardayre and J. D. Keasling, *Nature*, 2012, **488**, 320–328; (b) B. K. Highina, I. M. Bugaje and B. Umar, *Eur. J. Eng. Technol.*, 2014, 2, 117–125.
- 21 (*a*) A. Amelio, G. Genduso, S. Vreysen, P. Luis and B. Van der Bruggen, *Green Chem.*, 2014, **16**, 3045–3063; (*b*) ETH, safety and Environmental Technology Group, Ecosolvent: http://www.sust-chem.ethz.ch/tools/ecosolvent.
- 22 European Council Directive n° 1999/38/EC, 29 April 1999.
- 23 D. G. Blackmond, A. Amstrong, V. Coombe and A. Wells, *Angew. Chem., Int. Ed.*, 2007, **46**, 3798–3800.
- 24 Regulation (EC) n° 1005/2009 of the European Parliament and of the Council of 16 September 2009.
- 25 (a) A. Levet, C. Bordes, Y. Clément, P. Mignon, H. Chermette, P. Marote, C. Cren-Olivé and P. Lantéri, Chemosphere, 2013, 93, 1094–1103; (b) M. Cassotti, D. Ballabio, R. Todeschini and V. Consonni, SAR QSAR Environ. Res., 2015, 26, 217–243; (c) P. V. Durge and S. Deshmukh, Int. J. Res. Chem. Environ., 2012, 2, 319–321.
- 26 U.S. Environmental Protection Agency, Ecological Structure Activity Relationships (ECOSAR): http://www.epa.gov/oppt/newchems/tools/21ecosar.htm.
- 27 U. Tilstam, Org. Process Res. Dev., 2012, 16, 1273-1278.
- 28 Guidance for Industry Q3C-Tables and List, Feb. 2012, Revision 2, http://www.fda.gov/downloads/Drugs/GuidanceComplianceRegulatoryInformation/Guidances/ucm073395.pdf.
- 29 C. Blystone, National Institute of Environmental Health Sciences, sulfolane presentation to National Toxicology Programme Board of Scientific Counselors Meeting, December, 2011: http://ntp.niehs.nih.gov/ntp/about_ntp/bsc/ 2011/december/presentations/5_blystone_sulfolane.pdf.
- 30 Chevron Phillips Chemical Company LP, sulfolane W Data Sheet, March 2015: http://www.cpchem.com/msds/100000013352_SDS_JP_EN.PDF.

Paper

31 (a) G. A. Olah, Angew. Chem., Int. Ed., 2005, 44, 2636-2639; (b) G. A. Olah, A. Goeppert and G. K. S. Prakash, J. Org. Chem., 2009, 74, 487-498.

- 32 European Chemicals Agency, Classification & Labelling Inventory database: http://echa.europa.eu/information-onchemicals/cl-inventory-database.
- 33 G. Paggiola, A. J. Hunt, C. R. McElroy, J. Sherwood and J. H. Clark, Green Chem., 2014, 16, 2107-2110.
- 34 G. R. Akien and M. Poliakoff, Green Chem., 2009, 11, 1083-1100.
- 35 (a) T. Welton, Chem. Rev., 1999, 99, 2071-2083; (b) M. Smiglak, J. M. Pringle, X. Lu, L. Han, S. Zhang, H. Gao, D. R. MacFarlane and R. D. Rogers, Chem. Commun., 2014, 50, 9228-9250.
- 36 S. Tang and H. Zhao, RSC Adv., 2014, 4, 11251–11287.
- 37 J. Chen, S. K. Spear, J. G. Huddleston and R. D. Rogers, Green Chem., 2005, 7, 64-82.
- 38 (a) Q. Chu, M. S. Yu and D. P. Curran, Tetrahedron, 2007, 63, 9890-9895; (b) A. Ogawa and D. P. Curran, J. Org. Chem., 1997, 62, 450-451.
- 39 (a) P. G. Jessop, L. Phan, A. Carrier, S. Robinson, C. J. Dürr and J. R. Harjani, Green Chem., 2014, 16, 1187-1197; (b) J. R. Vanderveen, J. Durelle and P. G. Jessop, Green Chem., 2014, 16, 1187-1197.
- 40 F. Pena-Pereira, A. Kloskowski and J. Namiesnik, Green Chem., 2015, 17, 3687-3705.
- 41 European Fuel Oxygenates Association, Technical Product Bulletin, ETBE: http://www.efoa.eu/documents/document/ 20100715133931-etbe__product_bulletin_-_june_2006.pdf.
- 42 K. Watanabe, N. Yamagiwa and Y. Torisawa, Org. Process Res. Dev., 2007, 11, 251-258.
- 43 Methoxypentane® is a purified grade of TAME, under development by INEOS. Contact: reiner.taege@ineos.com.
- 44 (a) D. F. Aycock, Org. Process Res. Dev., 2007, 11, 156-159; (b) H. H. Khoo, L. L. Wong, J. Tan, V. Isoni and P. Sharratt, Resour., Conserv. Recycl., 2015, 95, 174-182.
- 45 http://www.biobasedeconomy.eu/research/kbbpps/.
- 46 CEN/TR 16227:2011 standard: http://standards.cen.eu/dyn/ www/f?p=204:110:0::::FSP_PROJECT,FSP_ORG_ID:33429,6003 &cs=15CED6AF979DA7E171EEB29A6967E753B.

- 47 CEN/TS 16766:2015 standard: http://standards.cen.eu/dyn/ www/f?p=204:110:0::::FSP_PROJECT,FSP_ORG_ID:40174,874780 &cs=1D5791A76BC10451069475465E86569C9.
- 48 (a) U.S. Department of Energy, Biomass Energy Data Book: http://cta.ornl.gov/bedb/biofuels/ethanol/Ethanol_Overview.shtml; (b) The University of York, The Essential Chemical Industry Online: http://www.essentialchemicalindustry.org/chemicals/ethanol.html; (c) ePURE, European Renewable Ethanol, State of the Industry Report, 2014: http://www.epure.org/sites/default/files/publication/ 140612-222-State-of-the-Industry-Report-2014.pdf.
- 49 http://www.oxiteno.com.br/cms/media/26210/isoamyl alcohol.pdf.
- 50 (a) J. B. McKinlay, C. Vieille and J. G. Zeikus, Appl. Microbiol. Biotechnol., 2007, 76, 727-740; (b) C. Delhomme, D. Weuster-Botz and F. E. Kühn, Green Chem., 2009, 11, 13-26.
- 51 J. H. Clark, D. J. Macquarrie and J. Sherwood, *Green Chem.*, 2012, 14, 90-93.
- 52 (a) D. M. Alonso, S. G. Wettstein and J. A. Dumesic, Green Chem., 2013, 15, 584-595; (b) G. Strappaveccia, E. Ismalaj, C. Petrucci, D. Lanari, A. Marrocchi, M. Drees, A. Facchetti and L. Vaccaro, Green Chem., 2015, 17, 365-372.
- 53 J. Sherwood, M. De bruyn, A. Constantinou, L. Moity, C. R. McElroy, T. J. Farmer, T. Duncan, W. Raverty, A. J. Hunt and J. H. Clark, Chem. Commun., 2014, 50, 9650-9652.
- 54 (a) J. Yang, J. N. Tan and Y. Gu, Green Chem., 2012, 14, 3304-3317; (b) R. Beerthuis, G. Rothenberg and N. R. Shiju, Green Chem., 2015, 17, 1341-1361.
- 55 C. S. M. Pereira, V. M. T. M. Silva and A. E. Rodrigues, Green Chem., 2011, 13, 2658-2671.
- 56 BASF, US Patent, 3555103, 1967.
- 57 B. Schäffner, F. Schäffner, S. P. Verevkin and A. Börner, Chem. Rev., 2010, 110, 4554-4581.
- 58 (a) P. Tundo and M. Selva, Acc. Chem. Res., 2002, 35, 706-716; (b) A. A. G. Shaikh and S. Sivaram, Chem. Rev., 1996, 96, 951-976.
- 59 (a) V. Antonucci, J. Coleman, J. B. Ferry, N. Johnson, M. Mathe, J. P. Scott and J. Xu, Org. Process Res. Dev., 2011, **15**, 939–994; (b) K. Watanabe, Molecules, 2013, **18**, 3183-3194.