

Cite this: *J. Mater. Chem. A*, 2024, 12, 19604

## Design and characterization of flexible electrode materials

Xiu Song (George) Zhao, \*<sup>a</sup> Hui Ying Yang \*<sup>b</sup> and Qiang Li \*<sup>a</sup>

DOI: 10.1039/d4ta90113d

rsc.li/materials-a

Flexible electrode materials form the cornerstone of technologies that blend seamlessly in our everyday lives. Unlike their rigid counterparts, flexible electrodes are able to stretch, bend and conform to uneven surfaces without ever losing functional integrity. The transformative nature of these electrodes has brought about many innovations in healthcare, environmental remediation,

energy storage and wearable electronics. To say that flexible electrodes have revolutionized the technological landscape is truly an understatement.

Healthcare, for example, benefits greatly from the use of flexible biosensors which adhere to the curvilinear contours of human skin. These sensors can capture minute physiological changes to a patient's condition and enable more intimate monitoring of a patient. Flexible biosensors can also help evaluate an athlete's performance during training and provide biomechanical information crucial to developing future training

regimes. Not only do flexible biosensors perform better, they also offer an unparalleled degree of comfort compared to traditional sensors requiring adhesives to stick onto skin. Another area of application that has seen monumental growth and interest is consumer electronics, specifically in energy storage. With the proliferation of flexible displays, rollable televisions, fitness trackers and smart textiles comes a need for energy storage solutions that can accommodate large omnidirectional strain/stress and possess high energy density.

<sup>a</sup>Qingdao University, China. E-mail: chezxs@qdu.edu.cn; liqiang@qdu.edu.cn

<sup>b</sup>Singapore University of Technology and Design, Singapore. E-mail: yanghuiying@sutd.edu.sg

**Xiu Song (George) Zhao**

Xiu Song (George) Zhao is a chair professor of Qingdao University. He currently heads a research institute (<https://imee.qdu.edu.cn>) at Qingdao University to conduct research focusing on innovative materials for energy. Prof. Zhao worked at National University of Singapore and the University of Queensland, Australia, before joining Qingdao University. Prof. Zhao's research focuses on nanoporous materials for energy and environmental applications. He is a world-leading scientist in materials science and chemistry. Prof. Zhao has been a Clarivate Analytic highly cited researcher since 2016 and Elsevier Highly Cited Chinese Researcher since 2019.

**Hui Ying Yang**

Hui Ying Yang is currently a professor in the pillar of Engineering Product Development at the Singapore University of Technology and Design. Her current research interests are advanced materials science, such as function engineering and chemical doping in low-dimensional nanomaterials, for a variety of high-efficiency devices and technologies with applications in sustainable energy and the environment.

In this themed collection, a comprehensive review of anode-free lithium-metal batteries for flexible systems is provided by Tang *et al.* (<https://doi.org/10.1039/D4TA02003K>). The review delves deep into the various components of lithium-metal batteries in the context of flexible systems and presents a realistic outlook of the various manufacturing strategies to achieve flexible lithium-based batteries. Tang *et al.* had analysed various promising electrolyte choices, recounted a number of coating strategies to achieve uniform lithium deposition and had concluded that the development of novel gel polymer electrolytes and ion-conducting artificial solid-electrolyte interphase layers represent the most promising directions. In a related vein, Li's group (<https://doi.org/10.1039/D4TA02143F>) have developed a strategy of fabricating active materials comprising of electroactive Co(OH)F core nanowire arrays encased in a lithiophilic CoS<sub>2</sub> shell to achieve homogenous lithium nucleation and deposition in flexible lithium-metal batteries. In their work, the CoS<sub>2</sub> shell layer undergoes lithiation to form Co/LiS<sub>2</sub> in which the LiS<sub>2</sub> phase is complemented by Co to achieve uniform lithium deposition and high charge transfer. Using

this unique configuration, they are able to achieve excellent cycling stability at a low overpotential of 13 mV across 2400 h of cycling. A full cell assembled with LiFePO<sub>4</sub> delivered an impressive 1500 cycles at 1 C.

While energy density and cycling stability are important parameters to consider, energy storage solutions for human-interactive devices also need to be able to integrate smoothly without disrupting the functionality of other components. This can be accomplished through a single streamlined manufacturing process. In Liu's work (<https://doi.org/10.1039/D4TA02127D>), a flexible, hemispherical eye sensor was fabricated using laser-scribing-assisted spray coating to provide independent monitoring of intraocular pressure. This novel application of flexible electrodes used the same Ti<sub>3</sub>C<sub>2</sub>T<sub>x</sub> MXene materials for two major components: a micro-supercapacitor powering the device and the strain sensor responsible for detecting changes in intraocular pressure. These components were integrated conveniently on a deformable P(VDF-TrFE) substrate and can be worn over an eye like a contact lens. Liu reported a specific capacitance of 32 mF cm<sup>-2</sup> with an energy density of 10 mW h cm<sup>-2</sup> for the micro-supercapacitor and a high sensitivity of 0.014 mm Hg<sup>-1</sup>.

In most research works, the flexibility of an electrode is usually a mechanical property complementary to its original functionality. Yet there are instances where mechanical deformations of a material can yield improved or additional functions. This is capitalized in Hasimoto's work (<https://doi.org/10.1039/D4TA02042A>) where large MoS<sub>2</sub> sheets were prepared on stretchable gold substrates for improved catalytic performance in hydrogen evolution reactions. Hasimoto *et al.* had leveraged on the principles of defect engineering to induce the formation of aligned cracks along the basal plane of MoS<sub>2</sub> sheets. Through a sequence of theoretical simulations and localised characterization, Hasimoto and his co-workers confirmed that electrocatalytic activity was indeed improved after the electrodes had been stretched. An impressive reduction of overpotential to 352 mV was measured at 10 mA cm<sup>-2</sup>, while cycling remained stable up to 500 cycles. The relative ease of preparing these materials is promising for scalable production.

While the majority of articles remained focused on energy storage, reflecting the enthusiasm of the scientific community at large, we are also seeing an expansion of flexible electrode applications across other disciplines, such as in desalination (<https://doi.org/10.1039/D4TA00236A>), CO<sub>2</sub> electrolysis (<https://doi.org/10.1039/D4TA01994F>) and mechanical sensing (<https://doi.org/10.1039/D3TA06257K>). We hope that the collection of articles will provide readers with a bird's eye view of the exciting possibilities in the field of flexible electrode materials and aid them in developing their own research strategies. Finally, we would like to thank all contributing authors, reviewers and editorial staff in the production of this current themed collection.

Published on 29 Phuphu 2024. Downloaded on 2024-10-01 06:19:23.



Qiang Li

Qiang Li is currently a professor in the Department of New Energy Science and Engineering, Qingdao University,

and directs the Laboratory of Magneto-Electrochemistry. His scientific research focuses on the intersection of magnetism and electrochemistry, including the development of advanced magnetic testing techniques in energy science and the efficient control of magnetism by electrochemical techniques.